REMS

www.rems.de

Innovative
manufacturer of
machines and tools
for pipe working

2024

Catalogue

Product information

Operating instructions

Parts lists

Product films

REMS App – All product information available any time, anywhere – quickly and easily.

On the building site or at your dealer: All operating instructions, parts lists, product information, product films and more can be called upon immediately*. Many other functions are also available to you.

Scan product logo
Are you standing in front of a REMS product? Just scan the product logo and you will get all the product details.

Scan product illustration
You can scan the product illustrations in our offer brochures and get all the details about the product.

Scan QR code
You can scan the REMS QR code and get all the details about the product.

ANDROID APP ON Google play
Available on the App Store

REMS App
Free application software from the Apple App Store or Android App at Google Play.

*Only with an existing data link via network operator or wifi.

Contents

Threading
Roll Grooving 20

Sawing 54

Cutting, chamfering, deburring, calibrating 72

Assembling 102

Testing, cleaning, disinfecting, preserving, flushing, filling 112

Bending 126

Radial Press Jointing 144

Axial Press Jointing 242

Expanding, Extracting 250

Soldering 262

Freezing 268

Pipe and Drain Inspection / Pipe and Drain Cleaning 272

Plastic Pipe Welding 290

Diamond Core Drilling
Diamond chasing saws 300

Drying, dehumidifying, aeration and deaeration 326

We deliver exclusively on the basis of our general conditions of sale and delivery.

The prices stated in this catalogue are valid for one piece respectively for one set (e.g. dies) or one pack (e.g. saw blades). Prices do not include any value added tax (VAT) and are subject to change without notice. We reserve the right to increase prices. These prices supersede all previous prices.

Drawings, illustrations, dimensions, weights, standards and other data stated in this catalogue are not binding and are subject to alteration. All power data stated to be understood as the rated power input. Subject to alternation. All rights reserved, particularly for translations, reproductions, illustrations, radio transmission, photomechanic reproductions or similar and storage of data in computers, including utilization in extracts.

© Copyright 2024
REMS GmbH & Co KG, Waiblingen.

Sale through specialist dealers.

They are creative and have plenty of practical experience, they continuously find possibilities for improvement of the work of the installation professional: REMS development engineers are innovative and therefore important factors in the success of the company.

REMS – heading technical progress for more than 110 years. Development is never finished.

Since its foundation in 1909 REMS has been developing products for the pipe working, especially for sanitary and heating installers. At first, hand tools and then subsequently machines and electric power tools. The stipulation of the company founder Christian Föll "REMS must be superior" has always been the benchmark for our actions. Today REMS is a leading manufacturer of machines and tools for the pipe working.

REMS development engineers have persuasive, groundbreaking ideas which ease the daily routines of the installations professional. They have all the significant requirements in their focus and use all their comprehensive practical experience. Experts from all areas of industry ensure that every possibility for improvement is integrated in the new development. In this way the perfect tools for the tough demands of the building site are created. The REMS products are highly valued because of their innovative technology as well as their high standards of quality and are being used everywhere in the world. Both trade and user profit in this way.

Again and again REMS is able to maintain its position at the forefront of technical progress as a result of its innovative products. Many valid national and international patents prove this.



Through the application of modern construction and development techniques, the quality of REMS products has been to the fore from the beginning: Safe use, robust design, simple operation, durability.

New ideas, technical progress and REMS belong together: e.g. REMS Amigo, REMS Tiger, REMS Curvo, REMS Akku-Press 22 V Connected, REMS Multi-Push – products, which have revolutionised the application technology.

Fully automatic 3D measuring machines are a part of the comprehensive quality control system at REMS. The accuracy of measurements at 0.001 mm guarantees the highest precision.

Highly modern production – guarantor for REMS quality products.

Made in Germany. Our own production plant is located in Waiblingen near Stuttgart, in the centre of Germany's high-tech industrial region. There highly modern equipment and facilities are available for research and development, for production and quality control. In addition to this there is a permanent staff of highly-qualified employees, who in part represent the 4th generation of service at REMS. They have the special level of knowledge and experience that is essential for the manufacture of quality products.

Quality means much more to REMS than simply dimensional accuracy and function. It is backed up by a comprehensive quality control system, which begins as early as the assessment of market needs and which is ever present during the product development and manufacture and continues with systematic quality analysis in the market. Furthermore the quality of the production processes is regularly monitored and affirmed by the testing agency that awards the GS safety sign.

All REMS products correspond with safety and accident prevention regulations and fulfil the respective appropriate European standards according to the terms of the EU directives. Additionally, with the exception of a few hand tools which are not safety relevant, all REMS products are checked and approved by independent testing agencies. All REMS products thereby meet an especially high standard with regard to work safety, functional safety and operational safety.

Permanent innovations in processes as well as investments in efficient CNC manufacturing systems engineering ensure that REMS products are amongst the best in the world.

Flexible assembly lines allow adjustment to the requirements of the customer at any time.

REMS is evaluated as having the largest number of training staff in the region. So it is able to maintain its own know-how at a high level.

Tightly defined test intervals during the whole manufacturing process as well as comprehensive function and safety checks after completion of the assembly ensure that no faulty product leaves the plant.

Reliable staff with many years experience are responsible for ensuring that the optimum progression of the hardening process in the material for each component is realised exactly.

Nobody hardens metal better than us. Therefore, we do it ourselves.

Highly durable, safe in application and extremely resilient – a tool can only meet such demands if the components are perfectly hardened.

An important cornerstone for the quality of REMS tools is laid in our own heat treatment shop. The decades of experience has provided important know-how and is the secret of REMS quality tools. The special heat treatment leads to an ideal combination of solidity and robustness and to an especially long durability, as, for example for threading dies, cutter wheels and pressing tongs. The heat treatment process is automatically monitored and permanently recorded by efficient computer technology. This allows a uniformly high product quality.

Our own heat treatment shop – an important aspect of the know-how and the secret of REMS quality tools.

The proven, indestructible REMS quality threading dies. Of robust, especially hardened special steel.

REMS cutter wheels complement the special demands of the various materials. In particular the special hardening process determines the durability of the REMS cutter wheels.

The art of hardening:
It creates extremely resilient components for the highest demands.

Only two from every 45 employees in the logistics industry know that time is money. Speed and absolute reliability are the most important factors for delivery and service.

REMS – for professionals.
Excellent service. On location everywhere.

REMS produces machines and tools for professionals – the demands required are high. REMS fulfils its tasks with competence, responsibility and a first-rate service. This also includes the swift delivery as well as maintenance and repair work. A high degree of flexibility and absolute reliability are the basis for the excellent service.

The whole logistics organisation is oriented towards the needs of our customers. In order to be able deliver promptly REMS keeps more than 10,000 items ready in the central storage facility. All wear and replacement parts are always available. A service that keeps down-times to a minimum.

In the case of a repair the area-wide network of contracted customer service workshops is available for a rapid and professional repair. Highly-qualified and well-trained staff repair and maintain the machines and tools for our customers. After completion of the repair or Inspection the products are returned again to the customer by the fastest means.

Speed is a question of logistics. REMS keeps wear and replacement parts in stock in a 14,000 m^2 storage facility.

The demands at the building site are extreme – wear parts are worn, the need for repairs arises. The REMS customer services department is ready and flexible. There is an extensive service organisation in more than 25 countries.

Service is extremely important for REMS:
All demonstration vehicles for the more than 200 REMS specialist advisors are fitted with testing equipment with which the function test and force of pressure measurement for REMS radial presses can be carried out on location everywhere.

Product training in the REMS training centre: Become familiar with, compare, evaluate.

REMS – business partner to the trade. Excellent advice for contented customers.

Only those who receive competent advice when purchasing find the individually best, economic solution for the tasks ahead. For this reason REMS assigns great significance to the product training of its own REMS specialist advisors and also the staff in the specialist stores.

In the REMS training centre, modern and fully-fitted demonstration, training and conference rooms are available in an area of 1,600 m^2. The practical-oriented training gives the staff of the specialist stores, in an understandable form, a broad basis and high specialist competence for product advice and successful sale. The detailed sales documentation with information relating to all necessary product specifications facilitate a swift product selection and are the basis for the simple and time-saving generation of offers.

This partnership with the specialist store also guarantees the user qualified, comprehensive product advice and excellent service.

REMS training centre in Waiblingen near Stuttgart.

Modern and fully-fitted demonstration rooms:
REMS creates many opportunities for the specialist-store staff to become familiar with the products.

Dennis Maaß, Christian Heipter, Ralf Bähler and Florian Zorn, four of more than 200 qualified REMS specialist advisors are flexible and, when needed, swiftly on location for training courses and presentations.

REMS – Market strength through a consistent product and sales philosophy.

REMS' basis for market strength is technically-advanced and high-quality products as well as a product range tightly concentrated on high turnover units and highly competitive prices thanks to the rational, economical in-house production.

At the centre of the sales philosophy the principle has always been that REMS products are sold exclusively via specialist dealers. These are supported by REMS in many ways. REMS specialist advisors equipped with demonstration vehicles carry out product training on location and demonstrate the REMS products at on-site visits, counter demonstrations and at in-house exhibitions. They advise in the selection of the tools and find the most comfortable, reliable and economical solution in each individual situation.

The consistent sales philosophy is designed for long-term results, trust and predictability.

This is how installation professional become familiar with the product range in practice: The REMS specialist advisors are on the road with demonstration vehicles and demonstrate the machines and tools in real situations, directly on the building site.

The REMS product presentation system – the ideal opportunity for the specialist stores to optimally present the REMS products: touch – compare – select.

Touch. Compare. Select.
Promoting the mutual sale.

The participation at many national and international trade fairs, the advertising in trade magazines and the direct mail marketing to the user is highly valued by trade outlets as sales-promotion measures.

The attractive REMS product presentation system provides the trade outlet with an optimal presentation of the REMS products: Touch, compare, select. The individual stocking with REMS products is carried out with close cooperation between the REMS specialist advisors and the trade outlet.

The online information system at www.rems.de offers extensive opportunities to find out information about the REMS group, the REMS products and their application possibilities and operation. Furthermore, the user has access to the complete online catalogue and detailed technical documentation, information about current trade fair appearances and addresses of REMS contracted customer service workshops, download opportunities of sales documentation, operating instructions, parts lists, product illustrations and product films, opportunities to order sales documentation in various languages for postal dispatch, e-mail addresses for REMS contacts and much more.

The REMS products are exhibited and demonstrated at many national and international trade fairs.

Practical for the trade, clear for the customers – the REMS product presentation system.

The online information system at www.rems.de

REMS App

REMS products are highly valued and used across the world because of their innovative technology and high standards of quality. REMS products are available in all locations where perfection in installation work is demanded.



More than 20,000 trade partners in Europe: REMS products are available locally everywhere.

Innovative products and a high standard of quality open new markets for REMS. In the last years the market area has been continuously build-up and extended. Reliable trade partners throughout Europe and beyond guarantee that ever more customers can be persuaded of the quality of REMS.

REMS sets benchmarks for quality throughout Europe – the sales are carried out through the tight network of reliable trade partners in the whole of Europe which are in turn supported by more than 200 well trained REMS specialist advisors.

Sales subsidiaries in many countries deliver optimum conditions for users and trade outlets.

6

Threading
Roll Grooving

	Hand die stocks	22
	Quick-change die heads S	23
	Electric die stocks	24
	Cordless die stock	28
	Threading machines	32
	Semi-automatic threading machines	42
	Pipe nipple chucks	46
	Thread-cutting oil	47
	Roll grooving attachments	48
	Roll grooving machine	49
	Cordless roll grooving machine	50
	Roll grooving machines	52

REMS eva

Hand die stock with
quick-change die heads

Proven quality die stock with excellent threading capabilities.	
Pipe threads	⅛ – 2", 16 – 50 mm
Bolt threads	6 – 30 mm, ¼ – 1"
Thread types see page 30, 31.	

REMS eva – the plumber's die stock.
Excellent start-cutting and threading.
Steel ratchet lever, thickly plastic coated.
Only one type of quick-change die heads.
Indestructible quality dies.

System advantage
Large working range up to 1¼" and up to 2" with only **one** ratchet lever. Only **one** type of small, compact quick-change die heads and only **one** type of dies. The same quick-change die heads fit all REMS die stocks and other suitable makes of die stocks. Efficient and easy stocking. No confusion possible.

Ratchet lever
Robust. Ratchet lever in steel, thickly plastic coated, for convenient operation. Serrated plastic handle for secure grip. Easy adjustment of ratchet rotation. Perfect, secure seating of quick-change die heads, fast and easy change.

Quick-change die heads
Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads. Quick-change die heads S for cutting pipe threads in hard-to-reach areas (page 23).

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with REMS Nippelspanner ⅜ – 2" (page 46).

German Quality Product

Info

Supply format
REMS eva Set. Hand die stock with quick-change die heads. For pipe threads ⅛ – 2", 16 – 50 mm, bolt threads 6 – 30 mm, ¼ – 1". For right and left-hand threads. 1 ratchet lever for the complete work range. Quick-change die heads with dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M.
In sturdy steel case or in a cardboard box.

Description/Size	Art.-No.	KM
REMS eva Set in steel case		
R ½ + ¾ + 1	520014	**840,00**
R ½ + ¾ + 1 + 1¼	520015	**998,00**
R ⅜ + ½ + ¾ + 1 + 1¼	520013	**1.140,00**
R ½ + ¾ + 1 + 1¼ + 1½ + 2	520017	**1.390,00**
R ⅜ + ½ + ¾ + 1 + 1¼ + 1½ + 2	520016	**1.540,00**
M 16 + 20 + 25 + 32 (M × 1,5)	520010	**1.180,00**
M 20 + 25 + 32 + 40 (M × 1,5)	520009	**1.260,00**
REMS eva Set in cardboard box		
R ½ + ¾	520008	**525,00**
R ½ + ¾ + 1	520004	**672,00**
R ⅜ + ½ + ¾ + 1 + 1¼	520003	**966,00**

REMS eva sets available for left-handed threads and NPT threads.

Accessories

Description	Art.-No.	KM
Ratchet lever for complete work range	522000	**341,00**
Quick-change die heads S see page 23.		
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
Steel case with inlay, for REMS eva ⅜ – 2"	526050	**223,00**
Thread-cutting oil see page 47.		
REMS Nippelspanner ⅜ – 2" see page 46.		
REMS Aquila 3B, pipe workstation with chain pipe vice on folding tripod stand, see page 105.		
REMS Aquila WB, chain pipe vice for workbench, see page 105.		

All prices excl. VAT

REMS quick-change die heads S

Accessories for REMS eva and other makes

For cutting pipe threads in hard-to-reach areas,
e.g. caved wall, lay bare pipes, trench.
Ideal for repair and renovation.

Pipe threads ⅜ – 1¼"

REMS quick-change die heads S – the trouble shooter for hard-to-reach areas.

Quick-change die heads S with specially mounted dies.

Additional, precise pipe guidance at the cover side ensure perfect pipe centering and easy start-cutting.

Extension of ratchet drive REMS eva for threading in caved areas.

Quick-change die heads S and extension fit into the ratchet lever REMS eva and other suitable die stocks.

German Quality Product

Info

Supply format

Die heads S Set. choice of quick-change die heads S for pipe threads tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT) respectively Taper Pipe Thread ASME B1.20.1, Extension 300 mm. In sturdy steel case.

Description	Art.-No.	KM
Set R ⅜ + ½ + ¾	520025R	**1.140,00**
Set R ½ + ¾ + 1	520026R	**1.160,00**
Set NPT ½ + ¾ + 1	520056R	**1.160,00**

Accessories

Description	Size	Art.-No.	KM
Ratchet lever for complete work range		522000	**341,00**
Quick-change die heads S Pipe threads tapered, right ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅜	521026	**315,00**
	R ½	521036	**328,00**
	R ¾	521046	**343,00**
	R 1	521056	**355,00**
	R 1¼	521066	**370,00**
Extension 300 mm		522051	**341,00**
Steel case with inlay for ratchet lever, 4 quick-change die heads S and extension.		526052R	**223,00**

REMS Amigo E

Electric die stock with
quick-change die heads

Powerful, super handy electric tools for threading with unique support bracket. Ready to use anywhere, without vice. Ideal for repair, renovation, job site.

Pipe threads	⅛ – 1", 16 – 32 mm
Bolt threads	6 – 30 mm, ¼ – 1"

Thread types see page 30, 31.

German Quality Product

Info

REMS Amigo E – the fastest, strongest and lightest up to 1".

System advantage
Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket
Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design
Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 3.4 kg, without die head. No heavy top, therefore single-hand operation possible. Perfect, secure seating of quick-change die heads.

Drive
Solid, compact, maintenance-free gear. Robust, powerful 950 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1500 W. Fast threading time 35 – 27 rpm. Safety tip switch.

Quick-change die heads
Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with REMS Nippelspanner ⅜ – 1" (2") (page 46).

Supply format

REMS Amigo E Set. Electric die stock with quick-change die heads. For pipe threads ⅛ – 1", 16 – 32 mm, bolt threads 6 – 30 mm, ¼ – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 950 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1500 W. Right and left-hand rotation. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M.
In sturdy steel case.

Description	Art.-No.	KM
Set R ½ + ¾ + 1	530013R220	**1.850,00**
Set M 20 + 25 + 32	530014R220	**1.980,00**

REMS Amigo E Set for NPT threads available.

Accessories

Description	Art.-No.	KM
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo E drive unit	530003R220	**1.050,00**
Support bracket	533000R	**334,00**
REMS REG St ¼ – 2", pipe deburrer, see page 97.	731700	**305,00**
Dual purpose holder for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger	543100	**536,00**
Ratchet lever see page 22.	522000	**341,00**
Thread-cutting oil see page 47.		
REMS Nippelspanner ⅜ – 2" see page 46.		
Steel case with inlay	536000	**223,00**

All prices excl. VAT

REMS Amigo

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use anywhere, without vice. Ideal for repair, renovation, job site.

Pipe threads	⅛ – 1¼", 16 – 40 mm
Bolt threads	6 – 30 mm, ¼ – 1"

Thread types see page 30, 31.

German Quality Product

Info

REMS Amigo – the smallest, lightest, strongest and fastest up to 1¼".

System advantage
Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket
Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design
Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 3.5 kg, without die head. No heavy top, therefore single-hand operation possible. Perfect, secure seating of quick-change die heads.

Drive
Solid, compact, maintenance-free gear. Robust, powerful 1200 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1800 W. Fast threading time 35 – 27 rpm. Safety tip switch.

Quick-change die heads
Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with REMS Nippelspanner ⅜ – 1¼" (2") (page 46).

Supply format

REMS Amigo Set. Electric die stock with quick-change die heads. For pipe threads ⅛ – 1¼", 16 – 40 mm, bolt threads 6 – 30 mm, ¼ – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1200 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1800 W. Right and left-hand rotation, overload protection switch. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.	KM
Set R ½ + ¾ + 1 + 1¼	530020R220	**2.230,00**
Set M 16 + 20 + 25 + 32 (M × 1,5)	530022R220	**2.360,00**
Set M 20 + 25 + 32 + 40 (M × 1,5)	530023R220	**2.520,00**

REMS Amigo Set for NPT threads available.

Accessories

Description	Art.-No.	KM
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo drive unit	530000R220	**1.260,00**
Support bracket	533000R	**334,00**
REMS REG St ¼ – 2", pipe deburrer, see page 97.	731700	**305,00**
Dual purpose holder for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger	543100	**536,00**
Ratchet lever see page 22.	522000	**341,00**
Thread-cutting oil see page 47.		
REMS Nippelspanner ⅜ – 2" see page 46.		
Steel case with inlay	536000	**223,00**

REMS Amigo 2

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use any-where, without vice. Ideal for repair, renovation, job site.

Pipe threads	⅛ – 2", 16 – 50 mm
Bolt threads	6 – 30 mm, ¼ – 1"

Thread types see page 30, 31.

German Quality Product

Info

REMS Amigo 2 – extremely strong up to 2".

System advantage
Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket
Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design
Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 6.5 kg, without die head. Perfect seating of quick-change die heads.

Drive
Solid, maintenance-free gear. Robust 1700 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Fast threading time 30 – 18 rpm. Safety tip switch.

Quick-change die heads
Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies
The proven, industructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with REMS Nippelspanner ⅜ – 1" (2") (page 46).

Supply format

REMS Amigo 2 Set. Electric die stock with quick-change die heads. For pipe threads ⅛ – 2", 16 – 50 mm, bolt threads 6 – 30 mm, ¼ – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W, safety tip switch, power increase thanks to automatic carbon brush adjustment, right and left-hand rotation. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7–1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.	KM
Set R ½ + ¾ + 1 + 1¼ + 1½ + 2	540020R220	**3.530,00**
Set M 20 + 25 + 32 + 40 + 50 (M × 1,5)	540022R220	**3.830,00**

REMS Amigo 2 Set for NPT threads available.
Other voltages on request.

Accessories

Description	Art.-No.	KM
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo 2 drive unit	540000R220	**2.230,00**
Support bracket Amigo 2	543000	**460,00**
REMS REG St ¼ – 2", pipe deburrer, see page 97.	731700	**305,00**
Dual purpose holder for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger	543100	**536,00**
Ratchet lever see page 22.	522000	**341,00**
Thread-cutting oil see page 47.		
REMS Nippelspanner ⅜ – 2" see page 46.		
Steel case with inlay	546000	**261,00**

All prices excl. VAT

REMS Amigo 2 Compact

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use any-where, without vice. Ideal for repair, renovation, job site.

Pipe threads	⅛ – 2", 16 – 50 mm
Bolt threads	6 – 30 mm, ¼ – 1"

Thread types see page 30, 31.

German Quality Product

Info

REMS Amigo 2 Compact – The smallest and lightest up to 2".

System advantage
Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket
Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design
Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 4.9 kg, without die head. Perfect seating of quick-change die heads.

Drive
Solid, maintenance-free gear. Robust 1200 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1800 W. Fast threading time 30 – 18 rpm. Safety tip switch.

Quick-change die heads
Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies
The proven, industructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with REMS Nippelspanner ⅜ – 1" (2") (page 46).

Supply format

REMS Amigo 2 Compact Set. Electric die stock with quick-change die heads. For pipe threads ⅛ – 2", 16 – 50 mm, bolt threads 6 – 30 mm, ¼ – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1200 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1800 W. Right and left-hand rotation. Overload protection. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to DIN DN 60423 M. In sturdy steel case.

Description	Art.-No.	KM
Set R ½ + ¾ + 1 + 1¼	540023R220	**3.240,00**
Set R ½ + ¾ + 1 + 1¼ + 1½ + 2	540024R220	**3.530,00**
Set M 20 + 25 + 32 + 40 + 50 (M × 1,5)	540025R220	**3.830,00**

REMS Amigo 2 Compact Set for NPT threads available.
Other voltages on request.

Accessories

Description	Art.-No.	KM
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo 2 Compact drive unit	540001R220	**2.230,00**
Support bracket Amigo 2 Compact	543010	**460,00**
REMS REG St ¼ – 2", pipe deburrer, see page 97.	731700	**305,00**
Ratchet lever see page 22.	522000	**341,00**
Thread-cutting oil see page 47.		
REMS Nippelspanner ⅜ – 2" see page 46.		
Steel case with inlay	546000	**261,00**

REMS Amigo 22 V

Cordless die stock with
quick-change die heads

Powerful, mobile, handy electric tool for threading with unique support bracket. Ready for use any-where, without vice. Ideal for repair, renovation, job site.
Li-Ion 22 V Technology. For battery and corded operation.

Pipe threads	⅛ – 1", 16 – 32 mm
Bolt threads	6 – 30 mm, ¼ – 1"

Thread types see page 30, 31.

**REMS Amigo 22 V – mobile, handy, light.
Li-Ion 21.6 V, 9.0 Ah battery, for approx. 52 ¾" threads with one battery charge*.**

System advantage
Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket
Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design
Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Mobile, handy, light. Drive unit with battery pack weighs only 5.6 kg. Practical D-shaped handle with soft grip. Perfect seating of quick-change die heads. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check by a 2-coloured green/red LED.

Drive
Solid, maintenance-free gear. Powerful battery motor 21.6 V, with large power reserve, 500 W output. High cutting speed 27 – 20 rpm. Safety tip switch.

Battery or mains operation
Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V batteries with 9.0 Ah capacity for long service life. Light and powerful, for 52 ¾" threads with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Quick-change die heads
Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies
The proven, industructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with REMS Nippelspanner ⅜ – 1" (2") (page 46).



German Quality Product

Info

REMS Amigo 22 V

Cordless die stock with
quick-change die heads

Supply format

REMS Amigo 22 V Set. Cordless die stock with quick-change die heads. For pipe threads ⅛ – 1", 16 – 32 mm, bolt threads 6 – 30 mm, ¼ – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful battery motor 21.6 V, 500 W. Safety switch. Right and left-hand rotation, machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 9.0 Ah battery, 100 – 240 V, 50 – 60 Hz, 90 W rapid charger. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to DIN DN 60423 M. In sturdy steel case.

Description	Art.-No.	KM
Set R ½ + ¾ + 1	530015R220	**3.890,00**
Set M 20 + 25 + 32	530016R220	**4.040,00**

REMS Amigo 22 V Set for NPT threads available.
Other voltages on request.

Accessories

Description	Art.-No.	KM
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Akku-Amigo 22 V drive unit, without battery	530004R22	**2.360,00**
Support bracket Amigo 2 Compact	543010	**460,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	**1.050,00**
REMS REG St ¼ – 2", pipe deburrer, see page 97.	731700	**305,00**
Ratchet lever see page 22.	522000	**341,00**
Thread-cutting oil see page 47.		
REMS Nippelspanner ⅜ – 2" see page 46.		
Steel case with inlay	566030R	**261,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛	521000	**410,00**
	R ¼	521010	**357,00**
	R ⅜	521020	**242,00**
	R ½	521030	**252,00**
	R ¾	521040	**263,00**
	R 1	521050	**273,00**
	R 1¼	521060	**284,00**
	R 1½	521070	**336,00**
	R 2	521080	**357,00**
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛ LH	521100	**492,00**
	R ¼ LH	521110	**429,00**
	R ⅜ LH	521120	**290,00**
	R ½ LH	521130	**303,00**
	R ¾ LH	521140	**315,00**
	R 1 LH	521150	**328,00**
	R 1¼ LH	521160	**341,00**
	R 1½ LH	521170	**404,00**
	R 2 LH	521180	**429,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT ⅛	521200	**410,00**
	NPT ¼	521210	**357,00**
	NPT ⅜	521220	**242,00**
	NPT ½	521230	**252,00**
	NPT ¾	521240	**263,00**
	NPT 1	521250	**273,00**
	NPT 1¼	521260	**284,00**
	NPT 1½	521270	**336,00**
	NPT 2	521280	**357,00**
Threads M for electric conduit EN 60423	M 16 × 1.5	521300	**315,00**
	M 20 × 1.5	521310	**315,00**
	M 25 × 1.5	521320	**328,00**
	M 32 × 1.5	521330	**341,00**
	M 40 × 1.5	521340	**404,00**
	M 50 × 1.5	521350	**429,00**

Right-hand pipe thread

Left-hand pipe thread

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛	521002RWS	**187,00**
	R ¼	521012RWS	**177,00**
	R ⅜	521022RWS	**177,00**
	R ½	521032RWS	**177,00**
	R ¾	521042RWS	**194,00**
	R 1	521052RWS	**194,00**
	R 1¼	521062RWS	**194,00**
	R 1½	521072RWS	**194,00**
	R 2	521082RWS	**194,00**
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛ LH	521102RWS	**225,00**
	R ¼ LH	521112RWS	**213,00**
	R ⅜ LH	521122RWS	**213,00**
	R ½ LH	521132RWS	**213,00**
	R ¾ LH	521142RWS	**233,00**
	R 1 LH	521152RWS	**233,00**
	R 1¼ LH	521162RWS	**233,00**
	R 1½ LH	521172RWS	**233,00**
	R 2 LH	521182RWS	**231,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT ⅛	521202RWS	**187,00**
	NPT ¼	521212RWS	**177,00**
	NPT ⅜	521222RWS	**177,00**
	NPT ½	521232RWS	**177,00**
	NPT ¾	521242RWS	**194,00**
	NPT 1	521252RWS	**194,00**
	NPT 1¼	521262RWS	**194,00**
	NPT 1½	521272RWS	**194,00**
	NPT 2	521282RWS	**194,00**
Threads M for electric conduit EN 60423	M 16 × 1.5	521302RWS	**233,00**
	M 20 × 1.5	521312RWS	**233,00**
	M 25 × 1.5	521322RWS	**233,00**
	M 32 × 1.5	521332RWS	**233,00**
	M 40 × 1.5	521342RWS	**233,00**
	M 50 × 1.5	521352RWS	**232,00**

German Quality Product

All prices excl. VAT



Attachment heads

Attachment heads for incorporating standard, round button dies of all thread types. Locking of button dies to the attachment head with stud bolt.

Description	Size	Art.-No.	KM
Attachment head for button dies	Ø 65 mm	731200	**309,00**
Attachment head for button dies	G 1¼	731250	**322,00**
Attachment head for button dies	Ø 105 mm	541401	**397,00**

Intermediate rings

Intermediate rings for different outside diameters of button dies.

Description	Size	I.D. mm	Art.-No.	KM
Intermediate rings to attachment head 731200	M 6–9	20/25	731205	**173,00**
	M 10–11	30	731210	**173,00**
	M 12–14 (Pg 7–9)	38	731220	**173,00**
	M 16–20 (Pg 11–13,5)	45	731230	**173,00**
	M 22–24 (Pg 16)	55	731240	**173,00**
without intermediate ring	M 27–30 (Pg 21–29)	65		
Intermediate rings to attachment head 541401 without intermediate ring	Ø 65/105 (Pg 21–29)	65	541404	**196,00**
	Ø 75/105	75	541406	**196,00**
	Ø 90/105 (Pg 36)	90	541410	**196,00**
	Pg 42–48	105		

Guide bushings

Guide bushings for easy and concentric start-cutting.

Description	Size	Art.-No.	KM
Guide bushings to attachment head 731200	Ø 6	731301	**54,60**
	Ø 8	731302	**54,60**
	Ø 10	731303	**54,60**
	Ø 12	731304	**54,60**
	Ø 14	731305	**54,60**
	Ø 16	731306	**54,60**
	Ø 18	731307	**54,60**
	Ø 20	731308	**54,60**
	Ø 22	731309	**54,60**
	Ø 24	731310	**54,60**
	Ø 27	731311	**54,60**
	Ø 30	731312	**54,60**
	Ø 12.8 (Pg 7)	731320	**54,60**
	Ø 15.5 (Pg 9)	731321	**54,60**
	Ø 18.9 (Pg 11)	731322	**54,60**
	Ø 20.7 (Pg 13.5)	731323	**54,60**
	Ø 22.8 (Pg 16)	731324	**54,60**
	Ø 28.6 (Pg 21)	731325	**54,60**
	Ø 37.3 (Pg 29)	731326	**54,60**
Guide bushings to attachment head 541401	Ø 28.6 (Pg 21)	541413	**63,00**
	Ø 37.3 (Pg 29)	541414	**63,00**
	Ø 47.3 (Pg 36)	541415	**63,00**
	Ø 54.3 (Pg 42)	541416	**63,00**

German Quality Product

REMS Tornado

Threading machine

Proven high performance machine for threading, cutting, deburring, threading of nipples, roll grooving.
For installation, metalworking, industry.
For job site and workshop.

Pipe threads	(1/16) 1/8 – 2", 16 – 63 mm
Bolt threads	(6) 10 – 60 mm, 1/4 – 2"
Thread types see page 40.	
Pipe grooving with REMS roll grooving attachment	DN 25 – 200 1 – 8"

REMS Tornado – a class of its own.
Automatic chuck. Universal automatic die head.
Automatic lubrication and cooling.

Operating principle
Rotating material - stationary tools.

Design
Robust, job site-proven. Favourable size and weight, e.g. REMS Tornado 2000 complete only 50 kg. Large work and chip compartment. Easy handling of chip tray. Adjustable height material support.
2 versions:
- Portable version with 3 tubular legs, with removable large oil basin and chip tray.
- Version T with integrated, even larger oil basin and chip tray. For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive
Extremely powerful and fast, e.g. R 2" thread in only 15 s.
Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:
- Strong universal motor, 1700 W. verload protection. Spindle speed 53 rpm.
- Pole-reversible capacitor motor, 2100 W. Overload protection. 2 spindle speeds 52 and 26 rpm, also under full load. **Extremely quiet running.**
- Pole-reversible 3~induction motor, 2000 W. Overload protection. 2 spindle speeds 52 and 26 rpm, also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step. Foot switch, can be loaded with the full body weight during operation.

Automatic chuck
2 automatic chucks with self-centering clamping jaws for easy and fast clamping and release of the material. Self-tightening, hence maximum clamping force. No slipping of pipes. Collets are available for clamping pipes < Ø 1/8" and bolts < Ø 10 mm.

Automatic lubrication and cooling
Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head
Only **one** universal automatic die head for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads. Fast and easy adjustment of thread size. Easy-to-read thread-size scale. Simple and fast change of dies through lock-in positioning in die holder.

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter
Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer
Robust, easy-to-handle deburring device with adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with the automatic internal clamping REMS Nippelfix 1/2 – 2" (4") or with the manual internal clamping REMS Nippelspanner 3/8 – 2" (page 46).

German Quality Product

Info

Choice of 3 powerful motors.

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25 – 300, 1 – 12" (page 48).
Roll grooving with REMS Tornado up to DN 200, 8".

Version T

Wheel stand (accessory)

Supply format

REMS Tornado. Threading machine for pipe threads (1/16) 1/8 – 2", 16 – 63 mm, bolt threads (6) 10 – 60 mm, 1/4 – 2". With maintenance-free gear, safety foot switch with emergency-stop, 2 automatic chucks, automatic lubrication and cooling. With tool set consisting of one universal automatic die head for all threads, also long threads, automatic opening, with automatic thread-length-stop for tapered threads. Dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R 1/2 – 3/4" and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever, adjustable height material support. Choice of 3 motors. Portable version with 3 tubular legs, with removable, large oil and chip tray. Version T with integrated, even bigger oil tray and chip tray, for workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version	Art.-No.	KM
2000	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 53 rpm. Portable, 3 legs.	340200R220	**9.430,00**
2010	Pole-reversible capacitor, motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs.	340201R220	**9.700,00**
2020	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs.	340202R380	**10.160,00**
2000 T	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 53 rpm For work bench, stand or wheel stand.	340206R220	**11.420,00**
2010 T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand.	340207R220	**11.700,00**
2020 T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand.	340208R380	**12.160,00**

Other voltages and NPT versions on request.

Version T

Collapsible wheel stand (Accessory)

Accessories

Description	Art.-No.	KM
Stand	344105R	**588,00**
Wheel stand with material shelf	344100R	**998,00**
Collapsible wheel stand	344150R	**1.430,00**
Dies see page 40.		
Universal automatic die head 1/16 – 2" quick-change die head instead of changing the dies	341000RR	**1.580,00**
REMS cutter wheel St 1/8 – 4", s 8	341614R	**31,30**
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	**4.540,00**

Robust, compact high performance machine for threading, cutting, deburring, threading of nipples, roll grooving. For installation, metalworking, industry. For job site and workshop.

Pipe threads	(1/16) 1/8 – 2", 16 – 63 mm
Bolt threads	(6) 8 – 60 mm, 1/4 – 2"
Thread types see page 40.	
Grooving of pipes with REMS roll grooving attachment	DN 25 – 300 1 – 12"

German Quality Product

Info

REMS Magnum – the compact up to 2".

Operating principle
Rotating material – stationary tools.

Design
Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 2000 L-T only 62 kg. Large work and chip compartment. Tool support.
2 versions:
- Light version L-T with removable large oil basin and chip tray.
- Version T with integrated, even larger oil basin and chip tray.

For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive
Extremely powerful and fast, e.g. thread R 2" in only 15 s.
Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:
- Strong universal motor, 1700 W.
  Overload protection. Spindle speed 53 rpm.
- Pole-reversible capacitor motor, 2100 W.
  Overload protection. 2 spindle speeds 52 and 26 rpm, also under full load. **Extremely quiet running.**
- Pole-reversible 3~ induction motor, 2000 W.
  Overload protection. 2 spindle speeds 52 and 26 rpm, also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step. Foot switch, can be loaded with the full body weight during operation.

Chuck
Proven quick-action hammer chuck, self-tightening. No slipping of pipes. Large space between chuck and centering device ensures secure clamping of long pipes. Rear centering device for alignment of the material. Collets are available for clamping pipes < Ø 1/8" and bolts < Ø 8 mm.

Automatic lubrication and cooling
Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head
Only **one** universal automatic die head for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads. Fast and easy adjustment of thread size. Simple and fast change of dies through lock-in positioning in die holder.

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter
Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer
Robust, easy-to-handle deburring device for adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with automatic internal clamping REMS Nippelfix 1/2 – 2" (4") or with manual internal clamping REMS Nippelspanner 3/8 – 2" (page 46).

REMS roll grooving attachment
Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25 – 300, 1 – 12" (page 48).

Choice of 3 powerful motors.

Version L-T

Stand
(Accessory)

Version T

Wheel stand
(accessory)

Supply format

REMS Magnum. Threading machine for pipe threads (1/16) 1/8 – 2", 16 – 63 mm, bolt thread (6) 8 – 60 mm, 1/4 – 2". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling. With complete tool set consisting of one universal automatic die head for all threads, also long threads; automatic opening, with automatic thread-length-stop for tapered threads, dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R 1/2 – 3/4" and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever. Tool support. Choice of 3 motors. Version L-T with removable large oil basin and chip tray. Version T with integrated, even bigger oil tray and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version	Art.-No.	KM
2000 L-T	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 53 rpm.	340226R220	**9.530,00**
2010 L-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running.	340227R220	**10.350,00**
2020 L-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running.	340228R380	**10.670,00**
2000 T*	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 53 rpm.	340220R220	**11.420,00**
2010 T*	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running.	340221R220	**12.240,00**
2020 T*	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running.	340222R380	**12.560,00**

Other voltages and NPT versions on request.
*T versions with REMS roll grooving device for roll grooving can only be used up to DN 200, 8".

Version L-T

Collapsible wheel stand
(Accessory)

Accessories

Description	Art.-No.	KM
Stand	344105R	**588,00**
Wheel stand with material shelf	344100R	**998,00**
Collapsible wheel stand	344150R	**1.430,00**
Dies see page 40.		
Universal automatic die head 1/16 – 2" quick-change die head instead of changing the dies	341000RR	**1.580,00**
Changeover valve, for reversing flow direction of the coolant-lubricant pump for cutting left-handed threads with REMS Magnum 2010, 2020, 3010, 3020, 4010 and 4020	342080RX	**290,00**
REMS cutter wheel St 1/8 – 4", s 8	341614R	**31,30**
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	**4.540,00**

Robust, compact high performance machine for threading, cutting, deburring, threading of nipples, roll grooving. For installation, metalworking, industry. For job site and workshop.

Pipe threads	(1/16) ½ – 3", 16 – 63 mm
Bolt threads	(6) 18 – 60 mm, ½ – 2"
Thread types see page 40.	
Pipe grooving with REMS roll grooving attachment	DN 25 – 300 1 – 12"

REMS Magnum – the super machine up to 3". Exceptionally round and clean threads up to 3" by using 5 threading dies.

Operating principle
Rotating material – stationary tools.

Design
Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 3000 L-T only 79 kg. Large work and chip compartment. Tool support.
2 versions:
– Light version L-T with removable large oil basin and chip tray.
– Version T with integrated, even larger oil basin and chip tray.
For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive
Extremely powerful and fast. Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:
– Strong universal motor, 1700 W.
  Overload protection. Spindle speed 23 rpm.
– Pole-reversible capacitor motor, 2100 W.
  Overload protection. 2 spindle speeds 20 and 10 rpm, also under full load. **Extremely quiet running.**
– Pole-reversible 3~ induction motor, 2000 W.
  Overload protection. 2 spindle speeds 20 and 10 rpm, also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step.
Foot switch,can be loaded with the full body weight during operation.

Chuck
Proven quick-action hammer chuck, self-tightening. No slipping of pipes. Large space between chuck and centering device ensures secure clamping of long pipes. Rear centering device for alignment of the material. Collets are available for clamping pipes < Ø ½" and bolts < Ø 18 mm.

Automatic lubrication and cooling
Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head
Only 1 universal automatic die head each for the sizes 1/16 – 2" and 2½ – 3" for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads. 5 dies 2½ – 3" ensure a favourable distribution of the cutting force onto the pipe, hence round and clean threads. Fast and easy adjustment of thread size. Simple and fast change of dies through lock-in positioning in die holder.

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter
Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer
Robust, easy-to-handle deburring device for adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Tool sets
For 2½ – 3" and ½ – 2" one complete tool set each adapted to the work range with universal die head, pipe cutter, inner-pipe-deburring device, pressing lever, dies.

German Quality Product

Info

Choice of 3 powerful motors.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with automatic internal clamping REMS Nippelfix ½ – 3" (4") or with manual internal clamping REMS Nippelspanner (page 46).

REMS roll grooving attachment
Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25 – 300, 1 – 12" (page 48).

Supply format

REMS Magnum. Threading machine for pipe threads (1/16) ½ – 3", 16 – 63 mm, bolt threads (6) 18 – 60 mm, ½ – 2". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling. With tool sets 1/16 – 2" and/or 2½ – 3", each consisting of universal automatic die head for all threads, also long threads; automatic opening, with automatic thread-length-stop for tapered threads, dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand, pipe cutter, inner pipe deburrer, pressing lever. Tool support. Choice of 3 motors. Version L-T with removable large oil basin and chip tray. Version T with integrated, even larger oil basin and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version/Equipment	Art.-No.	KM
3000 L-T	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 23 rpm.		
	Equipment R 2½ – 3	380303R220	**11.380,00**
	Equipment R ½ – 3	380309R220	**14.010,00**
3010 L-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 3	380304R220	**11.990,00**
	Equipment R ½ – 3	380310R220	**14.610,00**
3020 L-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 3	380305R380	**12.430,00**
	Equipment R ½ – 3	380311R380	**15.050,00**
3000 T*	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 23 rpm.		
	Equipment R 2½ – 3	380306R220	**13.270,00**
	Equipment R ½ – 3	380312R220	**15.890,00**
3010 T*	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 3	380307R220	**13.880,00**
	Equipment R ½ – 3	380313R220	**16.500,00**
3020 T*	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 3	380308R380	**14.320,00**
	Equipment R ½ – 3	380314R380	**16.940,00**

Other voltages and NPT versions on request.
*T versions with REMS roll grooving device for roll grooving can only be used up to DN 200, 8".

Accessories

Description	Art.-No.	KM
Stand	344105R	**588,00**
Wheel stand with material shelf	344100R	**998,00**
Collapsible wheel stand	344150R	**1.430,00**
Dies see page 40.		
Tool set R ½ – 2" complete with universal automatic die head 1/16 – 2", dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R ½ – ¾" and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever.	340100RR	**2.630,00**
Universal automatic die head 1/16 – 2" and others	341000RR	**1.580,00**
Universal automatic die head 2½ – 3"	381050R	**2.080,00**
Universal automatic die head 2½ – 4"	381000R	**3.680,00**
Changeover valve, for reversing flow direction of the coolant-lubricant pump for cutting left-handed threads with REMS Magnum 2010, 2020, 3010, 3020, 4010 and 4020	342080RX	**290,00**
REMS cutter wheel St ⅛ – 4", s 8	341614R	**31,30**
REMS cutter wheel St 1 – 4", s 12	381622R	**72,00**
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	**4.540,00**

Robust, compact high performance machine for threading, cutting, deburring, threading of nipples, roll grooving. For installation, metalworking, industry. For job site and workshop.

Pipe threads	(1⁄16) ½ – 4", 18 – 63 mm
Bolt threads	(6) 20 – 60 mm, ½ – 2"
Thread types see page 40.	
Pipe grooving with REMS roll grooving attachment	DN 25 – 300 1 – 12"

REMS Magnum – the super machine up to 4". Exceptionally round and clean threads up to 4" by using 6 threading dies.

Operating principle
Rotating material - stationary tools.

Design
Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 4000 L-T only 81 kg. Large work and chip compartment. Tool support.
2 versions:
– Light version L-T with removable large oil basin and chip tray.
– Version T with integrated, even larger oil basin and chip tray.
For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive
Extremely powerful and fast. Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:
– Strong universal motor, 1700 W.
  Overload protection. Spindle speed 23 rpm.
– Pole-reversible capacitor motor, 2100 W.
  Overload protection. 2 spindle speeds 20 and 10 rpm, also under full load. **Extremely quiet running.**
– Pole-reversible 3~ induction motor, 2000 W.
  Overload protection. 2 spindle speeds 20 and 10 rpm, also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step. Foot switch, can be loaded with the full body weight during operation.

Chuck
Proven quick-action hammer chuck, self-tightening. No slipping of pipes. Large space between chuck and centering device ensures secure clamping of long pipes. Rear centering device for alignment of the material. Collets are available for clamping pipes < Ø ½" and bolts < Ø 18 mm.

Automatic lubrication and cooling
Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head
Only 1 universal automatic die head each for the sizes 1⁄16 – 2" and 2½ – 4" for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads. 6 dies 2½ – 4" ensure a favourable distribution of the cutting force onto the pipe, hence round and clean threads. Fast and easy adjustment of thread size. Simple and fast change of dies through lock-in positioning in die holder.

Dies
The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter
Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer
Robust, easy-to-handle deburring device for adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Tool sets
For 2½ – 4" and ½ – 2" one complete tool set each adapted to the work range with universal die head, pipe cutter, inner-pipe-deburring device, pressing lever, dies.

German Quality Product

Info

Choice of 3 powerful motors.

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with automatic internal clamping REMS Nippelfix ½ – 4"
or with manual internal clamping REMS Nippelspanner ⅜ – 2" (page 46).

REMS roll grooving attachment
Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25 – 300, 1 – 12" (page 48).

Supply format

REMS Magnum. Threading machine for pipe threads (1/16) ½ – 4", 16 – 63 mm, bolt threads (6) 18 – 60 mm, ½ – 2". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling. With tool sets 1/16 – 2" and/or 2½ – 4", each consisting of universal automatic die head for all threads, also long threads; automatic opening, with automatic thread-length-stop for tapered threads, dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand, pipe cutter, inner pipe deburrer, pressing lever. Tool support. Choice of 3 motors. Version L-T with removable large oil basin and chip tray. Version T with integrated, even larger oil basin and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version/Equipment	Art.-No.	KM
4000 L-T	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 23 rpm.		
	Equipment R ½ – 2	380447R220	**10.920,00**
	Equipment R 2½ – 4	380441R220	**13.080,00**
	Equipment R ½ – 4	380444R220	**15.710,00**
4010 L-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R ½ – 2	380448R220	**11.530,00**
	Equipment R 2½ – 4	380442R220	**13.690,00**
	Equipment R ½ – 4	380445R220	**16.310,00**
4020 L-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 4	380443R380	**14.130,00**
	Equipment R ½ – 4	380446R380	**16.760,00**
4000 T*	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 23 rpm.		
	Equipment R 2½ – 4	380426R220	**14.970,00**
	Equipment R ½ – 4	380429R220	**17.590,00**
4010 T*	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 4	380427R220	**15.580,00**
	Equipment R ½ – 4	380430R220	**18.200,00**
4020 T*	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running.		
	Equipment R 2½ – 4	380428R380	**16.020,00**
	Equipment R ½ – 4	380431R380	**18.640,00**

Other voltages and NPT versions on request.
*T versions with REMS roll grooving device for roll grooving can only be used up to DN 200, 8".

Accessories

Description	Art.-No.	KM
Stand	344105R	**588,00**
Wheel stand with material shelf	344100R	**998,00**
Collapsible wheel stand	344150R	**1.430,00**
Dies see page 40.		
Tool set R ½ – 2" complete with universal automatic die head 1/16 – 2", dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R ½ – ¾" and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever.	340100RR	**2.630,00**
Universal automatic die head 1/16 – 2" and others	341000RR	**1.580,00**
Universal automatic die head 2½ – 4"	381000R	**3.680,00**
Changeover valve, for reversing flow direction of the coolant-lubricant pump for cutting left-handed threads with REMS Magnum 2010, 2020, 3010, 3020, 4010 and 4020	342080RX	**290,00**
REMS cutter wheel St ⅛ – 4", s 8	341614R	**31,30**
REMS cutter wheel St 1 – 4", s 12	381622R	**72,00**
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	**4.540,00**

REMS dies

For REMS Tornado, REMS Magnum

REMS dies (set)

The proven REMS quality dies with precise cutting geometry ensure anexcellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for materials < 500 N/mm² (MPa) for extremely long die life.

Dies for other threads (e.g. BSW) on request. HSS dies for materials that are difficult to cut ≥ 500 N/mm² (MPa) 50 % surcharge.
[1] Some dies only available in HSS.





German Quality Product



For universal automatic die head 1/16 – 2"

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/16 – 1/8 HSS[1]	341401RHSS	**995,00**
	R 1/4 – 3/8	341402RWS	**664,00**
	R 1/2 – 3/4	341403RWS	**664,00**
	R 1 – 2	341404RWS	**664,00**
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 1/16 – 1/8	341406RWS	**756,00**
	G 1/4 – 3/8	341407RWS	**756,00**
	G 1/2 – 3/4	341408RWS	**756,00**
	G 1 – 2	341409RWS	**756,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/16 – 1/8 HSS[1]	341411RHSS	**995,00**
	NPT 1/4 – 3/8	341412RWS	**664,00**
	NPT 1/2 – 3/4	341413RWS	**664,00**
	NPT 1 – 2	341414RWS	**664,00**
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1.20.1	NPSM 1/8	341416RWS	**756,00**
	NPSM 1/4 – 3/8	341417RWS	**756,00**
	NPSM 1/2 – 3/4 HSS[1]	341418RHSS	**1.140,00**
	NPSM 1 – 2 HSS[1]	341419RHSS	**1.140,00**
Conduit threads Pg DIN 40430	Pg 7	341466RWS	**756,00**
	Pg 9	341467RWS	**756,00**
	Pg 11	341468RWS	**756,00**
	Pg 13.5	341469RWS	**756,00**
	Pg 16	341470RWS	**756,00**
	Pg 21	341471RWS	**756,00**
	Pg 29	341472RWS	**756,00**
	Pg 36	341473RWS	**756,00**
	Pg 42	341474RWS	**756,00**
	Pg 48	341475RWS	**756,00**
Conduit threads M EN 60423	M 16 × 1.5	341493RWS	**756,00**
	M 20 × 1.5	341494RWS	**756,00**
	M 25 × 1.5	341495RWS	**756,00**
	M 32 × 1.5	341496RWS	**756,00**
	M 40 × 1.5	341497RWS	**756,00**
	M 50 × 1.5	341498RWS	**756,00**
	M 63 × 1.5	341499RWS	**756,00**
Metric bolt threads M ISO 261 (DIN 13)	M 6	341426RWS	**756,00**
	M 8	341427RWS	**756,00**
	M 10	341428RWS	**756,00**
	M 12	341429RWS	**756,00**
	M 14	341430RWS	**756,00**
	M 16	341431RWS	**756,00**
	M 18	341432RWS	**756,00**
	M 20	341433RWS	**756,00**
	M 22	341434RWS	**756,00**
	M 24	341435RWS	**756,00**
	M 27	341436RWS	**756,00**
	M 30	341437RWS	**756,00**
	M 33	341438RWS	**819,00**
	M 36	341439RWS	**819,00**
	M 39	341440RWS	**819,00**
	M 42	341441RWS	**819,00**
	M 45	341442RWS	**819,00**
	M 48	341443RWS	**819,00**
	M 52	341444RWS	**819,00**
	M 56 HSS[1]	341445RHSS	**1.230,00**
	M 60 HSS[1]	341446RHSS	**1.230,00**
Bolt threads UNC Unified Inch Screw Thread ASME B1.1	UNC 1/4 – 20 HSS[1]	341476RHSS	**1.140,00**
	UNC 5/16 – 18	341477RWS	**756,00**
	UNC 3/8 – 16 HSS[1]	341478RHSS	**1.140,00**
	UNC 7/16 – 14	341479RWS	**756,00**
	UNC 1/2 – 13 HSS[1]	341480RHSS	**1.140,00**
	UNC 9/16 – 12	341481RWS	**756,00**
	UNC 5/8 – 11 HSS[1]	341482RHSS	**995,00**
	UNC 3/4 – 10 HSS[1]	341483RHSS	**995,00**
	UNC 7/8 – 9 HSS[1]	341484RHSS	**995,00**
	UNC 1 – 8 HSS[1]	341485RHSS	**995,00**
	UNC 1 1/8 – 7	341486RWS	**664,00**
	UNC 1 1/4 – 7 HSS[1]	341487RHSS	**995,00**
	UNC 1 3/8 – 6	341488RWS	**819,00**
	UNC 1 1/2 – 6 HSS[1]	341489RHSS	**1.230,00**
	UNC 1 3/4 – 5	341490RWS	**664,00**
	UNC 2 – 4.5	341491RWS	**664,00**



For universal automatic die head 2 1/2 – 3"

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 2 1/2 – 3	381430RWS	**924,00**
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 2 1/2 – 3 HSS[1]	381431RHSS	**1.500,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 2 1/2 – 3 HSS[1]	381432RHSS	**1.390,00**
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1.20.1	NPSM 2 1/2 – 3 HSS[1]	381433RHSS	**1.500,00**

For universal automatic die head 2 1/2 – 4"

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 2 1/2 – 4	381401RWS	**1.400,00**
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 2 1/2 – 4 HSS[1]	381405RHSS	**2.230,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 2 1/2 – 4 HSS[1]	381410RHSS	**2.100,00**
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1.20.1	NPSM 2 1/2 – 4 HSS[1]	381415RHSS	**2.230,00**

All prices excl. VAT

REMS
Unimat 75

REMS Unimat 75

Threading machine

Semi-automatic high-performance machine
for efficient cutting of bolt and pipe threads.
For industry, metalworking, installation.

Bolt threads		6 – 72 mm ¼ – 2¾"
Pipe threads		1/16 – 2½", 16 – 63 mm
Tolerance class corresponding to ISO 261 (DIN 13)		"medium" (6 g)
Thread length	≤ Ø 30 mm ≤ Ø 72 mm	unlimited ≤ 200 mm
Chamfering	Range Chamfered Ø Maximum chamfer Chamfer angle	7 – 62 mm ≥ 7 mm 7 mm 45°
Peeling	Range Peeled Ø	7 – 62 mm ≥ 7 mm

Thread types see page 44.

German Quality Product

REMS Unimat 75 – high efficiency. Tangential-chaser-threading-system. Large threading range. Fast working, short resetting time. For single and series production. Low hourly rate for the machine. Simple operation. Relieves expensive turning machines and specialists.

Operating principle
Stationary material – rotating die head.

Design
Compact, rugged design for continous use. Die head with regrindable tangential chasers in self centering holder system. After start-cutting with feed lever and rack mechanism self feeding action of die head (no guide thread). Welded, sturdy machine stand with large oil compartment and removeable chip drawer.

Drive
Indestructible planetary gear with annulus gear for long threads up to Ø 30 mm. Proven and powerful pole-reversible three-phase motor, specially designed for threading, with hollow shaft, 2000/2300 W. Overload protection. Reverse switch for cutting right and left-hand threads. High operating speed, 2 spindle speeds 70 and 35 rpm.

Clamping device
Self-centering universal vice for the complete range with specially toothed and hardened clamping jaws. Choice of manual or hydraulic clamping with operation by foot switch (working pressure 6 bar).

Special clamping jaws
For drawn material, stud bolts, hex screws and pipe nipples, as accessory.

Automatic lubrication and cooling
Robust, proven oil pump with high pumping volume. Ample oil volume ensures longer service life of chasers, gear and motor.

Universal automatic die head
Only **one** universal automatic die head for all threads. Fine adjustment of thread diameter with spindle and scale. Die head closes automatically and opens automatically when the required thread length is reached. After starting the thread via feed lever and rack the chaser-system initiates an automatic feed-forward of the die head. All threads can be cut in a single pass. Copying unit for tapered threads. Instead of changing the dies, additional quick-change die heads ensure shorter resetting time.

Chasers
The proven regrindable REMS tangential chasers with precise cutting geometry ensure an excellent start-cutting performance and clean threads. Tool steel chasers made of special hardened steel for material < 500 N/mm² (MPa). HSS chasers for hard-to-machine material ≥ 500 N/mm² (MPa). The chasers sit in a special holder system. Chasers and holders together form a threading set.

Thread cutting on rebar
Special chaser dies M with additional, ground cut for cutting threads on rebar in a single pass. Driven by REMS Unimat 75 with oil-hydraulic/pneumatic vice, for high clamping pressure.

Machining examples

Info

REMS Unimat 75

Thread-cutting oil
REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading
Efficient with special clamping jaws 1/16 – 1¼" or with the automatic internal clamping REMS Nippelfix ½ – 2½" or with the manual internal clamping REMS Nippelspanner ⅜ – 2" (page 46).

Supply format

REMS Unimat 75 Basic. Semi-automatic threading machine for bolt threads 6 – 72 mm, ¼ – 2¾", pipe threads 1/16 – 2½", 16 – 63 mm. Machine on stand. Pole-reversible 3~ induction motor with hollow shaft, 400 V, 50 Hz, 2000/2300 W, right and left-hand rotation. Die head speed 70 and 35 rpm. Self-centering universal chuck for the complete clamping range, choice of manual or oil-hydraulic/pneumatic operation. Automatic lubrication and cooling. 1 universal automatic die head for all threads, opens and closes automatically. Without threading sets, without closing lever. Electric locking system of safety cover. Adjustment gauge. Wrench. In transport case.

Description	Version	Art.-No.	KM
REMS Unimat 75 Basic mS	manual clamping device	750003R380	**44.420,00**
REMS Unimat 75 Basic pS	oil-hydraulic/pneumatic vice clamping device	750004R380	**52.170,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Chasers and holders (threading sets) and chasers see page 44.		
Universal automatic die head, without threading sets, without closing lever	751000	**2.730,00**
Closing lever for closing and opening the chasers		
R for taper pipe threads, right-hand	751040R90	**357,00**
R-L for taper pipe threads, left-hand	751050R90	**357,00**
G for cylindrical pipe threads, right-hand	751060R90	**357,00**
G-L for cylindrical pipe threads, left-hand	751070R90	**357,00**
M for all bolt threads, right-hand	751080R90	**357,00**
M-L for all bolt threads, left-hand	751090R90	**357,00**
Chamfering/peeling die head 45°, Ø 7 – 62 mm, with chamfering/peeling chasers 45°, Ø 7 – 62 mm, HSS, with holder	751100	**6.710,00**
Chamfering/peeling die head 45°, Ø 7 – 62 mm, without threading sets	751102	**2.840,00**
Chamfering/peeling chasers 45°, Ø 7 – 46 mm, HSS, with holder	751096	**1.940,00**
Chamfering/peeling chasers 45°, Ø 40 – 62 mm, HSS, with holder	751098	**1.940,00**
Chamfering/peeling chasers 45°, Ø 7 – 62 mm, pack of 4, with holder	751097	**1.120,00**
Special clamping jaws, pair, for drawn material, stud bolts and hex screws. Workpiece length protrude from vice without thread, minimum 15 mm, Ø 6 – 42 mm	753240	**2.900,00**
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		

German Quality Product



German Quality Product

Chasers and holders (threading set)

The proven regrindable REMS tangential chasers with precise cutting geometry ensure an excellent start-cutting performance and clean threads. Tool steel chasers made of special hardened steel for material < 500 N/mm² (MPa). HSS chasers for hard-to-machine material ≥ 500 N/mm² (MPa). The chasers sit in a special holder system. Chasers and holders together form a threading set.

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/16 – 1/8	759250 RWS	**1.660,00**
	R 1/4 – 3/8	759251 RWS	**1.660,00**
	R 1/2 – 3/4	759252 RWS	**1.660,00**
	R 1 – 2	759253 RWS	**1.660,00**
	R 2 1/2	759254 RWS	**1.660,00**
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 1/16 – 1/8	759255 RWS	**1.660,00**
	G 1/4 – 3/8 HSS[1]	759256 RHSS	**2.040,00**
	G 1/2 – 3/4 HSS[1]	759257 RHSS	**2.040,00**
	G 1 – 2 HSS[1]	759258 RHSS	**2.040,00**
	G 2 1/2 HSS[1]	759259 RHSS	**2.040,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1. 20.1	NPT 1/16 – 1/8	759360 RWS	**1.660,00**
	NPT 1/4 – 3/8 HSS[1]	759361 RHSS	**2.040,00**
	NPT 1/2 – 3/4 HSS[1]	759362 RHSS	**2.040,00**
	NPT 1 – 2 HSS[1]	759363 RHSS	**2.040,00**
	NPT 2 1/2 HSS[1]	759364 RHSS	**2.040,00**
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1. 20.1	NPSM 1/16 – 1/8	759365 RWS	**1.660,00**
	NPSM 1/4 – 3/8	759366 RWS	**1.660,00**
	NPSM 1/2 – 3/4 HSS[1]	759367 RHSS	**2.040,00**
	NPSM 1 – 2 HSS[1]	759368 RHSS	**2.040,00**
Conduit threads Pg DIN 40430	Pg 7	759260 RWS	**1.660,00**
	Pg 9 – 16	759261 RWS	**1.660,00**
	Pg 21 – 48	759262 RWS	**1.660,00**
Conduit threads M EN 60423	M 16 – 20 × 1.5	759263 RWS	**1.660,00**
	M 25 – 32 × 1.5	759264 RWS	**1.660,00**
	M 40 – 50 × 1.5	759265 RWS	**1.660,00**
	M 63 × 1.5 HSS[1]	759330 RHSS	**2.040,00**
Threads M for rebar ISO 261 (DIN 13)	M 14 – 16 HSS	759274 RHSSZ	**2.040,00**
	M 18 – 22 HSS	759275 RHSSZ	**2.040,00**
	M 24 – 27 HSS	759276 RHSSZ	**2.040,00**
	M 30 – 33 HSS	759277 RHSSZ	**2.040,00**
	M 36 – 39 HSS	759278 RHSSZ	**2.280,00**
	M 42 – 45 HSS	759279 RHSSZ	**2.280,00**
Metric bolt threads M ISO 261 (DIN 13)	M 6 HSS[1]	759270 RHSS	**2.040,00**
	M 8	759271 RWS	**1.660,00**
	M 10	759272 RWS	**1.660,00**
	M 12	759273 RWS	**1.660,00**
	M 14 – 16	759274 RWS	**1.660,00**
	M 18 – 22	759275 RWS	**1.660,00**
	M 24 – 27	759276 RWS	**1.660,00**
	M 30 – 33	759277 RWS	**1.660,00**
	M 36 – 39	759278 RWS	**1.830,00**
	M 42 – 45	759279 RWS	**1.830,00**
	M 48 – 52 HSS[1]	759280 RHSS	**2.280,00**
	M 56 – 60 HSS[1]	759281 RHSS	**2.280,00**
	M 64 – 72 HSS[1]	759282 RHSS	**2.280,00**
Bolt threads UNC Unified Inch Screw Thread ASME B1.1	UNC 1/4 – 20	759370 RWS	**1.660,00**
	UNC 5/16 – 18	759371 RWS	**1.660,00**
	UNC 3/8 – 16	759372 RWS	**1.660,00**
	UNC 7/16 – 14	759373 RWS	**1.660,00**
	UNC 1/2 – 13	759374 RWS	**1.660,00**
	UNC 9/16 – 12	759375 RWS	**1.660,00**
	UNC 5/8 – 11	759376 RWS	**1.660,00**
	UNC 3/4 – 10	759377 RWS	**1.660,00**
	UNC 7/8 – 9	759378 RWS	**1.660,00**
	UNC 1 – 8 HSS[1]	759379 RHSS	**2.040,00**
	UNC 1 1/8 – 1 1/4 – 7	759380 RWS	**1.660,00**
	UNC 1 3/8 – 1 1/2 – 6	759381 RWS	**1.830,00**
	UNC 1 3/4 – 5	759382 RWS	**1.830,00**
	UNC 2 – 2 1/4 – 4.5	759383 RWS	**1.830,00**
	UNC 2 1/2 – 2 3/4 – 4	759384 RWS	**1.830,00**

Dies for other threads (e.g. bicycle threads, fine threads, BSW) and HSS chaser dies for materials above 500 N/mm² (MPa) that are difficult to cut on request. Dies with HSS chaser dies with 50% surcharge on chaser dies. [1] Some chasers only available in HSS. Threading sets for left-hand threads 50 % extra charge on chasers.

Chasers (set)

The proven regrindable REMS tangential chasers with precise cutting geometry ensure an excellent start-cutting performance and clean threads. Tool steel chasers made of special hardened steel for material < 500 N/mm² (MPa). HSS chasers for hard-to-machine material ≥ 500 N/mm² (MPa).

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/16 – 1/8	751501 RWS	**756,00**
	R 1/4 – 3/8	751502 RWS	**756,00**
	R 1/2 – 3/4	751503 RWS	**756,00**
	R 1 – 2 1/2	751504 RWS	**756,00**
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 1/16 – 1/8 HSS[1]	751505 RHSS	**1.140,00**
	G 1/4 – 3/8	751506 RHSS	**1.140,00**
	G 1/2 – 3/4 HSS[1]	751507 RHSS	**1.140,00**
	G 1 – 2 1/2 HSS[1]	751508 RHSS	**1.140,00**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1. 20.1	NPT 1/16 – 1/8	751544 RWS	**756,00**
	NPT 1/4 – 3/8 HSS[1]	751545 RHSS	**1.140,00**
	NPT 1/2 – 3/4 HSS[1]	751546 RHSS	**1.140,00**
	NPT 1 – 2 HSS[1]	751547 RHSS	**1.140,00**
	NPT 2 1/2 HSS[1]	751548 RHSS	**1.140,00**
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1. 20.1	NPSM 1/16 – 1/8	751549 RWS	**756,00**
	NPSM 1/4 – 3/8	751550 RWS	**756,00**
	NPSM 1/2 – 3/4 HSS[1]	751551 RHSS	**1.140,00**
	NPSM 1 – 2	751552 RWS	**756,00**
Conduit threads Pg DIN 40430	Pg 7	751509 RWS	**756,00**
	Pg 9 – 16	751510 RWS	**756,00**
	Pg 21 – 48	751511 RWS	**756,00**
Conduit threads M EN 60423	M 16 – 63 × 1.5 (M 10)	751518 RWS	**756,00**
Threads M for rebar ISO 261 (DIN 13)	M 14 – 16 HSS	751520 RHSSZ	**1.140,00**
	M 18 – 22 HSS	751521 RHSSZ	**1.140,00**
	M 24 – 27 HSS	751522 RHSSZ	**1.140,00**
	M 30 – 33 HSS	751523 RHSSZ	**1.140,00**
	M 36 – 39 HSS	751524 RHSSZ	**1.360,00**
	M 42 – 45 HSS	751525 RHSSZ	**1.360,00**
Metric bolt threads M ISO 261 (DIN 13)	M 6	751516 RHSS	**1.140,00**
	M 8	751517 RWS	**756,00**
	M 10 (M 16 – 63 × 1.5)	751518 RWS	**756,00**
	M 12	751519 RWS	**756,00**
	M 14 – 16	751520 RWS	**756,00**
	M 18 – 22	751521 RWS	**756,00**
	M 24 – 27	751522 RWS	**756,00**
	M 30 – 33	751523 RWS	**756,00**
	M 36 – 39	751524 RWS	**903,00**
	M 42 – 45	751525 RWS	**903,00**
	M 48 – 52	751526 RWS	**903,00**
	M 56 – 60	751527 RWS	**903,00**
	M 64 – 72	751528 RWS	**903,00**
Bolt threads UNC Unified Inch Screw Thread ASME B1.1	UNC 1/4 – 20	751557 RWS	**756,00**
	UNC 5/16 – 18	751558 RWS	**756,00**
	UNC 3/8 – 16	751559 RWS	**756,00**
	UNC 7/16 – 14	751560 RWS	**756,00**
	UNC 1/2 – 13	751561 RWS	**756,00**
	UNC 9/16 – 12	751562 RWS	**756,00**
	UNC 5/8 – 11	751563 RWS	**756,00**
	UNC 3/4 – 10	751564 RWS	**756,00**
	UNC 7/8 – 9	751565 RWS	**756,00**
	UNC 1 – 8 HSS[1]	751566 RHSSZ	**1.140,00**
	UNC 1 1/8 – 1 1/4 – 7	751567 RWS	**756,00**
	UNC 1 3/8 – 1 1/2 – 6	751568 RWS	**903,00**
	UNC 1 3/4 – 5	751569 RWS	**903,00**
	UNC 2 – 2 1/4 – 4.5	751570 RWS	**903,00**
	UNC 2 1/2 – 2 3/4 – 4	751571 RWS	**903,00**

Chaser dies for other threads (e.g. bicycle threads, fine threads, BSW) and HSS chaser dies for materials above 500 N/mm² (MPa) that are difficult to cut on request. HSS chaser dies with 50% surcharge. [1] Some chasers only available in HSS. Chasers for left-hand threads 50 % extra charge.

Thread tables

Taper Pipe Threads

Whitworth Pipe Thread
ISO 7-1, EN 10226 (DIN 2999, BSPT)
External thread taper 1:16
Flank angle 55°

Nominal Size **R BSPT**	Outside Ø of thread mm	T.P.I.
1/16	7.723	28
1/8	9.728	28
1/4	13.157	19
3/8	16.662	19
1/2	20.955	14
3/4	26.441	14
1	33.249	11
1 1/4	41.910	11
1 1/2	47.803	11
2	59.614	11
2 1/2	75.184	11
3	87.884	11
4	113.030	11

Standard Taper Pipe Thread
NPT, ASME B 1.20.1
External thread taper 1:16
Flank angle 60°

Nominal Size **NPT**	Outside Ø of thread mm	T.P.I.
1/16	7.938	27
1/8	10.287	27
1/4	13.716	18
3/8	17.145	18
1/2	21.336	14
3/4	26.670	14
1	33.401	11.5
1 1/4	42.164	11.5
1 1/2	48.260	11.5
2	60.325	11.5
2 1/2	73.025	8
3	88.900	8
3 1/2	101.600	8
4	114.300	8

Parallel PipeThreads

Whitworth Pipe Thread
ISO 228-1 (DIN 259, BSPP)
External thread parallel
Flank angle 55°

Nominal Size **G BSPP**	Outside Ø of thread mm	T.P.I.
1/16	7.723	28
1/8	9.728	28
1/4	13.157	19
3/8	16.662	19
1/2	20.955	14
3/4	26.441	14
1	33.249	11
1 1/4	41.910	11
1 1/2	47.803	11
2	59.614	11
2 1/2	75.184	11
3	87.884	11
3 1/2	100.330	11
4	113.030	11

Straight Pipe Thread for Fixtures
NPSM, ASME B 1.20.1
External thread parallel
Flank angle 60°

Nominal Size **NPSM**	Outside Ø of thread mm	T.P.I.
1/8	10.083	27
1/4	13.360	18
3/8	16.815	18
1/2	20.904	14
3/4	26.264	14
1	32.842	11.5
1 1/4	41.605	11.5
1 1/2	47.676	11.5
2	59.715	11.5
2 1/2	72.161	8
3	88.062	8
3 1/2	100.787	8
4	113.436	8

Metric Bolt Thread

Metric ISO Thread
ISO 261 (DIN 13)
External thread
Flank angle 60°

Nominal Size **M**	Outside Ø of thread mm	Pitch mm
6	5.974	1
8	7.972	1.25
10	9.968	1.5
12	11.966	1.75
14	13.962	2
16	15.962	2
18	17.958	2.5
20	19.958	2.5
22	21.958	2.5
24	23.952	3
27	26.952	3
30	29.947	3.5
33	32.947	3.5
36	35.940	4
39	38.940	4
42	41.937	4.5
45	44.937	4.5
48	47.929	5
52	51.929	5
56	55.925	5.5
60	59.925	5.5
64	63.920	6
68	67.920	6
72	71.920	6

American and British Bolt Threads

Unified Inch Screw Thread
UNC, ASME B 1.1
External thread
Flank angle 60°

Nominal Size **UNC**	Outside Ø of thread mm	T.P.I.
1/4	6.322	20
5/16	7.907	18
3/8	9.491	16
7/16	11.076	14
1/2	12.661	13
9/16	14.246	12
5/8	15.834	11
3/4	19.004	10
7/8	22.176	9
1	25.349	8
1 1/8	28.519	7
1 1/4	31.694	7
1 3/8	34.864	6
1 1/2	38.039	6
1 3/4	44.381	5
2	50.726	4.5
2 1/4	57.076	4.5
2 1/2	63.421	4
2 3/4	69.768	4

British Standard Parallel Screw Thread of Whitworth Form B.S.W.
BS 84 (obsolete): External thread
Flank angle 55°

Nominal Size **BSW**	Outside Ø of thread mm	T.P.I.
1/4	6.350	20
5/16	7.937	18
3/8	9.525	16
7/16	11.112	14
1/2	12.700	12
5/8	15.875	11
3/4	19.050	10
7/8	22.225	9
1	25.400	8
1 1/8	28.575	7
1 1/4	31.750	7
1 1/2	38.100	6
1 3/4	44.450	5
2	50.800	4.5
2 1/4	57.150	4
2 1/2	63.500	4
2 3/4	69.850	3.5

Threads for Electric Conduit

Conduit Thread
DIN 40 430
External thread parallel
Flank angle 80°

Nominal Size **Pg**	Outside Ø of thread mm	T.P.I.
7	12.5	20
9	15.2	18
11	18.6	18
13.5	20.4	18
16	22.5	18
21	28.3	16
29	37	16
36	47	16
42	54	16
48	59.3	16

Conduit Thread
EN 60423
External thread parallel
Flank angle 60°

Nominal Size **M**	Outside Ø of thread mm	Pitch mm
16	15.968	1.5
20	19.968	1.5
25	24.968	1.5
32	31.968	1.5
40	39.968	1.5
50	49.968	1.5
63	62.968	1.5

Outside diameter of thread is always the maximum diameter, for taper pipe threads this is measured at the scale line.

REMS Nippelspanner

Accessories for threading machines
and hand die stocks of all types and makes

Manual pipe nipple chuck for internal clamping
of short pipe pieces. For universal use.

Nipples and double nipples
in standard and special lengths ⅜ – 2"

German Quality Product

REMS Nippelspanner – efficient nipple-threading. Any length. Anywhere.

To be used universally for threading machines and for hand die stocks of all types and makes. For opening and non-opening die heads. Ideal accessory for REMS Amigo E, REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact, REMS Amigo 22V, REMS eva and other makes.

Ideal tool for using up short pipe pieces. Saves time and money.

Chucking and centering of pipe pieces by expanding of specially hardened spring steel segments.

Internal clamping, so no thread required for clamping.

Supply format

REMS Nippelspanner. Manual pipe nipple chuck for internal clamping of short pipe pieces.

Description	Size	Art.-No.	KM
REMS Nippelspanner	⅜"	110000R	**257,00**
	½"	110100R	**296,00**
	¾"	110200R	**338,00**
	1"	110300R	**464,00**
	1¼"	110400R	**550,00**
	1½"	110500R	**655,00**
	2"	110600R	**802,00**

Supply format

REMS Nippelspanner Set. Manual pipe nipple chuck for internal clamping of short pieces of pipe. In sturdy steel case.

Description	Art.-No.	KM
Set ½ + ¾ + 1 + 1¼"	110620R	**1.550,00**
Set ½ + ¾ + 1 + 1¼ + 1½ + 2"	110621R	**2.790,00**

REMS Nippelfix

Accessories for threading machines
with opening die head

Automatic pipe nipple chuck for internal clamping
of short pipe pieces.

Nipples and double nipples
in standard and special lengths ½ – 4"

German Quality Product

REMS Nippelfix – efficient nipple-threading up to 4". Any length. Anywhere. Automatic internal clamping. Super fast and simple.

For threading machines with opening die head: Pipe turning machines, machines with rotating die head, threading devices.

Ideal tool for using up short pipe pieces. Saves time and money.

Automatic quick-chuck and centering of pipe piece. No tools.

Automatic release after completion of nipple. Production of nipples possible without taking the Nipplefix out of the clamping device.

Internal clamping, so no thread required for clamping.

Specially hardened and ground clamping jaws for fast and safe clamping.

Supply format

REMS Nippelfix. Automatic pipe nipple chuck for internal clamping of short pipe pieces.

Description	Size	Art.-No.	KM
REMS Nippelfix	½"	111000R	**217,00**
	¾"	111100R	**259,00**
	1"	111200R	**334,00**
	1¼"	111300R	**406,00**
	1½"	111400R	**469,00**
	2"	111500R	**548,00**
	2½"	111700R	**756,00**
	3"	111800R	**977,00**
	4"	111900R	**1.050,00**

Supply format

REMS Nippelfix Set. Automatic pipe nipple chuck for internal clamping of short pieces of pipe. In sturdy steel case.

Description	Art.-No.	KM
Set ½ + ¾ + 1 + 1¼"	111620R	**1.350,00**
Set ½ + ¾ + 1 + 1¼ + 1½ + 2"	111621R	**2.220,00**

All prices excl. VAT

REMS Spezial

Thread-cutting oil

High-alloyed mineral oil based thread-cutting oil.
For all materials.

For drinking water supplies, comply with local regulations! Mineral oil based thread cutting materials are not permitted for drinking water pipes in AUT, CHE, DEU, DNK and FRA for example.

REMS Spezial – high-alloyed mineral based thread-cutting oil, can be washed out with water. High lubricating and cooling effect.

Specially developed for threading. High lubricating and cooling effect. Essential for clean threads, long service life of dies, tools and machines.

Can be washed out with water, approved by experts.

Also well suited as a cooling lubricant for sawing metals.

REMS Spezial spray without CFC's, so ozone-harmless.

REMS Spezial squirt bottle without propellants. Refillable.

German Quality Product

Supply format

REMS Spezial. High-alloyed mineral based thread-cutting oil.

Description	Packing	Art.-No.	KM
REMS Spezial	5 l can	140100R	**152,00**
	10 l can	140101R	**303,00**
	50 l barrel	140103R	**1.470,00**
	600 ml spray	140105R	**47,30**
	500 ml squirt bottle	140106R	**52,10**

REMS Sanitol

Thread-cutting oil

Synthetic, mineral oil-free thread-cutting oil.
Specially for drinking water supplies. For all materials.

REMS Sanitol – mineral oil-free, ethanol-free. Completely water soluable. High lubricating and cooling effect.

Developed especially for drinking water pipes but also excellently suitable for universal thread cutting. High lubricating and cooling effect. Essential for clean threads, long service life of dies, tools and machines.

Completely water soluable. Mineral oil-free, ethanol-free. Therefore no negative influence on the drinking water in terms of appearance, smell and taste.

Red in colour for flushing control. Perfect corrosion protector.

Viscosity at –10°C: ≤ 250 mPa s (cP). Pumpable to –28°C.

Also well suited as a cooling lubricant for sawing metals.

REMS Sanitol spray without CFC's, so ozone-harmless.

REMS Sanitol squirt bottle without propellants. Refillable.

German Quality Product

Supply format

REMS Sanitol. Synthetic, mineral oil free thread-cutting oil specially for drinking water supplies and for universal use.

Description	Packing	Art.-No.	KM
REMS Sanitol	5 l can	140110R	**353,00**
	50 l barrel	140113R	**3.360,00**
	600 ml spray	140115R	**68,70**
	500 ml squirt bottle	140116R	**75,60**

DVGW GEPRÜFT W1.303

SVGW SSIGE 7808-649

All prices excl. VAT

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic forward feed for grooving pipes of pipe coupling systems. For installation, sprinkler lines, commercial heating, industry and mining.
For job site and workshop.

Steel pipes	DN 25 – 300 1 – 12" s ≤ 7.2 mm
Stainless steel pipes, copper, aluminium, PVC pipes	

German Quality Product

Info

REMS roll grooving attachment – compact – universal. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller.

Design

Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Individually adjustable groove-depth-stop with fine adjustment, for automatic limitation of groove depth. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers

The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25 – 300, 1 – 12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54 – 159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1 – 1½", 2 – 6" and 8 – 12". Grooving rollers for aluminium, PVC pipes on request.

Drive

Only one roll grooving device for REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact, REMS Tornado and REMS Magnum. Fast, simple assembly. 3-face drive shaft of roll grooving attachment for secure clamping and optimum power transmission. Roll grooving attachments for threading machines of other makes, adjusted to support arm distance, diameter of support arm and spindle axis of the corresponding drive machine, on request.

Supply format

REMS roll grooving attachment. Roll grooving attachment for grooving pipes of pipe coupling systems DN 25 – 300, 1 – 12". Roll grooving attachment, hydraulic hand pump, built-in ring gauge for automatic groove-depth-stop, 1 pair of groove rollers (pressure roller, counter-pressure roller) 2 – 6", Allen key. For REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact, REMS Tornado and REMS Magnum or for other thread cutting machine makes. In a carton.

Description	fit onto	Art.-No.	KM
REMS roll grooving attachment	REMS Amigo/ Amigo 2 Compact[1] REMS Amigo 2[1] REMS Tornado[2] REMS Magnum[2]	347000R	**4.540,00**
Roll grooving attachment R 300	Ridgid 300	347001R	**4.540,00**

[1] Conversion kit Amigo/Amigo 2/Amigo 2 Compact (Art. No. 347007) required. Can be used for roll grooving devices manufactured from 2014 onwards.
[2] Can only be used for roll grooving up to DN 200, 8" on T versions.
Roll grooving attachments for other makes on request.

Accessories

Description	Art.-No.	KM
Grooving rollers 1 – 1½" (pair), for steel pipes	347030	**628,00**
Grooving rollers INOX 1 – 1½" (pair), for stainless steel pipes	347053	**1.520,00**
Grooving rollers 2 – 6" (pair), for steel pipes	347035	**628,00**
Grooving rollers INOX 2 – 6" (pair), for stainless steel pipes	347046	**1.710,00**
Grooving rollers 8 – 12" (set), for steel pipes	347040	**1.030,00**
Grooving rollers INOX 8 – 12" (pair), for stainless steel pipes	347047	**1.730,00**
Grooving rollers Cu 54 – 159 (pair) for Cu pipes	347034	**628,00**
Conversion kit Amigo / Amigo 2 / Amigo 2 Compact / Amigo 22V	347007R	**311,00**

REMS Herkules material supports, see page 107.

All prices excl. VAT

REMS Collum

Roll grooving machine

Powerful roll grooving machine for fast, economical grooving of pipes for pipe coupling systems.
For installation, sprinkler lines, commercial heating, industry and mining. For job site and workshop.

Steel pipes	DN 25 – 300 1 – 12" s ≤ 7.2 mm
Stainless steel pipes, copper, aluminium, PVC pipes	

REMS Collum – electrical roll grooving up to 12". Fast and economical feed of the pressure roller with oil-hydraulic pressure cylinder.

Design
Robust, compact construction suitable for building sites. Favourable dimensions, favourable weight, roll grooving device with drive machine only 31 kg. For work bench. Stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Drive
Fast and powerful, e.g. roll grooving of 6" steel pipe with REMS Collum in just 52 s. Sturdy, compact gear, maintenance-free. Robust, powerful 1200 W universal motor (REMS Collum and REMS Collum 2 Compact) or 1700 W universal motor (REMS Collum 2) for intensive use at large dimensions. Safety switch. Foot switch with coupling for ergonomic working as an accessory.

Roll grooving attachment
Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers
The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25 – 300, 1 – 12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54 – 159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1 – 1½", 2 – 6" and 8 – 12". Grooving rollers for aluminium, PVC pipes on request.

Material support
Extra sturdy REMS Herkules XL 12" material support for roll grooving of pipes up to 12" (page 107).

German Quality Product

Info

Wheel stand (Accessory)

Herkules 3B (Accessory)

Supply format

REMS Collum. Roll grooving attachment for grooving pipes of pipe coupling systems DN 25 – 300, 1 – 12". Roll grooving attachment, hydraulic hand pump, built-in ring gauge for automatic groove-depth-stop, 1 pair of groove rollers (pressure roller, counter-pressure roller) 2 – 6", Allen key. Choice of 3 drive units, with maintenance-free gear, powerful universal motor, safety switch.
For workbench, stand or wheel stand. In a carton.

Description	Version	Art.-No.	KM
Collum	Universal motor 230 V, 50 – 60 Hz, 1200 W, overload protection. 29 min^{-1}	347006R220	**5.590,00**
Collum 2	Universal motor 230 V, 50 – 60 Hz, 1700 W. 28 min^{-1}	347008R220	**6.260,00**
Collum 2 Compact	Universal motor 230 V, 50 – 60 Hz, 1200 W, overload protection. 26 min^{-1}	347009R220	**6.260,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Stand	849315R	**439,00**
Wheel stand	849310R	**712,00**
Foot switch with coupling	347010R220	**504,00**
REMS Herkules material supports, see page 107.		
Grooving rollers and other accessories, see page 48.		

REMS Collum 22 V

Cordless roll grooving machine

Powerful, mobile, cordless roll grooving machine for fast, economical grooving of pipes for pipe coupling systems. For installation, sprinkler lines, commercial heating, industry and mining. For job site and workshop. Li-Ion 22 V Technology. For battery and corded operation.

Steel pipes	DN 25 – 300 1 – 12" s ≤ 7.2 mm
Stainless steel pipes, copper, aluminium, PVC pipes	

REMS Collum 22 V – electrical roll grooving up to 12". Mobile, fast, economical. Feed of the pressure roller with oil-hydraulic pressure cylinder. Li-Ion 21.6 V, 9.0 Ah battery, for approx. 23 DN 100/4" grooves with one battery charge*.

Design

Compact, robust, building site-compatible, mobile. Convenient dimensions, comfortable weight, cordless roll grooving machine with drive unit just 34 kg. Practical D-shaped handle with soft grip. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check by a 2-coloured green/red LED. For work bench. Stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Powerful and fast, e.g. roll grooving of 4" steel pipe in just 77 s. Solid, maintenance-free gear. Powerful battery motor 21.6 V, with high power reserve, 500 W output, for intensive use with large dimensions. High grooving speed 27 – 20 rpm. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V batteries with 9.0 Ah capacity for long service life. Light and powerful, for approx. 23 DN 100/4" grooves with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Roll grooving attachment

Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers

The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25 – 300, 1 – 12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54 – 159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1 – 1½", 2 – 6" and 8 – 12". Grooving rollers for aluminium, PVC pipes on request.

Material support

Extra sturdy REMS Herkules XL 12" material support for roll grooving of pipes up to 12" (page 107).

German Quality Product

Info

REMS Collum 22 V

Cordless roll grooving machine

Wheel stand (Accessory)

Herkules 3B (Accessory)

Stand (Accessory)

Herkules XL 12" (Accessory)

Supply format

REMS Collum 22 V. Cordless roll grooving machine for grooving pipes for DN 25 – 300, 1 – 12" pipe coupling systems. Roll grooving attachment, hydraulic hand pump, built-in ring gauge for automatic groove-depth-stop, 1 pair of groove rollers (pressure roller, counter-pressure roller) 2 – 6", Allen key. Drive unit with maintenance-free gear, powerful battery motor 21.6 V, 500 W. Safety switch. Right and left-hand rotation, machine status check with overload protection, temperature monitoring, battery charging status check. Universal support. Li-Ion 21.6 V, 9.0 Ah battery, 100 – 240 V, 50 – 60 Hz, 90 W rapid charger. For workbench, stand or wheel stand. In a carton.

	Art.-No.	KM
	347005R220	**7.560,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Amigo 22 V drive unit, without battery	530004R22	**2.360,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	**1.050,00**
Stand	849315R	**439,00**
Wheel stand	849310R	**712,00**
REMS Herkules material supports, see page 107.		
Grooving rollers and other accessories, see page 48.		
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

REMS Magnum RG

Roll grooving machine

Robust, compact high performance machine with roll grooving attachment for pipe grooving of pipe coupling systems. For installation, sprinkler lines, commercial heating lines, industry and mining.
For job site and workshop.

Steel pipes	DN 25 – 300 1 – 12" s ≤ 7.2 mm
Stainless steel pipes, copper, aluminium, PVC pipes	
Pipe threads 1⁄16 – 2", 16 – 63 mm, bolt threads 6 – 60 mm, ¼ – 2", with conversion kit.	

German Quality Product

Info

REMS Magnum RG – the compact up to 12". Immensely powerful and extremely fast. Feed of the pressure roller with oil-hydraulic pressure cylinder.

Design
Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 2000 RG-T only 68 kg. Tool support. For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive
Immensely powerful and fast, e.g. roll grooving of 6" steel pipe with REMS Magnum 2010 RG-T in just 40 s. Completely maintenance-free gear which runs in a sealed oil bath. Choice of 3 powerful motors (see REMS Magnum page 34). Operator-friendly safety foot switch with emergency-stop, 2-step, can be loaded with the full body weight during operation.

Roll grooving attachment
Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers
The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25 – 300, 1 – 12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54 – 159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1 – 1½", 2 – 6" and 8 – 12". Grooving rollers for aluminium, PVC pipes on request.

Conversion kit for threading
Tool set ¼ – 2" complete with universal automatic die head, dies for pipe threads, tapered, ISO 7-1 (DIN 2999, BSPT) R ½ – ¾ and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever, pump for automatic oiling, oil basin, chip tray.

Material support
Extra sturdy REMS Herkules XL 12" material support for roll grooving of pipes up to 12" (page 107).

Stand
(Accessory)

Wheel stand (Accessory)

Herkules 3B
(Accessory)

Collapsible wheel stand
(Accessory)

Supply format

REMS Magnum RG. Roll grooving machine for pipe grooving of pipe coupling systems DN 25–300, 1–12". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling, tool support. Choice of 3 motors. Roll grooving attachment, hydraulic hand pump, built-in ring gauge with automatic groove-depth-stop, 1 set of grooving rollers (pressure roller, counterpressure roller) 2–6", hexagon key. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version	Art.-No.	KM
2000 RG-T	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm.	340230R220	**11.420,00**
2010 RG-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running.	340231R220	**12.140,00**
2020 RG-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running.	340232R380	**12.700,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Stand	344105R	**588,00**
Wheel stand with material support	344100R	**998,00**
Collapsible wheel stand	344150R	**1.430,00**
REMS Herkules material supports, see page 107.		
Grooving rollers and other accessories, see page 48.		
Conversion kit Magnum RG-T to L-T for threading.	340110RR	**2.940,00**

Sawing

	Universal electric reciprocating saws	58
	Cordless universal reciprocating saw	60
	Electric reciprocating pipe saws	62
	Pneumatic reciprocating pipe saw	64
	Cordless pipe reciprocating saw	66
	Saw blades for reciprocating saws	68
	Circular pipe sawing machine	70
	Universal circular metal sawing machine	71

REMS reciprocating saws

Legend

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades.
Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe. Adjustable mechanisms with a great variety of parts and a reduced system stability do not withstand the high in-feed pressure and the heavy-duty requirements of forceful cutting of steel pipes, particularly when a guide support with leverage is being used.



Sturdy, square lift rod in special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use and by applying multiple sawing force, e.g. using a guide support with leverage. For extremely long service life.

Special high sliding silicone gasket protects gear against water and dust.



Super stable, water and dust resistant, maintenance-free oscillating gear enables a simultaneous generation of saw and orbital stroke of lift rod and saw blade. Allround needle bearing mounted crank drive **(ANC)** reduces friction, heat generation, wear. Thus long service life also at extreme sawing.



Universal saw blade clamp for mounting all saw blades – with universal or double tang – without changing or turning the saw blade thrust piece.

Guide support for 400 % additional sawing force for fast, effortless sawing. Also for effortless demolition work.

V/bar

Drive motors
230 V, 110 V, 48 V,
22 V, 6 bar

Ergonomically shaped front housing grip with slip resistant protection cover, for forceful feed forward while sawing free-hand.

REMS reciprocating saws

Legend

VE

Vario-Electronic
Electronic stepless speed control of drive unit for sensitive start-sawing and for stroke selection during sawing according to the material. The stroke speed is controlled continuously by variable pressure on the touch switch from 0 to 2,800 rpm (REMS Puma VE), 0 to 2,400 rpm (REMS Cat VE, REMS Tiger VE) or 0 to 1,900 rpm (REMS Cat 22 V VE, REMS Tiger 22 V VE) (accelerator switch).

n ideal

Ideal speed
Deliberately fixed speed. Therefore optimum cutting speed for maximum protection of motor and gear and maximum service life of saw blades.

The ideal cutting speed of 2,400 rpm has been determined by extensive sawing tests with steel pipe which lead to optimum performance in combination with the aggressive, fixed orbital action, guide support and REMS special saw blade.

Power-transferring guide support
400 % more sawing power for effortless, ultra-fast sawing of pipes and profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, also free-hand without a pipe vice. Ideal handling, very quick and easy operation, only one handle for clamping and sawing. No free-swinging chain. No danger of jamming by limitation of swing angle. Straight machine handle for optimum forward feed.

Power-transferring chain guide support 6"
400 % more sawing power for effortless, ultra-fast sawing of Ø ⅛ – 6" pipes and other profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, even in very confined spaces. Clamping chain with strong chain links, easy clamping by quick closure and threaded spindle. Straight machine handle for optimum forward feed.

SR/ INOX

Speed-Regulation
Stepless electronic speed control of drive unit for selecting the speed according to the material. Ideal for sawing stainless steel pipe, cast pipe and for sawing boilers, tanks, bath tubs etc. The speed is continuously adjustable between 700 and 2,200 rpm on the dial. The electronic speed control which is being used keeps the selected speed constant, also under load, including speed generator, control electronics, residual current limitation for sensitive start-sawing, motor temperature control of field wires with PTC resistance (Positive Temperature Coefficient) and stall protection of gear and motor.

kg

Weight
High sawing efficiency at low weight by innovative, proven technology and perfect tuning of all components.
For effortless, fatique-free sawing and easy handling.

W

Power
All power data stated to be understood as the rated power input. The drive motors of REMS reciprocating saws have a very high efficiency of approx. 65% thanks to an outstanding technology and quality. Therefore the user has a high power output available which is useful particularly for sawing difficult-to-cut materials, e.g. steel pipe. High power output can only be used fully by levered sawing, e.g. with the REMS guide support.

V/bar

Drive Motors
Depending on model universal motors of voltages of 230 V, 110 V, 48 V, battery motors 22 V or pneumatic motors for 6 bar operating pressures are used. All drive motors are extremely powerful, fulfill highest quality demands and come with large power reserves, for long service life.

Saw blade holder with quick-change system
Practical saw blade holder with quick-change system for fast saw blade changing without tools. For holding single tang saw blades.

Continuously adjustable support shoe
Swivel support shoe for safe guiding of the saw on the material to be sawn. Support shoe continuously adjustable in longitudinal direction by 40 mm for better utilisation of partially blunted saw blades and for setting the plunge-in depth of the saw blade in the material.

Anti-vibration system
Special drive technology with mass compensation and vibration damping handles. For low vibration, effortless sawing.

Saw blade can be inserted turned 180°.
Saw blade can be inserted with the teeth facing down or turned 180° facing up for cuts in confined spaces with difficult access.

REMS Puma VE

Universal electric reciprocating saw

Powerful power tool for universal free-hand sawing. Only 3.8 kg. Ideal for assembly, disassembly, repair.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

REMS Puma VE – the powerful universal saw with anti-vibration system. Quick saw blade change without tools. Adjustable support shoe.

Universal use

Can be used anywhere, free hand, over head, in tight corners, flush with the wall. Extremely versatile and powerful. For all sawing work on the building site and for rescue and emergency operations. Also for plunge-cut sawing.

Design

Powerful, suitable for building sites. Handy, easy grip shape. Only 3.8 kg. Ergonomically designed front housing grip with non-slip, heat insulating protective jacket with soft grip, for powerful sawing thrust. Practical D-shaped handle with vibration damping soft grip. Drive rod runs in an enclosed drive housing for safe work. Large saw blade stroke, 30 mm, for better cut clearance. Fast stroke speed up to 2,800 rpm for fast sawing thrust and effective sawing. Robust crank drive, maintenance-free. High sliding special seal. Powerful, high capacity universal motor with large power reserve, 1,300 W, safety switch. 4 m long connecting lead. Safety switch.

Anti-vibration system

Special drive technology with mass compensation and vibration damping handles. For low vibration, effortless sawing.

Vario-Electronic

Continuous electronic stroke speed control for gentle start of sawing and selection of a stroke speed suitable for the material. The stroke speed can be continuously controlled by variable pressure on the safety switch from 0 to 2,800 rpm (accelerator switch).

Saw blade holder with quick-change system

Practical saw blade holder with quick-change system for fast saw blade changing without tools. For holding single tang saw blades. Saw blade can be inserted with the teeth facing down or turned 180° facing up for cuts in confined spaces with difficult access.

REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).

Continuously adjustable support shoe

Swivel support shoe for safe guiding of the saw on the material to be sawn. Support shoe continuously adjustable in longitudinal direction by 40 mm for better utilisation of partially blunted saw blades and for setting the plunge-in depth of the saw blade in the material. For economical working.





Info

Supply format

REMS Puma VE Set. Electric universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing, with anti-vibration system. Drive machine with D-shaped handle with soft grip, maintenance-free crank drive, powerful 230 V, 50 – 60 Hz, 1,300 W universal motor, safety switch, connecting cable 4 m. Continuous electronic stroke speed control (accelerator switch) 0 to 2,800 rpm. 30 mm stroke. Saw blade holder with quick-change system Adjustable support shoe. Hexagon key. 1 REMS saw blade 210-1.8/2.5. In sturdy steel case.

	Art.-No.	KM
	560023R220	**748,00**

Other voltages on request.



Accessories

Description	Art.-No.	KM
REMS Puma VE drive unit	560003R220	**670,00**
REMS saw blades see page 69.		
Steel case	566051R	**168,00**

All prices excl. VAT

REMS Cat VE

Universal electric reciprocating saw

Powerful, robust, handy power tool for universal free-hand sawing. Only 3.0 kg. Ideal for assembly, dismantling, repair.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Especially also for steel pipes

REMS Cat VE – saws anything, anywhere.
Extremely versatile and powerful.
Robust and handy.

Universal use
Ready for use anywhere, free-hand, overhead, in confined areas, flush to wall. Extremely versatile and efficient. Especially also for sawing metal pipes, sawing up boilers, tanks, bath tubs. For rescue and emergency operations. Also for plunge-cut sawing.

Design
Robust, job site-proven. Slender, handy design. Super light, only 3.0 kg. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward. Proven D-shaped handle. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful universal motor with ample reserve capacity, 1050 W. Safety tip switch.

Sturdy, square lift rod
In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life. Drive rod runs in an enclosed housing for safe work.

Oscillating drive with ANC
Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Aggressive orbital action
Agressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

Vario-Electronic
Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 2,400 rpm (acceleration switch).

Universal saw blade clamp
All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

REMS universal saw blade
Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.

REMS saw blades
Full range of REMS saw blades for free-hand sawing of different materials (page 69).

ANC

- reduced friction and wear
- substantially reduced heat generation
- for extremely long service life, also during tough use



German Quality Product

Info

Supply format

REMS Cat VE Set. Electric universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing. Drive unit with D-shaped handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1050 W, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 2,400 rpm. Universal saw blade clamp. Hexagon key. 1 REMS universal saw blade 150-1.8/2.5. In sturdy steel case.

	Art.-No.	KM
	560040R220	**1.180,00**

Other voltages on request.

3.0 kg | 1050 W | 230 V | VE

ANC

Accessories

Description	Art.-No.	KM
REMS Cat VE drive unit	560004R220	**1.180,00**
REMS saw blades see page 68–69.		
Steel case	566005R	**168,00**

REMS Cat 22 V VE

Cordless universal reciprocating saw

Powerful, mobile, handy power tool for universal free-hand sawing. Only 3.1 kg. Ideal for assembly, dismantling, repair. Li-Ion 22 V Technology. For battery and corded operation.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Especially also for steel pipes

REMS Cat 22 V VE – saws anything, anywhere. Mobile, handy, light. Li-Ion 21.6 V, 5.0 Ah battery, for approx. 75 1" steel pipe cuts with one battery charge*.

Universal use
Ready for use anywhere, free-hand, overhead, in confined areas, flush to wall. Mains independent. Extremely versatile and efficient, particularly for metal. Saws metal pipes, boilers, tanks, bath tubs, window frames, etc., for rescue and disaster service operations. Also for plunge-cut sawing.

Design
Robust, job site-proven. Mobile, handy, light. Drive unit with battery pack weighs only 3.1 kg. Slim form. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward. Practical D-shaped handle with soft grip. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful 21.6 V battery motor with ample reserve capacity, 500 W output. Safety tip switch. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.

Sturdy, square lift rod
In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life.

Oscillating drive with ANC
Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Vario-Electronic
Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 1,900 rpm (acceleration switch).

Aggressive orbital action
Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

Battery or mains operation
Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah battery, for approx. 66 1" steel pipe cuts, 5.0 Ah battery, for approx. 75 1" steel pipe cuts, 9.0 Ah for approx. 140 1" steel pipe cuts with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Universal saw blade clamp
All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

REMS universal saw blade
Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.

REMS saw blades
Full range of REMS saw blades for free-hand sawing of different materials (page 69).

ANC

- reduced friction and wear
- substantially reduced heat generation
- for extremely long service life, also during tough use

German Quality Product

Info

REMS Cat 22 V VE

Cordless universal reciprocating saw

Supply format

REMS Cat 22 V VE Set. Battery driven universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing. Drive unit with D-shaped handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful 21.6 V battery motor, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 1,900 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 5.0 Ah battery, 100 – 240 V, 50 – 60 Hz, 90 W rapid charger. Universal saw blade clamp. Hexagon key. 1 pcs REMS universal saw blade 150-1.8/2.5. In sturdy steel case.

	Art.-No.	KM
	560052 R220	**2.490,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS saw blades see page 68 – 69.		
REMS Cat 22 V VE drive unit, without battery	560010 R22	**1.430,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578 R220	**1.050,00**
Steel case with inlay	566030 R	**261,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS Tiger/VE/SR

Electric reciprocating pipe saws

Powerful, robust, handy power tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Only 3.0 kg. Ideal for assembly, dismantling, repair.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

For materials that are difficult to cut, e.g. stainless steel pipes, hard cast iron, use the REMS Tiger SR with electronic stroke speed control.

REMS Tiger – the saw for the pipe fitter.
Saws effortless, fast, right angle.
Robust and handy.

Power-transferring guide support

400 % more sawing power for effortless, ultra-fast sawing of pipes and profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, also free-hand without a pipe vice. Ideal handling, very quick and easy operation, only one handle for clamping and sawing. No free-swinging chain. No danger of jamming by limitation of swing angle. For optimum in-feed with guide support a straight machine handle is advantageous.

Power-transferring chain guide support 6"

400 % more sawing power for effortless, ultra-fast sawing of Ø ⅛ – 6" pipes and other profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, even in very confined spaces. Clamping chain with strong chain links, easy clamping by quick closure and threaded spindle. For optimum in-feed with guide support a straight machine handle is advantageous.

Right angle sawing

Right angle cut thanks to REMS guide support and REMS special saw blade. Essential for subsequent operations in pipe installation.

REMS special saw blade

REMS special saw blade (page 68), extra thick, rigid and unbendable, double tang, absolutely essential for right-angled sawing and fast disassembly of steel pipes with force-transmitting guide holder.

REMS universal saw blade

Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.

REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Design

Robust, job site-proven. Slender, handy design. Super light, only 3.0 kg. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant protection cover for forceful feed forward during free-hand sawing. Choice of practical D-shaped handle, advantegeous during free-hand sawing, or straight machine handle, advantegeous during sawing with guide support. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful universal motor with ample reserve capacity, 1050 W respectively 1400 W (REMS Tiger SR). Safety tip switch. Choice of drive unit with fixed, ideal speed, electronic speed control (Vario-Electronic) or electronic speed regulation. Overload protection (REMS Tiger) protects motor, gear and saw blade. The electronic tachometer speed controller (REMS Tiger SR) used for control keeps the preselected number of strokes constant even under load and includes tachogenerator, electronic control, start-up current limiter for soft start-up, overheating protection by temperature monitoring of the field winding of the motor with PTC resistance (Positive Temperature Coefficient) and blocking protection for gearbox and motor.

Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life. Drive rod runs in an enclosed housing for safe work.

Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful



German Quality Product



sawing also during extreme load conditions, e.g. sawing of steel pipe. Adjustable mechanisms with a great variety of parts and a reduced system stability do not withstand the high feed forward pressure and the heavy-duty requirements of forceful cutting of steel pipes, particularly when a guide support with leverage is being used.

Ideal speed (REMS Tiger)

Deliberately fixed speed. Therefore optimum cutting speed for maximum protection of motor and gear and maximum service life of saw blades. The ideal cutting speed of 2,400 rpm has been determined by extensive sawing tests with steel pipe which lead to optimum performance in combination with the aggressive, fixed orbital action, guide support and REMS special saw blade.

Vario-Electronic (REMS Tiger VE)

Electronic stepless speed control of drive unit for sensitive start-sawing and for speed selection during sawing according to the material. Also for plunge-cut sawing. The stroke speed can be continuously controlled by variable pressure on the safety switch from 0 to 2,400 rpm (accelerator switch).

Speed Regulation (REMS Tiger SR)

Stepless electronic speed control of drive unit for selecting the stroke according to the material. Ideal for sawing stainless steel pipe, cast pipe and for sawing boilers, tanks, bath tubs etc. Also for plunge-cut sawing. The number of strokes is steplessly adjustable on the dial from 700 to 2,200 rpm.

German Quality Product

Supply format

REMS Tiger Set. Electric reciprocating pipe saw for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1050 W, safety tip switch. Fixed stroke 2,400 rpm. Overload protection. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	KM
	560020R220	**1.470,00**

Other voltages, also 48 V on request.

Info

Supply format

REMS Tiger VE Set. Electric reciprocating pipe saw with Vario-Electronic for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with D-shape handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1050 W, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 2,400 rpm. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	KM
	560027R220	**1.510,00**

Other voltages on request.

Supply format

REMS Tiger SR Set. Electric reciprocating pipe saw with speed regulation (SR) for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1400 W, safety tip switch. Stepless electronic speed control 700 to 2,200 rpm with sensitive start-sawing, speed generator, temperature control and stall protection. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	KM
	560026R220	**1.660,00**

Other voltages on request.

Info

Accessories

Description	Art.-No.	KM
REMS Tiger drive unit	560000R220	**1.260,00**
REMS Tiger VE drive unit	560008R220	**1.300,00**
REMS Tiger ANC SR drive unit	560001R220	**1.450,00**
REMS saw blades see page 68–69.		
Guide support 2", for pipes Ø ⅛–2"	563000R	**334,00**
Guide support 4", for pipes Ø 2½–4"	563100R	**460,00**
Guide support 6", for pipes Ø 5–6"	563200R	**523,00**
Chain guide support 6", for Ø ⅛–6" pipes and other profiles	563203R	**416,00**
Dual purpose holder for sawing and threading, with REMS Tiger and REMS Amigo E, Amigo, Amigo 2	543100	**536,00**
Protective cap for guide support 2", 4" and 6", for clamping of thin-walled material	563008R	**40,80**
Steel case	566051R	**168,00**

REMS Tiger pneumatic

Pneumatic reciprocating pipe saw

Powerful, robust, handy compressed air tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Ideal for use in dangerous, e.g. in wet environment. For assembly, dismantling, repair.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

For materials that are difficult to cut, e.g. stainless steel pipes, hard cast iron, use the REMS Tiger SR with electronic stroke speed control.

**REMS Tiger pneumatic –
for sawing in dangerous environment.**

Saws effortless, fast, right-angle. Force transmitting guide support for 400 % more sawing power. Sturdy, square lift rod. Oscillating drive with ANC.

Aggressive orbital action for fast feed forward sawing and long service life of saw blades. Universal saw blade clamp.



Design

Robust, job site-proven. Slender, handy design. Super light, only 3.8 kg. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward during free-hand sawing. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful pneumatic motor with ample reserve capacity, 1000 W. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Operating pressure 6 bar, air consumption ≤ 1.6 m^3/min. Safety switch with lock.

Additional description see REMS Tiger, page 62 – 63.

German Quality Product

Info

Supply format

REMS Tiger pneumatic Set. Pneumatic reciprocating pipe saw for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful pneumatic 1000 W, operating pressure 6 bar, safety switch with lock. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Air inlet hose, air outlet hose. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	KM
	560022	**4.410,00**

Accessories

Description	Art.-No.	KM
REMS saw blades see page 68 – 69.		
REMS Tiger pneumatic drive unit	560002R	**3.780,00**
Guide support 2", for pipes Ø ⅛ – 2"	563000R	**334,00**
Guide support 4", for pipes Ø 2½ – 4"	563100R	**460,00**
Guide support 6", for pipes Ø 5 – 6"	563200R	**523,00**
Chain guide support 6", for Ø ⅛ – 6" pipes and other profiles	563203R	**416,00**
Dual purpose holder for sawing and threading, with REMS Tiger and REMS Amigo E, Amigo, Amigo 2	543100	**536,00**
Protective cap for guide support 2", 4" and 6", for clamping of thin-walled material	563008R	**40,80**
Steel case	566051R	**168,00**

All prices excl. VAT

REMS
Spezial 2"/140-3,2 HSS-Bi Made in Germany
Art.-Nr. 561001
ANC
REMS
Ras 22V LE
REMS 22V 9,0

REMS Tiger 22 V VE

Cordless pipe reciprocating saw

Powerful, mobile, handy power tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Only 3.4 kg. Ideal for assembly, dismantling, repair. Li-Ion 22 V Technology. For battery and corded operation.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

REMS Tiger 22 V VE – the saw for the pipe fitter. Saws effortless, fast, right angle. Mobile, handy, light. Li-Ion 21.6 V, 9.0 Ah battery, for approx. 80 1" steel pipe cuts with guide holder for approx. 140 1" steel pipe cuts without guide holder with one battery charge*.

Power-transferring guide support

400 % more sawing power for effortless, ultra-fast sawing of pipes and profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, also free-hand without a pipe vice. Ideal handling, very quick and easy operation, only one handle for clamping and sawing. No free-swinging chain. No danger of jamming by limitation of swing angle. For optimum in-feed with guide support a straight machine handle is advantageous.

Right angle sawing

Right angle cut thanks to REMS guide support and REMS special saw blade. Essential for subsequent operations in pipe installation.

REMS special saw blade

REMS special saw blade (page 68), extra thick, rigid and unbendable, double tang, absolutely essential for right-angled sawing and fast disassembly of steel pipes with force-transmitting guide holder.

REMS universal saw blade

Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.

REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Design

Robust, job site-proven. Mobile, handy, light. Drive unit with battery pack weighs only 3.4 kg. Slim form. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant protection cover for forceful feed forward during free-hand sawing. Practical D-shaped handle with soft grip. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful 21.6 V battery motor with ample reserve capacity, 500 W output. Safety tip switch. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.

Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life. Drive rod runs in an enclosed housing for safe work.

Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 1,900 rpm (acceleration switch).

Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

German Quality Product

Info

REMS Tiger 22 V VE

Cordless pipe reciprocating saw

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 9.0 Ah capacity, for long service life. Light and powerful, for approx. 80 1" steel pipe cuts with guide holder or approx. 135 1" steel pipe cuts without guide holder with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Supply format

REMS Tiger 22 V VE Set. Cordless pipe reciprocating saw with Vario Electronics (VE) for effortless, fast, right-angled sawing with guide holder and for free-hand sawing. Drive unit with spade handle, maintenance-free, water and dust proof oscillation drive with all-round needle bearing crank drive (ANC), aggressive orbital stroke, powerful 21.6 V, 500 W battery motor, safety switch. Continuous, electronic stroke speed control (accelerator switch) 0 to 1900 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 9.0 Ah battery, 100 – 240 V, 50 – 60 Hz, 90 W rapid charger. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	KM
	560053 R220	**2.730,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Tiger 22 V VE drive unit, without battery	560011 R22	**1.640,00**
REMS saw blades see page 68 – 69.		
Guide support 2", for pipes Ø ⅛ – 2"	563000 R	**334,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578 R220	**1.050,00**
Steel case with inlay	566030 R	**261,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS special saw blades

For REMS Tiger/VE/SR, Tiger pneumatic, Tiger 22 V VE and other makes

Special saw blades for right angle sawing and for fast dismantling of steel pipes with power transmitting guide support.

Steel pipes



REMS special saw blades – for right-angled sawing with force-transmitting guide holder, for 400% more sawing power.

Specially developed for REMS Tiger.

Absolutely essential for right angle sawing and for fast dismantling with power transmitting guide support. This produces multiple thrust pressure by a five-fold force-transmitting leverage, for 400% more sawing power. Normal saw blades with single tang do not withstand the high feed pressure during sawing with guide support, they break at the mounting point.

For this reason, extra thick REMS special saw blade, resistant to bending and distortion.

Double tang mounting with exceptionally wide clamping face ensures accurate seating and high stability.

Coarse, corrugated tooth pattern for rapid sawing. Long service life.

German Quality Product

REMS special saw blades ➔ REMS Tiger, etc.	Ø inches/ Length mm	Tooth pitch mm	Material*	Teeth	Colour			Art.-No.	KM
REMS special saw blade 2"/140-2.5 steel pipes ≤ 2"	2"/140	2.5	HSS-Bi		yellow	5		561007 R05	**126,00**
REMS special saw blade 2"/140-3.2 steel pipes ≤ 2"	2"/140	3.2	HSS-Bi		yellow	5		561001 R05	**118,00**
REMS special saw blade 4"/200-3.2 steel pipes ≤ 4"	4"/200	3.2	HSS-Bi		yellow	5		561002 R05	**156,00**
REMS special saw blade 6"/260-3.2 steel pipes ≤ 6"	6"/260	3.2	HSS-Bi		yellow	5		561008 R05	**202,00**

For hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes, use the finer toothed REMS universal saw blade instead of the REMS special saw blade in combination with REMS Tiger SR with electronic speed regulation (page 63).

REMS universal saw blades

For REMS Cat VE, Tiger/VE/SR, Cat 22 V VE and other makes

Universal saw blade for free-hand sawing and for sawing with power transmitting guide support. Instead of many different saw blades.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Highly flexible, also ideal for sawing flush with the wall.

REMS universal saw blades – for all sawing jobs.

Only 1 universal saw blade instead of many different saw blades for all sawing jobs.

Resilient material, highly flexible, also for flush-to-wall sawing.

Double tang mounting with exceptionally wide clamping face for accurate seating and high stability. Also for sawing with power transmitting guide support. Single tang saw blades are unable to cope with the high thrust pressure when sawing with a guide holder, they break at the clamping point.

Alternating tooth pitch (combi-teeth) for fast, smooth cut, very highly hardened in the teeth area. Straight-set teeth.

Thus outstanding cutting performance and prolonged service life.

German Quality Product

REMS universal saw blades ➔ REMS Tiger, REMS Cat, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			Art.-No.	KM
REMS universal saw blade 100-1.8/2.5 for all sawing work	100	Combo 1.8/2.5	HSS-Bi flexible		red	5		561006 R05	**80,90**
REMS universal saw blade 150-1.8/2.5 for all sawing work	150	Combo 1.8/2.5	HSS-Bi flexible		red	5		561005 R05	**116,00**
REMS universal saw blade 200-1.8/2.5 for all sawing work	200	Combo 1.8/2.5	HSS-Bi flexible		red	5		561003 R05	**154,00**
REMS universal saw blade 300-1.8/2.5 for all sawing work	300	Combo 1.8/2.5	HSS-Bi flexible		red	5		561004 R05	**227,00**

Also for nail-embedded wood, pallets. For hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes, lower speed required, e.g. by using REMS Tiger SR with electronic speed regulation (page 63).

All prices excl. VAT * HSS-Bi: bimetal high speed steel WS: tool steel HM: carbide

REMS saw blades

For REMS Puma VE, Cat VE, Tiger/VE/SR,
Cat 22 V VE, Tiger 22 V VE and other makes

Saw blades for free-hand sawing for different materials.

Alternating tooth pitch (combi-teeth) for fast, smooth cut, also when sawing mixed materials (wood/metal).

Flexible saw blades, also for sawing flush with wall.

- Corrugated teeth for smooth cut with low tooth pitch.
- Straight-set teeth for aggressive cut with coarse tooth pitch.
- Straight teeth for saw blades with very wide carbide teeth.
- Carbide-granulate for materials that are difficult to cut.

German Quality Product

REMS saw blades for metal ➔ REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour		Art.-No.	KM
REMS saw blade 150-1 sheet metal, metal, also stainless steel, ≥ 1.2 mm	150	1	HSS-Bi flexible		red	5	561105R05	**52,10**
REMS saw blade 200-1 sheet metal, metal, also stainless steel, ≥ 1.2 mm	200	1	HSS-Bi flexible		red	5	561106R05	**68,30**
REMS saw blade 90-1.4, curved blade metal, also stainless steel, ≥ 1.5 mm	90	1.4	HSS-Bi		red	5	561107R05	**48,30**
REMS saw blade 150-1.4 metal, also stainless steel, ≥ 1.5 mm	150	1.4	HSS-Bi flexible		red	5	561104R05	**54,40**
REMS saw blade 200-1.4 metal, also stainless steel, ≥ 1.5 mm	200	1.4	HSS-Bi flexible		red	5	561108R05	**68,70**
REMS saw blade 100-1.8 metal, also stainless steel, ≥ 2 mm	100	1.8	HSS-Bi flexible		red	5	561101R05	**46,60**
REMS saw blade 150-1.8 metal, also stainless steel, ≥ 2 mm	150	1.8	HSS-Bi flexible		red	5	561103R05	**54,40**
REMS saw blade 200-1.8 metal, also stainless steel, ≥ 2 mm	200	1.8	HSS-Bi flexible		red	5	561102R05	**68,30**
REMS saw blade 200-2.5 metal, also stainless steel, ≥ 3 mm	200	2.5	HSS-Bi flexible		red	5	561109R05	**68,30**
REMS saw blade 280-2.5 metal, also stainless steel, ≥ 3 mm	280	2.5	HSS-Bi flexible		red	5	561112R05	**86,50**

German Quality Product

REMS saw blades for wood and metal ➔ REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour		Art.-No.	KM
REMS saw blade 210-1.8/2.5 round tip, no sticking pallets, wood, wood with nails, metal ≥ **2.5** mm	210	Combo 1.8/2.5	HSS-Bi flexible		black	5	561113R05	**70,40**
REMS saw blade 150-2.5 wood, wood with nails, pallets, metal ≥ 3 mm	150	2.5	HSS-Bi flexible		black	5	561110R05	**52,10**
REMS saw blade 225-2.5, extra thick, for disassembly wood, wood with nails, metal ≥ **3** mm	225	2.5	HSS-Bi		black	3	561114R03	**67,00**
REMS saw blade 300-2.5, extra thick, for disassembly wood, wood with nails, metal ≥ **3** mm	300	2.5	HSS-Bi		black	3	561116R03	**89,30**
REMS saw blade 300-4.2 wood	300	4.2	WS		black	5	561111R05	**63,60**
REMS saw blade 225-3.2/5.0 wood, wood with nails	225	Combo 3.2/5.0	HSS-Bi flexible		black	5	561117R05	**79,40**
REMS saw blade 290-5.0/6.35 green wood	290	Combo 5.0/6.35	WS		black	5	561118R05	**86,50**
REMS saw blade 150-6.35 wood	150	6.35	WS		black	5	561119R05	**36,80**

REMS saw blades for different purposes ➔ REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour		Art.-No.	KM
REMS saw blade 150-4.2 breeze blocks, plasterboard	150	4.2	WS		white	5	561115R05	**45,60**
REMS saw blade 225-8.5 breeze blocks, hard wood	225	8.5	HM		white	1	561120R01	**119,00**
REMS saw blade 300-8.5 breeze blocks, hard wood	300	8.5	HM		white	1	561121R01	**142,00**
REMS saw blade 400-8.5 breeze blocks, hard wood	400	8.5	HM		white	1	561122R01	**204,00**
REMS saw blade 235-12 breeze blocks, pumice, brick	235	12	HM		white	1	561123R01	**165,00**
REMS saw blade 300-12 breeze blocks, pumice, brick	300	12	HM		white	1	561124R01	**191,00**
REMS saw blade 300-12, extra high blade breeze blocks, pumice, brick	300	12	HM		white	1	561125R01	**227,00**
REMS saw blade 200 cast iron etc.	200		HM-G		white	2	561126R02	**68,10**



All prices excl. VAT

* HSS-Bi: bimetal high speed steel WS: tool steel HM: carbide HM-G: carbide-granulate

REMS Turbo Cu-INOX

Circular pipe sawing machine

Compact, portable circular pipe sawing machine for burr-reduced, right angle and rapid sawing. For stainless steel pipes, carbon steel pipes and copper pipes of the press fitting systems etc. Also for cutting thin-walled sections for front-wall installation. For job site and workshop.

Stainless steel pipes, carbon steel pipes, copper pipes and other materials	≤ Ø 76 mm
REMS saw blade	Ø 225 mm

REMS Turbo Cu-INOX – burr-reduced, right angle, rapid. Burr-reduced sawing through double clamping vice. Powerful, e.g. Ø 22 mm in only 4 s. Easy to transport.

Ideal for pressfitting systems

In accordance with requirements:
Dry sawing, so no damage to O-rings from lubricants.
Burr-reduced through double clamping vice.
Optimum cutting speed prevents degradation of pipe material through overheating.

Design

Compact, robust, job site-proven. Small in size, handy, portable, only 17 kg. Easy sawing through favourable leverage effect. Fast saw blade change. Precise sawing. Mark on the saw blade protection cover showing the saw blade cutting line. Connection for driving outer/inner pipe deburrer REMS REG 10 – 54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Universal double clamping vice

Robust, easy-running universal double clamping vice for burr-reduced sawing. Both pipe ends remain securely clamped during sawing. Easy, secure clamping also of thin-walled pipes through inclined jaw. Only one strong clamping spindle for both clamping sides ensures even, effortless and secure clamping of the material.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 500 W. Powerful, e.g. stainless steel pipe Ø 22 mm in only 4 s. Ideal speed 60 rpm for optimum cutting speed and smooth sawing.

REMS saw blades

Top German quality. REMS circular saw blade HSS 225 × 2 × 32 mm, 220 teeth, for metal, adjusted to the efficiency of REMS Turbo Cu-INOX for sawing stainless steel tubes. Specially fine-toothed, hardened and ground. For easy and exact sawing. Prolonged durability. REMS circular saw blade HSS-E (cobalt alloyed) 225 × 2 × 32 mm, 220 teeth, for metal, for even better durability. Specially fine-toothed, hardened and ground.

Outer/inner pipe deburrer

Outer/inner pipe deburrer REMS REG 10 – 54 E for pipes Ø 10 – 54 mm, Ø ½ – 2⅛", for electric drive with the REMS Turbo Cu-INOX pipe circular sawing machine and others, see page 99.

German Quality Product

Info

Supply format

REMS Turbo Cu-INOX Basic. Circular pipe saw with universal double clamping vice for burr-reduced, right angle, rapid sawing. For stainless steel pipes, carbon steel pipes and copper pipes of the press fitting systems etc. Also for cutting thin-walled sections for front-wall installation. For REMS saw blade Ø 225 mm. With maintenance-free gear, proven universal motor 230 V or 110 V, 50 – 60 Hz, 500 W. Safety tip switch, saw blade protection cover. Speed 60 rpm. Ring spanner. Hexagon key. Without saw blade. For workbench, stand or wheel stand. In a carton.

	Art.-No.	KM
	849006R220	**2.610,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS circular saw blade HSS for metal, specially for stainless steel pipes, fine-toothing, 225 × 2 × 32 mm, 220 teeth.	849703R	**450,00**
REMS circular saw blade HSS-E (cobalt alloyed) circular saw blade HSS-E (cobalt alloyed) toothing, 225 × 2 × 32 mm, 220 teeth. Very long service life.	849706R	**626,00**
REMS REG 10 – 54 E outer/inner pipe deburrer, see page 99		
Stand	849315R	**439,00**
Wheel stand	849310R	**712,00**
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		

All prices excl. VAT

REMS Turbo K

Universal circular metal sawing machine
with automatic cooling lubricant unit

Compact, mobile, universal circular metal sawing machine for installation, metal working and industry. For job site and workshop.

	○	□	▭	⌐	●	■	▬
90°	78	55	70 × 50	50 × 50	40	40	50 × 30
45°	60	55	60 × 40	50 × 50	40	40	50 × 30

REMS saw blade Ø 225 mm

REMS Turbo K – the most powerful in its class.
Progressive drive, e.g. 2" steel pipe in only 5 s.
Easy to transport.

Design
Compact, robust, job site-proven. Small in size, handy, portable, complete only 22 kg. Automatic cooling lubricant unit. Easy sawing through favourable leverage effect. Fast saw blade change. Precise sawing. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Universal vice
Robust, easy-running universal vice with strong clamping spindle and large clamping lever for effortless, secure clamping of the material. Standard with clamp insert for thin-walled pipes. Quick setting of bevel angle thanks to clearly laid out scale and clamping lever. Simple, sturdy length stop.

Drive
Robust, maintenance-free gear, precisely mounted in roller and needle bearings. Proven universal motor, 1200 W. Extremely strong and powerful, e.g. 2" steel pipe in only 5 s. Ideal speed 115 rpm for fast and smooth sawing.

REMS saw blades
Top German quality. REMS universal circular saw blade HSS 225 × 2 × 32 mm for metal, 120 teeth, adjusted to the efficiency of REMS Turbo K. Specially toothed, hardened and ground. For easy and exact sawing. REMS universal circular saw blade HSS 225 × 2 × 32 mm, 220 teeth, adjusted for sawing stainless steel. Specially fine-toothed, hardened and ground. For an even better durability, REMS universal circular saw blade HSS-E (cobalt alloyed) 225 × 2 × 32 mm, 220 teeth. Specially fine-toothed, hardened and ground.

Kühlschmierstoffe
REMS Sanitol and REMS Spezial (page 47). High lubricating and cooling effect. Essential for clean cuts, long service life of saw blades and machine.

German Quality Product

Info

Supply format

REMS Turbo K Basic. Universal circular metal sawing machine with automatic cooling lubricant unit. For straight cuts and bevel cuts up to 45°. For REMS saw blade Ø 225 mm. Maintenance-free gear. Proven, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1200 W. Safety tip switch, saw blade protection cover, length stop. Clamp insert for thin-walled pipes. Speed 115 rpm. Ring spanner. Hexagon key. 1 filling of cooling lubricant REMS Spezial. Without saw blade. For workbench, stand or wheel stand. In a carton.

	Art.-No.	KM
	849007 R220	**3.270,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS universal circular saw blade HSS for metal, 225 × 2 × 32 mm, 120 teeth	849700 R	**389,00**
REMS circular saw blade HSS for metal, fine-toothing, 225 × 2 × 32 mm, 220 teeth	849703 R	**450,00**
REMS circular saw blade HSS-E (cobalt alloyed) for metal, fine-toothing, 225 × 2 × 32 mm, 220 teeth. Very long service life.	849706 R	**626,00**
Electronic speed regulator for hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes. Fixed, optimum speed.	565051 R220	**565,00**
Cooling lubricants see page 47.		
Stand	849315 R	**439,00**
Wheel stand	849310 R	**712,00**
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		



Made in Germany
REMS

Cutting
Chamfering
Deburring
Calibrating

	Pipe cutters	74
	Cutter wheels	81
	Electric pipe cutter/ Cordless pipe cutter	82
	Pipe cutting machines	84
	Pipe shears	90
	Pipe cutting and pipe chamfering tools	94
	Pipe deburrers	97
	Calibrating tools and outer-inner pipe deburrer	100

REMS RAS St

Robust quality tools for cutting pipes.
Meets high demands and long service life.

Steel pipes Ø ⅛ – 4", Ø 10 – 115 mm

REMS RAS St – quality pipe cutters.

Solid body in forged steel.

Robust spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe and a long service life.

Ergonomic, wide handle provides a powerful in-feed of spindle.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for pipes Ø ⅛ – 4" (10 – 115 mm), wall thickness s ≤ 8 mm, suitable for both pipe cutters. Cutter wheel for pipes Ø 1 – 4" to wall thickness s ≤ 12.5 mm available as accessory.

German Quality Products

Info

Supply format

REMS RAS St. Pipe cutter for steel pipes. With cutter wheel. In a carton.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
St ⅛ – 2"	⅛ – 2" 10 – 60	8	113000R	**460,00**
St 1¼ – 4"	1¼ – 4" 30 – 115	8	113100R	**838,00**

Accessories

Description	s ≤ mm	Art.-No.	KM
REMS cutter wheel St 1/8 – 4", s 8 for REMS RAS St ⅛ – 2" and St 1¼ – 4"	8	341614R	**31,30**
REMS cutter wheel St 1 – 4", s 12 for REMS RAS St 1¼ – 4"	12.5	381622R	**72,00**

All prices excl. VAT

REMS RAS Cu-INOX

Robust quality tools for cutting tubes.
Particularly suited for cutting stainless steel tubes.

Copper tubes, thin-walled
stainless steel tubes, thin-walled
steel, aluminium, brass tubes

Ø 3 – 120 mm
Ø ⅛ – 4"

REMS RAS Cu-INOX – for places with difficult access.

Small, handy, specially for use in restricted spaces.

Robust design and hardened back pressure rollers provide exact alignment to the tube and a long service life.

Large operating knob in metal for easy in-feed and cutting.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 3 – 28 S Mini with needle bearing cutter wheel and needle bearing counter-pressure rollers for very easy cutting.

Supply format

REMS RAS Cu-INOX. Pipe cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel. In blister pack.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
Cu-INOX 3 – 16	3 – 16 ⅛ – ⅝"	4	113200R	**57,80**
Cu-INOX 3 – 25	3 – 25 ⅛ – 1"	4	113230R	**70,00**
Cu-INOX 3 – 28 Mini	3 – 28 ⅛ – 1⅛"	4	113240R	**80,00**
Cu-INOX 3 – 28 S Mini on needle bearings	3 – 28 ⅛ – 1⅛"	4	113241R	**113,00**

Info

REMS RAS Cu-INOX – the compact version with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 3 – 35 S with needle bearing cutting wheel and needle bearing counter-pressure rollers for very easy cutting.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.



Supply format

REMS RAS Cu-INOX. Pipe cutting machine for copper pipes, thin-walled stainless steel pipes, thin-walled steel-aluminium pipes, brass pipes, with integrated pipe deburring device. With cutter wheel. In blister pack.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
Cu-INOX 3 – 35	3 – 35 ⅛ – 1⅜"	4	113350R	**124,00**
Cu-INOX 3 – 35 S on needle bearings	3 – 35 ⅛ – 1⅜"	4	113351R	**166,00**
Cu-INOX 3 – 42	3 – 42 ⅛ – 1¾"	4	113330R	**156,00**

All prices excl. VAT

REMS RAS Cu-INOX

REMS RAS Cu-INOX – quality pipe cutter.

Robust, solid design for heavy-duty application.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 8 – 64 S and REMS RAS Cu-INOX 8 – 42 S with needle bearing cutting wheel and needle bearing counter-pressure rollers for very easy cutting. Quick adjustment of the engagement spindle in both directions.

Only 1 cutter wheel for the complete working capacity Ø 3 – 120 mm.

Info

International Design Award

German Quality Products

Supply format

REMS RAS Cu-INOX. Pipe cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel. In blister pack/in box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
Cu-INOX 3 – 28	3 – 28 ⅛ – 1⅛"	4	113300R	**68,10**
Cu-INOX 6 – 42	6 – 42 ¼ – 1⅝"	4	113380R	**322,00**
Cu-INOX 8 – 42 S on needle bearings, with quick adjustment	8 – 42 ⅜ – 1⅝"	4	113385R	**331,00**
Cu-INOX 6 – 64	6 – 64 ¼ – 2½"	4	113400R	**376,00**
Cu-INOX 8 – 64 S on needle bearings, with quick adjustment	8 – 64 ⅜ – 2½"	4	113401R	**418,00**
Cu-INOX 64 – 120	64 – 120 2½ – 4"	4	113500R	**544,00**

Accessories

Description	Wall thickness s ≤ mm	Art.-No.	KM
REMS cutter wheel Cu-INOX 3 – 120, s 4	4	113210R	**24,40**
REMS cutter wheel Cu-INOX 3 – 120 S, s 4, on needle bearings	4	113213R	**42,70**
Universal deburring blade, ground		113360	**16,00**

All prices excl. VAT

REMS RAS Cu

Robust quality tools for cutting tubes.

Copper tubes	Ø 3 – 64 mm Ø ⅛ – 2½"

REMS RAS Cu – for places with difficult access.

Small, handy, specially for use in restricted spaces.

Robust design and hardened back pressure rollers provide exact alignment to the tube and a long service life.

Large operating knob in metal for easy in-feed and cutting.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Info

Supply format

REMS RAS Cu. Pipe cutter for copper tubes. With cutter wheel. In blister pack.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
Cu 3 – 16	3 – 16 ⅛ – ⅝"	3	113250R	**57,80**
Cu 3 – 25	3 – 25 ⅛ – 1"	3	113255R	**70,00**
Cu 3 – 28	3 – 28 ⅛ – 1⅛"	3	113260R	**80,00**

REMS RAS Cu – the compact version with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.

Supply format

REMS RAS Cu. Pipe cutter for copper tubes, with integrated pipe deburring device. With cutter wheel. In blister pack.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
Cu 3 – 35	3 – 35 ⅛ – 1⅜"	3	113340R	**118,00**
Cu 3 – 42	3 – 42 ⅛ – 1¾"	3	113320R	**141,00**

REMS RAS Cu

Pipe cutters

REMS RAS Cu – quality pipe cutter. With quick adjustment.

Solid, handy, U-shaped design.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Ratchet for quick adjustment in both directions.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for the complete working capacity Ø 3 – 120 mm.



German Quality Products

International Design Award

Supply format

REMS RAS Cu. Pipe cutter for copper tubes. With cutter wheel. In blister pack/in box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
Cu 8 – 42 with quick adjustment	8 – 42 ⅜ – 1⅝"	3	113370R	**313,00**
Cu 8 – 64 with quick adjustment	8 – 64 ⅜ – 2½"	3	113410R	**376,00**

Accessories

Description	Wall thickness s ≤ mm	Art.-No.	KM
REMS cutter wheel Cu 3 – 120, s 3	3	113225R	**24,40**
Universal deburring blade, ground		113360	**16,00**

REMS RAS P

Pipe cutters

REMS RAS P – the compact version with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.

Supply format

REMS RAS P. Pipe cutter for plasic pipes and multi-layer composite tubess, with integrated pipe deburring device. With cutter wheel. In blister pack.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	KM
P 10 – 32 T	10 – 32 ½ – 1⅜"	4,5	290001R	**118,00**
P 10 – 40 T	10 – 40 ½ – 1⅝"	4,5	290002R	**141,00**

All prices excl. VAT

REMS RAS P

High performance quality tools for cutting pipes.
With quick adjustment.

Plastic pipes,
multi-layer composite tubes — Ø 10 – 315 mm
Ø ½ – 12"

REMS RAS P – quality pipe cutter. With quick adjustment.

Solid, handy, U-shaped design.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Ratchet for quick adjustment in both directions.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Cutter wheels for different wall thicknesses (s).

REMS RAS P 50 – 125 with integrated pipe deburrer, on rotating bearing, adapts to the workpiece edge to be deburred. Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life. Fast, simple blade change. Additional guide roller, adjustable, for cutting Ø 110 mm or Ø 125 mm pipes Fast cutting wheel change without tools by cutting wheel axle with ball catch.



*German Quality Products

Info

International Design Award

P 50 – 110, s11
P 50 – 110, s16
P 50 – 110, s19

REMS RAS P/SW 45/L

Pipe cutter/pipe slitter

Robust quality tool with two cutting systems for cutting and slitting plastic corrugated protective pipes.	
Cutting	Ø ≤ 45 mm Ø ≤ 1¾"
Slitting (lengthwise cutting)	ID ≥ Ø 14 mm



Info

REMS RAS P/SW 45/L – Cutting and slitting of plastic corrugated protective pipes.

Stable magnesium version, extremely light.

Specially hardened and specially ground blades for cutting and slitting. German quality product.

Four-edged, wedge-shaped blades with a cutting angle of 90°, rotatable 4 times by 90° for four times longer life. Right-angled, burr-free cutting by pipe rest with shaft guide.

Automatic contact pressure when cutting.

Cutting depth limiting of the cutting tools during cutting prevents damage to the inside of the pipe.

Supply format

REMS RAS P/SW 45/L. Pipe cutter/pipe slitter for plastic corrugated protective pipes. With 3 blades. In blister pack.

	Pipes Ø mm/inch	Art.-No.	KM
	≤ 45 mm / ≤ 1¾"	113480R	**116,00**

Accessories

Description	Art.-No.	KM
Blade P/SW 45/L (pack of 3) for REMS RAS P/SW 45/L	113481R	**57,70**

REMS RAS W INOX

Pipe cutter

Highly resistant quality tool for cutting pipes.	
Corrugated metal hoses (corrugated pipes) of stainless steel, also jacketed	DN 10 – 32 (40) ⅜ – 1½" (2")

e.g.
Armaflex,
BANIDES,
Boagaz,
Chuchu Decayeux,
Clesse,
Eurotis,
FlexiPipe,
Gastite,
Gurtner

REMS RAS W INOX 10 – 32/40 S – Quality pipe cutter especially for cutting corrugated metal hoses (corrugated pipes) made of stainless steel.

Compact design for tough use.

Easy in-feed, easy cutting and precise, right angle cut.

Sturdy telescopic spindle, long spindle guide, cutting wheel on needle bearing and 2 specially hardened counter pressure rollers on needle bearings. Three high-molecular plastic guide rollers each on both sides, arranged triangularly for straight guidance of the corrugated metal hose (corrugated pipe) during the cutting process.

Ergonomically designed, comfortable rotary handle.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

German Quality Products

Info

Supply format

REMS RAS W INOX 10 – 32/40 S. Pipe cutter for corrugated metal hoses (corrugated pipes) of stainless steel, also jacketed. Counter pressure rollers on needle bearings. With cutting wheel, on needle bearing. In blister pack.

	Pipes	Art.-No.	KM
	DN 10 – 32 (40) / ⅜ – 1½" (2")	113450R	**439,00**

Accessories

Description	Art.-No.	KM
REMS cutter wheel W INOX 10 – 32/40 S on needle bearings	113461R	**24,00**

All prices excl. VAT

REMS cutter wheels

German Quality Products
For REMS pipe cutters and other makes

Specially hardened cutter wheels in approved, tough-hard REMS die steel, ensure a long service life. German Quality Products.

REMS cutter wheels also fit in suitable pipe cutters of other makes, see table with dimensional data.

REMS cutter wheel	Material	Wall thickness	to fit following pipe cutters	Capacity Ø	Art.-No.	KM
St ⅛ – 4", s 8	Steel pipes	s ≤ 8 mm	REMS RAS St ⅛ – 2"	⅛ – 2"	341614 R	**31,30**
			REMS RAS St 1¼ – 4"	1¼ – 4"		
St 1 – 4", s 12	Steel pipes	s ≤ 12.5 mm	REMS RAS St 1¼ – 4"	1¼ – 4"	381622 R	**72,00**
Cu-INOX 3 – 120, s 4	Copper tubes, stainless steel tubes	s ≤ 4 mm	REMS RAS Cu-INOX 3 – 16	3 – 16 mm	113210 R	**24,40**
			REMS RAS Cu-INOX 3 – 28	3 – 28 mm		
			REMS RAS Cu-INOX 3 – 35	3 – 35 mm		
			REMS RAS Cu-INOX 3 – 42	3 – 42 mm		
			REMS RAS Cu-INOX 6 – 42	6 – 42 mm		
			REMS RAS Cu-INOX 6 – 64	6 – 64 mm		
			REMS RAS Cu-INOX 64 – 120	64 – 120 mm		
			REMS RAS Cu 3 – 35	3 – 35 mm		
			REMS RAS Cu 3 – 42	3 – 42 mm		
Cu-INOX 3 – 120 S, s 4, on needle bearings	Copper tubes, stainless steel tubes	s ≤ 4 mm	REMS RAS Cu-INOX 3 – 28 S	3 – 28 mm	113213 R	**42,70**
			REMS RAS Cu-INOX 3 – 35 S	3 – 35 mm		
			REMS RAS Cu-INOX 8 – 42 S	8 – 42 mm		
			REMS RAS Cu-INOX 8 – 64 S	8 – 64 mm		
Cu-INOX b 3, s 4	Copper tubes, stainless steel tubes	s ≤ 4 mm	See table "Dimensional data for REMS cutter wheels"		113220 R	**24,40**
Cu 3 – 120, s 3	Copper tubes	s ≤ 3 mm	REMS RAS Cu-INOX 3 – 16	3 – 16 mm	113225 R	**24,40**
			REMS RAS Cu-INOX 3 – 25	3 – 25 mm		
			REMS RAS Cu-INOX 3 – 28	3 – 28 mm		
			REMS RAS Cu-INOX 3 – 35	3 – 35 mm		
			REMS RAS Cu-INOX 3 – 42	3 – 42 mm		
			REMS RAS Cu-INOX 6 – 42	6 – 42 mm		
			REMS RAS Cu-INOX 6 – 64	6 – 64 mm		
			REMS RAS Cu-INOX 64 – 120	64 – 120 mm		
			REMS RAS Cu 3 – 16	3 – 16 mm		
			REMS RAS Cu 3 – 25	3 – 25 mm		
			REMS RAS Cu 3 – 28	3 – 28 mm		
			REMS RAS Cu 3 – 35	3 – 35 mm		
			REMS RAS Cu 3 – 42	3 – 42 mm		
			REMS RAS Cu 8 – 42	8 – 42 mm		
			REMS RAS Cu 8 – 64	8 – 64 mm		
P 10 – 40, s 4,5	Plastic pipes, composite tubes	s ≤ 4,5 mm	REMS RAS P 10 – 32 T	10 – 32 mm	290023 R	**39,50**
			REMS RAS P 10 – 40 T	10 – 40 mm		
P 10 – 63, s 7	Plastic pipes, composite tubes	s ≤ 7 mm	REMS RAS P 10 – 40	10 – 40 mm	290016 R	**39,50**
			REMS RAS P 10 – 63	10 – 63 mm		
P 50 – 315, s 11	Plastic pipes, composite tubes	s ≤ 11 mm	REMS RAS P 50 – 110	50 – 110 mm	290116 R	**47,90**
			REMS RAS P 50 – 125	50 – 125 mm		
			REMS RAS P 110 – 160	110 – 160 mm		
			REMS RAS P 180 – 315	180 – 315 mm		
P 50 – 315, s 16	Plastic pipes, composite tubes	s ≤ 16 mm	REMS RAS P 50 – 110	50 – 110 mm	290216 R	**57,10**
			REMS RAS P 50 – 125	50 – 125 mm		
			REMS RAS P 110 – 160	110 – 160 mm		
			REMS RAS P 180 – 315	180 – 315 mm		
P 50 – 315, s 19	Plastic pipes, composite tubes	s ≤ 19 mm	REMS RAS P 50 – 110	50 – 110 mm	290316 R	**92,20**
			REMS RAS P 50 – 125	50 – 125 mm		
			REMS RAS P 110 – 160	110 – 160 mm		
			REMS RAS P 180 – 315	180 – 315 mm		
W INOX 10-32/40 S, on needle bearings	Corrugated metal hoses (corrugated pipes) of stainless steel		REMS RAS W INOX 10-32/40 S	DN 10 – 32 (40)	113461 R	**24,00**

Dimensional data for REMS cutter wheels



REMS cutter wheel	Art.-No.	OD mm	W mm	ID mm
St ⅛ – 4", s 8	341614 R	32.30	18.94	9.04
St 1 – 4", s 12	381622 R	41.30	18.94	9.04
Cu-INOX 3 – 120, s 4	113210 R	19.70	4.93	5.00
Cu-INOX 3 – 120 S, s 4	113213 R	19.70	4.93	5.00
Cu-INOX b 3, s 4	113220 R	18.70	3.07	4.80
Cu 3 – 120, s 3	113225 R	18.70	4.93	5.00
P 10 – 40, s 4,5	290023 R	20,50	4,93	5,00
P 10 – 63, s 7	290016 R	25.20	5.97	6.00
P 50 – 315, s 11	290116 R	35.30	10.95	8.00
P 50 – 315, s 16	290216 R	45.30	10.95	8.00
P 50 – 315, s 19	290316 R	51.30	10.95	8.00
W INOX 10-32/40 S	113461 R	26.60	4.93	5.00

German Quality Products



REMS Nano

Electric pipe cutter

Powerful, handy electric tool for cutting pipe and tubing. For trade and industry. For the building site and the workshop.	
Stainless steel pipes of pressfitting systems, carbon steel, copper	Ø 12 – 28 mm Ø 10 – 35 mm
Multilayer composite pipes	Ø 10 – 40 mm

REMS Nano – cutting up to Ø 40 mm.
Ultra-light. Fast. Right angled. Chip-free.
Without outer burr. Dry.

Ideal for pressfitting systems

Right angled cutting, according to requirements
Chip-free, no chips in piping system
No outer burr, no damage to O-ring by outer burr
Dry cutting, no damage to O-rings from lubricants
Fast, prevents degradation of pipe material through overheating.

Design

Mobile, electric pipe cutting machine for fast, right angled cutting without outer burr. Handy and light, only 1.9 kg. Also for fixing to the workbench or in the vice. Strong, torsion-free aluminium structure for right angled cutting. Easy cutting of the pipes by specially designed cutter wheel. Powered cutter wheel for fast cutting. Energy-saving in-feed due to ergonomically designed pressing lever. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Pipe support

3 sturdy, specially arranged counter-pressure rollers made of hardened precision steel for low-friction turning and safe guidance of the pipes to be cut in the whole working range Ø 10 – 40 mm and for optimisation of the contact points of the cutting wheel on the pipe to be cut **(Patent EP 2 077 175)**. No setting.

Drive

Robust gear precisely mounted in ball and needle bearings, maintenance-free. Proven DC motor 230 V, 130 W. Powerful. e.g. copper pipe Ø 22 mm in only 3 s. Ideal speed 130 rpm for optimum cutting speed of the pipes. Safety switch.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Nano and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Patent EP 2 077 175

German Quality Product

Info

Supply format

REMS Nano Basic-Pack. Electric pipe cutting machine for fast, right angled cutting of pipes Ø 10 – 40 mm, without outer burr. For pipes of the press fitting systems made of stainless steel, carbon steel, Ø 12 – 28 mm, copper Ø 10 – 35 mm. Multilayer composite tubes Ø 10 – 40 mm. With maintenance-free gear, proven DC motor 130 V, 50 – 60 Hz, 200 W. Speed 130 rpm. Back pressure rollers made of hardened precision steel. Safety switch. Single open ended wrench size 8. Without cutter wheel. In carrying bag.

	Art.-No.	KM
	844010R220	**1.080,00**

Accessories

Description	Art.-No.	KM
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	844050R	**77,30**
REMS cutter wheel V for multilayer composite pipes	844051R	**77,30**
Carrying bag	574436R	**77,70**
L-Boxx system case with inlay for REMS Nano/ Nano 12 V, rapid charger, battery, REMS REG 8 – 35, 2 x REMS cutter wheels, metre rule	844045R	**296,00**
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		



Herkules Y

Jumbo

Herkules 3B

All prices excl. VAT

REMS Nano 12 V

Cordless pipe cutter

Powerful, mobile, handy electric tool for cutting pipe and tubing. For trade and industry. For the building site and the workshop.	
Stainless steel pipes of pressfitting systems, carbon steel,	Ø 12 – 28 mm
copper	Ø 10 – 35 mm
Multilayer composite pipes	Ø 10 – 40 mm

REMS Nano 12 V – cutting up to Ø 40 mm. Mobile, handy, ultra-light. Fast. Right angled. Chip-free. Without outer burr. Dry.

Ideal for pressfitting systems

Right angled cutting, according to requirements
Chip-free, no chips in piping system
No outer burr, no damage to O-ring by outer burr
Dry cutting, no damage to O-rings from lubricants
Fast, prevents degradation of pipe material through overheating.

Design

Mobile, battery-powered pipe cutting machine for fast, right angled cutting without outer burr. Handy and light, only 2.1 kg. Also for fixing to the workbench or in the vice. Strong, torsion-free aluminium structure for right angled cutting. Easy cutting of the pipes by specially designed cutter wheel. Powered cutter wheel for fast cutting. Energy-saving in-feed due to ergonomically designed pressing lever. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Pipe support

3 sturdy, specially arranged counter-pressure rollers made of hardened precision steel for low-friction turning and safe guidance of the pipes to be cut in the whole working range Ø 10 – 40 mm and for optimisation of the contact points of the cutting wheel on the pipe to be cut **(Patent EP 2 077 175)**. No setting.

Drive

Robust, precision ball and needle bearing gears, maintenance-free. Powerful battery motor 12 V, with large power reserve, 270 W output. Super fast, e.g. copper pipe Ø 22 mm in just 3 s. Ideal speed 130 rpm for optimum cutting speed of the pipes. Safety switch.

Li-Ion technology

Battery Li-Ion 12 V with 2.5 Ah capacity. Light and powerful. High energy density for many cuts. Overheating and overloading protection by temperature monitor (NTC). Rapid charger 220 – 240 V, 10.8 – 18 V, 65 W, for short charging times. No memory effect for maximum battery performance.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Nano 12 V and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Patent EP 2 077 175

German Quality Product

Info

Supply format

REMS Nano 12 V Basic-Pack. Electric pipe cutting machine for fast, right angled cutting of pipes Ø 10 – 40 mm, without outer burr. For pipes of the press fitting systems made of stainless steel, carbon steel, Ø 12 – 28 mm, copper Ø 10 – 35 mm. Multilayer composite tubes Ø 10 – 40 mm. With maintenance-free gear, powerful battery motor 12 V, 270 W. Speed 130 rpm. Safety switch. Battery Li-Ion 12 V, 2.5 Ah, rapid charger 220 – 240 V, 50 – 60 Hz, 10.8 – 18 V, 65 W. Counter pressures rollers made of hardened precision steel. Single open ended wrench size 8. Without cutting wheel. In carrying bag.

	Art.-No.	KM
	844011R220	**1.430,00**

Accessories

Description	Art.-No.	KM
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	844050R	**77,30**
REMS cutter wheel V for multilayer composite pipes	844051R	**77,30**
Battery Li-Ion 12 V, 2.5 Ah	844510R12	**282,00**
Rapid charger 220 – 240 V, 50 – 60 Hz, 10.8 – 18 V, 65 W	571560R220	**313,00**
Carrying bag	574436R	**77,70**
L-Boxx system case with inlay for REMS Nano/ Nano 12 V, rapid charger, battery, REMS REG 8 – 35, 2 x REMS cutter wheels, metre rule	844045R	**296,00**
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		



REMS Cento

Pipe cutting machine

Light, portable compact machine. Universal for cutting and deburring pipes. For trade and industry. For the building site and the workshop.	
Stainless steel pipes of pressfitting systems, carbon steel, copper	Ø 8 – 108 mm
Steel pipes EN 10255 (DIN 2440)	DN 6 – 100 Ø ⅛ – 4", Ø 10 – 115 mm
Cast iron pipes (SML) EN 877 (DIN 19522)	DN 50 – 100
Plastic pipes SDR 11 Wall thickness s ≤ 10 mm	Ø 10 – 110 mm Ø ⅛ – 4"
Multilayer composite pipes	Ø 10 – 110 mm
REMS Cento RF Set Welded drain pipe/down pipe made of stainless steel (EN 1124)	Ø 40 – 110 mm

REMS Cento – Cutting and deburring up to Ø 115 mm. Super fast. Right angled. Chip-free. No outer burr. Dry cutting.

Universal for many pipe types.

Ideal for pressfitting systems

Right angled cutting, according to requirements
Chip-free, no chips in piping system
No outer burr, no damage to O-ring by outer burr
Dry, no damage to the O-ring by coolants-lubricants.
Fast, prevents degradation of pipe material through overheating.

Design

Compact, mobile pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and light, only 16.8 kg. Stable, distortion-free cast construction for right angled cutting. Easy pipe-cutting through specially designed cutter wheel. Powered cutter wheel and linear advance for fast cutting **(Patent EP 1 782 904)**. Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle. Cutter wheel protected – as movement restricted to before any contact with the rollers. Connection for driving outer/inner pipe deburrer REMS REG 10 – 54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning. An alternative feed lever is available for operating the drive unit on the floor, see accessories.

Running rollers

4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes Ø 22 – 115 mm, Ø ¾ – 4" to be cut, trapezoidally arranged, replaceable. No setting work required in the whole working range Ø 22 – 115 mm. Stainless tubular steel rollers as accessory. Cutting of pipes Ø 8 – 22 mm by placing two pipe sections Ø 28 × 220 mm on the running rollers. REMS Cento RF with 4 sturdy polyamide rollers mounted on ball bearings, to avoid damage to the pipe surfaces, for low-friction rotation of the welded drain pipes/downpipes of stainless steel (EN 1124) Ø 40 – 110 mm to be cut; pipe guides Ø 75 and 110 mm prevent the pipe from becoming oval shaped.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 1200 W. Powerful, e.g. stainless steel pipe Ø 54 mm in just 4 s. Ideal speed 115 rpm for optimum cutting speed of the pipes. Safety foot-switch with emergency stop.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Cento and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Pipe support

Pipe support, height adjustable, for pipes Ø 40 – 110 mm, Ø 1½ – 4", with operation of the drive unit with feed lever on the floor. Easy moving of the material in all directions when turning, pulling and pushing by four stainless steel balls mounted in a rust-protected housing. Safe guiding of long pipes by use of several pipe supports.

REMS pipe deburrer

Inner pipe deburrer REMS REG 28 – 108 for pipes Ø 28 – 108 mm, Ø ¾ – 4", with circulating friction element on the deburrer housing **(Patent EP 2 500 122)** for electrical rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22 V pipe cutting machine, as an accessory. Outer/inner pipe deburrer REMS REG 10 – 54 E for pipes Ø 10 – 54 mm, Ø ½ – 2⅛", for electric drive with the REMS Cento, REMS Cento 22 V pipe cutting machines, see page 99.

Marking device

Marking device for marking the insertion depth for fittings on pipes, as an accessory.

German Quality Product

Info

All prices excl. VAT

REMS Cento

Pipe cutting machine

Supply format

REMS Cento Basic. Pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8 – 115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8 – 108 mm. For steel pipes EN 10255 (DIN 2440) DN 6 – 100, Ø ⅛ – 4", Ø 10 – 115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50 – 100, plastic tubes SDR 11, wall thickness s ≤ 10 mm, Ø 10 – 110 mm, Ø ⅛ – 4", composite tubes Ø 10 – 110 mm. With maintenance-free gear, proven universal motor 230 V or 110 V, 50 – 60 Hz, 1200 W. Speed 115 rpm. Rollers in hardened precision steel pipe for pipes Ø 22 – 115 mm, Ø ¾ – 4". Safety foot-switch. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

	Art.-No.	KM
	845001R220	**2.960,00**

Other voltages on request.

Supply format

REMS Cento RF Set. Pipe cutting machine especially for fast, right-angled cutting of welded drain pipes/down pipes made of stainless steel (EN 1124) Ø 40 – 110 mm. As Art. No. 845001, but with rollers made of polyamide and pipe guides Ø 75 and 110 mm. Safety foot switch. Ring spanner. With cutting wheel RF. For workbench, stand or wheel stand. In a carton.

	Art.-No.	KM
	845003R220	**4.700,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Feed lever with spring plug for operating the drive unit on the floor (for drive units manufactured from 2014 onwards).	845218R	**186,00**
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050R	**225,00**
REMS cutter wheel Cu specially for pipes of copper pressfitting systems	845053R	**225,00**
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052R	**225,00**
REMS cutter wheel V for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051R	**225,00**
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055R	**225,00**
REMS cutting wheel RF for cutting welded drain pipes/ down pipes made of stainless steel (EN 1124) with REMS Cento RF.	845054R	**225,00**
Pipe support 1, height adjustable, for pipes Ø 40 – 110 mm, Ø 1½ – 4", with operation of the drive unit with feed lever on the floor	845220R	**309,00**
Hardened, precision tubular steel rollers (pack of 4)	845118R	**435,00**
Stainless tubular steel INOX rollers (pack of 4)	845110RINOX	**613,00**
Polyamide roller (pack of 4)	845131RPA	**718,00**
Marking device for marking the insertion depth for fittings on pipes. For REMS Cento, REMS Cento 22 V.	845530R	**263,00**
REMS REG 10 – 54 E, outer/inner pipe deburrer, see page 99		
REMS REG 28 – 108, inner pipe deburrer for pipes Ø 28 – 108 mm, Ø ¾ – 4", for electric rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22 V pipe cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).	113840R	**674,00**
Stand	849315R	**439,00**
Wheel stand	849310R	**712,00**
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		
L-Boxx H system case for REMS Cento/Cento RF	845085R	**289,00**



Patent EP 2 500 122

REMS Cento 22 V

Cordless pipe cutting machine

Light, mobile compact machine. Universal for cutting and deburring pipes. For trade and industry. For the building site and the workshop. Li-Ion 22 V Technology. For battery and corded operation.	
Stainless steel pipes of pressfitting systems, carbon steel, copper	Ø 8 – 108 mm
Steel pipes EN 10255 (DIN 2440)	DN 6 – 100 Ø ⅛ – 4", Ø 10 – 115 mm
Cast iron pipes (SML) EN 877 (DIN 19522)	DN 50 – 100
Plastic pipes SDR 11 Wall thickness s ≤ 10 mm	Ø 10 – 110 mm Ø ⅛ – 4"
Multilayer composite pipes	Ø 10 – 110 mm

REMS Cento 22 V – Mobile cutting and deburring up to Ø 115 mm. Super fast. Right angled. Chip-free. No outer burr. Dry cutting. Li-Ion 22 V Technology. Li-Ion 21.6 V, 5.0 Ah battery, for approx. 280 stainless steel pipe sections of the Ø 22 mm press fitting systems with one battery charge*.

Universal for many pipe types.

Ideal for pressfitting systems

Right angled cutting, according to requirements
Chip-free, no chips in piping system
No outer burr, no damage to O-ring by outer burr
Dry, no damage to the O-ring by coolants-lubricants.
Fast, prevents degradation of pipe material through overheating.

Design

Compact, mobile cordless pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and light, drive unit with battery only 17.6 kg. Stable, distortion-free cast construction for right angled cutting. Easy pipe-cutting through specially designed cutter wheel. Powered cutter wheel and linear advance for fast cutting **(Patent EP 1 782 904)**. Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle. Cutter wheel protected – as movement restricted to before any contact with the rollers. Practical handle for easy transport. Connection for driving outer/inner pipe deburrer REMS REG 10 – 54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning. An alternative feed lever is available for operating the drive unit on the floor, see accessories.

Running rollers

4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes Ø 22 – 115 mm, Ø ¾ – 4" to be cut, trapezoidally arranged, replaceable. No setting work required in the whole working range Ø 22 – 115 mm. Stainless tubular steel rollers as accessory. Cutting of pipes Ø 8 – 22 mm by placing two pipe sections Ø 28 × 220 mm on the running rollers.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Powerful 21.6 V battery motor, e.g. stainless steel pipe Ø 54 mm in just 7 s. Ideal speed 84 rpm for optimum cutting speed of the pipes. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED. Safety foot-switch with emergency stop.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah battery for approx. 246 stainless steel pipe sections, 5.0 Ah battery for approx. 280 stainless steel pipe sections, 9.0 Ah for approx. 520 stainless steel pipe sections of the Ø 22 mm press fitting systems with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Cento 22 V and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Pipe support

Pipe support, height adjustable, for pipes Ø 40 – 110 mm, Ø 1½ – 4", with operation of the drive unit with feed lever on the floor. Easy moving of the material in all directions when turning, pulling and pushing by four stainless steel balls mounted in a rust-protected housing. Safe guiding of long pipes by use of several pipe supports.

German Quality Product

Info

REMS Cento 22 V

Cordless pipe cutting machine

REMS pipe deburrer

Inner pipe deburrer REMS REG 28 – 108 for pipes Ø 28 – 108 mm, Ø ¾ – 4", with circulating friction element on the deburrer housing **(Patent EP 2 500 122)** for electrical rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22 V pipe cutting machine, as an accessory. Outer/inner pipe deburrer REMS REG 10 – 54 E for pipes Ø 10 – 54 mm, Ø ½ – 2⅛", for electric drive with the REMS Cento, REMS Cento 22 V pipe cutting machines, see page 99.

Marking device

Marking device for marking the insertion depth for fittings on pipes, as an accessory.

Supply format

REMS Cento 22 V Basic. Cordless pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8 – 115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8 – 108 mm. For steel pipes EN 10255 (DIN 2440) DN 6 – 100, Ø ⅛ – 4", Ø 10 – 115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50 – 100, plastic tubes SDR 11, wall thickness s ≤ 10 mm, Ø 10 – 110 mm, Ø ⅛ – 4", composite tubes Ø 10 – 110 mm. With maintenance-free gear, powerful 21.6 V battery motor. Speed 84 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Rollers in hardened precision steel pipe for pipes Ø 22 – 115 mm, Ø ¾ – 4". Safety foot-switch. Li-Ion 21.6 V, 5.0 Ah battery, 100 – 240 V, 50 – 60 Hz, 90 W rapid charger. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

	Art.-No.	KM
	845002R220	**4.160,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	**1.050,00**
Feed lever with spring plug for operating the drive unit on the floor.	845218R	**186,00**
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050R	**225,00**
REMS cutter wheel Cu specially for pipes of copper pressfitting systems	845053R	**225,00**
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052R	**225,00**
REMS cutter wheel V for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051R	**225,00**
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055R	**225,00**
Pipe support 1, height adjustable, for pipes Ø 40 – 110 mm, Ø 1½ – 4", with operation of the drive unit with feed lever on the floor	845220R	**309,00**
Hardened, precision tubular steel rollers (pack of 4)	845118R	**435,00**
Stainless tubular steel INOX rollers (pack of 4)	845110RINOX	**613,00**
Marking device for marking the insertion depth for fittings on pipes. For REMS Cento, REMS Cento 22 V.	845530R	**263,00**
REMS REG 10 – 54 E, outer/inner pipe deburrer, see page 99		
REMS REG 28 – 108, inner pipe deburrer for pipes Ø 28 – 108 mm, Ø ¾ – 4", for electric rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22 V pipe cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).	113840R	**674,00**
Stand	849315R	**439,00**
Wheel stand	849310R	**712,00**
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

Patent EP 2 500 122

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS DueCento

Pipe cutting machine

Robust, mobile compact machine. Universal for cutting pipes. For trade and industry. For the building site and the workshop.	
Stainless steel pipes of pressfitting systems, carbon steel, copper	Ø 54 – 225 mm
Steel pipes EN 10255 (DIN 2440)	DN 40 – 150 Ø 1½ – 6"
Cast iron pipes (SML) EN 877 (DIN 19522)	DN 50 – 200
Plastic pipes SDR 11 Wall thickness s ≤ 21 mm	Ø 40 – 225 mm
Multilayer composite pipes	Ø 40 – 110 mm

REMS DueCento – Cutting up to Ø 225 mm.
Right angled. Chip-free. Ready for welding. Fast.
No outer burr. Dry cutting.

Universal for many pipe types.

Right angled cutting, according to requirements
Chip-free, no chips in the pipe system, no dust
Weldable, for muff and butt welds
Fast, without impairment of the pipe material by overheating
Without outside burr, easy insertion into connecting muffs
Dry cutting, without impairment by coolant lubricants

Design

Compact, mobile pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and easily transportable, only 37 kg. Stable, distortion-free cast construction for right angled cutting. Easy pipe-cutting through specially designed cutter wheel. Powered cutter wheel and linear advance for fast cutting **(Patent EP 1 782 904)**. Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle. Cutter wheel protected – as movement restricted to before any contact with the rollers. Practical chassis with two rubber tyred wheels for easy transport.

Running rollers

4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes to be cut, arranged in convex square for centred thrust pressure of the cutting wheel in the working range Ø 100 – 225 mm, Ø 4 – 6", without setting work **(Patent EP 2 740 556)**. Roller insert for cutting pipes Ø 40 – 110 mm, Ø 1½ – 4", as an accessory.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 1200 W. Powerful, e.g. plastic tube PE Ø 225 mm in just 15 s. Ideal speed 115 rpm for optimum cutting speed of the pipes. Safety foot-switch with emergency stop.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS DueCento and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Pipe supports

Pipe supports, height adjustable, for pipes Ø 40 – 110 mm, Ø 1½ – 4" and Ø 100 – 225 mm, Ø 4 – 8". Easy moving of the material in all directions when turning, pulling and pushing by four stainless steel balls mounted in a rust-protected housing. Safe guiding of long pipes by use of several pipe supports.



German Quality Product

Info

Supply format

REMS DueCento Basic. Pipe cutting machine for fast, right angled cutting of pipes Ø 40 – 225 mm, without outside burr. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 54 – 225 mm. For steel pipes EN 10255 (DIN 2440) DN 40 – 150, Ø 1½ – 6", cast pipes (SML) EN 877 (DIN 19522) DN 50 – 200, plastic tubes SDR 11, wall thickness s ≤ 21 mm, Ø 40 – 225 mm, Ø 1¼ – 8", composite tubes Ø 40 – 110 mm. With maintenance-free gears, proven universal motor 110 / 230 V, 50 – 60 Hz, 1,200 W. Speed 115 rpm. Hardened, precision tubular steel rollers for pipes Ø 100 – 225 mm, Ø 4 – 6". Safety foot switch. Ring spanner. Without cutter wheel. 2 height adjustable pipe supports 1 for pipes Ø 100 – 225 mm, Ø 4 – 8". In a carton.

	Art.-No.	KM
	845004R220	**5.860,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050R	**225,00**
REMS cutter wheel Cu specially for pipes of copper pressfitting systems	845053R	**225,00**
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052R	**225,00**
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055R	**225,00**
REMS cutter wheel V, s 10 for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051R	**225,00**
REMS cutter wheel P, s 21 for plastic and multilayer composite tubes, wall thickness s ≤ 21 mm	845057R	**284,00**
Pipe support 1, height adjustable for pipes Ø 100 – 225 mm, Ø 4 – 8"	845220R	**309,00**
Pipe support 2, height adjustable, for pipes Ø 40 – 110 mm, Ø 1½ – 4" (roller insert required)	845230R	**309,00**
Roller insert for cutting pipes Ø 40 – 110 mm, Ø 1½ – 4"	845060R	**492,00**



REMS ROS P flex

One-hand pipe shears

Robust quality tool for clean, fast cutting of pipes in one cut. Stable magnesium version. For one-hand operation.

Flexible plastic hoses,
soft plastic pipes ≤ Ø 28 mm
≤ Ø 1⅛"

Info

REMS ROS P flex – Fast cutting in one cut. Ideal for cutting flexible plastic hoses and soft plastic pipes.

Stable magnesium version, extremely light.

Ergonomically designed handles for fast cutting in one cut.
For one-hand operation.

Blade drawback by spring-loaded articulated lever.

Specially hardened and specially ground, wedge-shaped blade with cutting angle of 110°, PTFE-coated. Ideal for cutting hoses and soft plastic pipes.

Right-angled, burr-free cutting by pipe rests on both sides and bilaterally clamped blade.

One-hand locking for safe transport and protection of the blade.

Chip-free cutting – no chips left in the pipe.

REMS ROS P flex 28 S with softgrip. Needle bearing-mounted articulated lever for easy cutting in one step.

Supply format

REMS ROS P flex. One-hand pipe shears for flexible plastic hoses and soft plastic pipes. With blade. In blister pack.

Description	Pipes ≤ Ø mm/inch	Art.-No.	KM
P flex 14	14 9/16"	291400R	**109,00**
P flex 22	22 ⅞"	291410R	**121,00**
P flex 28 S on needle bearings	28 1⅛"	291430R	**171,00**

Accessories

Description	Art.-No.	KM
Blade P flex 14 for REMS ROS P flex 14	291401R	**54,10**
Blade P flex 22 for REMS ROS P flex 22	291411R	**60,40**
Blade P flex 28 for REMS ROS P flex 28 S	291431R	**68,00**

All prices excl. VAT

REMS ROS P 26/SW 35 S

One-hand pipe shears

Robust quality tool for clean, fast cutting of pipes in one cut. With integrated pipe cutter for protective corrugated tubes. Stable magnesium version. For one-hand operation.

Plastic tubes, composite tubes	≤ Ø 26 mm ≤ Ø 1"
Protective corrugated plastic tubes	Ø 18 – 35 mm Ø ¾ – 1⅜"

REMS ROS P 26/SW 35 S – Universal for many materials. Ideal for cutting composite pipes and PEX pipes. Fast cutting in one cut. With integrated pipe cutter for protective plastic corrugated tube.

Stable magnesium version, extremely light.

Ergonomically designed handles with softgrip for fast cutting in one cut. For one-hand operation.

Needle bearing-mounted articulated lever for easy cutting in one step.

Blade drawback by spring-loaded articulated lever.

One-hand locking for safe transport and protection of the blade.

Specially hardened and specially ground, rounded blade for low-wear working, PTFE-coated. 4 counter pressure rollers on needle bearings. For easy swivelling of the pipe shears during the cutting process. Ideal for cutting composite pipes, PEX pipes and similar.

Right-angled, burr-free cutting by extra-wide pipe rests on both sides and bilaterally clamped blade.

Cutting of protective corrugated pipes by 4 cutting tools at the end of the handle.

Three-edged, wedge-shaped cutting tools with a cutting angle of 120°, rotatable 3 times by 120° for three times longer life.

Cutting depth limiting of the cutting tools during cutting of corrugated protective pipes prevents damage to the inside of the pipe.

Chip-free cutting – no chips left in the pipe.

Info

Supply format

REMS ROS P 26/SW 35 S. One-hand pipe shears for plastic and composite pipes with integrated pipe cutter for plastic corrugated protective pipes. 4 counter pressure rollers on needle bearings. With blade and 4 cutting tools. In blister pack.

	Pipes ≤ Ø mm/inch	Art.-No.	KM
	P 26/1" SW 35/1⅜"	291242R	**236,00**

Accessories

Description	Art.-No.	KM
Blade P 26/SW 35 for REMS ROS P 26/SW 35 S	291243R	**94,10**
Cutting tool P26/SW 35, pack of 4 for REMS ROS P 26/SW 35 S	291244R	**94,10**

Robust quality tool for clean, fast cutting of pipes in one cut. Stable magnesium version. For one-hand operation.

Plastic pipes, multilayer composite pipes ≤ Ø 26 mm
≤ Ø 1"

REMS ROS P 26 – fast cutting in one cut.

Stable magnesium version, extremely light.

Ergonomically designed handles for fast cutting in one cut. For one-hand operation.

Blade drawback by spring-loaded articulated lever.

One-hand locking for safe transport and protection of the blade.

Specially hardened and specially ground blade, PTFE-coated.

Right-angled, burr-free cut by pipe rest on both sides and blade guided on both sides.

Chipless cutting – no chips remaining in pipe.

Info

Supply format

REMS ROS P 26. One-hand pipe shears for plastic and multilayer composite tubes. With blade. In blister pack.

	Pipes ≤ Ø mm/inch	Art.-No.	KM
	26 1"	291240R	**116,00**

Robust quality tool for clean, fast cutting of pipes in one cut. Stable magnesium version. For one-hand operation.

PEX pipes and similar ≤ Ø 28 mm
≤ Ø 1⅛"

REMS ROS PEX 28 S – fast cutting in one cut. Ideal for cutting PEX pipes.

Stable magnesium version, extremely light.

Ergonomically designed handles with softgrip for fast cutting in one cut. For one-hand operation.

Needle bearing-mounted articulated lever for easy cutting in one step.

Blade drawback by spring-loaded articulated lever.

One-hand locking for safe transport and protection of the blade.

Specially hardened and specially ground, wedge-shaped blade with cutting angle of 150° for low-wear working, PTFE-coated. Ideal for cutting PEX pipes.

Right-angled, burr-free cut by pipe rest on both sides and blade guided on both sides.

Chipless cutting – no chips remaining in pipe.

Info

Supply format

REMS ROS PEX 28 S. One-hand pipe shears for PEX pipes, on needle bearing. With blade. In blister pack.

	Pipes ≤ Ø mm/inch	Art.-No.	KM
	28 / 1⅛"	291420R	**177,00**

Accessories

Description	Art.-No.	KM
Blade P 26 for REMS ROS P 26	291241R	**46,40**
Blade PEX 28 for REMS ROS PEX 28 S	291421R	**70,50**

REMS ROS P

One-hand pipe shears with ratchet feed/
pipe shears with ratchet feed

Handy quality tools for clean, fast pipe cuts.
For thin-walled pipes also. Sturdy aluminium/
magnesium version. For single-hand operation.

Plastic pipes, multi-layer composite tubes ≤ Ø 63 mm
≤ Ø 2"

REMS ROS P 35 / ROS P 35 A / ROS P 42 / ROS P 42 PS / ROS P 42 S / ROS P 63 P / ROS P 63 S

Sturdy aluminium version, REMS ROS P 42 S and magnesium (Mg) version P 63 S, ultra light.

Specially hardened, wedge-shaped blade, also for thin-walled pipes.

For single-hand operation. Effortless working through power transmitting ratchet feed.

Quick reverse saves time and effort. REMS ROS P 35 A with automatic quick reverse after completion of cutting.

Right angle, burr-free cut through exact pipe support and guided blade on both sides.

Chipless cutting – no chips remaining in pipe.



Supply format

REMS ROS P. One-hand pipe shears for plastic pipes and multi-layer composite tubes. With blade. In blister pack/in box.

Description	Pipes ≤ Ø mm/inch	Art.-No.	KM
P 35 with quick reverse	35 1⅜"	291200R	**126,00**
P 35 A with automatic quick reverse	35 1⅜"	291220	**160,00**
P 42 with quick reverse	42 1⅝"	291250R	**275,00**
P 42 PS with quick reverse	42 1⅝"	291000RPS	**170,00**
P 42 S with quick reverse	42 1⅝"	291010R	**192,00**
P 63 P with quick reverse	63 2"	291270R	**334,00**
P 63 S with quick reverse	63 2"	291290R	**366,00**

Robust quality tools for clean, fast pipe cuts.
Robust steel version.

Plastic pipes ≤ Ø 75 mm, ≤ Ø 2½"

REMS ROS P 75 P

Robust steel version for rugged conditions and long life, with end stop for powerful engagement, also ideal for thick-walled plastic pipes.

Rough, non-slip handle for good grip.

Specially hardened and specially ground, wedge-shaped blade with cutting angle of 150° for low-wear working.

Fast, easy operation through guided ratchet on both sides and fine-toothed ratchet gear, specially hardened.

Right angle, burr-free cut through two-point pipe support and guided blade on both sides.

Chipless cutting – no chips remaining in pipe.

Supply format

REMS ROS P 75 P. Pipe shear for plastic pipes. With blade. In a carton.

Description	Pipes ≤ Ø mm/inch	Art.-No.	KM
	75 / 2½"	291101R	**729,00**

Info

Accessories

Description	Art.-No.	KM
Blade P 35 for REMS ROS P 35	291201	**50,40**
Blade P 35 A for REMS ROS P 35 A	291221	**64,10**
Blade P 42 for REMS ROS P 42	291251	**110,00**
Blade P 42 PS for REMS ROS P 42 PS	291023	**68,10**
Blade P 42 S for REMS ROS P 42 S	291036R	**84,90**
Blade P 63 P for REMS ROS P 63 P	291271	**134,00**
Blade P 63 S for REMS ROS P 63 S	291037R	**134,00**
Blade P 75 P for REMS ROS P 75 P	291112	**292,00**



REMS Cut 110 P

Pipe cutting and pipe chamfering tool

Robust quality tool for right-angle, plain cutting and chamfering (15°) in one operation. Can be used anywhere, free-hand, on parallel vice or work bench.

Plastic pipes in
ABS, PB, PE, PE-HD, PE-X,
PP, PVC, PVDF Ø 40 – 110 mm

REMS Cut 110 P – cutting and chamfering at the same time.

Robust metal design for tough use.

Cutting and chamfering in one operation. While turning the tool shaft, also cutting only possible.

Fast and easy to use, ergonomic clamping grip.

Spring loaded clamp inserts in plastic for concentric clamping of different pipe sizes. Easy to change without tools.

Steplessly adjustable clamping pressure accomodates pipe tolerances.

Cutting and chamfering tool in hard metal with optimum cutter geometry ensures precise cutting and chamfering. Long service life.

Holder for workbench for effortless operation.

Tool set Cu-INOX and clamp inserts for cutting welded rain gutter pipes in copper, titanium zinc, stainless steel, as accessory.

Supply format

REMS Cut 110 P Set. Pipe cutting and pipe chamfering tool for plastic pipes in ABS, PB, PE, PE-HD, PE-X, PP, PVC, PVDF, Ø 40 – 110 mm.Quick clamping device Ø 110 mm with 2 each of clamping inserts Ø 50 and 75 mm. Tool set P with cutting and chamfering blade P, s 11. In sturdy case.

Description	Art.-No.	KM
Set 50 + 75 + 110	290400R	**993,00**

Accessories

Description	Pipes Ø mm	Art.-No.	KM
Clamping inserts (pack of 2)	40	290420	**166,00**
	50	290421	**166,00**
	52	290422	**166,00**
	56	290444	**166,00**
	58	290423	**166,00**
	60	290445	**166,00**
	63	290427	**166,00**
	75	290424	**166,00**
	76	290446	**166,00**
	78	290425	**166,00**
	80	290447	**166,00**
	87	290448	**166,00**
	90	290426	**166,00**
	100	290449	**166,00**
Tool set P with cutting and chamfering blade P, s 11		290432R	**175,00**
Cutting and chamfering blade P, s 11		290430	**70,80**
Cutting and chamfering blade P, s 15.5		290431	**114,00**
Tool set Cu-INOX with cutter wheel Cu-INOX 3 – 120, s 4		290433R	**175,00**
REMS cutter wheel Cu-INOX 3 – 120, s 4		113210R	**24,40**
Holder for work bench		290440R	**188,00**
Case		290437	**131,00**



All prices excl. VAT

REMS Cut 110 Cu-INOX

Pipe cutting tool

Robust quality tool for right-angle cutting of welded pipe. Can be used anywhere, free-hand, on parallel vice or work bench.

Welded copper drainpipe/downpipe, Titanium zinc, stainless steel (EN 1124) Ø 50 – 110 mm

REMS Cut 110 Cu-INOX – Easy cutting of downpipes.

Robust metal design for tough use.

Fast and easy to use, ergonomic clamping grip.

Spring loaded clamp inserts in plastic for concentric clamping of different pipe sizes. Easy to change without tools.

Steplessly adjustable clamping pressure accomodates pipe tolerances.

Cutting and chamfering tool in hard metal with optimum cutter geometry ensures precise cutting and chamfering. Long service life.

Holder for workbench for effortless operation.

Tool set P and clamp inserts for right-angle, plain cutting and chamfering (15°) of plastic pipe, as accessory, see page 94.

Supply format

REMS Cut 110 Cu-INOX Set. Pipe cutter for welded drainpipes/downpipes made of copper, titanium zinc, stainless steel (EN 1124), Ø 50 – 110 mm. Quick action clamp Ø 110 mm with clamp inserts. Tool set Cu-INOX with cutter wheel Cu-INOX 3 – 120, s 4. In sturdy case.

Description	Art.-No.	KM
Set 50 + 75 + 110	290412R	**1.080,00**
Set 60 + 80 + 100 + 110	290410R	**1.310,00**
Set 76 + 87 + 100 + 110	290411R	**1.360,00**

Accessories

Description	Art.-No.	KM
Clamp inserts, see page 94.		
Tool set Cu-INOX with cutter wheel Cu-INOX 3 – 120, s 4	290433R	**175,00**
REMS cutter wheel Cu-INOX 3 – 120, s 4	113210R	**24,40**
Holder for work bench	290440R	**188,00**

All prices excl. VAT

Handy quality tools for simple and fast external chamfering (15°) of pipes.	
Plastic pipes	Ø 16 – 250 mm, Ø ¾ – 10"
Wall thickness	≤ PN 16

REMS RAG – chamfering at 15°.

Chamfering at 15° on commonly used plastic pipes.

Also suited for deburring plastic pipes. Ensures easy joining of sleeves to be welded.

Easily adjusted for pipe diameter and wall thickness.

Very fast and easy chamfering due to a particularly favourable cutting geometry of the chamfering blades.

Two adjacent, identical chamfering blades, one of which cuts the chamfer and the other one serves as a support for the pipe during chamfering. If the cutting chamfering blade is worn, it can be exchanged with the support part, for double the service life.

Easy-to-slide V-block with two different bevel angles for good guidance of small pipe sizes. In high-grade, glass-fibre reinforced polyamide.

German Quality Product

Supply format

REMS RAG. Pipe chamfering tool for plastic pipes. With blades. In a carton.

Description	Pipes ≤ Ø mm/inch	Art.-No.	KM
P 16 – 110	16 – 110 / ¾ – 4"	292110R	**433,00**
P 32 – 250	32 – 250 / 1¼ – 10"	292210R	**506,00**

Accessories

Description	Art.-No.	KM
Chamfering blades (pack of 2) for REMS RAG P 16 – 250	292011	**173,00**

REMS REG Universal

Universal deburrer

Universal quality tool for deburring tubes and edges of different materials.

Copper, steel, brass, aluminium, plastic.

REMS REG Universal – the all-purpose deburrer.

Robust metal design for tough use.

Easy handling and good grip thanks to ergonomically designed hexagon handle.

Rotating universal deburrer blade in handle accommodates to the work piece edge to be deburred.

Specially hardened and specially ground universal deburrer blade guarantees easy deburring and long service life.

Fast, simple blade replacement by pulling back the front sliding sleeve.



Supply format

REMS REG Universal. Universal deburrer. For copper, steel, brass, aluminium, plastic. On cardboard.

	Art.-No.	KM
	113910R	**54,20**

Accessories

Description	Art.-No.	KM
Universal deburring blade, ground	113360	**16,00**

REMS REG St ¼ – 2"

Inner pipe deburrer

Robust quality tool for inner pipe deburring.
For electric operation.

Steel pipes and other pipes Ø ¼ – 2"

REMS REG St ¼ – 2": effortless electric deburring.

Inner pipe deburrer with octagonal attachment head for operating by means of electric die stocks with octagonal seat, e.g. REMS Amigo E, REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact.

Specially hardened and designed deburring blade ensures easy deburring and extremely long life. Double edges for optimum chip flow, specially for small sizes.

German Quality Product

Supply format

REMS REG St ¼ – 2". Inner pipe deburrer for electric operation. For steel pipes and other pipes, Ø ¼ – 2". In a carton.

	Art.-No.	KM
	731700	**305,00**

REMS REG 3 – 35

Outer-inner tube deburrer

Sturdy manual tool for outer-inner tube deburring.

Copper, brass, aluminium, steel, plastic tubes Ø 3 – 35 mm
Ø ⅛ – 1⅜"

REMS REG 3 – 35 – the sharp edge.

Fast, effortless deburring through 3 specially hardened and ground deburring blades.

Robust housing in shock-proof, resistant plastic.

German Quality Product

Supply format

REMS REG 3 – 35. Outer-inner tube deburrer. For copper, brass, aluminium, steel, plastic tubes, Ø 3 – 35 mm, Ø ⅛ – 1⅜". In blister pack.

	Art.-No.	KM
	113900R	**40,60**

REMS REG 8 – 35

Outer-inner pipe deburrer

Robust quality tool for removing outer and inner burr from pipes.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes — Ø 8 – 35 mm, Ø ⅜ – 1⅜"

REMS REG 8 – 35 – the multiple edge up to Ø 35 mm.

Easy, effortless deburring through multiple blades which are specially hardened and ground.

Robust metal design for tough use.

Supply format

REMS REG 8 – 35. Outer-inner pipe and tube deburrer. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 8 – 35 mm, Ø ⅜ – 1⅜". In blister pack.

	Art.-No.	KM
	113825R	**136,00**

REMS REG 10 – 42

Outer-inner pipe deburrer

Robust, solid all-metal tool for outer-inner pipe and tube deburring. For manual or electric operation.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes — Ø 10 – 42 mm, Ø ½ – 1⅝"

German Quality Product

REMS REG 10 – 42 – by hand or electric. Specially for stainless steel pipes.

Ideal for pipes of all types. Specially for stainless steel tubes of pressfitting systems.

Easy and fast deburring through an appropriate, solid all-metal tool, equipped with 4 specially hardened and ground deburring blades

Driver for electrical drive by REMS Helix 22 V VE cordless drill/screwdriver (page 108) and other power drills/screwdrivers (speed ≤ 300 rpm), as an accessory.

Supply format

REMS REG 10 – 42. Outer-inner pipe and tube deburrer for manual or electric operation. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 10 – 42 mm, Ø ½ – 1⅝". Without adapter for electric drive. In blister pack.

	Art.-No.	KM
	113810R	**246,00**

Accessories

Description	Art.-No.	KM
Adapter for REMS REG 10 – 42	113815R	**106,00**
REMS Helix 22 V VE, cordless drill/screwdriver, see page 108		

All prices excl. VAT

REMS REG 10 – 54

Outer-inner pipe deburrer

Robust quality tool for removing outer and inner burr from pipes.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes — Ø 10 – 54 mm, Ø ½ – 2⅛"



REMS REG 10 – 54 – the multiple edge up to Ø 54 mm.

Easy, effortless deburring through multiple blades which are specially hardened and ground.

Robust metal design for tough use.

Supply format

REMS REG 10 – 54. Outer-inner pipe and tube deburrer. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 10 – 54 mm, Ø ½ – 2⅛". In blister pack.

	Art.-No.	KM
	113830R	**155,00**

REMS REG 10 – 54 E

Outer-inner pipe deburrer

Robust quality tool for removing outer and inner burr from pipes. For manual operation or electric drive.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes — Ø 10 – 54 mm, Ø ½ – 2⅛"

REMS REG 10 – 54 E – by hand or electrically. Especially for stainless steel pipes.

Easy, effortless deburring through multiple blades which are specially hardened and ground.

Integrated hexagonal driver for electrical drive by REMS Helix 22 V VE cordless drill/screwdriver (page 108) and other power drills/screwdrivers with ¼" bit holders (speed ≤ 300 rpm), by the REMS Cento or REMS Cento 22 V pipe cutting machine (page 84 – 87) and by the REMS Turbo Cu-INOX pipe circular sawing machine (page 70) **(Patent EP 2 058 067)**.

Robust metal design for tough use.

Supply format

REMS REG 10 – 54 E. Outer-inner pipe and tube deburrer for manual or electric operation. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 10 – 54 mm, Ø ½ – 2⅛". In blister pack.

	Art.-No.	KM
	113835R	**284,00**

Accessories

Description
REMS Helix 22 V VE, cordless drill/screwdriver, see page 108
REMS Cento, pipe cutting machine, see page 84
REMS Cento 22 V, cordless pipe cutting machine, see page 86
REMS Turbo Cu-INOX, pipe circular sawing machine, see page 70

REMS KaliGrat E

Calibrating tool and outer-inner pipe deburrer

Robust, quality tool for calibration and outer-inner deburring of pipes. For manual operation or electric drive.

Multi-layer composite tubes Ø 14 – 63 mm

REMS KaliGrat E – simultaneous calibration and outer-inner deburring. Ratchet handle with changeable calibrating and deburring heads, with quick-change holder.

Universally usable for calibration after the cutting/cropping process, for inner deburring, to avoid damaging the fitting O-ring and for outer deburring.

Easy handling and fast feeding due to ergonomically designed plastic handle with ratchet function.

Robust steel version of the calibrating mandrel with integrated deburring blades for heavy-duty applications and long life. The calibrating mandrel and deburring blades are adapted to different pipe dimensions and wall thicknesses. Sturdy sleeve for protecting the calibrating mandrel and deburring blades from damage.

All calibrating and deburring heads with integrated hexagonal connection for manual operation with the REMS KaliGrat E ratchet handle or for electrical drive by the REMS Helix 22 V VE cordless power drill/screwdriver (page 108) and other power drills/screwdrivers with ¼" bit holders (speed ≤ 500 min^{-1}).

Quick calibrating and deburring head change by ratchet handle with quick-change holder with spring locking.

Supply format

REMS KaliGrat E Set. Calibrating tool and outer-inner pipe deburrer, for manual operation or electric drive. For Ø 14 – 63 mm composite tubes. Ratchet handle with quick-change holder with spring locking, calibrating and deburring heads. In sturdy case.

Version Ø mm × wall thickness mm	Art.-No.	KM
Set 16×2 + 20×2 + 25×2.5/26×3	114000R	**691,00**
Set Allround 26 14×2 + 16×2 + 16×2.25 + 18×2 + 20×2 + 20×2.25 + 20×2.5 + 25×2.5/26×3	114001R	**1.290,00**

Accessories

Description	Art.-No.	KM
REMS KaliGrat E ratchet handle, with quick-change holder, for easy driving of the REMS KaliGrat E calibrating and deburring heads	114044R	**162,00**
REMS KaliGrat E Ø 14×2 mm	114032R	**103,00**
REMS KaliGrat E Ø 16×2 mm	114033R	**122,00**
REMS KaliGrat E Ø 16×2.25 mm	114034R	**122,00**
REMS KaliGrat E Ø 18×2 mm	114035R	**114,00**
REMS KaliGrat E Ø 20×2 mm	114036R	**130,00**
REMS KaliGrat E Ø 20×2.25 mm	114037R	**130,00**
REMS KaliGrat E Ø 20×2.5 mm	114038R	**130,00**
REMS KaliGrat E Ø 25×2.5/26×3 mm	114039R	**152,00**
REMS KaliGrat E Ø 32×3 mm	114040R	**187,00**
REMS KaliGrat E Ø 40×3.5 mm	114041R	**240,00**
REMS KaliGrat E Ø 50×4 mm	114042R	**340,00**
REMS KaliGrat E Ø 63×4.5 mm	114043R	**625,00**
Case with inlay	114030R	**126,00**
REMS Helix 22 V VE, cordless drill/screwdriver, see page 108		

All prices excl. VAT

REMS KaliGrat R

Calibrating tools and inner pipe deburrers

Robust, quality tools for calibration and inner deburring of pipes.

Multi-layer composite tubes Ø 16 – 63 mm

REMS KaliGrat R – simultaneous calibration and inner deburring. Ratchet handle with graduated calibrating mandrel with integrated deburring blades.

Universally usable for composite tubes for calibration after the cutting/cropping process and for inner deburring, to avoid damaging the fitting O-ring.

Easy handling and fast feeding due to ergonomically designed plastic handle with ratchet function.

Robust steel version of the calibrating mandrel with integrated deburring blades for heavy-duty applications and long life. The graduated calibrating mandrel and deburring blades are adapted to different pipe dimensions and wall thicknesses.

Supply format

REMS KaliGrat R. Calibrating tool and inner pipe deburrer. For Ø 16 – 63 mm composite tubes. Ratchet handle with calibrating mandrel for different diameters and wall thicknesses, with integrated deburring blades. In blister pack.

Version Ø mm × wall thickness mm	Art.-No.	KM
R4 16×2 + 20×2 + 25×2.5/26×3 + 32×3	114045R	**198,00**
R4 16×2 + 20×2.25 + 25×2.5/26×3 + 32×3	114046R	**198,00**
R3 40×3.5 + 50×4 + 63×4.5	114047R	**396,00**
R3 40×4 + 50×4.5 + 63×6	114048R	**396,00**

REMS KaliGrat H

Calibrating tools and outer-inner pipe deburrers

Robust, quality tools for calibration and outer-inner deburring of pipes.

Multi-layer composite tubes Ø 16 – 26 mm

REMS KaliGrat H – simultaneous calibration and outer-inner deburring. Star handle with calibrating mandrels and deburring blades.

Universally usable for calibration after the cutting/cropping process, for inner deburring, to avoid damaging the fitting O-ring and for outer deburring.
One product for several pipe sizes.

Easy handling and fast feeding due to ergonomically designed plastic housing with star handle.

Robust steel version of the calibrating mandrel with integrated deburring blades for heavy-duty applications and long life. The calibrating mandrel and deburring blades are adapted to different pipe dimensions and wall thicknesses. Sturdy sleeve for protecting the calibrating mandrel and deburring blades from damage.

Supply format

REMS KaliGrat H. Calibrating tool and outer-inner pipe deburrer.
For composite tubes. In blister pack.

Version Ø mm × wall thickness mm	Art.-No.	KM
16×2 + 20×2 + 26×3	114060R	**234,00**
16×2 + 20×2 + 25×2.5	114061R	**234,00**

Assembling

	Water pump pliers	104
	Pipe workstation Chain pipe vices	105
	Folding workbenches	106
	Material supports	107
	Cordless power drill/screwdriver	108
	Electric LED flood light Cordless LED flood light	110

REMS Catch S

Swedish pattern wrench 'S'

Rugged quality tools for tough use and long service life.
All-steel, drop forged.

Swedish model according to DIN 5234 - Form C.

Pipes ≤ Ø 3"
Nuts, bolts, flat material

REMS Catch S – for professional use.

Swedish model with S-shaped jaws for secure 3-point grip.
Self-locking thus secure gripping and holding even on smooth pipes.

Rugged design in chrome-vanadium steel, all steel, drop forged, tempered, powder-coated. Hardened, highly wear resistant toothing.

Ergonomically shaped handle, slip-proof. Stop prevents jamming.
Adjusting nut cannot be lost. Reinforced sleeve.

Supply format

REMS Catch S. Swedish pattern wrench 'S'. DIN 5234 – Form C.
In plastic bag.

Description Pipes ≤ Ø inch	Width mm	Art.-No.	KM
S ½"	36	116000R	**105,00**
S 1"	47	116005R	**113,00**
S 1½"	60	116010R	**151,00**
S 2"	78	116015R	**202,00**
S 3"	112	116020R	**404,00**

REMS Catch W

Water pump pliers

Rugged quality tools for tough use and long service life.
All-steel, drop forged.

According to ISO 8976 with box joint.

Pipes ≤ Ø 1½"
Square, hexagonal joints, flat material

REMS Catch W – for professional use.

Gripping pliers with reinforced, ground, box joint. 7 grip positions.
Self-locking thus secure gripping and holding, even on smooth pipes.

Rugged design in chrome-vanadium steel, all-steel, drop forged, tempered, powder-coated. Hardened, highly wear resistant toothing.

Ergonomically shaped handle, slip-proof. Stop prevents jamming.

Supply format

REMS Catch W. Water pump pliers, 7 grip positions. ISO 8976.
In plastic bag.

Description	Pipes ≤ Ø inch	Art.-No.	KM
W 175	1"	116050R	**51,50**
W 240	1¼"	116055R	**59,20**
W 300	1½"	116060R	**87,20**

All prices excl. VAT

REMS Aquila 3B

Portable pipe workstation with chain pipe vice

Sturdy, easy to carry pipe workstation with integrated chain pipe vice on folding tripod stand. With practical shelf plate. For trade and industry. For the building site and the workshop.

Clamping range	Ø 10 – 165 mm Ø ⅛ – 6"
Load capacity	≤ 450 kg

Info

REMS Aquila 3B – portable pipe workstation. Safe clamping of pipes up to 6". Everywhere on site.

Sturdy, torsion-free die-cast structure of the work plate with integrated chain pipe vice, pipe rest, tool holders, 3 benders for bending pipes Ø 10 – 26 mm, Ø ⅜ – ¾", clamping head.

Specially toothed double clamping jaws, easily changeable, prism-shaped, for safe clamping of the pipes in the whole working range. Specially hardened, for long life.

Clamping chain with strong chain links, easy clamping by quick closure and trapezoidal threaded spindle.

Well accessible working range in front of the chain pipe vice for free swing of even long tools.

Especially suitable for pipe installation, e.g. for cutting, thread cutting, bending, assembly.

Adjustable clamping head for clamping the pipe workstation between the ceiling and the floor, for especially secure standing.

Proven tripod stand for secure standing, folding, for easy erection and transport.

Practical shelf plate for tools and work material.

REMS Herkules height adjustable material supports (see page 107).

Supply format

REMS Aquila 3B. Pipe workstation with chain pipe vice for clamping pipes, solid material Ø 10 – 165 mm, Ø ⅛ – 6". Work plate with integrated chain pipe vice with double clamping jaws, pipe rest, tool holders, 3 benders for bending pipes Ø 10 – 26 mm, Ø ⅜ – ¾", clamping head. Folding tripod stand with shelf plate. Load capacity ≤ 450 kg. In a carton.

	Art.-No.	KM
	120270R	**1.080,00**

REMS Aquila WB

Chain pipe vice for workbench

High quality, robust chain pipe vice for fixing to a workbench. Excellent quality for long life. For trade and industry. For the building site and the workshop.

Clamping range	Ø 10 – 165 mm Ø ⅛ – 6"

German Quality Product

Info

REMS Aquila WB – safe clamping of pipes up to 6".

Sturdy, torsion-free die-cast structure of the base plate with integrated chain pipe vice, pipe rest, bender.

Specially toothed double clamping jaws, easily changeable, prism-shaped, for safe clamping of the pipes in the whole working range. Specially hardened, for long life.

Clamping chain with strong chain links, easy clamping by quick closure and trapezoidal threaded spindle.

Well accessible working range in front of the chain pipe vice for free swing of even long tools.

Especially suitable for pipe installation, e.g. for cutting, thread cutting, bending, assembly.

For fixing to the workbench. Pay attention to load capacity of the workbench.

REMS Herkules height adjustable material supports (see page 107).

Supply format

REMS Aquila WB. High quality chain pipe vice for clamping pipes, solid material Ø 10 – 165 mm, Ø ⅛ – 6". Base plate with integrated chain pipe vice with double clamping jaws, pipe rest, bending device. For work bench. In a carton.

	Art.-No.	KM
	120250R	**628,00**

REMS Jumbo

Sturdy, easy to carry folding workbenches for universal use. Worktop in accordance with DIN 68 705. For trade and industry. For the building site and the workshop.

REMS Jumbo E – handy and light.	
Work top	Birch-Multiplex, 800 × 600 × 22 mm
Height	800 mm
Weight	23 kg
Load capacity	≤ 300 kg
REMS Jumbo – the indestructible folding workbench. Handy and light. German quality product.	
Work top	Beech-Multiplex, 1100 × 700 × 26 mm
Height	800 mm
Weight	28 kg
Load capacity	≤ 300 kg

German Quality Product

Info

REMS Jumbo – assembled and disassembled at lightning speed. With toggle catch. Worktops in accordance with DIN 68 705. Highly resistant up to 300 kg.

Handy and light. REMS Jumbo E only 23 kg, REMS Jumbo only 28 kg.

Worktop made of special Birch-Multiplex plywood (REMS Jumbo E) or Beech-Multiplex plywood (REMS Jumbo), in accordance with DIN 68 705 weather-proof glued, impregnated, vice-proof and tear-proof, flat and torsion-free.

Impact and splinter resistant thanks to steel edge protection. Screws and nuts galvanised,

Especially safe standing by strong tubular steel frame with toggle catch, assembled and disassembled at lightning speed. Easy to carry.

Highly resistant, max. load capacity 300 kg.

Supply format

REMS Jumbo. Folding workbench with toggle catch. Worktop in accordance with DIN 68 705. Load capacity ≤ 300 kg. In a carton.

Description	Work top	Size mm	Art.-No.	KM
REMS Jumbo E	Birch-Multiplex	800 × 600	120240R	**586,00**
REMS Jumbo	Beech-Multiplex	1100 × 700	120200R	**901,00**

All prices excl. VAT

REMS Herkules

Vertically adjustable material support with roller guidance for rotating and stationary pipe and solid material.
For trade and industry. For the building site and the workshop.

Pipes, solid material	Ø (⅛) ¾ – 6", Ø (6) 26 – 168 mm
Load capacity	≤ 150 kg

German Quality Product

Info



REMS Herkules – the sturdy support.

Easy moving of the material in all directions when turning, pulling and pushing by two stainless steel balls mounted in a rust-protected housing in the range Ø ¾ – 6", Ø 26 – 168 mm.

Especially suitable for pipe installation, e.g. for cutting, thread cutting, roll grooving, welding, soldering.

Robust, job site-proven design. Dismantles for transport and stocking.

Optionally on safe standing tripod or with clamping device for workbench.

Height adjustable, REMS Herkules 3B from 690 to 1,180 mm from the floor, REMS Herkules Y from 35 to 580 mm from the workbench surface.

Supply format

REMS Herkules. Vertically adjustable material support for pipes, solid material Ø (⅛) ¾ – 6", Ø (6) 26 – 168 mm. Optionally on tripod or with clamping device for workbench. Load capacity ≤ 150 kg. In a carton.

Description	Version	Art.-No.	KM
REMS Herkules 3B	Tripod with protection caps	120120R	**676,00**
REMS Herkules Y	Clamping fixture for work bench	120130R	**408,00**

Height adjustable material support with ball guide for rotating and standing tubular and solid material.
For trade and industry. For the building site and the workshop.

Pipes, solid material	Ø (⅛) 1¼ – 12", Ø (6) 42 – 324 mm
Load capacity	≤ 450 kg

REMS Herkules XL 12" – extra stable for pipes up to 12".

Especially suitable for pipe installation, e.g. for roll grooving, cutting, thread cutting, welding, soldering.

Easy moving of the material in all directions when turning, pulling and pushing by two stainless steel balls mounted in a rust-protected housing in the range Ø 1¼ – 12", Ø 42 – 324 mm.

Robust, job site-proven design. Securely standing tripod, folds up for transport and storage.

Height adjustable from 505 to 915 mm from the floor.

Threaded spindle for simple alignment of the pipe, with fixing device.

Practical handle for easy transport.



Supply format

REMS Herkules XL 12". Height adjustable, fold-up for pipes, solid material Ø 1¼ – 12", Ø 42 – 324 mm. Load capacity ≤ 450 kg. In a carton.

	Art.-No.	KM
	120125R	**733,00**

REMS Helix 22 V VE

Cordless power drill/screwdriver

Powerful, mobile, handy power tool for drilling, driving in/loosening screws and deburring pipes. For assembly, disassembly, repair. Li-Ion 22 V Technology. For battery and corded operation.	
Drilling in steel, stone	≤ Ø 13 mm
Drilling in wood	≤ Ø 32 mm
Drilling with tile drills, e.g. in ceramic, fine clay, granite, marble	≤ Ø 14 mm
Driving in/loosening of screws	≤ Ø 8 mm

REMS Helix 22 V VE – drilling, screw riving and deburring. With powerful, brushless battery motor.

Design

Ultra light, ultra small, ultra handy. Drive machine with battery pack weighs only 1.6 kg. Can therefore be used everywhere, free hand, over head, also in very confined spaces. Optimum weight distribution for one-hand operation. Ergonomically designed housing. Drive machine with keyless quick chuck, clamping range 1.5 – 13 mm, right and left hand rotation. 2 continuously adjustable speed ranges from 0 to 560 rpm and 0 to 1,900 rpm, 15 torque stages plus drilling stage, hard torque of 50 Nm in both speed ranges, soft torque of 12 Nm in the fast and 30 Nm in the slow speed range for powerful screwdriving. Integrated LED work light for illuminating the work place. Belt clip. For cordless and mains operation. 1 bit with double blade slot/cross-head, 50 mm long. Bit set as accessory.

Drive

Powerful electro-mechanical drive with powerful, brushless battery motor 21.6 V, 500 W output, robust, 2-step, precision, ball bearing-mounted gear, maintenance-free. Safety switch.

Vario-Electronic

Continuous electronic speed control for gentle start drilling, driving in/loosening of screws and selection of the speed suitable for the material when drilling and driving in/loosening screws. The speed can be continuously controlled by variable pressure on the safety switch from 0 to 560 rpm or 0 to 1,900 rpm (accelerator switch (VE)).

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 1.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. 220 – 240 V/21.6 V, 15 A output, voltage supply for mains operation instead of Li-Ion battery 21.6 V, as accessory.

LED

Info

REMS Helix 22 V VE

Cordless power drill/screwdriver

Supply format

REMS Helix 22 V VE Set. Cordless power drill/screwdriver with Vario-Electronics (VE) for drilling in steel, stone, ≤ Ø 13 mm, wood ≤ Ø 32 mm and other materials and for driving in/loosening screws ≤ Ø 8 mm. Drive machine with keyless quick chuck, clamping range 1.5 – 13 mm, right and left hand rotation. Electromechanical drive with powerful, brushless battery motor 21.6 V, 500 W, 2-step robust gear. 2 continuously adjustable speed ranges from 0 to 560 rpm and 0 to 1,900 rpm, 15 torque stages plus drilling stage, hard torque of 50 Nm in both speed ranges. Safety switch. Integrated LED work light. Belt clip. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. 1 bit with double blade slot/cross-head, 50 mm long. In carrying bag.

	Art.-No.	KM
	190110 R220	**1.010,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS REG 10 – 42. Outer/inner pipe deburrer for pipes Ø 10 – 42 mm, Ø ½ – 1⅝", see page 98		
REMS REG 10 – 54 E. Outer/inner pipe deburrer for pipes Ø 10 – 54 mm, Ø ½ – 2⅛", see page 99		
REMS KaliGrat E. Calibrating tool and outer-inner pipe deburrer for multi-layer composite tubes Ø 14 – 63 mm, see page 100		
REMS tile drilling, Ø 5 – 14 mm, see page 320		
REMS Helix 22 V VE drive unit, without battery	190100 R22	**484,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567 R220	**838,00**
Carrying bag	190053 R	**94,50**
Bit set, comprising quick-change bit holder, magnetic, with automatic bit lock, 12 bits (4 Torx, 3 cross-head PH, 3 cross-head PZ, 2 slotted), in practical magazine with elastic band for fixing to wrist or to the power tool.	190051 R	**32,20**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

REMS Lumen 5000/7000/10000

Electric LED flood light

Powerful, electric LED flood light with high light intensity. For the building site and the workshop.

REMS Lumen 5000	
Light flux	5000 lm
REMS Lumen 7000	
Light flux	7000 lm
REMS Lumen 10000	
Light flux brightness stage 1	5000 lm
Light flux brightness stage 2	10000 lm

REMS Lumen 5000/7000/10000 – electric lighting. With high light intensity. Handy, light. Continuous swivel.

Universal use

Powerful, mobile, electric LED flood light with high light intensity for universal use on the building site or in the workshop. REMS Lumen 10000 with 2 selectable brightness stages for any application purpose.

Design

Handy, light, electric LED flood light. REMS Lumen 5000 only 1.8 kg, REMS Lumen 7000 only 2.2 kg, REMS Lumen 10000 only 3.0 kg. Impact-resistant aluminium housing, dust-proof, protected against water jets from all directions. LEDs protected by impact-resistant, unbreakable acrylic glass. Flood light housing swivels through 360°, fixable by star grips, for optimum alignment of the light. On/Off switch. Tubular steel frame with rubber feet for a firm stand. Practical, non-slip handle. Practical, sturdy, telescopic tripod stand, only 1.9 kg, for accurate positioning of the LED flood light, adjustable height from 615 to 1,590 mm above floor level, collapsible for easy transport, as an accessory.

LED flood light

Modern, energy-saving LED flood light with high light intensity. Lights immediately without switch-on delay. Brightness of the LEDs in REMS Lumen 10000 selectable in 2 stages. 120° radiation angle for good illumination. Colour temperature 5,000 K. Efficient heat dissipation by high-quality, aluminium, ribbed heat sinks. Overheating regulates the power supply automatically, for continuous operation.

Info

Supply format

REMS Lumen. Electric LED flood light with high light intensity. 230 V, 50 – 60 Hz. 5 m connecting lead. In a carton.

Description	Light flux ≤ lm	Power ≤ W	Art.-No.	KM
Lumen 5000	5000	50	175220R220	**166,00**
Lumen 7000	7000	70	175221R220	**200,00**
Lumen 10000	10000	100	175222R220	**250,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS 3B telescopic stand, on a tripod, height-adjustable, collapsible	175230R	**62,80**

All prices excl. VAT

REMS Lumen 2800 22 V

Cordless LED flood light

Powerful, mobile cordless LED flood light with high light intensity. Li-Ion 22 V Technology. For battery and corded operation. For the building site and the workshop.

Light flux brightness stage 1	1100 lm
Light flux brightness stage 2	2000 lm
Light flux brightness stage 3	2800 lm

REMS Lumen 2800 22 V – lights everywhere. With high light intensity. Mobile, handy, light. For battery and corded operation. Continuous swivel.

Universal use

Powerful, mobile, cordless LED flood light with high light intensity for universal use on the building site or in the workshop. 3 selectable brightness stages, ideal for any application purpose.

Design

Handy, lightweight, cordless LED flood light, only 1.7 kg, with battery only 2.1 kg. Impact-resistant plastic housing. LEDs protected by impact-resistant, unbreakable acrylic glass. Flood light housing swivels through 360°, fixable by wing nuts, for optimum alignment of the light. On/Off switch. Tubular steel frame with plastic plate and pluggable hook, for fastening or hanging the flood light. Practical, non-slip handle. 220 – 240 V, 50 – 60 Hz, 138 W power supply, for mains operation included. Holder for REMS Li-Ion 21.6 V integrated into the housing for cordless instead of mains operation. In cordless operation with Li-Ion 21.6 V, 2.5 Ah, 54 Wh (output). Practical, sturdy, telescopic tripod stand, only 1.9 kg, for accurate positioning of the LED flood light, adjustable height from 615 to 1,590 mm above floor level, collapsible for easy transport, as an accessory.

LED flood light

Modern, energy-saving LED flood light with high light intensity. Lights immediately without switch-on delay. LED brightness selectable in 3 stages. 120° radiation angle for high illumination. Colour temperature 6,500 K. Efficient heat dissipation by high-quality, aluminium, ribbed heat sinks prevents overheating. For continuous operation.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory.

Description	Operating hours h*		
	Stage 1	Stage 2	Stage 3
Battery Li-Ion 21.6 V, 2.5 Ah	5.4	2.4	1.6
Battery Li-Ion 21.6 V, 4.4 Ah	9.6	4.2	2.8
Battery Li-Ion 21.6 V, 5.0 Ah	10.9	4.8	3.2
Battery Li-Ion 21.6 V, 9.0 Ah	19.6	8.6	5.7

Info

Supply format

REMS Lumen 2800 22 V Set Power-Edition. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Voltage supply 220 – 240 V, 50 – 60 Hz, 138 W. Without battery, without rapid charger. In a carton.

	Art.-No.	KM
	175210 R220	**292,00**

Other voltages on request.

Supply format

REMS Lumen 2800 22 V Set. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Voltage supply 220 – 240 V, 50 – 60 Hz, 138 W. In a carton.

	Art.-No.	KM
	175211 R220	**922,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
REMS 3B telescopic stand, on a tripod, height-adjustable, collapsible	175230 R	**62,80**

All prices excl. VAT

*Ambient temperature approx. 20°C.



Pressure testing
Cleaning
Disinfecting
Preserving
Flushing
Filling

	Hand pressure testing pump	114
	Electric pressure testing pump	115
	Electric decalcifying pump	116
	Electronic flushing unit with compressor	117
	Electronic flushing and pressure testing unit with compressor	120
	Disinfection unit TW, cleaning and preservation unit H	123
	Machine cleaner	123
	Electric filling and flushing unit	124

REMS Push

Hand pressure testing pump

Proven, reliable testing pump for pressure and tightness tests of piping systems and receptacles.	
Testing and pressure range	≤ 6 MPa/60 bar/870 psi
Water, oil, glycol	
pH-value of liquids	7 – 12
Temperature of liquids	≤ 60°C
Viscosity of liquids	≤ 1.5 mPa s

Info

REMS Push – reliable pressure hold.

Universal use
For plumbing, heating, solar system and sprinkler installations, for compressed air, steam and cooling systems, oil installations, for boiler and pressure vessel building.

Design
Robust, job-site proven metal design for tough use. REMS Push with corrosion-resistant, powder-coated 12 ltr steel tank. Distortion resistant lever with ergonomic handle, doubles as carrying handle when locked. Wear resistant pressure piston in brass, Ø 30 mm. High-pressure hose with ½"-connection. Fine scale pressure gauge (accessory), p ≤ 1.6 MPa/16 bar/232 psi, for reading a pressure change of 0.01 MPa/0.1 bar/1.45 psi for tightness testing according to DIN 1988, as accessory.

Stainless steel tank
REMS Push INOX with 12 ltr stainless steel tank. For extremely long life.

Functioning
Pressure and tightness test with water or oil. Double valve system for reliable pressure built-up, with rust-proof steel balls. High pumping capacity with long stroke, fine pressure adjustment at short pushes. High pressure hose with fabric ply prevents measurement errors.

Supply format

REMS Push. Hand pressure testing pump with pressure gauge, p ≤ 6 MPa/ 60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi, Corrosion-resistant, powder-coated 12 ltr steel tank. 1.5 m high-pressure hose with ½"-connection. In a carton.

	Art.-No.	KM
	115000R	**563,00**

Supply format

REMS Push INOX. Hand pressure testing pump with pressure gauge, p ≤ 6 MPa/60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi. 12 ltr stainless steel tank. 1.5 m high-pressure hose with ½"-connection. In a carton.

	Art.-No.	KM
	115001R	**725,00**

Accessories

Description	Pressure p ≤ MPa/bar/psi	Art.-No.	KM
Connecting piece with pressure gauge and shut off valve	6/60/870	115110R	**250,00**
Fine scale pressure gauge	1.6/16/232	115045	**161,00**

All prices excl. VAT

REMS E-Push 2

Electric pressure testing pump

Powerful, electric pressure testing pump for pressure and tightness tests of piping systems and receptacles.	
Testing and pressure range	≤ 6 MPa/60 bar/870 psi
Pumping capacity	6.5 l/min
Water, hydrous solutions, emulsions	
pH-value of liquids	7 – 10
Temperature of liquids	≤ 60°C
Viscosity of liquids	≤ 1.5 mPa s

REMS E-Push 2 – electric charging and testing. Up to 60 bar. With adjustable pressure limiting. 1300 W. Self sucking.

Universal use

In sanitary, heating, solar and sprinkler installation, for compressed air, steam and cooling systems, oil installations, in boiler and pressurised vessel construction.

Design

Robust, compact, light. Weighs only 10 kg. Easy to carry. Wear reduced high power piston pump. Pressure gauge, damped by filling with glycerine, p ≤ 6 MPa/60 bar/870 psi. High-pressure hose with fabric ply prevents measurement errors. Suction hose with suction filter. Non-return valve in the suction hose prevents the suction hose from running empty in standstill times; therefore shorter suction times. Suction hose and high pressure hose with ½"-connection. Connecting piece with pressure gauge, p ≤ 6 MPa/60 bar/870 psi, and shut off valve for pressure and tightness testing also after removal of the high pressure pump, e.g. theft protection or for use at several testing points, as accessory. Fine scale pressure gauge, p ≤ 1.6 MPa/16 bar/232 psi, for reading a pressure change of 0.01 MPa/0.1 bar/1.45 psi for tightness testing according to DIN 1988, as accessory.

High power piston pump

Self-sucking high power piston pump running in a sealed oil bath with wear reduced pressure piston in stainless steel. Proven, powerful capacitor motor, 1300 W, very powerful and fast. High pumping capacity of 6.5 l/min. Pressure and tightness testing up to 6 MPa/60 bar/870 psi.

Adjustable pressure limiting

Pressure limiting in 6 stages, 1 – 6 MPa/10 – 60 bar/145 – 870 psi, adjustable to the necessary pressure in the pipe system/tank.

Info

Supply format

REMS E-Push 2. Electric pressure testing pump with pressure gauge, p ≤ 6 MPa/60 bar/ 870 psi, for pressure and leak testing of pipe systems and tanks up to 6 MPa/60 bar/870 psi, with adjustable pressure limiting. Pump unit with capacitor motor 230 V, 50 Hz, 1300 W. 1.5 m suction hose with ½" connection and gaskets, suction filter with non-return valve. 1.5 m high-pressure hose with ½" connection and gaskets. In a carton.

	Art.-No.	KM
	115500R220	**1.910,00**

Accessories

Description	Pressure p ≤ MPa/bar/psi	Art.-No.	KM
Connecting piece with pressure gauge and shut off valve	6/60/870	115110R	**250,00**
Fine scale pressure gauge	1.6/16/232	115045	**161,00**

REMS Calc-Push

Electric decalcifying pump

Powerful, electric decalcifying pump for effective decalcifying of pipes and containers, e.g. flow heaters, boilers, hot water tanks, cold water tanks, heat exchangers, heating and cooling systems.	
Useful container volume	21 l
Displacement	≤ 30 l/min
Displacement pressure	≤ 0.1 MPa/1.0 bar/15 psi
Transport height	≤ 10 m
Temperature of decalcifying solution	≤ 50°C

Info

REMS Calc-Push – effective electric decalcifying. High displacement. 3-way lever for reversal of flow direction, with zero setting.

Universal use

For effective decalcifying of pipes and containers, e.g. flow heaters, boilers, hot water tanks, cold water tanks, heat exchangers, heating and cooling systems.

Design

Robust, compact, light, weights just 9.2 kg. Impact-proof plastic container for the decalcifying solution, useful container volume 21 l, with practical screw-on cap for closing the plastic container during transport. Flexible ½", 2.3 m long flexible PVC fabric hoses, with hose screw fittings with Rp ½" female thread and caps. 3-way lever for reversing the flow direction to remove even heavy lime deposits from both sides, with zero setting to interrupt the flow. Easy to carry due to centrally arranged handle with practical hose holders.

Unscrewable pump unit

Compact pump unit, consisting of a centrifugal pump and condenser motor, unscrewable, for easy cleaning of the pump unit and the plastic container after the decalcifying process. Self-sucking centrifugal pump, suitable for different decalcifying solutions of acetic acid, sulphuric acid, citric acid, formic acid, phosphoric acid, sulfamic acid. With proven, powerful condenser motor with quiet running, 165 W, on/off switch. High displacement ≤ 30 l/min for effective decalcifying.

Supply format

REMS Calc-Push. Electric decalcifying pump for effective decalcifying of pipes and containers, e.g. flow heaters, boilers, hot water tanks, cold water tanks, heat exchangers, heating and cooling systems. Displacement ≤ 30 l/min, useful container volume 21 l. Pump unit with condenser motor 230 V, 50 Hz, 165 W. Displacement pressure ≤ 0.1 MPa/1.0 bar/15 psi. Transport height ≤ 10 m. Flexible ½", 2.3 m long flexible PVC fabric hoses, with hose screw fittings with Rp ½" female thread and caps. 2 double nipples ⅜" – ½", 2 double nipples ½" – ¾". In a carton.

	Art.-No.	KM
	115900R220	**1.680,00**

Other voltages on request.

All prices excl. VAT

REMS Multi-Push S

Electronic flushing unit with compressor

Powerful, compact, electronic flushing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems and for operation of pneumatic tools.	
Flushing and desilting	
Water pressure pipe network	p ≤ 1 MPa/10 bar/145 psi
Pipe diameter installation	≤ DN 50, 2"
Disinfection of drinking water installations	
Cleaning and preservation of radiators and area heating systems	
Water temperature	5 – 35°C
Water flow	≤ 5 m^3/h
Operation of pneumatic tools	
Operating pressure	p ≤ 0.8 MPa/8 bar/116 psi
Suction rate	≤ 230 Nl/min

Patent EP 2 954 960

REMS Multi-Push S – Flushing with water or a water/air mixture. Easy switching of the air supply during the flushing process when desilting. Permanent process monitoring. Logging. USB interface.

Universal use

Only **one** device for flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, e.g. for desilting, cleaning and preservation of radiators and area heating systems, flushing and disinfection of drinking water installations in accordance with EN 806-4:2010 and for operating pneumatic tools.

Design

Powerful, compact, electronic flushing unit with oil-free compressor. Handy, easily portable, only 32 kg. Measuring and control devices for automatically running the flushing programs and for documenting the results. Safety devices for avoiding contamination of the pipe network by flow-back. Overpressure valve for pressure limiting. 5 µm condensation and particle filters. Large tubular steel frame as a compressed air tank. Two practical handles for easy carrying. Space-saving, folding handle grip for easy movement. Mobile tubular steel frame with two rubber-tyred wheels for easy transport and 2 rubber feet for firm standing. Connecting cable with integrated personal protection switch (PRCD). 2 hooks for winding up the power cable. Captive seals for input and output of the REMS Multi-Push S to avoid contamination during transport and storage. Practical hood for protecting the machine during transport and storage as an accessory.

Compressor

Proven, powerful, oil-free piston compressor with crank drive, with capacitor motor 230 V, 1500 W. Pressure gauge for displaying the air pressure in the compressed air tank. Emergency stop button.

Hoses

Transparent Ø 1" suction/pressure hose, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps, for flushing, disinfection, cleaning, preservation. Captive caps for the inputs and outputs of the hoses to avoid contamination during transport and storage. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push S and suction/pressure hoses at the end of work.

Input and control unit

Easy desilting operation by buttons to switch over the air supply during the flushing process. Menu-guided input and menu-guided control for flushing drinking water installations according to EN 806-4:2010 with the possibility for the user to change the factory-set default values for adaptation to the applicable national safety provisions, rules and regulations for the application site. Format selection for date and time and selection of the different units. Input and control unit with 3" display with modern LCD technology, 76 mm screen diagonal, 128 × 64 pixels. Permanent process monitoring during the program sequences. USB port for USB stick or printer. The respective latest version software for the input and control unit is available via USB stick as a download under www.rems.de > Downloads > Software.

German Quality Product

Info

REMS Multi-Push S

Electronic flushing unit with compressor

Desilting and flushing
Buttons for easy switching of the air supply during the flushing process when desilting radiator and flat heater systems with the following possibilities: (1) without compressed air, (2) intermittent compressed air, (3) constant compressed air.

Flushing according to EN 806-4
Flushing of drinking water installations with water or with a water/air mixture with intermittent compressed air in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK).

Disinfection
REMS V-Jet TW disinfection unit for disinfection of drinking water installations in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK) and other pipe systems, as an accessory. REMS Peroxi Color, consisting of a 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume and 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution, as an accessory. Feeding of the disinfectant solution without additional dosing pump **(Patent EP 2 954 960).**

Cleaning and preservation
REMS V-Jet H cleaning and preservation unit for cleaning and preserving radiators and area heating systems, as an accessory. Cleaner, dyed green for filling and wash-out check and corrosion protection, dyed blue for filling check, for approx. 100 l line volume respectively, as an accessory. Feeding of cleaner and corrosion protection without additional dosing pump **(Patent EP 2 954 960).**

Operation of pneumatic tools
Connection for pneumatic tools up to an air requirement ≤ 230 Nl/min, adjustable, for adaptation to the pneumatic tool being used. Pressure gauge for controlling the air pressure supplied by the compressed air tank. Pneumatic hose with quick coupling DN 7.2, as an accessory.

Logging
Results of the flushing programs are saved with date, time and log number in the selected language and can be transferred to USB stick or printer for documentation. Printer as an accessory. Additions to saved data, e.g. customer name, project number, tester, are possible on external devices (e.g. PC, laptop, tablet-PC, Smartphone).

Supply format

REMS Multi-Push S Set. Electronic flushing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, e.g. for desilting, cleaning and preservation of radiators and area heating systems, flushing and disinfection of drinking water installations and for operation of pneumatic tools ≤ 230 Nl/min. Input and control unit. Piston compressor with crank drive, capacitor motor 230 V, 50 Hz, 1,500 W, person circuit breaker (PRCD). Mobile tubular steel frame. Fastenings for water input and output of the REMS Multi-Push S. Two Ø 1" suction/pressure hoses, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push S and suction/pressure hoses at the end of work. Without disinfection unit, without cleaning and preservation unit. In a carton

	Art.-No.	KM
	115810R220	**5.020,00**

Other voltages on request.

All prices excl. VAT

REMS Multi-Push S

Electronic flushing unit with compressor

Description	Art.-No.	KM
Fine filter with fine filter cartridge 90 µm, washable, with large dirt collection vessel	115609R	**250,00**
Fine filter cartridge 90 µm, for fine filter with fine filter cartridge 90 µm	043054	**81,10**
Compressed air hose Ø 14 mm, 1.5 m long, with quick couplings DN 7.2 (plug, socket), for connecting pneumatic tools	115621R	**126,00**
Ø 1" suction/pressure hose, with fabric inlay, 1.5 m long, with G 1" screw fittings for flushing, disinfection, cleaning, preservation and pressure testing with water.	115633R	**120,00**
Double nipple 1", for connecting 2 suction/pressure hoses and blowing out the suction/pressure hoses	045159	**21,00**
Printer for printing the stored results of the flushing and test programs, 1 roll of paper, USB connecting cable, power supply/charger Ni-Mh 100 – 240 V, 50 – 60 Hz, 3 W	115604R	**1.030,00**
Paper roll, pack of 5 for printer	090015R	**38,20**
Case with inlays for printer, paper rolls and other accessories	115703R	**143,00**
REMS V-Jet TW, disinfection unit for drinking water installations, for feeding dosing solution for disinfection	115602R	**615,00**
REMS Peroxi Color, 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume, 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution.	115605R	**166,00**
Test strips H_2O_2 0 – 1,000 mg/l, pack of 100, for checking the concentration of the disinfection solution	091072	**144,00**
Test strips H_2O_2 0 – 50 mg/l, pack of 100, for checking the complete flushing out of the disinfection solution after disinfection	091073	**144,00**
REMS V-Jet H, cleaning and preservation unit for radiators and area heating systems, for feeding cleaner and corrosion protection.	115612R	**615,00**
REMS CleanH 1 l bottle of cleaner for radiators and area heating systems, dyed green for filling and wash-out check, for approx. 100 l line volume.	115607R	**116,00**
REMS NoCor 1 l bottle of corrosion protection for preservation of radiators and area heating systems, dyed blue for filling check, for approx. 100 l line volume.	115608R	**124,00**
Hood for protecting the machine during transport and storage	115677R	**79,40**
XL-Boxx system case for hoses	579600RMP	**401,00**

REMS Multi-Push SL/SLW

Electronic flushing and pressure testing unit with compressor

Powerful, compact, electronic flushing and pressure testing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, for pressure testing of pipe systems and vessels with compressed air or water, as a pneumatic pump for controlled filling of all types of vessels with compressed air and for operation of pneumatic tools.

Flushing and desilting	
Water pressure pipe network	p ≤ 1 MPa/10 bar/145 psi
Pipe diameter installation	≤ DN 50, 2"
Disinfection of drinking water installations	
Cleaning and preservation of radiators and area heating systems	
Water temperature	5 – 35°C
Water flow	≤ 5 m^3/h
Pressure test with compressed air	p ≤ 0.4 MPa/4 bar/58 psi
Pressure test with water	p ≤ 1.8 MPa/18 bar/261 psi
Pneumatic pump for controlled filling of all types of vessels with compressed air	p ≤ 0.8 MPa/8 bar/116 psi
Operation of pneumatic tools	
Operating pressure	p ≤ 0.8 MPa/8 bar/116 psi
Suction rate	≤ 230 Nl/min

REMS Multi-Push SL/SLW – just one device with more than 10 automatically running flushing and pressure testing programs. Permanent process monitoring. Logging. USB interface.

Universal use

Only **one** device for flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, for pressure testing of pipe systems and vessels with compressed air or water, e.g. drinking water installations, radiators or area heating systems, for pressure testing of gas installations with compressed air, as a pneumatic pump for controlled filling of all types of vessels with compressed air, e.g. for pumping up expansion vessels or tyres and for operating pneumatic tools. **(Patent EP 2 816 231)**.

Design

Powerful, compact, electronic flushing and pressure testing unit with oil-free compressor. Handy, easily portable, REMS Multi-Push SL only 37 kg, REMS Multi-Push SLW only 39 kg. Measuring and control devices for automatically running the flushing and test programs and for documenting the results. Safety devices for avoiding contamination of the pipe network by flow-back. Overpressure valves for pressure limiting. 5 µm condensation and particle filters. Large tubular steel frame as a compressed air tank. Two practical handles for easy carrying. Space-saving, folding handle grip for easy movement. Mobile tubular steel frame with two rubber-tyred wheels for easy transport and 2 rubber feet for firm standing. Connecting cable with integrated personal protection switch (PRCD). 2 hooks for winding up the power cable. Captive seals for inputs and outputs of the REMS Multi-Push SL/SLW to avoid contamination during transport and storage. Practical hood for protecting the machine during transport and storage as an accessory.

REMS Multi-Push SLW additionally with hydro-pneumatic water pump for generating the necessary water pressure for hydrostatic pressure testing of pipe systems and vessels with water.

Compressor

Proven, powerful, oil-free piston compressor with crank drive, with capacitor motor 230 V, 1500 W. Pressure gauge for displaying the air pressure in the compressed air tank. Emergency stop button.

Hoses

Transparent Ø 1" suction/pressure hose, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps, for flushing, disinfection, cleaning, preservation and pressure testing with water. High-pressure hose Ø ½", with fabric inlay, 1.5 m long, with ½" hose screw fittings, with caps, for pressure testing with water with REMS Multi-Push SLW. Captive caps for the inputs and outputs of the hoses to avoid contamination during transport and storage. Compressed air hose Ø 8 mm, 1.5 m long, with quick coupling DN 5 and ½" hose screw fitting, for pressure testing with compressed air. Compressed air hose Ø 8 mm, 1.5 m long, with quick coupling DN 5 (plug, socket) for gas testing with compressed air. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push SL/SLW and suction/pressure hoses at the end of work.

Patent EP 2 816 231
Patent EP 2 954 960



German Quality Product

REMS Multi-Push SL/SLW

Electronic flushing and pressure testing unit with compressor

Input and control unit
More than 10 flushing and test programs in 26 languages. Easy desilting operation by buttons to switch over the air supply during the flushing process. Menu-guided input and menu-guided control for flushing drinking water installations according to EN 806-4:2010 with the possibility for the user to change the factory-set default values for adaptation to the applicable national safety provisions, rules and regulations for the application site. Format selection for date and time and selection of the different units. Input and control unit with 3" display with modern LCD technology, 76 mm screen diagonal, 128 × 64 pixels. Permanent process monitoring during the program sequences. USB port for USB stick or printer. The respective latest version software for the input and control unit is available via USB stick as a download under www.rems.de > Downloads > Software.

Desilting and flushing
Buttons for easy switching of the air supply during the flushing process when desilting radiator and flat heater systems with the following possibilities: (1) without compressed air, (2) intermittent compressed air, (3) constant compressed air.

Flushing according to EN 806-4
Flushing of drinking water installations with water or with a water/air mixture with intermittent compressed air in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK).

Disinfection
REMS V-Jet TW disinfection unit for disinfection of drinking water installations in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK) and other pipe systems, as an accessory. REMS Peroxi Color, consisting of a 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume and 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution (page 123). Feeding of the disinfectant solution without additional dosing pump **(Patent EP 2 954 960).**

Cleaning and preservation
REMS V-Jet H cleaning and preservation unit for cleaning and preserving radiators and area heating systems, as an accessory. Cleaner, dyed green for filling and wash-out check and corrosion protection, dyed blue for filling check, for approx. 100 l line volume respectively (page 123). Feeding of cleaner and corrosion protection without additional dosing pump **(Patent EP 2 954 960 pending).**

Pressure testing with compressed air
Leak testing of drinking water installations with compressed air according to information leaflet "Leak Testing of Drinking Water Installations with Compressed Air, Inert Gas or Water" (January 2011) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK), leak testing of gas installations with compressed air according to the technical rule "DVGW-TRGI 2018, Technical Rules for Gas Installations - DVGW Worksheet G 600" of the German Gas and Water Association (DVGW) and leak testing of other pipe systems and vessels with compressed air.

Load testing of drinking water installations with compressed air according to information leaflet "Leak Testing of Drinking Water Installations with Compressed Air, Inert Gas or Water" (January 2011) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK), load testing of gas installations with compressed air according to the technical rule "DVGW-TRGI 2018, Technical Rules for Gas Installations - DVGW Worksheet G 600" of the German Gas and Water Association (DVGW) and load testing of other pipe systems and vessels with compressed air.

Pressure testing with water
REMS Multi-Push SLW with hydro-pneumatic water pump for hydrostatic pressure testing of drinking water installations with water in accordance with EN 806-4:2010, test method A, B or C or test method B, modified in accordance with information leaflet "Leak Testing of Drinking Water Installations with Compressed Air, Inert Gas or Water" (January 2011) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK) and for pressure testing of other pipe systems and vessels.

Pneumatic pump
Pneumatic pump for controlled filling of all types of vessels with compressed air ≤ 0.8 MPa/8 bar/116 psi, with automatic switch-off on reaching the preset air pressure, e.g. for pumping up expansion vessels or tyres.

Operation of pneumatic tools
Connection for pneumatic tools up to an air requirement ≤ 230 Nl/min, adjustable, for adaptation to the pneumatic tool being used. Pressure gauge for controlling the air pressure supplied by the compressed air tank. Pneumatic hose with quick coupling DN 7.2, as an accessory.

Logging
Results of the flushing and test programs are saved with date, time and log number in the selected language and can be transferred to USB stick or printer for documentation. Printer as an accessory. Additions to saved data, e.g. customer name, project number, tester, are possible on external devices (e.g. PC, laptop, tablet-PC, Smartphone).

REMS Multi-Push SL/SLW

Electronic flushing and pressure testing unit with compressor

Supply format

REMS Multi-Push SL Set. Electronic flushing and pressure testing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, e.g. for desilting, cleaning and preservation of radiators and area heating systems, flushing and disinfection of drinking water installations, for pressure testing of pipe systems and vessels with compressed air, as a pneumatic pump for controlled filling of all types of vessels with compressed air p ≤ 0.8 MPa/8 bar/116 psi, and for operation of pneumatic tools ≤ 230 Nl/min. Input and control unit. Piston compressor with crank drive, capacitor motor 230 V, 50 Hz, 1,500 W, person circuit breaker (PRCD). Mobile tubular steel frame. Fastenings for water inputs and outputs of the REMS Multi-Push. Two Ø 1" suction/pressure hoses, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps. One Ø 8 mm compressed air hose, 1.5 m long, with quick coupling DN 5 and G ½" hose screw fitting, for pressure testing with compressed air. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push and suction/pressure hoses at the end of work. Without disinfection unit, without cleaning and preservation unit. In a carton

	Art.-No.	KM
	115610R220	**6.290,00**

Other voltages on request.

Info

Supply format

REMS Multi-Push SLW Set. Same as REMS Multi-Push SL Set, Art. No. 115610, additionally with hydro-pneumatic water pump for hydrostatic pressure testing of drinking water installations with water in accordance with EN 806-4:2010, test method A, B or C or test method B and for pressure testing of other pipe systems and vessels. One high-pressure hose Ø ½", 1.5 m long, with ½" hose screw fittings, with caps. In a carton.

	Art.-No.	KM
	115611R220	**8.120,00**

Other voltages on request.

Info

Accessories

Description	Art.-No.	KM
Fine filter with fine filter cartridge 90 µm, washable, with large dirt collection vessel	115609R	**250,00**
Fine filter cartridge 90 µm, for fine filter with fine filter cartridge 90 µm	043054	**81,10**
Pressure gauge, p ≤ 6 MPa/60 bar/870 psi, for pressure and leak testing of pipe systems and vessels up to 6 MPa/60 bar/870 psi.	115140	**226,00**
Fine scaled pressure gauge, p ≤ 1.6 MPa/16 bar/ 232 psi, for pressure and leak testing of pipe systems and vessels up to 1.6 MPa/16 bar/232 psi. CL 1.0.	115045	**161,00**
Fine scaled pressure gauge, p ≤ 250 hPa/250 mbar/ 3.6 psi, for pressure and leak testing of pipe systems and vessels up to 250 hPa/250 mbar/3.6 psi. CL 1.6.	047069	**486,00**
Compressed air hose Ø 14 mm, 1.5 m long, with quick couplings DN 7.2 (plug, socket), for connecting pneumatic tools	115621R	**126,00**
Compressed air hose Ø 8 mm, 7 m long, with quick coupling DN 5 (plug) and G ½" hose screw fitting, for pressure testing with compressed air.	115667R	**132,00**
Compressed air hose Ø 8 mm, 1.5 m long, with quick coupling DN 5 (plug, socket) for gas testing with compressed air.	115747R	**137,00**
High-pressure hose Ø ½", 7 m long, with G ½" hose screw fittings, with caps, for pressure testing of pipe systems and vessels with water with REMS Multi-Push SLW.	115661R	**261,00**
Ø 1" suction/pressure hose, with fabric inlay, 1.5 m long, with G 1" screw fittings for flushing, disinfection, cleaning, preservation and pressure testing with water.	115633R	**120,00**
Double nipple 1", for connecting 2 suction/pressure hoses and blowing out the suction/pressure hoses	045159	**21,00**

All prices excl. VAT

REMS Multi-Push SL/SLW

Electronic flushing and pressure testing unit with compressor

Description	Art.-No.	KM
Printer for printing the stored results of the flushing and test programs, 1 roll of paper, USB connecting cable, power supply/charger Ni-Mh 100–240 V, 50–60 Hz, 3 W	115604R	**1.030,00**
Paper roll, pack of 5 for printer	090015R	**38,20**
Case with inlays for printer, paper rolls and other accessories	115703R	**143,00**
REMS V-Jet TW, disinfection unit for drinking water installations, for feeding dosing solution for disinfection	115602R	**615,00**
REMS Peroxi Color, 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume, 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution.	115605R	**166,00**
Test strips H_2O_2 0–1,000 mg/l, pack of 100, for checking the concentration of the disinfection solution	091072	**144,00**
Test strips H_2O_2 0–50 mg/l, pack of 100, for checking the complete flushing out of the disinfection solution after disinfection	091073	**144,00**
REMS V-Jet H, cleaning and preservation unit for radiators and area heating systems, for feeding cleaner and corrosion protection.	115612R	**615,00**
REMS CleanH 1 l bottle of cleaner for radiators and area heating systems, dyed green for filling and wash-out check, for approx. 100 l line volume.	115607R	**116,00**
REMS NoCor 1 l bottle of corrosion protection for preservation of radiators and area heating systems, dyed blue for filling check, for approx. 100 l line volume.	115608R	**124,00**
Hood for protecting the machine during transport and storage	115677R	**79,40**
XL-Boxx system case for hoses	579600RMP	**401,00**

REMS CleanM

Machine cleaner

Highly effective machine cleaner for fast, reliable removal of oily and greasy soiling of all kinds.
For cleaning and degreasing machines, tools etc.
For trade and industry.

REMS CleanM – you can't get cleaner than that. Very high cleaning effect.

Especially for fast, reliable removal of oily and greasy soiling of all kinds. Easily biodegradable according to OECD 302 B. Free from substances classified as harmful to the environment.

Universal cleaner for trade and industry. For cleaning and degreasing machines and tools.

Can also be used for removing lime scale.

REMS CleanM spray bottle without propellant.

German Quality Product

Info

Supply format

REMS CleanM. Highly effective machine cleaner for fast and reliable removal of oily and greasy soiling. For cleaning and degreasing machines, tools etc.

	Packing	Art.-No.	KM
	500 ml spray bottle	140119R	**39,30**

All prices excl. VAT

REMS Solar-Push

Electric filling and flushing unit

Powerful electric filling and flushing unit for fast, easy filling, flushing and venting of closed systems. Ideal for solar power systems, ground heat systems and underfloor/wall heating.

Tank volume	30 litres
REMS Solar-Push K 60 with centrifugal pump	
Transport capacity at 40 m pumping head	16 l/min
Transport volume	≤ 36 l/min
Transport pressure	≤ 0.55 MPa/5.5 bar/80 psi
Temperature of the transported media (constant load)	≤ 60°C
pH value of the transported media	6.5 – 9.5
REMS Solar-Push I 80 with impeller pump	
Transport capacity at 40 m pumping head	18 l/min
Transport volume	≤ 27 l/min
Transport pressure	≤ 0.65 MPa/6.5 bar/94 psi
Temperature of the transported media (constant load)	≤ 80°C
pH value of the transported media	6.5 – 9.5
Media transported: heat transfer liquids, antifreeze, water, aqueous solutions, emulsions	

German Quality Product

REMS Solar-Push – filling, flushing and venting in one action. Self priming. High transport capacity.

System advantage

Filling, flushing and venting in one action. Ideal for solar power systems, ground heat systems and underfloor/wall heating. Also for filling tanks.

Design

Powerful, electric filling and flushing unit on stable, mobile tubular steel frame for secure standing. 2 large, air-filled tyres for easy transport in rugged building site conditions. Practical hose holder. Low weight, REMS Solar-Push I only 19 kg, REMS Solar-Push K only 20 kg. Sturdy plastic tank to hold 30 litres, made of UV-stabilised PE, with filling level indicator, removable, for easy cleaning, with large opening for easy filling. Practical screw cap for fast opening and closing. Return connection ¾" with immersion pipe avoids foaming of the transport medium when it enters the plastic tank. Stop tap for easy cleaning and easy changing of the plastic tank when using different transport media. Two practical handles for easy carrying of the plastic tank. High temperature-resistant connecting hose between plastic tank and pump. Fine filter in the suction line with large viewing window for easy recognition of residue air in the circuit as well as emitted contamination, e.g. chips, solder and welding residue.

REMS Solar-Push K 60

Self-suction centrifugal pump, suitable for different transport media, e.g. heat transfer liquids, antifreeze, water, aqueous solutions, emulsions. With proven, powerful condenser motor with quiet running, 940 W, on/off switch. High transport volume 36 l/min for fast filling, efficient flushing and venting of closed systems and for filling tanks. Pressure relief valve for simple pressure relief in the pressure hose at the end of operation, as an accessory. For continuous load ≤ 60°C. 2 pieces flexible, transparent PVC fabric hoses ½" T60, for pressure and return lines, each 3 m long, with ¾" hose screw fittings, temperature-resistant ≤ 60°C.

REMS Solar-Push I 80

Dry self-suction impeller pump with special impeller, suitable for different transport media, e.g. heat transfer liquids, antifreeze, water, aqueous solutions, emulsions. With proven, powerful condenser motor with quiet running, 1000 W, on/off switch. High transport volume 27 l/min for fast filling, efficient flushing and venting of closed systems and for filling tanks. Pressure relief valve for simple pressure relief in the pressure hose at the end of operation. For continuous load ≤ 80°C. 2 flexible EPDM fabric hoses ½" T100 (synthetic rubber) for pressure and return lines, each 3 m long, with ¾" hose screw fittings, high temperature-resistant ≤ 100°C.

Extensive accessories

Shut-off valve for closing the pressure or return line, e.g. during transport. Fine filter with fine filter bag 70 µm, consisting of a screw cap with return line connection for return line with ¾" union, adapter and fine filter bag 70 µm, or fine filter with fine filter cartridge 90 µm, washable, with large dirt collection vessel, for return line with ¾" connection for flushing underfloor heating/wall radiators and clearing sludge. Flow direction changeover valve complete with EPDM fabric hose ½" T100, for flushing underfloor heating/wall radiators and effective clearance of sludge by pressure surges when flow direction changes. Changeover valve for alternative suction of the transport medium from another tank, e.g. for larger volumes.

K 60

I 80

REMS Solar-Push

Electric filling and flushing unit

Info

Supply format

REMS Solar-Push K 60. Electric filling and flushing unit for fast, easy filling, flushing and venting of closed systems. Transport volume ≤ 36 l/min, tank volume 30 l. With centrifugal pump, temperature-resistant for continuous load ≤ 60°C. Transport pressure ≤ 0.55 MPa/5.5 bar/80 psi. Condenser motor 230 V, 50 Hz, 940 W. 2 pieces flexible, transparent PVC fabric hoses ½" T60, each 3 m long, temperature-resistant ≤ 60°C. On sturdy tubular steel frame with air-filled wheels. In box.

	Art.-No.	KM
	115312R220	**1.890,00**

Other voltages on request.

Supply format

REMS Solar-Push I 80. Electric filling and flushing unit for fast, easy filling, flushing and venting of closed systems. Transport volume ≤ 27 l/min, tank volume 30 l. With impeller pump, temperature-resistant for continuous load ≤ 80°C. Transport pressure ≤ 0.65 MPa/6.5 bar/94 psi. Transport capacity at 40 m transport height 10 l/min. Condenser motor 230 V, 50 Hz, 1000 W. Pressure relief valve. 2 pieces flexible, EPDM fabric hoses ½" T100, each 3 m long, high temperature-resistant ≤ 100°C. On sturdy tubular steel frame with air-filled wheels. In box.

	Art.-No.	KM
	115311R220	**2.310,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
PVC fabric hose ½" T60 for pressure or return line, 3 m long, with ¾" hose screw fittings, temperature-resistant ≤ 60°C.	115314R	**87,20**
EPDM fabric hose ½" T100 for pressure or return line, 3 m long, with ¾" hose screw fittings, high temperature-resistant ≤ 100°C	115315R	**117,00**
EPDM fabric hose ½" T165 for pressure or return line, 3 m long, with ¾" hose screw fittings, high temperature-resistant ≤ 165°C	115319R	**427,00**
¾" shut-off valve for closing the pressure or return line, e.g. during transport.	115324R	**106,00**
30 l plastic tank made of UV-stabilised PE.	115375R	**334,00**
Pressure relief valve for Solar-Push K 60.	115217R	**150,00**
Fine filter with fine filter bag 70 µm, consisting of a screw cap with return line connection for return line with ¾" union, adapter, 1 file filter bag 70 µm, for flushing underfloor heating/wall radiators and clearing sludge	115220	**213,00**
Fine filter bag 70 µm (pack of 10), fine file filter with fine filter bag 70 µm	115221R10	**180,00**
Fine filter with fine filter cartridge 90 µm, washable, with large dirt collection vessel, for return line with ¾" union, for flushing underfloor heating/wall radiators and clearing sludge	115323R	**445,00**
Fine filter cartridge 90 µm, for fine filter with fine filter cartridge 90 µm	043054	**81,10**
Flow direction changeover valve complete with EPDM fabric hose ½" T100, for flushing underfloor heating/wall radiators and effective clearance of sludge by pressure surges when flow direction changes	115326R	**590,00**
Changeover valve for alternative suction of the transport medium from another tank, e.g. for larger volumes.	115325R	**176,00**

All prices excl. VAT

45
90

Bending

	Single-hand tube bender	128
	Oil-hydraulic hand pipe bender	130
	Cordless electro-hydraulic tube bender	132
	Oil-hydraulic pipe bender	134
	Electric pipe and tube bender	136
	Cordless tube bender	140
	Hand tube bender	142

REMS Swing

Single-hand tube bender

Practical one-hand pipe bender for dimensionally accurate bending of pipes up to 90°. Ideal for on-site work. For trade and industry. For the building site and the workshop.	
Soft copper pipes, also thin-walled	Ø 10 – 22 mm Ø ⅜ – ⅞" s ≤ 1 mm
Coated soft copper tubes	Ø 10 – 18 mm Ø ⅜ – ⅝" s ≤ 1 mm
Soft, coated carbon steel pipes of the pressfitting systems	Ø 12 – 18 mm s ≤ 1.2 mm
Soft precision steel tubes	Ø 10 – 18 mm s ≤ 1 mm
Multi-layer composite tubes	Ø 14 – 32 mm



REMS Swing – bending tubes where they are installed. Ultra light, ultra small, ultra handy. Universally usable for many pipe types. Ultra fast operation by practical multifunction lever for fast in-feed and fast return. Proven, reliable ratchet feed. Ideal also for coated tubes.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Also for copper thin-walled heating tubes according to EN 1057 and for tubes of pressfitting systems.

Cost advantage

Bender recovered after a few bends through savings on fittings. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, job site-proven. Handy and light, drive unit only 0.9 kg. Can be used anywhere, free-hand, in confined areas. Easy, quick working, e.g. Ø 22 mm copper pipe bend in just 9 s. Marked bending formers for exact bending. Overbend, tier bend possible. Easy and rapid changing of bending formers. Back former support S Ø 10 – 26 mm, rotatable according to the size of the pipe to be bent, with back formers for pipes Ø 10 – 26 mm, ⅜ – ⅞". Back former support Ø 32 mm with back formers for pipe Ø 32 mm. Device for reverse bending on laid pipes up to Ø 22 mm, ⅞", as accessory.

Bending formers and sliding pieces

In high-strength, high-slide, glass-fibre reinforced polyamide. Angle scale on each bending former for dimensionally accurate bending. See table on page 129 for bending formers. UP bending formers with smaller bending radii for Uponor Uni Pipe PLUS composite pipes, see below.

Drive

Sturdy drive unit with proven, reliable ratchet feed for the complete work range up to Ø 32 mm. Practical multi-function lever for fast in-feed and fast return saves time and effort.

German Quality Product

Info

Supply format

REMS Swing UP Set. Single-hand tube bender Ø 16 – 32 mm, up to 90°. for Uponor Uni Pipe PLUS composite pipes Ø 16 – 32 mm. With UP drive unit, UP bending formers with smaller bending radii, UP back former supports Ø 16 – 32 mm with back formers, in a sturdy steel box/case.

Description mm	Art.-No.	KM
Set 16 + 20 + 25 + 32	153030R	**1.120,00**

Accessories

Description	Art.-No.	KM
REMS Swing UP drive unit	153300R	**311,00**
UP back former support Ø 16 – 32 mm with back formers for pipes Ø 16 – 32 mm	153307R	**197,00**
UP bending former Ø 16 mm, bending radius 32 mm	153303R	**94,30**
UP bending former UP Ø 20 mm, Biegeradius 40 mm	153304R	**94,30**
UP bending former UP Ø 25 mm, Biegeradius 62,5 mm	153305R	**94,30**
UP bending former UP Ø 32 mm, Biegeradius 80 mm	153306R	**307,00**
Steel case with inlay	153265R	**112,00**

Supply format

REMS Swing Set. Single-hand tube bender Ø 10 – 32 mm, Ø ⅜ – ⅞", up to 90°. Soft copper pipes Ø 10 – 22 mm, Ø ⅜ – ⅞", s ≤ 1 mm, soft, coated copper pipes Ø 10 – 18 mm, Ø ⅜ – ⅝", s ≤ 1 mm, soft, coated carbon steel pipes of the pressfitting systems Ø 12 – 18 mm, s ≤ 1.2 mm, soft precision steel pipes Ø 10 – 18 mm, s ≤ 1 mm, composite tubes Ø 14 – 32 mm. Up to Ø 26 mm with drive unit, bending formers, back former supports S Ø 10 – 26 mm with back formers, in a sturdy steel box/case. Up to Ø 32 mm with drive unit, bending formers, 2 back former supports Ø 10 – 26 mm and Ø 32 mm with back formers, in a sturdy steel case.

Description mm	inch	Art.-No.	KM
Set 12 + 15 + 18 + 22	½ + ⅝ + ¾ + ⅞"	153025R	**727,00**
Set 10 + 12 + 15 + 18 + 22	⅜ + ½ + ⅝ + ¾ + ⅞"	153021R	**760,00**
Set 12 + 14 + 16 + 18 + 22	½ + ¾ + ⅞"	153020R	**760,00**
Set 14 + 16 + 20 + 25/26		153026R	**727,00**
Set 14 + 16 + 18 + 20 + 25/26		153022R	**760,00**
Set 16 + 20 + 25/26 + 32		153029R	**1.160,00**
Set Allround 22 **10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22**	⅜ + ½ + ⅝ + ¾ + ⅞"	153027R	**977,00**
Set 16 + 18 + 20 + 25/26 + 32		153023R	**1.230,00**
Set Allround 32 **10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22 + 25/26 + 32**	⅜ + ½ + ⅝ + ¾ + ⅞"	153028R	**1.380,00**

Accessories

Description	Art.-No.	KM
REMS Swing drive unit	153100R	**311,00**
Back former support S Ø 10 – 26 mm with back formers for pipes Ø 10 – 26 mm, ⅜ – ⅞"	153125RX	**126,00**
Back former support Ø 32 mm with back formers for pipe Ø 32 mm	153115RX2	**270,00**
Device for reverse bending on laid pipes up to Ø 26 mm, ⅞"	153140	**313,00**
Steel case with inlay	153265R	**112,00**
Case with inlay	153270R	**219,00**

Bending former for tubes Ø mm/inch	Bending radius[1] mm	suitable for: Cu	Cu-U	St 10305-U	St 10305	V	Art.-No.	KM
10, ⅜"	30	●			●		153155R	**64,90**
12, 10 U, ½"	36	●	●		●		153160R	**64,90**
14, 12 U	50	●		●	●	●	153170R	**64,90**
15, 12 U, ⅝"	55	●	●		●		153175R	**64,90**
16, 14 U	55	●	●		●	●	153180R	**64,90**
17, 15 U	60			●		●	153185R	**64,90**
18, 14 U, 15 U, 16 U, ¾"	72	●	●		●	●	153190R	**64,90**
20, 18 U	79	●	●	●		●	153195R	**64,90**
22, 18 U, ⅞"	86	●	●				153200R	**64,90**
25, 26	88					●	153205R	**64,90**
32	128					●	153210R	**122,00**

[1] Bending radius mm at the neutral axis of the bend (DVGW GW 392)

Cu: soft copper tubes, also thin-wall
St 10305-U: soft, coated carbon steel pipes of the pressfitting systems EN 10305-3
St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3
U: coated
V: multi-layer composite tubes of pressfitting systems

REMS Hydro-Swing

Oil-hydraulic hand pipe bender

Effort-saving, oil-hydraulic hand pipe bender for dimensionally accurate bending of pipes up to 90°. Ideal for on-site work. For trade and industry. For the building site and the workshop.	
Soft copper pipes, also thin-walled	Ø 10 – 22 mm Ø ⅜ – ⅞" s ≤ 1 mm
Coated soft copper tubes	Ø 10 – 18 mm Ø ⅜ – ⅝" s ≤ 1 mm
Pipes of press fitting systems made of:	
stainless steel, nickel steel	Ø 15 – 22 mm s ≤ 1.2 mm
Soft, coated carbon steel	Ø 12 – 18 mm s ≤ 1.2 mm
Soft precision steel tubes	Ø 10 – 22 mm s ≤ 1.5 mm
Multi-layer composite tubes	Ø 14 – 32 mm

REMS Hydro-Swing – bending tubes where they are installed. Universally usable for many pipe types. Effortless working due to oil-hydraulic force transmission.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Also for copper thin-walled heating tubes according to EN 1057 and for tubes of pressfitting systems.

Cost advantage

Bender recovered after a few bends through savings on fittings. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Robust, compact drive unit with closed, maintenance-free hydraulic system. Handy and light, only 2.4 kg. Can be used anywhere, even in confined spaces. Easy, quick working, e.g. Ø 22 mm copper pipe bend in just 18 s. Marked bending formers for exact bending. Overbend, tier bend possible. Easy and rapid changing of bending formers. Back former support H-S Ø 10 – 26 mm, rotatable according to the size of the pipe to be bent, with back formers for pipes Ø 10 – 26 mm, ⅜ – ⅞". Back former support Ø 32 mm with back formers for pipes Ø 32 mm. Device H-S for reverse bending on laid pipes up to Ø 26 mm, ⅞", as accessory.

Bending formers and sliding pieces

Bending formers and back formers made of high strength, high sliding, glass fibre reinforced polyamide or aluminium bending formers. Angle scale on each bending former for dimensionally accurate bending. See table on page 131 for bending formers.

Drive

Oil-hydraulic drive unit with hydraulic cylinder made from high-quality, rolled hydraulic tube. Ergonomically designed thrust lever for strength saving pressure build-up with manual hydraulic pump. Reliable hydraulic thrust with overload protection in the foremost piston position and overpressure valves for safe working.

German Quality Product

Info

REMS Hydro-Swing

Oil-hydraulic hand pipe bender

Supply format

REMS Hydro-Swing Set. Oil-hydraulic hand pipe bender Ø 10 – 32 mm, Ø ⅜ – ⅞", up to 90°. Soft copper pipes Ø 10 – 22 mm, Ø ⅜ – ⅞", s ≤ 1 mm, soft, coated copper pipes Ø 10 – 18 mm, Ø ⅜ – ⅝", s ≤ 1 mm, pipes of the press fitting systems made of soft, coated carbon steel Ø 12 – 18 mm, s ≤ 1.2 mm, soft precision steel pipes Ø 10 – 18 mm, s ≤ 1.5 mm, composite tubes Ø 14 – 32 mm. Up to Ø 26 mm with drive unit, polyamide bending formers, back former support H-S Ø 10 – 26 mm with back formers, in a sturdy case. Up to Ø 32 mm with drive unit, polyamide bending formers, 2 back former supports Ø 10 – 26 mm and Ø 32 mm with back formers, in a sturdy case.

Description mm	inch	Art.-No.	KM
Set 12 + 15 + 18 + 22	½ + ⅝ + ¾ + ⅞"	153525RX	**1.420,00**
Set 10 + 12 + 15 + 18 + 22	⅜ + ½ + ⅝ + ¾ + ⅞"	153521RX	**1.470,00**
Set 12 + 14 + 16 + 18 + 22	½ + ¾ + ⅞"	153520RX	**1.470,00**
Set 14 + 16 + 20 + 25/26		153526R	**1.420,00**
Set 14 + 16 + 18 + 20 + 25/26		153522R	**1.470,00**
Set 16 + 20 + 25/26 + 32		153529R	**1.580,00**
Set Allround 22 **10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22**	⅜ + ½ + ⅝ + ¾ + ⅞"	153527RX	**1.530,00**
Set 16 + 18 + 20 + 25/26 + 32		153523R	**1.630,00**
Set Allround 32 **10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22 + 25/26 + 32**	⅜ + ½ + ⅝ + ¾ + ⅞"	153528RX	**1.740,00**

Supply format

REMS Hydro-Swing INOX Set. REMS Hydro-Swing with aluminium bending formers, especially also for
Geberit Mapress Stainless Steel (EN 10088, 1.4401),
Geberit Mapress Stainless Steel (EN 10088, 1.4521, nickel-free),
Geberit Mapress Carbon Steel (EN 10305-3, 1.0034 (E195)),
Viega Sanpress (EN 10088, 1.4401),
Viega Prestabo (EN 10305-3, 1.0308 (E235)).

Description mm	Art.-No.	KM
Set 15 + 18 + 22	153510R	**1.570,00**

Accessories

Description	Art.-No.	KM
REMS Hydro-Swing drive unit	153500R	**1.160,00**
Back former support H-S Ø 10 – 26 mm with back formers for pipe Ø 10 – 26 mm, ⅜ – ⅞"	153501R	**141,00**
Back former support Ø 32 mm with back formers for pipe Ø 32 mm	153115RX2	**270,00**
Device H-S for reverse bending on laid pipes up to Ø 26 mm, ⅞"	153450R	**481,00**
Case with inlay	153570R	**219,00**

Bending former for tubes Ø mm/inch	Bending radius[1] mm	suitable for: Cu	Cu-U	St 10217	St 10305	St 10305-U	V		
10, ⅜"	30	●			●			153155R	**64,90**
12, 10 U, ½"	36	●	●		●			153160R	**64,90**
14, 12 U	50	●			●	●	●	153170R	**64,90**
15, 12 U, ⅝" [2]	55	●	●	●	●			153531R	**149,00**
15, 12 U, ⅝"	55	●	●		●			153175R	**64,90**
16, 14 U	55	●	●		●		●	153180R	**64,90**
17, 15 U	60					●	●	153185R	**64,90**
18, 14 U, 15 U, 16 U, ¾" [2]	72	●	●	●	●		●	153532R	**149,00**
18, 14 U, 15 U, 16 U, ¾"	72	●	●		●		●	153190R	**64,90**
20, 18 U	79	●	●			●	●	153195R	**64,90**
22, 18 U, ⅞" [2]	86	●	●	●	●			153540R	**149,00**
22, 18 U, ⅞"	86	●	●					153200R	**64,90**
25, 26	88						●	153205R	**64,90**
32	128						●	153210R	**122,00**

[1] Bending radius mm at the neutral axis of the bend (DVGW GW 392)
[2] Aluminium bending formers

Cu: soft copper tubes, also thin-wall, EN 1057
St 10217: stainless, nickel steel pipes of the press fitting systems EN 10217-7, EN 10312, series 2, material 1.4401
St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3
St 10305-U: soft, coated carbon steel pipes of the pressfitting systems EN 10305-3
U: coated
V: multi-layer composite tubes of pressfitting systems

REMS Hydro-Swing 22 V

Cordless tube bender

Universal, mobile, handy electric tool for dimensionally accurate bending of pipes up to 90°. Ideal for on-site work. For trade and industry. For the building site and the workshop. Li-Ion 22 V Technology. For battery and corded operation.	
Soft copper pipes, also thin-walled	Ø 10 – 22 mm Ø ⅜ – ⅞" s ≤ 1 mm
Coated soft copper tubes	Ø 10 – 18 mm Ø ⅜ – ⅝" s ≤ 1 mm
Pipes of press fitting systems made of: stainless steel, nickel steel Soft, coated carbon steel	 Ø 15 – 22 mm s ≤ 1.2 mm Ø 12 – 18 mm s ≤ 1.2 mm
Soft precision steel tubes	Ø 10 – 22 mm s ≤ 1.5 mm
Multi-layer composite tubes	Ø 14 – 32 mm

REMS Hydro-Swing 22 V – bending tubes where they are installed. Mobile, handy, light. Universally usable for many pipe types. Li-Ion 21.6 V, 2.5 Ah battery, for approx. 110 stainless steel pipe bends of the Ø 22 mm press fitting systems with one battery charge*.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Also for copper thin-walled heating tubes according to EN 1057 and for tubes of pressfitting systems.

Cost advantage

Cordless tube bender recovered after a few bends through savings on fittings. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Robust, compact drive unit with closed, maintenance-free hydraulic system. Mobile, handy, light. Drive machine with battery pack weights only 3.0 kg. Can be used anywhere, even in confined spaces. Easy, quick working, e.g. Ø 22 mm stainless steel pipe bend in just 8 s. Marked bending formers for exact bending. Overbend, tier bend possible. Easy and rapid changing of bending formers. Back former support H-S Ø 10 – 26 mm, rotatable according to the size of the pipe to be bent, with back formers for pipes Ø 10 – 26 mm, ⅜ – ⅞". Back former support Ø 32 mm with back formers for pipes Ø 32 mm. LED work light for illuminating the work place. Device H-S for reverse bending on laid pipes up to Ø 26 mm, ⅞", as accessory.

Bending formers and sliding pieces

Bending formers and back formers made of high strength, high sliding, glass fibre reinforced polyamide or aluminium bending formers. Angle scale on each bending former for dimensionally accurate bending. See table on page 133 for bending formers.

Drive

Tons of thrust for crease-free bending within seconds. Thrust force 9 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 110 pipe bends, 4.4 Ah for approx. 190 pipe bends, 5.0 Ah for approx. 220 pipe bends, 9.0 Ah for approx. 396 pipe bends of the stainless steel Ø 22 mm press fitting systems with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

German Quality Product

Info

Supply format

REMS Hydro-Swing 22 V INOX Set. REMS Hydro-Swing 22 V with aluminium bending formers, especially also for
Geberit Mapress Stainless Steel (EN 10088, 1.4401),
Geberit Mapress Stainless Steel (EN 10088, 1.4521, nickel-free),
Geberit Mapress Carbon Steel (EN 10305-3, 1.0034 (E195)),
Viega Sanpress (EN 10088, 1.4401),
Viega Prestabo (EN 10305-3, 1.0308 (E235)).

Description mm	Art.-No.	KM
Set 15 + 18 + 22	153419R220	**3.000,00**

Other voltages on request.

All prices excl. VAT

REMS Hydro-Swing 22 V

Cordless tube bender

Supply format

REMS Hydro-Swing 22 V Set. Cordless tube bender Ø 10 – 32 mm, Ø ⅜ – ⅞", up to 90°. Soft copper pipes Ø 10 – 22 mm, Ø ⅜ – ⅞", s ≤ 1 mm, soft, coated copper pipes Ø 10 – 18 mm, Ø ⅜ – ⅝", s ≤ 1 mm, pipes of the press fitting systems made of soft, coated carbon steel Ø 12 – 18 mm, s ≤ 1.2 mm, soft precision steel pipes Ø 10 – 18 mm, s ≤ 1.5 mm, composite tubes Ø 14 – 32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Up to Ø 26 mm with polyamide bending formers, back former support H-S Ø 10 – 26 mm with back formers. Up to Ø 32 mm with polyamide bending formers, 2 back former supports Ø 10 – 26 mm and Ø 32 mm with back formers. In XL-Boxx system case.

Description mm	inch	Art.-No.	KM
Set 12 + 15 + 18 + 22	½ + ⅝ + ¾ + ⅞"	153410RX220	**2.820,00**
Set 10 + 12 + 15 + 18 + 22	⅜ + ½ + ⅝ + ¾ + ⅞"	153411RX220	**2.900,00**
Set 12 + 14 + 16 + 18 + 22	½ + ¾ + ⅞"	153412RX220	**2.900,00**
Set 14 + 16 + 20 + 25/26		153413R220	**2.820,00**
Set 14 + 16 + 18 + 20 + 25/26		153414R220	**2.900,00**
Set 16 + 20 + 25/26 + 32		153415R220	**3.000,00**
Set Allround 22 10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22	⅜ + ½ + ⅝ + ¾ + ⅞"	153416RX220	**3.150,00**
Set 16 + 18 + 20 + 25/26 + 32		153417R220	**3.210,00**
Set Allround 32 10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22 + 25/26 + 32	⅜ + ½ + ⅝ + ¾ + ⅞"	153418RX220	**3.610,00**
Basic-Pack (ohne Biegesegmente und Gleitstücke)		153401R220	**2.440,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Hydro-Swing 22 V drive unit, without battery	153400R22	**1.110,00**
Back former support H-S Ø 10 – 26 mm with back formers for pipe Ø 10 – 26 mm, ⅜ – ⅞"	153501R	**141,00**
Back former support Ø 32 mm with back formers for pipe Ø 32 mm	153115RX2	**270,00**
Device H-S for reverse bending on laid pipes up to Ø 26 mm, ⅞"	153450R	**481,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V	571567R220	**838,00**
XL-Boxx system case with inserts	153455R	**473,00**

REMS Lumen 2800 22 V, cordless LED flood light, see page 111

Bending former for tubes Ø mm/inch	Bending radius[1] mm	suitable for: Cu	Cu-U	St 10217	St 10305	St 10305-U	V		
10, ⅜"	30	●			●			153155R	**64,90**
12, 10 U, ½"	36	●	●		●			153160R	**64,90**
14, 12 U	50	●			●	●	●	153170R	**64,90**
15, 12 U, ⅝" [2]	55	●	●	●	●			153531R	**149,00**
15, 12 U, ⅝"	55	●	●		●			153175R	**64,90**
16, 14 U	55	●	●		●		●	153180R	**64,90**
17, 15 U	60					●	●	153185R	**64,90**
18, 14 U, 15 U, 16 U, ¾" [2]	72	●	●	●	●		●	153532R	**149,00**
18, 14 U, 15 U, 16 U, ¾"	72	●	●		●		●	153190R	**64,90**
20, 18 U	79	●	●			●	●	153195R	**64,90**
22, 18 U, ⅞" [2]	86	●	●	●	●			153540R	**149,00**
22, 18 U, ⅞"	86	●	●					153200R	**64,90**
25, 26	88						●	153205R	**64,90**
32	128						●	153210R	**122,00**

[1] Bending radius mm at the neutral axis of the bend (DVGW GW 392)
[2] Aluminium bending formers

Cu: soft copper tubes, also thin-wall, EN 1057
St 10217: stainless, nickel steel pipes of the press fitting systems EN 10217-7, EN 10312, series 2, material 1.4401
St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3
St 10305-U: soft, coated carbon steel pipes of the pressfitting systems EN 10305-3
U: coated
V: multi-layer composite tubes of pressfitting systems

REMS Python

Oil-hydraulic pipe bender

Robust, oil-hydraulic pipe bender for dimensionally accurate bending of pipes up to 90°. For trade and industry. For the building site and the workshop.	
Steel pipes EN 10255	Ø ⅜ – 2"
Multilayer composite tubes	Ø 32 – 75 mm

REMS Python – extremely easy bending up to Ø 2", 75 mm. Ideal for steel pipes EN 10255 and for multilayer composite tubes of the pressfitting systems. Also for producing level bends in different planes.

Universal use

For locksmith work, sanitary and heating installation and machine and plant engineering. Excellently suitable for steel pipes EN 10255 and for multilayer composite tubes of the pressfitting systems.

System advantage

Only **one** bender drive for the whole working range up to Ø 2", Ø 75 mm. Thus simple, inexpensive stocking. No confusion possible.

Cost advantage

Pipe bender is amortised after just a few bends by saving on fittings. No costs for fittings, storage, procurement. Saving of welds, press connections and working time. Increased safety due to fewer pipe connections.

Design

Robust, oil-hydraulic drive unit with closed, maintenance-free hydraulic system. 2 slide roller supports and 2 slide rollers form a closed bending frame for high rigidity and precision when bending. Upper back former support tiltable for easy insertion and removal of the pipe, with marked plug positions for the back formers according to the pipe size to be bent, with angle scale 0 to 90°. Upper slide roller support with laterally adjustable slide roller bearing plate for producing over-bends and level bends according to requirements also in different planes. Can be used anywhere, any time. No setting. Easy, effortless, quick working, e.g. 90° bend Ø 63 mm only 60 s. Tripod as accessory.

Bending formers and back formers

Bending formers St for steel pipes, form and pressure stable, made of highly resistant spheroidal iron. Bending formers V for multilayer composite tubes, form and pressure stable, made of torsion-free shell-cast aluminium. See page 135. Marking on every bending former for dimensionally accurate bending. Angle gauge with angle scale 0 to 180° for dimensionally accurate bending, as an accessory. Optimum matching of bending formers and back formers guarantees material-compatible bending without cracks and creases. High strength back formers for low friction support of the thrust pressure. Fast changing of the bending formers and back formers by simple plug system.

Drive

Oil-hydraulic drive unit with hydraulic cylinder made from high-quality, rolled hydraulic tube. Overload protection of the hydraulic thrust in the foremost piston position and overpressure valves for safe working. Ergonomically designed thrust lever for strength saving pressure build-up with manual hydraulic pump. No danger of crushing due to end limiting of the thrust lever, for high work safety.

German Quality Product

Bridges.

Info

REMS Python

Oil-hydraulic pipe bender

Doglegs on several levels.

Supply format

REMS Python Set. Oil-hydraulic pipe bender for dimensionally accurate bending of pipes up to 90°. Steel pipes EN 10255 Ø ⅜ – 2", multilayer composite tubes Ø 32 – 75 mm. Drive unit with back former supports, upper back former support with laterally adjustable back former support bearing plate, 2 back formers, bending formers St or V. In sturdy carrying case.

Description	Art.-No.	KM
Set St ⅜ + ½ + ¾ + 1 + 1¼"	590020R	**3.390,00**
Set St ½ + ¾ + 1 + 1¼ + 1½ + 2"	590021R	**3.660,00**
Set V 40 + 50 + 63 mm	590022R	**3.450,00**

Accessories

Description	Art.-No.	KM
Drive unit with back former supports and back formers	590000R	**3.000,00**
Slide piece Ø 75 mm (pack of 2)	590111R	**750,00**
Tripod	590150R	**341,00**
Carrying case with practical handles	590160R	**500,00**
Angle gauge for dimensionally accurate bending	590153R	**87,40**

Bending former for pipes Ø mm/inch	Bending radius[1] mm	Bending radius[2] mm	suitable for St 10255	suitable for V				Art.-No.	KM
St ⅜"	50		●					590051R	**94,70**
St ½"	65		●					590052R	**113,00**
St ¾"	85		●					590053R	**136,00**
St 1"	100		●					590054R	**136,00**
St 1¼"	150		●					590055R	**152,00**
St 1½"	170		●					590056R	**185,00**
St 2"	220		●					590057R	**278,00**
V 32 mm	112	128		●				590061R	**125,00**
V 40 mm	140	160		●				590058R	**158,00**
V 50 mm	175	200		●				590059R	**215,00**
V 63 mm	220	252		●				590060R	**303,00**
V 75 mm	260	298		▲				590062R	**668,00**

St 10255: Steel pipes (threaded pipes) EN 10255
V: multilayer composite pipes of the pressfitting systems
▲ 2 slide pieces Ø 75 mm (Art. No. 590111) required

[1] Bending radius mm on the inside of the bend (EN 10255)
[2] Bending radius mm at the neutral axis of the bend (DVGW VP 632)

REMS Curvo

Electric pipe and tube bender

Universal, compact electric tool for cold bending of pipes and tubes up to 180°. Can be used anywhere, without vice. For trade and industry. For the building site and the workshop.	
Hard, half-hard, soft copper tubes also thin-wall	Ø 10 – 35 mm Ø ⅜ – 1⅜"
Coated soft copper tubes, also thin-wall	Ø 10 – 18 mm
Thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1	Ø ⅜ – 1⅜"
Pipes of press fitting systems made of stainless steel Carbon steel (coated)	Ø 12 – 28 mm Ø 12 – 28 mm
Soft precision steel tubes	Ø 10 – 28 mm
Steel pipes EN 10255	Ø ¼ – ¾"
Electric conduit EN 50086	Ø 16 – 32 mm
Multi-layer composite tubes	Ø 14 – 40 mm

REMS Curvo – wrinkle-free bending.
Universal for many pipe types. Instant use without setting. Fast and creep speed operation for precise bending. Rapid change of bending and back formers.

Universal use
For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage
Only one type of bending and back formers for REMS Curvo 22 V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage
Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design
Compact, handy electric tool with integral absorbtion of torque during bending. Super light, drive unit only 8 kg. Can be used anywhere, anytime. No setting. Simple, effortless, fast working, e.g. 90° bends, Ø 22 mm in only 6 s. Fast and creep speed operation for precise bending. Overbend, double bend, tier bend, reversed bend possible. Height adjustable machine support as accessory.

Bending formers and back formers
Form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide. Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale 0 to 180° provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers. Bending formers and back formers for different sizes, materials and bending radii (page 143).

Drive
Robust, maintenance-free gear. Final point safety in both directions through safety slipping clutch. Proven, powerful universal motor, 1000 W. Right and left-hand rotation. Stepless electronic safety switch for rapid and creep speed operation.

Bending lubricant
REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

German Quality Product

Info

Basic-Pack

Supply format

REMS Curvo Set. Electric pipe and tube bender Ø 10 – 40 mm, Ø ¼ – 1⅜", up to 180°. Hard, semi-hard, soft copper pipes, also thin-walled, Ø 10 – 35 mm, Ø ⅜ – 1⅜", soft coated copper pipes, also thin-walled, Ø 10 – 18 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ⅜ – 1⅜", pipes of the press fitting systems of stainless steel Ø 12 – 28 mm, carbon steel, also coated, Ø 12 – 28 mm, soft precision steel pipes Ø 10 – 28 mm, steel pipes EN 10255 Ø ¼ – ¾", electrical installation pipes EN 50086 Ø 16 – 32 mm, composite tubes Ø 14 – 40 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 230 V or 110 V, 50 – 60 Hz, 1000 W, stepless electronic safety switch, right and left-hand rotation, insert bolt. Bending formers and back formers. In sturdy steel case.

Description	Art.-No.	KM
Set 15 + 18 + 22	580026R220	**3.530,00**
Set 15 + 18 + 22 + 28[1]	580027R220	**3.930,00**
Set 15 + 18 + 22 + 28[2]	580036R220	**4.160,00**
Set 15 + 18 + 22 + 28[3]	580035R220	**4.080,00**
Set 12 + 15 + 18 + 22	580020R220	**3.720,00**
Set 12 + 15 + 18 + 22 + 28[1]	580033R220	**4.270,00**
Set 12 + 15 + 18 + 22 + 28[2]	580037R220	**4.350,00**
Set 15 + 22 + 28[1]	580022R220	**3.720,00**
Set 15 + 22 + 28[2]	580040R220	**3.950,00**
Set 17 + 20 + 24	580023R220	**3.870,00**
Set 12 + 14 + 16 + 18 + 22	580021R220	**3.910,00**
Set 12 + 14 + 16 + 18 + 22 + 28[1]	580031R220	**4.330,00**
Set 12 + 14 + 16 + 18 + 22 + 28[2]	580038R220	**4.540,00**
Set 14 + 16 + 18 + 22 + 28[1]	580028R220	**4.120,00**
Set 14 + 16 + 18 + 22 + 28[2]	580039R220	**4.350,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞"	580024R220	**4.750,00**
Set 16 + 20 + 26 + 32	580025R220	**4.520,00**
Set 16 + 20 + 25 + 32	580034R220	**4.350,00**
Set 20 + 25 + 32	580029R220	**4.290,00**
Set 32 + 40	580030R220	**4.350,00**
Basic-Pack (without bending and back formers)	580010R220	**2.690,00**

REMS Curvo Set delivered with the smaller radius bending and back former (except Art.-No. 580029 and 580030), see page 143.

[1] Bending former and back former 28, R102, Art. No. 581070, for hard, semi-hard copper pipes, also thin-walled. See page 143.

[2] Bending former and back former 28, ¾" (DN 20), R102, Art. No. 581260, for hard copper pipes Ø 28 mm, Ø 1⅛", pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". See page 143.

[3] Bending former and back former 28, ¾" (DN 20), R114, Art. No. 581310, for hard, semi-hard copper pipes Ø 28 mm, pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm. See page 143.

Accessories

Description	Art.-No.	KM
Bending formers and back formers see page 143.		
REMS Curvo drive unit	580000R220	**2.400,00**
Insert bolt	582036	**82,50**
REMS bending spray, 400 ml	140120R	**58,40**
Steel case with insert	586000R	**261,00**
Machine support 3B, height adjustable,on tripod	586100R	**494,00**
Machine support WB, height adjustable, for mounting on work bench	586150R	**347,00**

3B

WB

REMS Curvo 50

Electric pipe and tube bender

Universal, compact electric tool for cold bending of pipes and tubes up to 90°. Can be used anywhere, without vice. For trade and industry. For the building site and the workshop.	
Steel pipes EN 10255 (DIN 2440)	Ø ¼ – 1¼"
Stainless steel pipes EN ISO 1127, EN 10217-1	Ø ½ – 1¼" s ≤ 2.6 mm
Hard, half-hard, soft copper tubes	Ø 10 – 42 mm
Thin-wall copper tubes	Ø 10 – 35 mm
Thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1	Ø ⅜ – 1⅝"
Pipes of press fitting systems made of stainless steel Carbon steel, also coated	 Ø 12 – 42 mm Ø 12 – 42 (28) mm
Multi-layer composite tubes	Ø 14 – 50 mm
Further materials, see REMS Curvo	

German Quality Product

Info

REMS Curvo 50 – wrinkle free bending of large pipes.

Universal use
For metalwork and in sanitary, heating, air conditioning, refrigeration and hydraulic applications. Specially suited for steel pipe EN 10255, pipe for press-fitting systems, for hard and half hard copper pipe and for thin-walled copper heating pipe according to EN 1057.

System advantage
Bending formers and back formers of REMS Curvo 22 V, REMS Curvo and REMS Sinus (page 143) also fit in the REMS Curvo 50 drive machine with adaptor block 10 – 40, support 10 – 40. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage
Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design
Compact, handy electric tool with integral absorption of torque during bending. Can be used anywhere, anytime. No setting. Simple, effortless, fast working, e.g. 90° bends of steel pipe Ø 1¼" in only 37 s. Fast and creep speed operation for precise bending. Overbend, tier bend, reversed bend possible.

Bending formers and back formers
Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers. Bending formers and back formers for different sizes, materials and bending radii (page 143). Bending formers and back formers REMS Curvo 50 (Ø 35 R 100, Ø 42 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1¼" R 140): Form and pressure resistant bending formers in ductile iron and back formers in high-strength, high-slide glass-fibre reinforced polyamide.

Drive
Robust, maintenance-free gear. Final point safety in both directions through safety slipping clutch. Proven, powerful universal motor, 1000 W. Right and left-hand rotation. Stepless electronic safety switch for rapid and creep speed operation.

Bending lubricant
REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

Supply format

REMS Curvo 50 Basic-Pack. Electric pipe and tube bender Ø 10 – 50 mm, up to 90°. Steel pipes EN 10255 Ø ¼ – 1¼", stainless steel pipes EN ISO 1127, EN 10217-7, Ø ½ – 1¼", s ≤ 2.6 mm, hard, semi-hard, soft copper pipes, Ø 10 – 42 mm, thin-walled copper pipes Ø 10 – 35 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ⅜ – 1⅝", pipes of the press fitting systems of stainless steel Ø 12 – 42 mm, carbon steel Ø 12 – 42 mm, coated carbon steel Ø 12 – 28 mm, composite tubes Ø 14 – 50 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 230 V or 110 V, 50 – 60 Hz, 1000 W, stepless electronic safety switch, right and left-hand rotation. Adaptor block 35 – 50, Support 35 – 50, insert bolt. In sturdy carrying case.

	Art.-No.	KM
	580110R220	**7.040,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
Bending formers and back formers see page 143.		
REMS Curvo 50 drive unit	580100R220	**6.220,00**
Adaptor block 35 – 50, Support 35 – 50, for bending formers and back formers Ø 35 R 100, Ø 42 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1¼" R 140 (see page 143).	582110R	**374,00**
Adaptor block 10 – 40, Support 10 – 40, for bending formers and back formers REMS Curvo, REMS Curvo 22 V, REMS Sinus (see page 143).	582120R	**613,00**
Insert bolt	582036	**82,50**
REMS bending spray, 400 ml	140120R	**58,40**
Carrying case with practical handles	590160R	**500,00**
Steel case with insert for each bending former and back former R 100 and R 135/R 140, 90°	586012R	**223,00**

REMS Curvo 22 V

Cordless tube bender

Universal, mobile electric tool for cold bending of pipes up to 180°. Can be used anywhere, without vice. For trade and industry. For the building site and the workshop. Li-Ion 22 V Technology. For battery and corded operation.	
Hard, half-hard, soft copper tubes also thin-wall	Ø 10 – 28 mm Ø ⅜ – 1⅛"
Coated soft copper tubes, also thin-wall	Ø 10 – 18 mm
Thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1	Ø ⅜ – 1⅛"
Pipes of press fitting systems made of stainless steel Carbon steel, also coated	Ø 12 – 28 mm Ø 12 – 28 mm
Soft precision steel tubes	Ø 10 – 28 mm
Steel pipes EN 10255	Ø ¼ – ¾"
Electric conduit EN 50086	Ø 16 – 25 mm
Multi-layer composite tubes	Ø 14 – 40 mm

REMS Curvo 22 V – wrinkle-free bending of pipes. Mobile, handy, light. Universal for many pipe types. Ready to use immediately without setting. Fast and creep speed with immediate stop for precise bending. Quick change of bending and back formers. Li-Ion 21.6 V, 5.0 Ah battery, for approx. 90 pipe bends of the stainless steel Ø 22 mm press fitting systems with one battery charge*.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Mains independent. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage

Only one type of bending and back formers for REMS Curvo 22 V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, mobile, handy electric tool with integral absorbtion of torque during bending. Super light, drive machine with battery pack weights only 8.5 kg. Electronic charging status check with low discharge protection. Practical D-shaped handle with soft grip. Can be used anywhere, anytime. No setting. Simple, effortless, fast working, e.g. 90° bend Ø 22 mm only 6 s. Fast and creep speed with immediate stop for precise bending. Overbend, double bend, tier bend, reversed bend possible. Height adjustable machine support as accessory.

Bending formers and back formers

Form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide. Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale 0 to 180° provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers. Bending formers and back formers for different sizes, materials and bending radii (page 143).

Drive

Robust, maintenance-free gear. Final point safety in both directions through safety slipping clutch. Powerful battery motor 21.6 V, with large power reserve, 500 W output. Right and left-hand rotation. Stepless electronic safety switch for fast and creep speed, with immediate stop. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah battery, for approx. 79 pipe bends, 5.0 Ah battery, for approx. 90 pipe bends, 9.0 Ah for approx. 160 pipe bends of the stainless steel Ø 22 mm press fitting systems with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

German Quality Product

Info

Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

Basic-Pack

Supply format

REMS Curvo 22 V Set. Cordless tube bender Ø 10 – 40 mm, Ø ¼ – 1⅛", to 180°. Hard, semi-hard, soft copper pipes, also thin-walled, Ø 10 – 28 mm, Ø ⅜ – 1⅛", soft coated copper pipes, also thin-walled, Ø 10 – 18 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ⅜ – 1⅛", pipes of the press fitting systems of stainless steel Ø 12 – 28 mm, carbon steel, also coated, Ø 12 – 28 mm, soft precision steel pipes Ø 10 – 28 mm, steel pipes EN 10255 Ø ¼ – ¾", electrical installation pipes EN 50086 Ø 16 – 25 mm, composite tubes Ø 14 – 40 mm, etc. Drive machine with D-shaped handle, maintenance-free gear with safely slipping clutch, powerful battery motor 21.6 V, stepless, electronic safety switch with immediate stop, right and left-hand rotation. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 5.0 Ah battery, 100 – 240 V, 50 – 60 Hz, 90 W rapid charger. Insert bolt. Bending and back formers. In sturdy steel case.

Description	Art.-No.	KM
Set 15 + 18 + 22	580051R220	**5.140,00**
Set 15 + 18 + 22 + 28[1]	580052R220	**5.700,00**
Set 15 + 18 + 22 + 28[2]	580053R220	**5.650,00**
Set 15 + 18 + 22 + 28[3]	580054R220	**5.570,00**
Set 12 + 15 + 18 + 22	580055R220	**5.210,00**
Set 12 + 15 + 18 + 22 + 28[1]	580056R220	**5.760,00**
Set 12 + 15 + 18 + 22 + 28[2]	580057R220	**5.840,00**
Set 15 + 22 + 28[1]	580058R220	**5.210,00**
Set 15 + 22 + 28[2]	580059R220	**5.440,00**
Set 17 + 20 + 24	580060R220	**5.360,00**
Set 12 + 14 + 16 + 18 + 22	580061R220	**5.400,00**
Set 12 + 14 + 16 + 18 + 22 + 28[1]	580062R220	**5.820,00**
Set 12 + 14 + 16 + 18 + 22 + 28[2]	580063R220	**6.030,00**
Set 14 + 16 + 18 + 22 + 28[1]	580064R220	**5.610,00**
Set 14 + 16 + 18 + 22 + 28[2]	580065R220	**5.840,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞"	580066R220	**6.240,00**
Set 16 + 20 + 26 + 32	580067R220	**6.010,00**
Set 16 + 20 + 25 + 32	580068R220	**5.840,00**
Set 20 + 25 + 32	580069R220	**5.780,00**
Basic-Pack (without bending and back formers)	580014R220	**4.180,00**

Other voltages on request.
REMS Curvo 22 V Set delivered with the smaller radius bending and back former (except Art.-No. 580069), see page 143.

[1] Bending former and back former 28, R102, Art. No. 581070, for hard, semi-hard copper pipes, also thin-walled. See page 143.

[2] Bending former and back former 28, ¾" (DN 20), R102, Art. No. 581260, for hard copper pipes Ø 28 mm, Ø 1⅛", pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm. See page 143.

[3] Bending former and back former 28, ¾" (DN 20), R114, Art. No. 581310, for hard, semi-hard copper pipes Ø 28 mm, pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm. See page 143.

Accessories

Description	Art.-No.	KM
Bending formers and back formers see page 143.		
REMS Curvo 22 V drive unit, without battery	580004R22	**2.920,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	**1.050,00**
Insert bolt	582036	**82,50**
REMS bending spray, 400 ml	140120R	**58,40**
Steel case with inlay	566030R	**261,00**
Machine support 3B, height adjustable, on tripod	586100R	**494,00**
Machine support WB, height adjustable, for mounting on work bench	586150R	**347,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

3B

WB

REMS Sinus

Hand tube bender

Universal, robust hand tool for cold bending up to 180°. Can be used anywhere. For trade and industry. For the building site and the workshop.	
Hard, half-hard, soft copper tubes, also thin-wall	Ø 10 – 22 mm Ø ⅜ – ⅞"
Coated soft copper tubes, also thin-wall	Ø 10 – 18 mm
Pipes of press fitting systems made of stainless steel, carbon steel (coated) Carbon steel	Ø 12 – 18 mm Ø 12 – 22 mm
Soft precision steel tubes	Ø 10 – 20 mm
Electric conduit EN 50086	Ø 16 – 20 mm
Multi-layer composite tubes	Ø 14 – 32 mm



REMS Sinus – wrinkle-free bending. Universal for many tubes. Easy bending through long lever arms. Selectable lever positioning ensures optimum bending position and power transmission. Only one type of bending and back formers for REMS Sinus and REMS Curvo.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage

Only one type of bending and back formers for REMS Curvo 22 V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, handy unit of bender drive and bending tools. Can be used anywhere, in parallel vice or free hand as double-hand-bender. Easy bending through long lever arms. Selectable lever positioning ensures optimum bending position and power transmission. Robust design, drive unit in hardened steel for high stress. Simple and rapid changing of bending and back formers. Crossover, swan-neck and U-bends possible.

Bending formers and back formers

For different pipe sizes, materials and bending radii, see page 143.

Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and for uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

German Quality Product

Info

Supply format

REMS Sinus Set. Hand tube bender Ø 10 – 32 mm, Ø ⅜ – ⅞", up to 180°. Hard, half-hard, soft copper tubes, also thin-wall Ø 10 – 22 mm, Ø ⅜ – ⅞", coated soft copper tubes, also thin-wall Ø 10 – 18 mm, pipes of the press fitting systems made of stainless steel, carbon steel (coated) Ø 12 – 18 mm, soft precision steel tubes Ø 10 – 22 mm, soft precision steel tubes, Ø 10 – 20 mm, electric conduit EN 50086, Ø 16 – 20 mm, multi-layer composite tubes Ø 14 – 32 mm and others. Drive unit, insert bolt. Bending formers and back formers. REMS bending spray. In sturdy steel case.

Description	Art.-No.	KM
Set 15 + 18 + 22	154001R	**1.630,00**
Set 14 + 16 + 18	154002R	**1.570,00**
Set 12 + 15 + 18 + 22	154003R	**1.830,00**
Set 10 + 12 + 14 + 16 + 18 + 22	154004R	**2.310,00**
Basic-Pack (without bending and back formers and bending spray)	154010R	**947,00**

REMS Sinus Set is delivered with bending formers and back formers of the smaller radius, see page 143.

Accessories

Description	Art.-No.	KM
Bending and back formers see page 143.		
Insert bolt	582036	**82,50**
REMS Curvo drive unit	580000R220	**2.400,00**
REMS Sinus drive unit	154000R	**607,00**
REMS bending spray, 400 ml	140120R	**58,40**
Steel case with inlay	154160R	**261,00**

All prices excl. VAT

Bending formers and back formers

Accessories for REMS Curvo 50, REMS Curvo, REMS Curvo 22 V and REMS Sinus

Bending formers and back formers, 180°, form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide or aluminum 90° (Ø 21.3 R 103, Ø 26.9 R 102, Ø 33.7 R 100, Ø 35 R 100, Ø 42 R 140, Ø 42.4 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1¼" R 140). Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers.

Bending former and back former for pipes Ø mm/inch O.D.	R mm	X mm 90°	X mm 45°	Bending former material	REMS Sinus								REMS Curvo								REMS Curvo 22 V								REMS Curvo 50								Art.-No.	KM
					Cu	Cu-U	St 10312	St 10305-U	St 10305	St 10255	St 50086	V	Cu	Cu 12735	Cu-U	St 10312	St 10305-U	St 10305	St 10255	St 50086	V	Cu	Cu 12735	Cu-U	St 10312	St 10305-U	St 10305	St 10255	St 50086	V	Cu	Cu 12735	Cu-U	St 10312	St 1127	St 10305-U	St 10305	St 10255	St 50086	V		
10	40	45	20	P	●				●				●					●				●					●				▲					▲				581400	**366,00**
12	45	49	22	P	●		●		●				●			●		●				●			●		●				▲			▲		▲				581410	**275,00**
14, 10 U, ¼" (DN 6)	50	53	23	P	●	●			●			●	●		●			●	●		●	●		●			●	●		●	▲		▲			▲	▲		▲	581420	**267,00**
15, 12 U	55	56	25	P	●		●	●	●				●			●	●	●				●			●	●	●				▲			▲			▲	▲			581430	**299,00**
16, 12 U	60	62	28	P	●	●			●		●	●	●		●			●		●	●		●				●		●	●	▲		▲			▲		▲	▲	581440	**301,00**
17, 15 U	56	60	27	P				●				●					●				●					●			●						▲				▲	581110	**368,00**
18, 14 U, 15 U, ⅜" (DN 10)	70	75	33	P	●	●	●		●			●	●		●	●		●	●		●	●		●	●		●	●		●	▲		▲	▲		▲	▲		▲	581450	**303,00**
20, 16 U, 18 U	75	80	36	P	●	●		●			●	●	●		●			●	●		●	●		●			●	●		●	▲		▲			▲		▲	▲	581080	**481,00**
21.3, ½" (s = 1.6/2.0/2.6)	103	110	50	S																													■			■			581480	**1.090,00**
22, 18 U, ½" (DN 15)	77	81	36	A	●	●			●				●		●	●		●	●			●		●	●		●	●			▲		▲	▲		▲	▲			581460	**359,00**
22, 18 U, ½" (DN 15)	88	91	41	P									●		●	●		●				●		●	●		●				▲		▲	▲		▲				581470	**527,00**
24, 22 U	75	85	38	P									●				●					●				●					▲					▲				581130	**584,00**
25	98	103	46	P								●	●					●		●	●	●					●		●	●	▲					▲		▲	▲	581180	**643,00**
26	98	108	49	A								●						●			●						●			●						▲				581270	**886,00**
26.9, ¾" (s = 1.6/2.0/2.6)	102	108	49	S																													■			■			581490	**1.220,00**
28[1]	102[3]	108	49	P									●									●									▲									581070	**563,00**
28, ¾" (DN 20)[2]	102	110	50	A									●			●		●	●			●			●		●	●			▲			▲		▲	▲			581260	**867,00**
28, ¾" (DN 20)[2]	114	120	54	A									●			●		●	●			●			●		●	●			▲			▲		▲	▲			581310	**752,00**
30, 28 U	98	105	47	P									●				●					●				●					▲					▲				581150	**708,00**
32	98	110	50	P								●								●									●									▲	581280	**687,00**
32	114	121	54	A									●						●	●									●		▲						▲	▲	581320	**886,00**
1" (DN 25)	100	105	47	S																															■				581520	**1.010,00**
33.7, 1" (s = 1.6/2.0/2.6)	100	105	47	S																													■			■			581520	**1.010,00**
35	100	105	47	S																											■			■			■			581500	**1.010,00**
35	140	150	68	A									●																		▲			▲						581350	**1.190,00**
40	140	148	67	A																●									●									▲	581330	**1.200,00**
42	140	155	70	S																											■			■			■			581510	**1.080,00**
1¼" (DN 32)	140	150	68	S																															■				581530	**1.050,00**
42.4, 1¼" (s = 2.0/2.6)	140	150	68	S																													■			■			581530	**1.050,00**
50	135	143	64	S																																		■	581540	**1.420,00**
⅜" (9.5 mm)	43	48	22	P	●								●	●								●	●								▲	▲								581200	**462,00**
½" (12.7 mm)	52	60	27	P	●								●	●								●	●								▲	▲								581210	**441,00**
⅝" (15.9 mm)	63	70	32	P	●								●	●								●	●								▲	▲								581220	**496,00**
¾" (19.1 mm)	75	82	37	P	●								●	●								●	●								▲	▲								581230	**590,00**
⅞" (22.2 mm)	98	107	48	P	●								●	●								●	●								▲	▲								581240	**691,00**
1" (25.4 mm)	101	112	50	A									●									●									▲									581360R	**901,00**
1" (25.4 mm)	101	112	50	P									●									●									▲									581370	**685,00**
1⅛" (28.6 mm)	102	110	44	A									●	●								●	●								▲	▲								581260	**867,00**
1⅛" (28.6 mm)	115	117	53	A									●									●									▲									581380	**752,00**
1¼" (31.8 mm)	114	123	55	A									●																		▲	▲								581320	**886,00**
1¼" (31.8 mm)	133	145	65	A									●																		▲									581390	**1.260,00**
1⅜" (34.9 mm)	100	105	47	S																												■								581500	**1.010,00**
1⅜" (34.9 mm)	140	150	68	A									●	●																	▲	▲								581350	**1.190,00**
1⅝" (41.3 mm)	140	155	70	S																											■	■								581510	**1.080,00**

R mm — Bending radius mm at the neutral axis of the bend (DVGW GW 392)
X mm — Correction dimension for a 90° or 45° bend
s mm — Wall thickness
[1] hard, semi-hard copper pipes, also thin-walled, EN 1057
[2] hard copper pipes EN 1057
[3] According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm.
▲ Adaptor block 10 – 40, support 10 – 40 (Art.-No. 582120) necessary.
■ Adaptor block 35 – 50, support 35 – 50 (Art.-No. 582110) necessary.
Cu: hard, half-hard, soft copper tubes, also thin-wall, EN 1057
Cu 12735: Copper pipes K65 for refrigeration and air conditioning technology in accordance with EN 12735-1, EN 12449
St 10312: stainless steel pipes of the press fitting systems EN 10312, series 2, EN 10088, EN 10217-7
St 1127: stainless steel pipes EN ISO 1127, EN 10217-7
St 10305-U: coated, soft carbon steel pipes of the press fitting systems EN 10305-3
St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3, carbon steel pipes EN 10305-3
St 10255: Steel pipes (threaded pipes) EN 10255
St 50086: Electrical installation pipes DIN EN 50086
U: coated
V: multi-layer composite tubes of pressfitting systems
P: Bending former made of glass fibre-reinforced polyamide
A: Bending former made of aluminium
S: Bending former made of spheroidal iron

Bending to size
If a bend is required at a certain point on the pipe, a length correction must be made to suit the pipe size. The correction dimension X specified in Fig. 1 must be considered for a 90° or 45° bend. The set dimension L must be reduced by the amount X here. If, e.g., the dimension L for pipe size 22 is 400 mm and a bend with a bending radius of 77 mm is to be made, the dimension line should be marked on the pipe at 319 mm. This line is then – as shown in Fig. 1 – to be aligned with the 0-mark on the bending former.



Fig. 1

REMS

Radial Press Jointing

	Cordless radial press Mini	147
	Pressing tongs Mini	152
	Cropping tongs Mini	184
	Manual radial press	185
	Electric radial press	186
	Electro-hydraulic radial presses	187
	Cordless radial presses	190
	Pressing tongs / pressing rings	198
BTGA suissetec VDKF	Hold-Harmless and Indemnification Agreement	240
	Cropping tongs	241
	Cable shears	241



6 million!

REMS produced 6 million pressing tongs/pressing rings up to the end of 2023. This success confirms the leading role of REMS in press-jointing technology.

REMS Mini-Press 14 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. For battery and corded operation.

Pipe pressing joints	Ø 10 – 40 mm 7 Ø ⅜ – 1 ¼

Complete range of REMS pressing tongs Mini/ pressing rings for all common pressfitting systems, see page 152 – 183.

REMS Mini-Press 14 V ACC – universal up to Ø 40 mm. Super light, super small, super handy. Secure crimping in seconds. With automatic circuit control. Automatic locking of the pressing tongs.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152 – 183). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/ pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection **(Patent EP 1 952 948).** Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing **(Patent EP 2 347 862)**.

Design

Super light, super small, super handy. Drive unit with battery only 2.4 kg. Drive unit with pressing tongs V 22 only 33 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Ergonomically designed housing. LED work light for illuminating the work place. Swivelling pressing tongs seat. Secure seating of pressing tongs/adapter tongs by automatic locking. Electronic charging status check with flat battery protection and charging status indicator with 2-coloured LED.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 14.4 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion PLUS technology. Highly resistant Li-Ion 14.4 V battery with 2.5 or 5.0 Ah capacity for long service life. Light and powerful. Li-Ion 14.4 V, 2.5 Ah batteries for approx. 275 pressings, 5.0 Ah for approx. 550 pressings Viega Profipress DN 15 with one battery charge*. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 220 – 240 V, 10.8 – 18 V, 65 W, for short charging times. Voltage supply 220 – 240 V/14.4 V, 33 A output, for mains operation instead of Li-Ion battery 14.4 V, as accessory.

Patent EP 1 952 948
Patent EP 2 347 862

with automatic circuit control and charging status check

German Quality Product

Info

Supply format

REMS Mini-Press 14 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10 – 40 mm, Ø ⅜ – 1 ¼". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W, obust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, Safety tip switch. LED work light. Battery Li-Ion 14.4 V, 2.5 Ah, rapid charger 220 – 240 V, 50 – 60 Hz, 10.8 – 18 V, 65 W.

Version	Art.-No.	KM
In sturdy steel case.	578012R220	**3.050,00**
In L-Boxx system case.	578013R220	**3.130,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS pressing tongs Mini/pressing rings see page 152 – 183.		
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	**292,00**
REMS cropping tongs Mini for threaded rods see page 184.		
REMS Mini-Press 14 V ACC drive unit, without battery	578001R14	**2.190,00**
Battery Li-Ion 14.4 V, 2.5 Ah	571545R14	**326,00**
Battery Li-Ion 14.4 V, 5.0 Ah	571555R14	**460,00**
Rapid charger 220 – 240 V, 50 – 60 Hz, 10.8 – 18 V, 65 W	571560R220	**313,00**
Voltage supply 220 – 240 V/14.4 V, 50 – 60 Hz, 33 A, for mains operation instead of battery Li-Ion 14.4 V.	571565R220	**712,00**
Steel case with inlay	578290R	**223,00**
L-Boxx system case with inserts	578299R	**296,00**

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS Mini-Press 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for all common pressfitting systems. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints	Ø 10 – 40 mm Ø ⅜ – 1 ¼"

Complete range of REMS pressing tongs Mini/ pressing rings for all common pressfitting systems, see page 152 – 183.

with automatic circuit control and charging status check

Patent EP 1 952 948
Patent EP 2 347 862

REMS Mini-Press 22 V ACC – universal up to Ø 40 mm. Super light, super small, super handy, ultra fast. Pressing under 4 s. With automatic circuit control, Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah battery for approx. 390 pressings Viega Profipress DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152 – 183). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/ pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection **(Patent EP 1 952 948).** Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing **(Patent EP 2 347 862)**.

Design

Super light, super small, super handy. Drive unit with battery only 2.5 kg. Drive unit with pressing tongs V 15 only 31 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 390 pressings, 4.4 Ah for approx. 685 pressings, 5.0 Ah for approx. 780 pressings, 9.0 Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

German Quality Product

Info

REMS Mini-Press 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Supply format

REMS Mini-Press 22 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10 – 40 mm, Ø ⅜ – 1 ¼". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, obust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W.

Version	Art.-No.	KM
In sturdy steel case.	578010R220	**3.620,00**
In L-Boxx system case.	578014R220	**3.700,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS pressing tongs Mini/pressing rings see page 152 – 183.		
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	**292,00**
REMS cropping tongs Mini for threaded rods see page 184.		
REMS Mini-Press 22 V ACC drive unit, without battery	578002R22	**2.570,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	**838,00**
Steel case with inlay	578290R	**223,00**
L-Boxx system case with inserts	578299R	**296,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS Mini-Press S 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for all common pressfitting systems. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints	Ø 10 – 40 mm Ø ⅜ – 1 ¼"

Complete range of REMS pressing tongs Mini/ pressing rings for all common pressfitting systems, see page 152 – 183.

REMS Mini-Press S 22 V ACC – universal up to Ø 40 mm. Super light, super small, super handy, ultra fast. Pressing under 4 s. With automatic circuit control, Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah battery for approx. 390 pressings Viega Profipress DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152 – 183). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/ pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection **(Patent EP 1 952 948).** Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing **(Patent EP 2 347 862)**.

Design

Super light, super small, super handy. Drive unit with battery only 2.6 kg. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 390 pressings, 4.4 Ah for approx. 685 pressings, 5.0 Ah for approx. 780 pressings, 9.0 Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Patent EP 1 952 948
Patent EP 2 347 862

with automatic circuit control and charging status check

German Quality Product

Info

REMS Mini-Press S 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Supply format

REMS Mini-Press S 22 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10 – 40 mm, Ø ⅜ – 1 ¼". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, obust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W.

Version	Art.-No.	KM
In sturdy steel case.	578015R220	**3.620,00**
In L-Boxx system case.	578016R220	**3.700,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS pressing tongs Mini/pressing rings see page 152 – 183.		
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	**292,00**
REMS cropping tongs Mini for threaded rods see page 184.		
REMS Mini-Press S 22 V ACC drive unit, without battery	578003R22	**2.570,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	**838,00**
Steel case with inlay	578290R	**223,00**
L-Boxx system case with inserts	578299R	**296,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

for all common pressfitting systems

Select REMS pressing tongs Mini/ REMS pressing rings yourself!

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 183) required for driving REMS pressing rings. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

REMS pressing tongs Mini (PZ-2B)

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection **(Patent EP 1 952 948)**. Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing **(Patent EP 2 347 862)**.

REMS Mini ACz, Fz, HEz, RFz, RFIz pressing tongs with teeth prevent formation of burr on the pressfitting **(Patent EP 2 027 971)**.

REMS pressing ring S (PR-2B)

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183.

Traceability according to EN 1775:2007

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.

Patent EP 1 952 948
Patent EP 2 347 862

German Quality Product



REMS Mini pressing tongs (PZ-2B)

REMS pressing ring S (PR-2B), continuously swivellable

Confirmation of suitability

See page 239.

Hold-Harmless and Indemnification Agreement

See page 240.

ZVSHK BTGA suissetec VDKF























































Pressing tongs with teeth prevent formation of burr on the pressfitting. Patent EP 2 027 971

Example REMS pressing tongs Mini V: "V" imprint on pressed fitting for traceability according to EN 1775:2007

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
	A			
Aalberts integrated piping systems VSH MultiPress	U 14		578372	353,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Aalberts integrated piping systems VSH MultiPress Gas	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
Aalberts integrated piping systems VSH SudoPress Carbon	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Aalberts integrated piping systems VSH SudoPress Copper	V 12		578324	298,00
	V 14		578326	298,00
	VG 14		578338	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	VG 16		578340	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Aalberts integrated piping systems VSH SudoPress Copper Gas	V 12		578324	298,00
	V 14		578326	298,00
	VG 14		578338	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	VG 16		578340	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Aalberts integrated piping systems VSH SudoPress Stainless	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Aalberts integrated piping systems VSH XPress Carbon	M 12		578310	298,00
	M 15		578312	298,00
	M 18[1)]		578314	298,00
	M 22		578316	298,00
	M 28[1)]		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Aalberts integrated piping systems VSH XPress Copper	M 12		578310	298,00
	M 15		578312	298,00
	M 18[1)]		578314	298,00
	M 22		578316	298,00
	M 28[1)]		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Copper Gas	M 15		578312	298,00
	M 18[1)]		578314	298,00
	M 22		578316	298,00
	M 28[1)]		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Stainless	M 15		578312	298,00
	M 18[1)]		578314	298,00
	M 22		578316	298,00
	M 28[1)]		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Stainless Gas	M 15		578312	298,00
	M 18[1)]		578314	298,00
	M 22		578316	298,00
	M 28[1)]		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
AC-FIX PRESS (Global Piping Systems)	H 12		578396	324,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	VX 16		578552	413,00
	VX 20		578554	413,00
AC-FIX PRESS DUO (Global Piping Systems)	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
ACOME MT	ACz 12		578608	373,00
	ACz 16		578610	373,00
	ACz 20		578612	373,00
	ACz 25		578614	373,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
AHLSELL A-press elförzinkad M	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
AHLSELL A-press elförzinkad V	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
AHLSELL A-press koppar M	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
AHLSELL A-press koppar V	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
AHLSELL A-press rostfritt	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
AIRBEL PRESSCLIM	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
AIRBEL SERTINOX	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
ALB Sistema Multicapa para calefacción y sanitario	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
ALB Sistema Multicapa para gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
ALTECH Altech	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
APE MULTYGAS Serie AP Gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
APE Serie AP	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
APE Serie APL	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
AQUATECHNIK Press-fitting metal	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
AQUATECHNIK Universal	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
ARKA DUROsystem	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
Aschl NIR	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ASSOTHERM IPC-RAC Carbon Steel	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
ASSOTHERM IPI-RAX Inox	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ASSOTHERM IPI-RAX Inox Gas	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ASSOTHERM IPM-Multistrato	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	THL 32		578368	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
ASSOTHERM IPR-RRA Copper	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ASSOTHERM IPR-RRA Copper Gas	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)	US ⅜"		578534	407,00
	US ½"		578536	407,00
	US ¾"		578538	407,00
	US 1"		578540	407,00
ATUSA ITALIA INSTALPRESS CARBON STEEL PRESS FITTINGS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ATUSA ITALIA INSTALPRESS STAINLESS STEEL PRESS FITTINGS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
AUSTEC PEX-B, PEX-AL-PEX (AUS)	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
AUSTEC PEX-AL-PEX GAS (AUS)	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
AYOR FIXOCONNECT Press	H 12		578396	324,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
AYOR FIXOMULTIX	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	U 40		578386	479,00
AYOR SOMATHERM FOR YOU -1	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	U 16		578374	335,00
	U 20		578378	335,00
AYOR SOMATHERM FOR YOU -2	H 12		578396	324,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
B				
Bampi BALPEX serie LP	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
Bampi BALPEX serie MP	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Bampi BALPEX Gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
BARBI EASYPRESS (Industrial Blansol)	H 12		578396	324,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
BARBI MULTIPEX (Industrial Blansol)	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 18		578638	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
BEGETUBE/ IVAR	B 14		578466	391,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
Béné inox Série 41	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Brass Form Master-Al-Pex	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Brass & Fittings	RFz 16		578492	373,00
PRESSMAN	RFz 18		578638	373,00
MultiPress	ACz 20		578612	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
Brass & Fittings	RFz 16		578492	373,00
PRESSMAN RetiPress	RFz 18		578638	373,00
	ACz 20		578612	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
BRASSTECH	B 16		578468	391,00
MULTItermoSAN	B 20		578472	391,00
Brasspress	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00

C

Cello Products	VUS ½" (OD 15,9 mm)		578566	359,00
<B>Press	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
CGR	H 16		578400	324,00
DYNAFLU	H 20		578406	324,00
multicouche	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
CGR	H 12		578396	324,00
DYNAFLU	H 16		578400	324,00
PER	H 20		578406	324,00
	H 25		578408	324,00
	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
CHIALI	TH 16		578352 R	359,00
CHIALIPEX	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
Climatrix	H 16		578400	324,00
Climatrix Rhinopex	H 20		578406	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Climatrix	TH 11,6		578344	359,00
Variotherm	TH 16		578352 R	359,00
System TH	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
ClouSet	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
Comap	RFz 12		578490	373,00
PEX Press	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
Comap	TH 14		578348	359,00
Multiskin	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	THL 32		578368	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
Comap	TH 16		578352 R	359,00
Multiskin Gas	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	THL 32		578368	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
COMISA	TH 14		578348	359,00
Press System	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	B 14		578466	391,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
COMISA	TH 16		578352 R	359,00
Press System Gas	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
CONEL	M 15		578312	298,00
CONNECT INOX	M 18		578314	298,00
	M 22		578316	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
CONEL	F 16		578456	342,00
CONNECT	F 20		578460	342,00
MULTI	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)**	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
(DN 26)	U 25		578380	335,00
	U 32		578382	393,00
	VP 16		578482	358,00
	VP 20		578484	358,00
	VP 32		578488	395,00
CONEL	F 16		578456	342,00
CONNECT	F 20		578460	342,00
MV2	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)**	Mini Z8	574734 R	277,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	277,00
Conex Bänninger	M 15		578312	298,00
<A> Press Inox	M 18		578314	298,00
(304)	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Conex Bänninger	M 15		578312	298,00
<A> Press Inox	M 18		578314	298,00
(316L)	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Conex Bänninger	F 16		578456	342,00
>B< Flex	F 18		578458	342,00
	F 20		578460	342,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 18		578638	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
Conex Bänninger	F 16		578456	342,00
>B< Flex Gas	F 18		578458	342,00
	F 20		578460	342,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 18		578638	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
Conex Bänninger	BMP ¼"		578700	355,00
>B< MaxiPro	BMP ⅜"		578702	355,00
	BMP ½"		578704	355,00
	BMP ⅝"		578706	355,00
	BMP ¾"		578708	355,00
	BMP ⅞"		578710	355,00
	BMP 1"		578712	355,00
	BMP 1⅛"		578714	355,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Conex Bänninger >B< Press	V 12		578324	298,00
	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
	M 15		578312	298,00
	M 22		578316	298,00
	M 28		578318	298,00
Conex Bänninger >B< Press Carbon	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Conex Bänninger >B< Press Gas	V 12		578324	298,00
	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Conex Bänninger >B< Press Inox	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Conex Bänninger >B< Press Solar	V 12		578324	298,00
	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
D				
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
DUOPIPE SYSTEMS DUOFIL MKSYSTEM	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
DW Verbundrohr multitubo systems	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
E				
EBRILLE Isomonflex	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	H 26		578410	324,00
	TH 26		578362 R	359,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
EBRILLE Monflex	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	H 26		578410	324,00
	TH 26		578362 R	359,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
EFFEBI EFFEBI-PRESS Aisi316 System M Profile[1)]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
EFFEBI EFFEBI-PRESS Aisi316 System V Profile	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
EFFEBI EFFEBI-PRESS Carbon-S System M Profile[1)]	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
EFFEBI EFFEBI-PRESS Carbon-S System V Profile	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
EFFEBI EFFEBI-PRESS COPPER	V 12		578324	298,00
	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
EFFEBI EFFEBI-PRESS UNICO	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
EFFEBI	V 12		578324	298,00
EFFEBI-PRESS	V 15		578328	298,00
UNICO	V 18		578332	298,00
(GAS)	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
EFFEBI	M 15		578312	298,00
PRESSTIGE	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
EFFEBI	M 15		578312	298,00
PRESSTIGE 4E05	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
EFFEBI	M 15		578312	298,00
PRESSTIGE-GAS	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
EFFEBI	TH 16		578352 R	359,00
TOF-GAS	TH 20		578358 R	359,00
MULTIPINZA	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
EFFEBI	TH 16		578352 R	359,00
TOF	TH 18		578356	359,00
MULTIPINZA	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	F 16		578456	342,00
	F 18		578458	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	Fz 40		578478	500,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
EFIELD	U 16		578374	335,00
MULTILAYER PRESS	U 18		578376	335,00
DINGAS	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
EFIELD	U 16		578374	335,00
MULTILAYER PRESS	U 18		578376	335,00
WATER	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
Elkhart	VUS ½" (OD 15,9 mm)		578566	359,00
APOLLOXPRESS	VUS ¾" (OD 22,2 mm)		578568	359,00
Fittings Copper	VUS 1" (OD 28,6 mm)		578570	359,00
and Low-Lead Brass	VUS 1¼" (OD 34,9 mm)		578606	359,00
EMMETI	B 16		578468	391,00
GERPEX-	B 20		578472	391,00
FIVPRESS	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	H 16		578400	324,00
	H 20		578406	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	U 16		578374	335,00
	U 20		578378	335,00
EMPUR	TH 14		578348	359,00
	TH 15		578350	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 15 S (PR-2B)**	Mini Z8	574780 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Esta Rohr	M 15		578312	298,00
simplesta SH M	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Esta Rohr	M 15		578312	298,00
simplesta ST M	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
EUROTUBI	M 12		578310	298,00
EUROPA	M 15		578312	298,00
C-Steel Pressfitting	M 18		578314	298,00
System M-Profile[1)]	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
EUROTUBI	M 15		578312	298,00
EUROPA	M 18		578314	298,00
Inox Pressfitting	M 22		578316	298,00
System M-Profile[1)]	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Evans	VAU 15 (½") (OD 12,7 mm)		578630	308,00
Components	VAU 20 (¾") (OD 19,1 mm)		578632	308,00
Presslok	VAU 25 (1") (OD 25,4 mm)		578634	308,00
	F			
FAR Rubinetterie	TH 14		578348	359,00
PRESSFAR	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
F.B.Q. BARONIO	V 12		578324	298,00
BQ PRESS SOLAR	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
F.B.Q. BARONIO	V 12		578324	298,00
BQ PRESS WATER	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
F.B.Q. BARONIO	V 12		578324	298,00
BQ PRESS GAS	V 14		578326	298,00
	V 15		578328	298,00
	V 16		578330	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 14 S (PR-2B)	Mini Z8	574800 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 16 S (PR-2B)	Mini Z8	574802 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FERCOFLOOR	RFz 16		578492	373,00
DUO Press	RFz 20		578494	373,00
FERCO PEX	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
FERCOFLOOR	RFz 16		578492	373,00
DUO Press	RFz 20		578494	373,00
MULTIFER	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
FERRO systems	TH 16		578352 R	359,00
BRASELI	TH 20		578358 R	359,00
GPF GAS	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
FERRO systems	U 16		578374	335,00
BRASELI	U 18		578376	335,00
GPF MULT	U 20		578378	335,00
Pressfitting	U 25		578380	335,00
MULTICAPA	U 32		578382	393,00
	U 40		578386	479,00
FERRO systems	U 16		578374	335,00
BRASELI	U 18		578376	335,00
GPF PPSU	U 20		578378	335,00
Pressfitting PEX y	U 25		578380	335,00
MULTICAPA	U 32		578382	393,00
	U 40		578386	479,00
FERRO systems	RFz 16		578492	373,00
BRASELI	RFz 20		578494	373,00
GPF PRESS	RFz 25		578496	373,00
Pressfitting PEX	RFz 32		578498	373,00
FILINOX	M 15		578312	298,00
Instalpress Steel	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
FILINOX	M 15		578312	298,00
Instalpress Inox	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
FITTINGS ESTÁNDAR	RFz 16		578492	373,00
ECO-PRESS	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
FITTINGS ESTÁNDAR	RFz 16		578492	373,00
MULTICAPA	RFz 18		578638	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
FITTINGS ESTÁNDAR	RFz 16		578492	373,00
PE-X	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
FORNARA	B 16		578468	391,00
ForPress	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
FORZA	K16/P18		578592	373,00
WATER CRIMP	K/20		578594	373,00
(AUS)	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00
FORZA STAINLESS	K16/P18		578592	373,00
WATER CRIMP	K/20		578594	373,00
FORZA	U 16		578374	335,00
STESSO PEX	U 20		578378	335,00
WATER AND GAS	U 25		578380	335,00
CRIMP AUS)	U 32		578382	393,00
	U 40		578386	479,00
FORZA	K16/P18		578592	373,00
GAS CRIMP	K/20		578594	373,00
(AUS)	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00
FORZA	VAU 15 (OD 12,7 mm)		578630	308,00
COPPER V PRESS	VAU 20 (OD 19,1 mm)		578632	308,00
(AUS)	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
FORZA	V 15		578328	298,00
STAINLESS V PRESS	V 22		578334	298,00
(AUS)	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FRABO	M 15		578312	298,00
FRABOPRESS	M 18		578314	298,00
316 GAS M	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
FRABO	V 15		578328	298,00
FRABOPRESS	V 18		578332	298,00
316 GAS V	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FRABO	M 15		578312	298,00
FRABOPRESS	M 18		578314	298,00
316 M	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
FRABO	V 12		578324	298,00
FRABOPRESS	V 15		578328	298,00
316 V	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FRABO	V 12		578324	298,00
FRABOPRESS	V 15		578328	298,00
CHROME	V 18		578332	298,00
	V 22		578334	298,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
FRABO	M 15		578312	298,00
FRABOPRESS	M 18		578314	298,00
C-STEEL M	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
FRABO	V 12		578324	298,00
FRABOPRESS	V 15		578328	298,00
C-STEEL V	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
FRABO	M 12		578310	298,00
FRABOPRESS	M 15		578312	298,00
GAS M	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
FRABO	V 12		578324	298,00
FRABOPRESS	V 15		578328	298,00
GAS V	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FRABO	V 12		578324	298,00
FRABOPRESS	V 15		578328	298,00
KOMBI	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FRABO	M 12		578310	298,00
FRABOPRESS M	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
FRABO	V 15		578328	298,00
FRABOPRESS	V 18		578332	298,00
SOLAR	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
FRABO	V 12		578324	298,00
FRABOPRESS V	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Fränkische	F 16		578456	342,00
alpex-duo XS	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)**	Mini Z8	574734 R	277,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	277,00
Fränkische	F 16		578456	342,00
alpex F50 PROFI	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)**	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
(DN 26)	U 25		578380	335,00
	U 32		578382	393,00
	VP 16		578482	358,00
	VP 20		578484	358,00
	VP 32		578488	395,00
Fränkische alpex L	Fz 40		578478	500,00

G

gabotherm H+S	TH 10		578342	359,00
	TH 12		578346	359,00
	TH 14		578348	359,00
	TH 15		578350	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 10 S (PR-2B)**	Mini Z8	574772 R	252,00
	TH 12 S (PR-2B)**	Mini Z8	574776 R	252,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 15 S (PR-2B)**	Mini Z8	574780 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Gallagher USA	H 12 (¼")		578396	324,00
YogaPipe ACR	U 14 (⅜")		578372	353,00
	U 16 (½")		578374	335,00
	U 18 (⅝")		578376	335,00
	U 20 (¾")		578378	335,00
	U 25 (⅞")		578380	335,00
	U 32 (1⅛")		578382	393,00
Geberit Mapress	M 12		578310	298,00
C-STAHL	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Geberit Mapress	M 22		578316	298,00
C-STAHL Sprinkler	M 28		578318	298,00
nass				298,00
Geberit Mapress	M 12		578310	298,00
Edelstahl	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Geberit Mapress Edelstahl Gas	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Geberit Mapress Edelstahl Sprinkler	M 22		578316	298,00
	M 28		578318	298,00
Geberit Mapress Kupfer	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Geberit Mapress Kupfer Gas	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Geberit Mepla	G 16		578444	359,00
	G 20		578446	359,00
	G 26		578448	381,00
	G 32		578450	407,00
	G 40		578452	527,00
Geberit Mepla Therm	G 16		578444	359,00
	G 20		578446	359,00
	G 26		578448	381,00
Geberit Volex	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
General Fittings 5T00	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	U 40		578386	479,00
General Fittings Ewoprex	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	U 40		578386	479,00
General Fittings Serie 5S00	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
General Fittings Trident	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
General Fittings Trident Gas	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
Giacomini Raccordi RM Giacomini	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	U 40		578386	479,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Giacomini RM MULTIGAS	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
Giacomini Valvole Giacomini serie R850V	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
	SA 15		578514	358,00
	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Golan Pipe Systems (Scandinavia) Alu-Pres	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
Grinnell G-PRESS Copper Fittings	VUS ½" (OD 15,9 mm)		578566	359,00
	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
GS Wärmesysteme System TH	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
GS Wärmesysteme System V	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

H

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
HASTINIK Hastinik/Hitpress	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
heima24	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
HELIROMA Klimapress	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
HELIROMA Klimapress PPSU	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
Henco	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	HE 32		578370 R	429,00
Herotec tempusPRESS PLUS	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
Herotec tempusPRESS PLUS PPSU	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
HERZ PIPEFIX	TH 10		578342	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 10 S (PR-2B)**	Mini Z8	574772 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	277,00
HIDRONIX MULTIGAS	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
HIDRONIX MULTIPIPE	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
HIDRONIX UNICO	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
HITEC Sistema Multistrato	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
HITHERM-ISOTUBI NUMEPRESS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
HITHERM-ISOTUBI HTpress	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
HITHERM-ISOTUBI HTfire	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
HITHERM-ISOTUBI HTair	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Hopewell press fit system	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
hp praski BAVARIA-press	TH 10		578342	359,00
	TH 12		578346	359,00
	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 10 S (PR-2B)**	Mini Z8	574772 R	252,00
	TH 12 S (PR-2B)**	Mini Z8	574776 R	252,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
I				
ICMA Sempiter	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
ICMA Sempigas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Idrosanitaria Bonomi Homegas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
Idrosanitaria Bonomi Idropress	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
IDROSISTEMI Ta-Press	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	Fz 40		578478	500,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
IDROTRADE Storm Multipinza	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	THL 32		578368	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
IDROTRADE StormPRES[1]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
IDROTRADE StormSTEEL[1]	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ILTA INOX/CHIBRO Pressfitting Cuni	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
ILTA INOX/CHIBRO Pressfitting inox	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Instantor Press System	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Instantor Copper Press Imperial	VI ½" (OD 14,7 mm)		578716	355,00
	VI ¾" (OD 21,0 mm)		578718	355,00
	VI 1" (OD 27,4 mm)		578720	355,00
	VI ½" S (PR-2B)	Mini Z8	574850 R	252,00
	VI ¾" S (PR-2B)	Mini Z8	574852 R	252,00
	VI 1" S (PR-2B)	Mini Z8	574854 R	252,00
Instantor Copper Press Metric	M 15		578312	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
IPA IPANA Press	TH 10		578342	359,00
	TH 11,6		578344	359,00
	TH 12		578346	359,00
	TH 14		578348	359,00
	TH 15		578350	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 22		578588	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 28		578590	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 10 S (PR-2B)**	Mini Z8	574772 R	252,00
	TH 11,6 S (PR-2B)**	Mini Z8	574774 R	252,00
	TH 12 S (PR-2B)**	Mini Z8	574776 R	252,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 15 S (PR-2B)**	Mini Z8	574780 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 22 S (PR-2B)**	Mini Z8	574790 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 28 S (PR-2B)**	Mini Z8	574796 R	277,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	277,00
IPA THu IPANA Press	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
IPALPEX (Industrie du Plastique et Accessoires)	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	THL 32		578368	359,00
	TH 40		578624	475,00
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	K16/P18		578592	373,00
IPLEX PIPELINES AUSTRALIA Iplex K1 (Gas)	K16/P18		578592	373,00
	K/20		578594	373,00
	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
IPLEX PIPELINES AUSTRALIA Iplex K2	K16/P18		578592	373,00
	K/20		578594	373,00
	K/25		578596	373,00
ISOTUBI NUMEPRESS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
IVAR ALPEX-GAS	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
IVAR Ivar-Press	B 14		578466	391,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	Fz 40		578478	500,00
IVAR MULTI PRESS GAS ITALIA	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	U 16		578374	335,00
	U 20		578378	335,00
IVAR Multi Press MP	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	F 16		578456	342,00
	F 18		578458	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	Fz 40		578478	500,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
IVAR Multi Press Leak (MPL)	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
IVAR Plastic Multi Press PMP	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
IVAR Plastic Multi Press Leak (PMPL)	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
IVT Edelstahl-Presssystem	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
IVT PRIPRESS	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
	J			
Jäger - Aquatec Aquapress H	H 14		578398	324,00
	H 16		578400	324,00
	H 17		578402	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 40		578386	479,00
Jäger - Aquatec C-Stahl Press Typ M	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Jäger - Aquatec Edelstahl Press Typ M	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Jäger - Aquatec Kupfer Press Typ V	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Jansen AG JANSEN COMISA	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Jaraflex-Presssystem	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
JUNGWOO JWPress	VUS ½" (OD 15,9 mm)		578566	359,00
	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
	K			
KAN	TH 14		578348	359,00
KAN-therm Press LBP	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
KAN	M 15		578312	298,00
KAN-therm Inox	M 18[1]		578314	298,00
	M 22		578316	298,00
	M 28[1]		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
KAN	M 12		578310	298,00
KAN-therm Steel	M 15		578312	298,00
	M 18[1]		578314	298,00
	M 22		578316	298,00
	M 28[1]		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
KAN	TH 14		578348	359,00
KAN-therm	TH 16		578352 R	359,00
UltraPRESS	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
KE KELIT	M 15		578312	298,00
COPPERFIX	M 18		578314	298,00
Kupfer	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
KE KELIT	U 16		578374	335,00
KELIT KELOX	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
KE KELIT	U 16		578374	335,00
KELOX-PPSU-W	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
KE KELIT	U 16		578374	335,00
KELOX-ULTRAX	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
KE KELIT	U 16		578374	335,00
KELOX-ULTRAX-W	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
KE KELIT	U 16		578374	335,00
KELOX-WINDOX-U	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
KE KELIT	U 16		578374	335,00
KELOX-WINDOX-W	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
KE KELIT	M 15		578312	298,00
steelFIX	M 18		578314	298,00
C-Stahl	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
KE KELIT	M 15		578312	298,00
steelFIX	M 18		578314	298,00
Edelstahl	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
KEMBLA	VAU 15 (OD 12,7 mm)		578630	308,00
KemPress	VAU 20 (OD 19,1 mm)		578632	308,00
(AUS)	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
KEMBLA	VAU 15 (OD 12,7 mm)		578630	308,00
KemPress Gas	VAU 20 (OD 19,1 mm)		578632	308,00
(AUS)	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
KISAN	KI 16		578524	379,00
Kisan KD	KI 20		578526	379,00
	KI 25		578528	379,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
KISAN	KI 16		578524	379,00
Kisan WL	KI 20		578526	379,00
	KI 25		578528	379,00
	KI 32		578530	511,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
KISAN	KI 16		578524	379,00
Kisan WM	KI 20		578526	379,00
	KI 25		578528	379,00
	KI 32		578530	511,00
KISAN	U 20		578378	335,00
Kisan WR	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
KISAN	M 15		578312	298,00
Kistal C	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
KISAN	M 15		578312	298,00
Kistal Inox	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	L			
LEGEND-PRESS	VUS ½" (OD 15,9 mm)		578566	359,00
press fitting	VUS ¾" (OD 22,2 mm)		578568	359,00
system	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
LK Systems	V 12		578324	298,00
LK >B<Press	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
LK Systems	V 12		578324	298,00
LK >B<Press	V 15		578328	298,00
Elförzinkat	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
LK Systems	V 15		578328	298,00
LK >B<Press	V 18		578332	298,00
Gas	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
LK Systems	TH 16		578352 R	359,00
LK Universal	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00

M

MAINCOR	U 16		578374	335,00
MAINPRESS	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
MAINCOR	U 16		578374	335,00
MAINFLOR	U 20		578378	335,00
Mair Heiztechnik	H 11,5		578394	324,00
M-Press	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Ma.s.ter System	TH 14		578348	359,00
PRESSMASTER	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Meier Tobler	H 16		578400	324,00
Metalplast - Stramax	H 20		578406	324,00
Serie MM	H 25		578408	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
METALGRUP	U 16		578374	335,00
Permatubo	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
METALGRUP	RFz 16		578492	373,00
PexGrup	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
METALGRUP	U 16		578374	335,00
MultiGrup	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
Mueller Streamline	VUS ½" (OD 15,9 mm)		578566	359,00
PRS Copper Press	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
MULTITHERM	TH 16		578352 R	359,00
PRESSSYSTEM	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Multicapas Industrial	RFz 16		578492	373,00
AIS PEX	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
Multicapas Industrial	H 16		578400	324,00
AIS XPRT	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Multicapas Industrial multitubo systems MC	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
Multicapas Industrial multitubo systems MM	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
multipipe Deutschland multipipe mp	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

N

NEUTHERM MEKUPRESS-HT	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
NIBCO Press System Copper	VUS ½" (OD 15,9 mm)		578566	359,00
	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
NICOLL FLUXO	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
NUPI Industrie Italiane Multinupi	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 18		578458	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
Nussbaum Optifitt-Press	VMP ⅜" (OD 17,2 mm)		578660	413,00
	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Nussbaum Optiflex-Flowpress	VRX 16		578640	377,00
	VRX 20		578642	377,00
	VRX 25		578644	413,00
	VRX 32		578646	413,00
Nussbaum Optipress Aquaplus	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Nussbaum Optipress Gaz	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Nussbaum Optipress-Therm	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

O

Oventrop Cofit P	H 16 A		578420	413,00
	H 20 A		578426	413,00
	H 26 A		578430	413,00
	H 32 A		578432	413,00
Oventrop Cofit PD	H 16 A		578420	413,00
	H 20 A		578426	413,00
	H 26 A		578430	413,00
Oventrop Cofit PDK	H 16 A		578420	413,00
	H 20 A		578426	413,00
Oventrop Cofit PD-HT	H 16 A		578420	413,00
	H 20 A		578426	413,00
	H 32 A		578432	413,00
Oventrop Cofit PDK-HT	H 16 A		578420	413,00
	H 20 A		578426	413,00

P

PBTub SERTIPRESS	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
PBTub SERTI-STEEL[1)]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
Pegler Yorkshire	> Aalberts integrated piping systems			
PERFEXIM PERFEKT SYSTEM	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
PERFEXIM PERFEKT SYSTEM PLUS	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
PERFILTUBO PERFILALUPEX	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
PERFILTUBO PERFILPRESS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
PEXTUBE PexTube	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Pipelife C-PRESS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Pipelife RADOPRESS	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Pipetec Connect	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
PLASTICA ALFA Multypex	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
PLASTICA ALFA Multypex Air	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
PLASTICA ALFA Multypexalfa Gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
PLASTICA ALFA Multypexalfa Gas protek	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
PLASTICA ALFA Multypex Plus	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
PLASTICA ALFA Multypex Thermo	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
PLASTICA ALFA Multypex Thermo Plus	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
PLÁSTICOS FERRO FERROPLAST GPF MULT Pressfitting MULTICAPA	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
PLÁSTICOS FERRO FERROPLAST GPF PPSU Pressfitting PEX y MULTICAPA	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
PLÁSTICOS FERRO FERROPLAST GPF PRESS Pressfitting PEX	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
PLUMBING PLUS EZIPEX Crimp (AUS)	K16/P18		578592	373,00
	K/20		578594	373,00
	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00
PLUMBING PLUS EZIPEX Gas (AUS)	K16/P18		578592	373,00
	K/20		578594	373,00
	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00
PLUMBING PLUS UNIPEX Water & Gas (AUS)	Yz 16 UNI		578740	373,00
	Yz 20 UNI		578742	373,00
	Yz 25 UNI		578744	373,00
	Yz 32 UNI		578746	373,00
PLUMBING PLUS EZIPRESS Gas (AUS)	VAU 15 (OD 12,7 mm)		578630	308,00
	VAU 20 (OD 19,1 mm)		578632	308,00
	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	277,00
PLUMBING PLUS EZIPRESS Solar (AUS)	VAU 15 (OD 12,7 mm)		578630	308,00
	VAU 20 (OD 19,1 mm)		578632	308,00
	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	277,00
PLUMBING PLUS EZIPRESS Water (AUS)	VAU 15 (OD 12,7 mm)		578630	308,00
	VAU 20 (OD 19,1 mm)		578632	308,00
	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	277,00
POLYPIPE POLYSURE	TH 10		578342	359,00
	TH 15		578350	359,00
	TH 22		578588	359,00
	TH 28		578590	359,00
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Österreich) POLYSAN-C Stahl-Press-System M	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Österreich) POLYSAN-Edelstahl Press-System 1.4520	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Österreich) POLYSAN-Edelstahl Press-System Gas	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster-reich) POLYSAN-Edelstahl Press-System Wasser	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster-reich) POLYSAN-Press-System	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster-reich) POLYSAN-Henco-Press-System	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	HE 32		578370 R	429,00
	HEz 40[3]		578572	623,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
POLYSAN (España) „Rainbow"	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
Prandelli Multyrama Pf	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 40		578386	479,00
Prandelli Multyrama Pfm	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 40		578386	479,00
PURMO Cleverfit Radial	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	VP 16		578482	358,00
	VP 20		578484	358,00
	VP 32		578488	395,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
	R			
Raccorderie Metalliche aesPRES[1]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Raccorderie Metalliche inoxPRES[1]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Raccorderie Metalliche MARINEPRES[1]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Raccorderie Metalliche steelPRES[1]	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
RBM Tita-fix	B 14		578466	391,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	F 16		578456	342,00
	F 18		578458	342,00
	F 20		578460	342,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
RBM Tita-gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Redi Nicoll Fluxo	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Redi Nicoll Fluxo Gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
RIFENG LD PRESS FITTING (F8)	LD 16		578652	370,00
	LD 20		578654	370,00
	LD 25		578656	370,00
RIFENG U PRESS FITTING (F5)	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
RIFENG TH PRESS FITTING (F9)	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
RIQUIER A SERTIR	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
RIQUIER Système multicouche	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	U 40		578386	479,00
Roth PressCheck	RN 14		578434	335,00
	RN 16		578454	335,00
	RN 17		578436	335,00
	RN 20		578438	335,00
	RN 25/26		578440	335,00
	RN 32		578442	393,00
Rubinetterie Bresciane Bonomi TURBO CuNi	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO INOX	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO INOX GAS	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO STEEL	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO PRESS	B 14		578466	391,00
	B 16		578468	391,00
	B 18		578470	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	H 14		578398	324,00
	H 16		578400	324,00
	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 14		578372	353,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
Rubinetterie Bresciane Bonomi TURBO PRESS GAS	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

S

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SA.MI PLASTIC	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
SA.MI PLASTIC Multistrato Gas	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA	B 16		578468	391,00
3fit-Press Pb-free	B 20		578472	391,00
Serie 25000	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	Fz 40		578478	500,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
SANHA	B 16		578468	391,00
3fit-Press PPSU	B 20		578472	391,00
Serie 35000	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
SANHA	VMP ½" G (OD 21,3 mm)		578666 R	413,00
Heavy Steel Press	VMPz ¾" (OD 26,9 mm)		578664	413,00
SANHA	VMP ½" G (OD 21,3 mm)[6]		578666 R	413,00
Heavy Steel Press Gas	VMPz ¾" (OD 26,9 mm)		578664	413,00
SANHA-NiroSan	SA 15		578514	358,00
Gas Presssystem	SA 18		578518	358,00
Serie 17000	SA 22		578520	358,00
	SA 28		578522	358,00
	M 15[1]		578312	298,00
	M 18[1]		578314	298,00
	M 22[1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15[1]		578328	298,00
	V 18[1]		578332	298,00
	V 22[1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-NiroSan	SA 15		578514	358,00
Industry	SA 18		578518	358,00
Presssystem	SA 22		578520	358,00
Serie 18000	SA 28		578522	358,00
	M 15[1]		578312	298,00
	M 18[1]		578314	298,00
	M 22[1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15[1]		578328	298,00
	V 18[1]		578332	298,00
	V 22[1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA-NiroSan-	SA 15		578514	358,00
Presssystem	SA 18		578518	358,00
Serie 9000	SA 22		578520	358,00
	SA 28		578522	358,00
	M 15[1]		578312	298,00
	M 18[1]		578314	298,00
	M 22[1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15[1]		578328	298,00
	V 18[1]		578332	298,00
	V 22[1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA-NiroSan	SA 15		578514	358,00
SF Presssystem	SA 18		578518	358,00
Serie 19000	SA 22		578520	358,00
(silicone free)	SA 28		578522	358,00
	M 15[1]		578312	298,00
	M 18[1]		578314	298,00
	M 22[1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15[1]		578328	298,00
	V 18[1]		578332	298,00
	V 22[1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA	SA 15		578514	358,00
NiroTherm	SA 18		578518	358,00
Serie 91000	SA 22		578520	358,00
	SA 28		578522	358,00
	M 15[1]		578312	298,00
	M 18[1]		578314	298,00
	M 22[1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15[1]		578328	298,00
	V 18[1]		578332	298,00
	V 22[1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA	SA 15		578514	358,00
NiroTherm	SA 18		578518	358,00
Industry	SA 22		578520	358,00
Serie 98000	SA 28		578522	358,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 15 [1]		578328	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA-Press	SA 12		578510	519,00
Chrom	SA 15		578514	358,00
Serie 16000	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 12		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	V 12		578324	298,00
	V 15 [1]		578328	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
SANHA-Press	SA 12		578510	519,00
GAS Pressfittings	SA 14		578512	519,00
Serie 10000/	SA 15		578514	358,00
Serie 11000	SA 16		578516	358,00
	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 12		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 12		578324	298,00
	V 14		578326	298,00
	VG 14		578338	298,00
	V 15 [1]		578328	298,00
	V 16		578330	298,00
	VG 16		578340	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-Press	SA 12		578510	519,00
Pressfittings	SA 14		578512	519,00
Serie 6000	SA 15		578514	358,00
	SA 16		578516	358,00
	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 12		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 12		578324	298,00
	V 14		578326	298,00
	VG 14		578338	298,00
	V 15 [1]		578328	298,00
	V 16		578330	298,00
	VG 16		578340	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA-Press	SA 12		578510	519,00
SOLAR	SA 15		578514	358,00
Pressfittings	SA 18		578518	358,00
Serie 12000/	SA 22		578520	358,00
Serie 13000	SA 28		578522	358,00
	M 12		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 12		578324	298,00
	V 15 [1]		578328	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For taking suitable pressing inserts.

[3] Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

[4] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[5] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[6] Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[7] Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA	SA 12		578510	519,00
PURAPRESS	SA 14		578512	519,00
Serie 8000	SA 15		578514	358,00
	SA 16		578516	358,00
	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 12 [1]		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28 [1]		578318	298,00
	M 35 [1]		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 12		578324	298,00
	V 14		578326	298,00
	VG 14		578338	298,00
	V 15 [1]		578328	298,00
	V 16		578330	298,00
	VG 16		578340	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA-Therm	SA 12		578510	519,00
Serie 24000	SA 15		578514	358,00
	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 12		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 12		578324	298,00
	V 15 [1]		578328	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
SANHA-Therm	SA 12		578510	519,00
Industry	SA 15		578514	358,00
Serie 28000	SA 18		578518	358,00
	SA 22		578520	358,00
	SA 28		578522	358,00
	M 12		578310	298,00
	M 15 [1]		578312	298,00
	M 18 [1]		578314	298,00
	M 22 [1]		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
	V 12		578324	298,00
	V 15 [1]		578328	298,00
	V 18 [1]		578332	298,00
	V 22 [1]		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANITOP	M 15		578312	298,00
PERMATUBO INOX	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
SANPRO	TH 16		578352 R	359,00
THPRESS	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
SATEC SK VITerm	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	U 40		578386	479,00
SAVEUR REFLEX	TH 16		578352 R	359,00
PEX Water	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
SAVEUR REFLEX	TH 16		578352 R	359,00
PEX-AL-PEX	TH 20		578358 R	359,00
Gas	TH 25		578360	359,00
	TH 32		578364	359,00
Schütz	TH 14		578348	359,00
duo-flex	TH 16		578352 R	359,00
tri-o-flex	TH 17		578354	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
Schwer Fittings	M 12		578310	298,00
AQUApress	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Seppelfricke	> Aalberts integrated piping systems			
SESTA	TH 14		578348	359,00
SESTA GAS	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
SESTA	H 16		578400	324,00
sistema	H 20		578406	324,00
multistrato	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	U 16		578374	335,00
	U 20		578378	335,00
SIGMA LI	TH 16		578352 R	359,00
Premium	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
SLOVARM	U 16		578374	335,00
PEX-THERM	U 20		578378	335,00
	H 26		578410	324,00
	U 32		578382	393,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
STANDARD	H 16		578400	324,00
HIDRAULICA	H 20		578406	324,00
MultiStandard	H 25		578408	324,00
	H 32		578412	324,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
steeltrade	M 15		578312	298,00
Presssystem	M 18[1)]		578314	298,00
Edelstahl	M 22		578316	298,00
Kontur M	M 28[1)]		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
STELBI	H 16		578400	324,00
Polikraft	H 20		578406	324,00
	H 26		578410	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
STELBI	TH 16		578352 R	359,00
Stelgas	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
STH Westco	M 15		578312	298,00
COPPER PRESS	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00

T

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
TDM BRASS	H 16		578400	324,00
Serie 1600	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	THL 32		578368	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
TDM BRASS	H 16		578400	324,00
Serie 2600	H 18		578404	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	THL 32		578368	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
TDM BRASS	TH 16		578352 R	359,00
Serie 1700 gas	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	THL 32		578368	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
TermoConcept	Basic E01[2)]		578618	618,00
TC-PRESS				
THERMOLUTZ	H 14		578398	324,00
	H 16		578400	324,00
	TH 20		578358 R	359,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
TE-SA	TH 14		578348	359,00
TE-SA press	TH 16		578352 R	359,00
serie 800	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
THERMACOME	H 16		578400	324,00
ACOPEX ALU	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
TIEMME	TH 14		578348	359,00
1650 AL-COBRAPEX	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	THL 32		578368	359,00
	TH 40		578624	475,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
TIEMME	RFz 12		578490	373,00
1700 COBRAPEX	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
	TH 40		578624	475,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
TIEMME	TH 16		578352 R	359,00
1650 AL-COBRAPEX	TH 20		578358 R	359,00
GAS	TH 26		578362 R	359,00
	THL 32		578368	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
TIGRE	TH 16		578352 R	359,00
ALPEX GÁS	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
TKM	TH 14		578348	359,00
Systemtechnik	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
TRA Multi TRA+	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
	U 40		578386	479,00
TRA MULTITRAPRESS	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
TRA TRAPRESS	H 12		578396	324,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	RFz 12		578490	373,00
	RFz 16		578492	373,00
	RFz 20		578494	373,00
	RFz 25		578496	373,00
	RFz 32		578498	373,00
Tradelink	K16/P18		578592	373,00
TradePex Crimp	K/20		578594	373,00
Water	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00
Tradelink	K16/P18		578592	373,00
TradePex Crimp	K/20		578594	373,00
Gas	K/25		578596	373,00
	K32		578598	373,00
	K1/40		578600	373,00
TUBIPLAST ITALY	H 16		578400	324,00
MULTILAYER PIPE	H 18		578404	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 18		578376	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
TUBIPLAST ITALY	TH 16		578352 R	359,00
MULTILAYER PIPE	TH 18		578356	359,00
GAS SYSTEM	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
TWEETOP	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00

U

UNICAL AG	U 16		578374	335,00
MAX-MULTIPEX	U 20		578378	335,00
	H 26		578410	324,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
UNIDELTA	TH 16		578352 R	359,00
DELTAPRESS	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
	U 40		578386	479,00
UNIDELTA	TH 16		578352 R	359,00
DELTAPRESS GAS	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 32		578382	393,00
Uponor	UP 14		578576	335,00
	UP 16		578578	335,00
	UP 20		578582	335,00
	UP 25		578584	335,00
	UP 32		578586	393,00
	U 40		578386	479,00

V

Valsir Bravopress	B 16		578468	391,00
	B 20		578472	391,00
	B 26		578474	431,00
	B 32		578476	431,00
	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	H 32 V		578602	413,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00
Valsir PEXAL	H 14		578398	324,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	H 32 V		578602	413,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7)]		578392	393,00
	U 32		578382	393,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Van Marcke NV SYSTEMPEX	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
Van Marcke NV Tubipress	M 12		578310	298,00
	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 12 S (PR-2B)	Mini Z8	574736 R	252,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
Variotherm System TH	TH 11,6		578344	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
VESBO CARBON	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
VESBO INOX	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
VESBO MULTIPRESS TH-U	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 26[7]		578392	393,00
	U 32		578382	393,00
VESBO VPREMIUM	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
Viega Fonterra	VX 12		578550	413,00
	VP 14/15		578480	358,00
	VP 16/17		578482	358,00
	VP 20		578484	358,00
	VP 25		578486	358,00
Viega MegaPress (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega MegaPress 304 FKM (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
				182,50
Viega MegaPress 316 (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega MegaPress 316 FKM (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
				182,50
Viega MegaPress CuNi (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega MegaPress FKM (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega MegaPresG (ASTM)[5]	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega Megapress (EN)[4]	VMP ⅜" (OD 17,2 mm)		578660	413,00
	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega MegapressS (EN)[4]	VMP ⅜" (OD 17,2 mm)		578660	413,00
	VMP ½" G (OD 21,3 mm)		578666 R	413,00
	VMPz ¾" (OD 26,9 mm)		578664	413,00
Viega Pexfit	VX 16		578552	413,00
	VX 20		578554	413,00
	VX 25		578556	413,00
Viega Pexfit G	VX 16		578552	413,00
	VX 20		578554	413,00
	VX 25		578556	413,00
Viega Prestabo	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
Viega Profipress	V 12		578324	298,00
	VG 14		578338	298,00
	V 15		578328	298,00
	VG 16		578340	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Viega Profipress G	V 12		578324	298,00
	VG 14		578338	298,00
	V 15		578328	298,00
	VG 16		578340	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Viega Profipress S	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Viega Profipress Therm	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
Viega ProPress (ASTM)[5]	VUS ½" (OD 15,9 mm)		578566	359,00
	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
	VUS ½" S (PR-2B) (OD 15,9 mm)	Mini Z8	574764 R	252,00
	VUS ¾" S (PR-2B) (OD 22,2 mm)	Mini Z8	574766 R	252,00
	VUS 1" S (PR-2B) (OD 28,6 mm)	Mini Z8	574768 R	252,00
	VUS 1¼" S (PR-2B) (OD 34,9 mm)	Mini Z8	574770 R	252,00
Viega ProPress 304 FKM (ASTM)[5]	VUS ½" (OD 15,9 mm)		578566	359,00
	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
Viega ProPress 316 (ASTM)[5]	VUS ½" (OD 15,9 mm)		578566	359,00
	VUS ¾" (OD 22,2 mm)		578568	359,00
	VUS 1" (OD 28,6 mm)		578570	359,00
	VUS 1¼" (OD 34,9 mm)		578606	359,00
Viega Propress WATER System AUS	VAU 15 (OD 12,7 mm)		578630	308,00
	VAU 20 (OD 19,1 mm)		578632	308,00
	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	277,00
	VAU 32 S (PR-2B) (OD 31,8 mm)	Mini Z8	574856 R	277,00
Viega PropressG GAS System AUS	VAU 15 (OD 12,7 mm)		578630	308,00
	VAU 20 (OD 19,1 mm)		578632	308,00
	VAU 25 (OD 25,4 mm)		578634	308,00
	VAU 32 (OD 31,8 mm)		578636	324,00
Viega Raxinox	VRX 16		578640	377,00
	VRX 20		578642	377,00
Viega Raxofix	VRX 16		578640	377,00
	VRX 20		578642	377,00
	VRX 25		578644	413,00
	VRX 32		578646	413,00
Viega Sanfix	VP 16/17		578482	358,00
	VP 20		578484	358,00
	VP 25		578486	358,00
	VP 32		578488	395,00
Viega Sanfix Fosta	VP 16/17		578482	358,00
	VP 20		578484	358,00
	VP 25		578486	358,00
	VP 32		578488	395,00
Viega Sanpress	V 12		578324	298,00
	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 12 S (PR-2B)	Mini Z8	574748 R	252,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Viega Sanpress Inox	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Viega Sanpress Inox G	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00
Viega Smartpress	VX 16		578552	413,00
	VX 20		578554	413,00
	VX 25		578556	413,00
Viega Temponox	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Viessmann	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
Vogel & Noot EASYTEC	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
VSH	> Aalberts integrated piping systems			

W

Watts MTR Art press	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
WATTS RADIANT Watts WaterPEX	US ⅜"		578534	407,00
	US ½"		578536	407,00
	US ¾"		578538	407,00
	US 1"		578540	407,00
WATTS RADIANT Watts RadiantPEX	US ⅜"		578534	407,00
	US ½"		578536	407,00
	US ¾"		578538	407,00
	US 1"		578540	407,00
WATTS RADIANT Watts RadiantPEX-AL	U 16 (½")		578374	335,00
	U 20 (⅝")		578378	335,00
	U 25 (¾")		578380	335,00
	U 32 (1")		578382	393,00
Wavin Tigris K5/M5	B 16		578468	391,00
	B 20		578472	391,00
	B 32		578476	431,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 25		578408	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 25		578360	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
	U 25		578380	335,00
	U 32		578382	393,00
	U 40		578386	479,00
	UP 16		578578	335,00
	UP 20		578582	335,00
	UP 25		578584	335,00
	UP 32		578586	393,00
WEECON PRESS-C-Stahl	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
WEECON PRESS-Edelstahl	M 15		578312	298,00
	M 18		578314	298,00
	M 22		578316	298,00
	M 28		578318	298,00
	M 35		578390	361,00
	M 15 S (PR-2B)	Mini Z8	574738 R	252,00
	M 18 S (PR-2B)	Mini Z8	574740 R	252,00
	M 22 S (PR-2B)	Mini Z8	574742 R	252,00
	M 28 S (PR-2B)	Mini Z8	574744 R	252,00
	M 35 S (PR-2B)	Mini Z8	574746 R	277,00
WEECON PRESS-Kupfer	V 15		578328	298,00
	V 18		578332	298,00
	V 22		578334	298,00
	V 28		578336	298,00
	V 35		578604	361,00
	V 15 S (PR-2B)	Mini Z8	574752 R	252,00
	V 18 S (PR-2B)	Mini Z8	574756 R	252,00
	V 22 S (PR-2B)	Mini Z8	574758 R	252,00
	V 28 S (PR-2B)	Mini Z8	574760 R	252,00
	V 35 S (PR-2B)	Mini Z8	574762 R	277,00

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
WEM	U 16		578374	335,00
WIELAND-WERKE	TH 14		578348	359,00
cuprotherm CTX	TH 16		578352 R	359,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
WKS-Press	TH 14		578348	359,00
	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
WÜRTH	TH 16		578352 R	359,00
Würth	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	HE 32		578370 R	429,00
X				
XtraConnect	F 16		578456	342,00
	F 20		578460	342,00
	F 26		578462	370,00
	F 32		578464	370,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	252,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	252,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	252,00
	F 32 S (PR-2B)	Mini Z8	574734 R	277,00
	H 16		578400	324,00
	H 20		578406	324,00
	H 26		578410	324,00
	H 32		578412	324,00
	TH 16		578352 R	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
	U 16		578374	335,00
	U 20		578378	335,00
(DN 26)	U 25		578380	335,00
	U 32		578382	393,00
	VP 16		578482	358,00
	VP 20		578484	358,00
	VP 32		578488	395,00
Y				
YX COPPER	Yz 16 UNI		578740	373,00
UNIPEX Water & Gas	Yz 20 UNI		578742	373,00
(AUS)	Yz 25 UNI		578744	373,00
	Yz 32 UNI		578746	373,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	KM
Z				
ZEWOTHERM	TH 12		578346	359,00
Zewo Press Premium	TH 16		578352 R	359,00
	TH 17		578354	359,00
	TH 18		578356	359,00
	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 40		578624	475,00
	TH 12 S (PR-2B)**	Mini Z8	574776 R	252,00
	TH 16 S (PR-2B)**		574782 R	252,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	252,00
	TH 20 S (PR-2B)**		574788 R	252,00
	TH 26 S (PR-2B)**		574794 R	252,00
	TH 32 S (PR-2B)		574798 R	277,00
ZEWOTHERM	TH 16		578352 R	359,00
Zewo Press PPSU	TH 20		578358 R	359,00
	TH 26		578362 R	359,00
	TH 32		578364	359,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	252,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	277,00
ZURN	US ⅜"		578534	407,00
INDUSTRIES	US ½"		578536	407,00
ZURN PEX	US ¾"		578538	407,00
	US 1"		578540	407,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

Accessories

Description	Art.-No.	KM
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	**292,00**
Steel case with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	**196,00**
L-Boxx system case with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	**296,00**
Steel case with insert for 8 pressing tongs Mini/ cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295R	**196,00**
L-Boxx system case with insert for 11 pressing tongs Mini and 6 pressing rings S (PR-2B)	578659R	**296,00**

REMS cropping tongs Mini

High performance cropping tongs Mini in forged and specially hardened steel for cutting threaded rods.

Steel, stainless steel up to hardness classification 4.8 (400 N/mm²) M 6 – M 10

REMS cropping tongs Mini – cuts in just 2 seconds!

Made of forged and specially hardened steel.

Reversible cropping inserts for double service life.

M cropping inserts with high precision thread contour machined on CNC machining centres for exact guiding of the threaded rod in the cutting process Pliers parts, cropping inserts and specially machined and hardened cutting edges, made to fit exactly, for cutting without burr

Threaded rod can be screwed into a threaded connection of the pipe clip or the nut without rework after cutting

Cutting device in pliers design **(Patent EP 1 459 825, patent US 7,284,330).** Very compact design and low weight of the REMS Mini cropping tongs due to special arrangement of the cropping tongs connection **(Patent EP 1 952 948)**. Recesses in the connecting plate for safe guidance of the connecting lugs for offset-free pressing **(Patent EP 2 347 862)**.

Can be driven by all REMS radial presses 22 kN.



German Quality Product

Patent EP 1 952 948
Patent EP 1 459 825
Patent US 7,284,330
Patent EP 2 347 862

Supply format

REMS cropping tongs Mini. Cropping tongs with 1 pair of reversible cropping inserts for steel, stainless steel, M 6 – M 10. In a carton.

Description	for threaded rods	Art.-No.	KM
REMS cropping tongs Mini M 6	M 6	578620	**490,00**
REMS cropping tongs Mini M 8	M 8	578621	**490,00**
REMS cropping tongs Mini M 10	M 10	578622	**490,00**

Accessories

Description	for threaded rods	Art.-No.	KM
Cropping inserts M 6 (pair)	M 6	571891	**225,00**
Cropping inserts M 8 (pair)	M 8	571896	**225,00**
Cropping inserts M 10 (pair)	M 10	571866	**225,00**
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm		578295R	**196,00**

All prices excl. VAT

REMS Eco-Press

Manual radial press

Universal, manual radial press for producing pipe pressing joints for common pressfitting systems.

Pressing joints with plastic and multi-layer composite tubes — Ø 10 – 26 mm, Ø ⅜ – 1"

Complete range of REMS pressing tongs/ pressing rings for all common pressfitting systems, see page 198 – 238.



German Quality Product

Info

REMS Eco-Press – universal up to Ø 26 mm. Secure crimping in seconds.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. For driving the REMS pressing rings S (PR-2B) adapter tongs Z8 are required, see page 238.

Design

Compact, handy, light. Drive unit with short tubular arms only 1.6 kg. Works anywhere, free-hand, overhead, in confined areas. Secure seating of pressing tongs through locking pins. Dividable tubular arms for individual adjustment of leverage to accomodate different force demands of different pressfitting systems.

Pressing operation

A perfect joint is achieved when pressing tongs close completely. Final-lock-positioning, the pressing jaws remain in a closed position until opening. This way, the perfect pressing joint (completely closed pressing jaws) can be observed.

Supply format

REMS Eco-Press drive unit. Manual radial press with final-lock-positioning for producing pressing joints of plastic and multi-layer composite tubes Ø 10 – 26 mm, Ø ⅜ – 1". For driving REMS pressing tongs/pressing rings. With dividable tubular arms. In skin package.

	Art.-No.	KM
	574000R	**460,00**

Accessories

Description	Art.-No.	KM
REMS pressing tongs/pressing rings, see page 198 – 238.		
Adapter tongs Z8 for driving REMS pressing rings S (PR-2B)	574702R	**292,00**
REMS cropping tongs for threaded rods see page 241.		
Carrying bag for drive unit and for 3 pressing tongs	574436R	**77,70**
Steel case with insert for drive unit and for 3 pressing tongs	574430R	**196,00**

REMS Power-Press SE

Electric radial press 32 kN

Universal, handy electric tool for producing pipe pressing joints for all common pressfitting systems.

Pipe pressing joints Ø 10 – 108 (110) mm
Ø ⅜ – 4"

Complete range of REMS pressing tongs/ pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Power-Press SE – universal up to Ø 110 mm.
Secure crimping in seconds.
Automatic locking of pressing tongs.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 4.7 kg. Works anywhere, free-hand, overhead, in confined areas. Secure seating of pressing tongs/adapter tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing chains.

Pressing operation by touch-control

For reliable service, operating and functional safety. A perfect joint is achieved when pressing tongs close completely. The pressing tongs remain in a closed position until machine is switched and runs into reverse. The perfect pressing joint (completely closed pressing jaws) can be observed.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-mechanical drive with proven universal motor, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle. Overload protection. Safety tip switch.

Two connections for REMS Eco-Press manual radial press and REMS 32 kN radial presses.

German Quality Product

Info

Supply format

REMS Power-Press SE Basic-Pack. Electric radial press 32 kN for producing pressing joints Ø 10 – 108 (110) mm, Ø ⅜ – 4". For driving REMS pressing tongs/ pressing rings and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-mechanical drive with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle, overload protection, safety tip switch. In sturdy steel case.

	Art.-No.	KM
	572111 R220	**1.950,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Power-Press SE Drive Unit	572101 R220	**1.850,00**
REMS pressing tongs/pressing rings see page 198 – 238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
Steel case with insert	570280 R	**223,00**

All prices excl. VAT

REMS Power-Press ACC

Electro-hydraulic radial press 32 kN
with automatic retraction

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems.

Pipe pressing joints	Ø 10 – 108 (110) mm Ø ⅜ – 4"

Complete range of REMS pressing tongs/ pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Power-Press ACC – universal up to Ø 110 mm. Secure crimping in seconds. With automatic circuit control. Automatic locking of pressing tongs.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 4.7 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

German Quality Product

Info

Supply format

REMS Power-Press ACC Basic-Pack. Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints Ø 10 – 108 (110) mm, Ø ⅜ – 4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Version	Art.-No.	KM
In sturdy steel case.	577010R220	**2.960,00**
In L-Boxx system case.	577013R220	**3.050,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Power-Press ACC Drive Unit	577000R220	**2.750,00**
REMS pressing tongs/pressing rings see page 198 – 238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
Steel case with insert	570280R	**223,00**
L-Boxx system case with inserts	571283R	**296,00**

REMS Power-Press XL ACC

Electro-hydraulic radial press XL 32 kN
with automatic retraction

Universal, powerful power tool with automatic circuit control for making press joints of all common press fitting systems.

Pipe pressing joints	Ø 10 – 108 (110) mm Ø ⅜ – 4"

Complete range of REMS pressing tongs/pressing rings/ pressing rings XL for all common pressfitting systems, see page 198 – 238.

REMS Power-Press XL ACC – universal up to Ø 110 mm. Pressing of Ø 10 – 108 mm in just one action. Ultra-fast, e.g. Geberit Mapress stainless steel Ø 108 mm in only 15 seconds. With automatic circuit control. Automatic locking of pressing tongs.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings/pressing rings XL for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/XL pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings/pressing rings XL are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs are required, as an accessory, for driving the REMS (PR) pressing rings.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.5 kg. Long working stroke for pressings in a single action, ideal for large dimensions. Ultra-fast, e.g. Geberit Mapress stainless steel Ø 108 mm in only 15 seconds. Ergonomically designed housing with soft grip and recessed handle. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/ pressing rings. Adjustable hand guard.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

German Quality Product

Info

Supply format

REMS Power-Press XL ACC Basic-Pack. Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints Ø 10 – 108 (110) mm, Ø ⅜ – 4". For driving REMS pressing tongs/pressing rings/pressing rings XL and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Version	Art.-No.	KM
In transport case XL.	579010R220	**4.830,00**
In XL-Boxx system case.	579012R220	**4.750,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Power-Press XL ACC drive Unit	579000R220	**4.240,00**
Adapter tongs Z6 XL for driving REMS pressing rings 64.0 – 108.0 XL (PR-3S), 2½ – 4" XL (PR-3S) with REMS Power-Press XL ACC	579120R	**756,00**
Adapter tongs for other REMS pressing rings see page 238.		
REMS pressing tongs/pressing rings/pressing rings XL see page 198 – 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
Transport case XL with inlays and practical carrying handles	579240R	**584,00**
XL-Boxx system case with inserts	579601R	**502,00**

All prices excl. VAT

REMS
REMS
REMS
XL

REMS Akku-Press E 22 V ACC

Cordless radial press 32 kN with automatic circuit control

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints	Ø 10 – 108 (110) mm Ø ⅜ – 4"

Complete range of REMS pressing tongs/ pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Akku-Press E 22 V ACC – universal up to Ø 110 mm. Secure crimping in seconds. With automatic circuit control. Anti-vibration system. Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah battery for approx. 200 pressings Viega Profipress DN 15 with one battery charge*.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, handy, super light. Drive unit with battery only 3.3 kg. Drive unit with pressing tongs V 15 only 35.5 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing and soft grips. LED work light for illuminating the work place. Machine status check. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking. Also for other suitable makes of pressing tongs/pressing rings.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 200 pressings, 4.4 Ah for approx. 350 pressings, 5.0 Ah for approx. 400 pressings, 9.0 Ah for approx. 720 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 70 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Two connections for REMS Eco-Press manual radial press and REMS 32 kN radial presses.

with automatic circuit control and charging status check

German Quality Product

Info

LED



The little one amongst the big. Only 3.3 kg.

REMS Akku-Press E 22 V ACC

Cordless radial press 32 kN with automatic circuit control

Supply format

REMS Akku-Press E 22 V ACC Basic-Pack. Cordless radial press 32 kN with automatic circuit control for making press joints Ø 10 – 108 (110) mm, Ø ⅜ – 4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Anti-vibration system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 100 – 240 V, 50 – 60 Hz, 70 W.

Version	Art.-No.	KM
In sturdy steel case.	576016 R220	**3.660,00**
In L-Boxx system case.	576017 R220	**3.740,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS pressing tongs/pressing rings see page 198 – 238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
REMS Akku-Press E 22 V ACC drive unit, without battery	576006 R22	**2.540,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567 R220	**838,00**
Steel case with inlay	571290 R	**223,00**
L-Boxx system case with inserts	576345 R	**296,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS Akku-Press 22 V ACC

Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display

Universal, handy electric tool with automatic circuit control, pressure monitoring and result display, for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints	Ø 10 – 108 (110) mm Ø ⅜ – 4"

Complete range of REMS pressing tongs/ pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Akku-Press 22 V ACC – universal up to Ø 110 mm. Secure crimping in seconds. With automatic circuit control, pressure monitoring and result display. Anti-vibration system. Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah battery for approx. 200 pressings Viega Profipress DN 15 with one battery charge*.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, handy, super light. Drive unit with battery only 3.3 kg. Drive unit with pressing tongs V 15 only 35.5 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing and soft grips. LED work light for illuminating the work place. Machine status check. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking. Also for other suitable makes of pressing tongs/pressing rings.

Pressure monitoring and result display

Electronic pressure sensor for thrust force monitoring. Pressure evaluation after the pressing process. Result display with 2-coloured white/red LED.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 200 pressings, 4.4 Ah for approx. 350 pressings, 5.0 Ah for approx. 400 pressings, 9.0 Ah for approx. 720 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

German Quality Product

Info

LED



The little one amongst the big. Only 3.3 kg.

REMS Akku-Press 22 V ACC

Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display

Supply format

REMS Akku-Press 22 V ACC Basic-Pack. Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display, for making press joints Ø 10 – 108 (110) mm, Ø ⅜ – 4". For driving REMS pressing tongs/ pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Anti-vibration system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 100 – 240 V, 50 – 60 Hz, 90 W.

Version	Art.-No.	KM
In sturdy steel case.	576010 R220	**4.290,00**
In L-Boxx system case.	576011 R220	**4.370,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS pressing tongs/pressing rings see page 198 – 238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
REMS Akku-Press 22 V ACC drive unit, without battery	576000 R22	**3.130,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567 R220	**838,00**
Steel case with inlay	571290 R	**223,00**
L-Boxx system case with inserts	576345 R	**296,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS Akku-Press 22 V Connected

Cordless radial press 32 kN with Connected functionality via Wi-Fi radio standard and OLED display

Universal, handy electric tool with Connected functionality via Wi-Fi radio standard and OLED display for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22 V Technology.
For battery and corded operation.

Pipe pressing joints	Ø 10 – 108 (110) mm Ø ⅜ – 4"

Complete range of REMS pressing tongs/ pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Akku-Press 22 V Connected – universal up to Ø 110 mm. Secure crimping in seconds. With selectable ACC drive mode. Connected functionality via Wi-Fi radio standard and OLED display. Pressure monitoring and result display. Anti-vibration system. Automatic locking of pressing tongs. Electrically monitored closing position of the tong retaining bolt. Voice recordings with voice recognition. Creating reports with texts and pictures. Geolocalisation of the pressing sites. Li-Ion 21.6 V, 2.5 Ah battery for approx. 200 pressings Viega Profipress DN 15 with one battery charge*.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, handy, super light. Drive unit with battery only 3.3 kg. Drive unit with pressing tongs V 15 only 36.3 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with strong carrying ring for a shoulder strap. Soft-grip surfaces. Two rows of LED work lights for illuminating the workplace as required, adjustable brightness in 4 stages and lighting time. Machine status check with charging state indication by 2-coloured green/red LED. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking. Electrically monitored closing position of the tong retaining bolt. Also for other suitable makes of pressing tongs/pressing rings.

Connected functionality

REMS Akku-Press 22 V Connected offers various additional functionalities such as, for example: Recording of measuring/pressing data, creation of reports with your own company logo, display of error messages, configuration of the product (language, date, time, time zone, pressure unit, LED lighting time and LED brightness, standby time, ACC drive mode, information signal tones, etc.), set-up of usage bars (immediate bar or feedback interval as anti-theft, time and date ranges for barring times, limitation of the number of performable pressings), geolocalisation of the pressing sites, conversion of voice recordings into editable text, upload and save images of pressings, display of notices (annual inspection and periodic testing, new firmware version, battery state, etc.), download and installation of new firmware version.

Pressure monitoring and result display

Electronic pressure sensor for thrust force monitoring. Monitoring and display of pressure and maximum pressure during the pressing process. Pressure analysis after the pressing process with result display in the OLED display and with coloured LEDs. Display of the pressure-time diagram of the performed pressing directly in the OLED display. Storage of the measured/pressing data.

Voice recordings with voice recognition

A voice recording can be made and stored for every pressing with the microphone integrated into the drive unit. These can be converted into editable text and transferred to reports in the Service Portal.



German Quality Product

REMS Akku-Press 22 V Connected

Cordless radial press 32 kN with Connected functionality via Wi-Fi radio standard and OLED display

Wi-Fi connection to the Cloud

REMS Akku-Press 22V Connected sends collected data (measuring and pressing data, error messages, configuration of the product, voice recordings, etc.) to the Cloud after registration and with an existing Internet connection. The data are processed and stored there. The user can access these data, upload and store pictures of pressings, create reports with texts and pictures and change the drive unit settings through the REMS Service Portal. The changes are transferred back to the drive unit via an existing Internet connection.

Selectable ACC drive mode

When ACC drive mode is switched on, the drive unit ends the pressing process automatically, emits an acoustic signal (clicking) and automatically returns (automatic circuit control). When ACC mode is switched off, the drive unit stops just before reaching the required pressure to be able to be able to monitor complete closing of the pressing tongs, pressing ring and pressing segments better at the end of the pressing process. The pressing process must be continued by pressing the safety switch again. The drive unit ends the pressing process automatically, emits an acoustic signal (clicking) and automatically returns (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. High-performance, electro-hydraulic drive with powerful, brushless, maintenance free 21.6 V, 400 W battery motor, robust planetary gear, eccentric piston pump and compact high-performance hydraulic system. Safety switch.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 210 pressings, 4.4 Ah for approx. 370 pressings, 5.0 Ah for approx. 420 pressings, 9.0 Ah for approx. 750 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.



The little one amongst the big. Only 3.3 kg.

Electrically monitored closing position of the tong retaining bolt.

Supply format

REMS Akku-Press 22 V Connected Basic-Pack. Cordless radial press 32 kN with selectable ACC drive mode, Connected functionality via Wi-Fi radio standard and OLED display, pressure monitoring and result display, for making press joints Ø 10 – 108 (110) mm, Ø ⅜ – 4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electrically monitored closing position of the tong retaining bolt. Electro-hydraulic drive with powerful, brushless, maintenance free 21.6 V, 400 W battery motor, robust planetary gear, eccentric piston pump and compact high-performance hydraulic system. Anti-vibration system. Safety tip switch. LED work lights. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 100 – 240 V, 50 – 60 Hz, 90 W.

Version	Art.-No.	KM
In sturdy steel case.	576014 R220	**6.390,00**
In L-Boxx system case.	576015 R220	**6.470,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS pressing tongs/pressing rings see page 198 – 238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
REMS Akku-Press 22 V Connected drive unit, without battery	576003 R22	**5.230,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567 R220	**838,00**
Steel case with inlay	571290 R	**223,00**
L-Boxx system case with inserts	576345 R	**296,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C. Wi-Fi disabled. LED work lights off.

REMS Akku-Press XL 45 kN 22 V ACC

Cordless radial press XL 45 kN
with automatic circuit control

Universal, powerful electric tool with automatic circuit control for producing XL pipe pressing joints for all common pressfitting systems. Thrust force 45 kN. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints XL	Ø 64 – 108 mm Ø 2½ – 4"

Complete range of REMS pressing rings XL for all common pressfitting systems, see page 198 – 238.

REMS Akku-Press XL 45 kN 22 V ACC – the powerful one with 45 kN thrust force. Pressing of Ø 64 – 108 mm in a single action. Anti-vibration system. Super fast, e.g. Geberit Mapress stainless steel Ø 108 mm in just 15 s. With automatic circuit control. Secure seating of adapter tongs by automatic locking.

Li-Ion 21.6 V, 5.0 Ah battery, for approx. 150 pressings Geberit Mapress stainless steel Ø 108.0 mm with one battery charge*.

Pressing rings XL for all common systems

Full range of REMS pressing rings XL for driving by REMS Akku-Press XL 45 kN 22 V ACC (page 198 – 238). Highly durable pressing rings XL made of tenacious, specially hardened special steel. Pressing contours of REMS pressing rings XL are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing.

Adapter tongs Z7 XL 45 kN

For driving REMS pressing rings XL by REMS Akku-Press XL 45 kN 22 V ACC adapter tongs Z7 XL 45 kN are required.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit with battery only 6.5 kg. Long working stroke for pressings in a single action. Super fast, e.g. Geberit Mapress stainless steel Ø 108 mm in just 15 s. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing and soft grips. LED work light for illuminating the work place. Machine status check. Swivelling pressing ring seat, rotation angle > 360 °. Secure seating of adapter tongs by automatic locking.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 45 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric dual-piston pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah batteries for approx. 130 pressings, 5.0 Ah batteries for approx. 150 pressings, 9.0 Ah for approx. 270 pressings Geberit Mapress stainless steel Ø 108.0 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

German Quality Product

Info

REMS Akku-Press XL 45 kN 22 V ACC

Cordless radial press XL 45 kN
with automatic circuit control

Supply format

REMS Akku-Press XL 45 kN 22 V ACC Basic-Pack Z7. Cordless radial press 45 kN with automatic circuit control for making press joints XL Ø 64 – 108 mm, Ø 2½ – 4". For driving REMS pressing rings XL. Swivelling pressing ring seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric dual-piston pump and compact high power hydraulic system. Anti-vibration system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 5.0 Ah, rapid charger 100 – 240 V, 50 – 60 Hz, 90 W. Adapter tongs Z7 XL 45 kN. In XL-Boxx system case.

	Art.-No.	KM
	579014 R220	**6.460,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Akku-Press XL 45 kN 22 V ACC drive unit, without battery	579001 R22	**4.180,00**
Adapter tongs Z7 XL 45 kN for driving REMS pressing rings 64.0 – 108.0 XL (PR-3S), 2½ – 4" XL (PR-3S), 2½ – 4" XL (PR-3B) with REMS Akku-Press XL 45 kN 22 V ACC	579123 R	**798,00**

REMS pressing rings XL see page 198 – 238		
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578 R220	**1.050,00**
XL-Boxx system case with inserts	579601 R	**502,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

for all common pressfitting systems

Select REMS pressing tongs/ REMS pressing rings yourself!

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the pressing tongs/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Driven by REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force or, if the system requires, by REMS Akku-Press XL 45 kN 22 V ACC with 45 kN thrust force, see the table below. Adapter tongs (page 238) required for driving REMS (PR) pressing rings. All pressing tongs marked with * have an optional connection for manual drive through the radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

REMS pressing tongs (PZ-2B)

REMS pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Most sold standard version. REMS ACz, Fz, RFz, RFlz, VMPz pressing tongs with teeth prevent formation of burr on the pressfitting **(Patent EP 2 027 971)**.

REMS pressing tongs (PZ-4G)

REMS pressing tongs (PZ-4G) with two pivoted, parallel aligned pressing segments for linear pressing of midsize dimensions.

REMS pressing tongs (PZ-S)

REMS pressing tongs (S) with one fixed and two pivoted pressing segments, for midsize dimensions. REMS VMPz pressing tongs with teeth prevent formation of burr on the pressfitting.

REMS pressing rings (PR-3S)

REMS pressing ring (PR-3S) with 3 pressing segments, 2 swivel guided, for large dimension complex pressings. Ideal pressing through radially controlled movement of pressing segments. Adapter tongs required, see page 238.

REMS pressing rings (PR-3B)

REMS pressing rings (PR-3B) with 3 pressing segments for high quality, large dimension pressings Optimum pressing by radially controlled movement of the pressing segments. Adapter tongs required, see page 238. REMS VAUFz, VFz, VMPz, VUSFz pressing rings with teeth prevent formation of burr on the pressfitting.

REMS pressing ring (PR-2B)

REMS pressing ring (PR-2B) with 2 pressing jaws, for secure engagement of the pressing jaws in tight spaces, for midsize dimensions. Adapter tongs required for driving the REMS (PR-2B) pressing rings, see page 238.

REMS pressing ring S (PR-2B)

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 238.

Traceability according to EN 1775:2007

REMS pressing tongs/pressing rings with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs or the suitable pressing ring have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.

Confirmation of suitability

See page 239.

Hold-Harmless and Indemnification Agreement

See page 240.

Two connections for REMS Eco-Press manual radial press and REMS 32 kN radial presses.

German Quality Product

REMS pressing tongs (PZ-2B)

REMS pressing tongs (PZ-4G)

REMS pressing tongs (PZ-S)

REMS pressing rings (PR-3S)

REMS pressing rings (PR-3B)

REMS pressing rings (PR-2B)

REMS pressing ring S (PR-2B), continuously swivellable

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

ACz



B



BMP



ECI



F



FTB



Fz



G



H



HA



HE

HEz

K



KI



M



MT

PF



RFIz



RFz



RN



SA

TH



THL



U



UP



US



V



VAU



VAUFz



VFz



VG



VIC



VMP



VMPz



VP



VR



Pressing tongs with teeth prevent formation of burr on the pressfitting. Patent EP 2 027 971



Example REMS pressing tongs M: "M" imprint on pressed fitting for traceability according to EN 1775:2007

VRX



VUS

VUSFz

VX



Yz



System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
	A			
Aalberts integrated piping systems VSH MultiPress	U 14*		570760	353,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Aalberts integrated piping systems VSH MultiPress Gas[2)]	U 16[2)]		570765	353,00
	U 20[2)]		570775	353,00
	U 25[2)]		570780	353,00
	TH 16[2)]		570460	377,00
	TH 20[2)]		570470	377,00
	TH 16 S (PR-2B)[2)]	Z8	574782 R	252,00
	TH 20 S (PR-2B)[2)]	Z8	574788 R	252,00
Aalberts integrated piping systems VSH SudoPress Carbon	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	XP 66,7 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579108 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579111 R	2.750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Aalberts integrated piping systems VSH SudoPress Copper	V 12		570107	313,00
	V 14		570112	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 16 S (PR-2B)	Z8	574802 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Aalberts integrated piping systems VSH SudoPress Copper Gas	V 12		570107	313,00
	V 14		570112	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 16 S (PR-2B)	Z8	574802 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Aalberts integrated piping systems VSH SuoPress Stainless	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	M 76,1 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579111 R	2.750,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Aalberts integrated piping systems VSH XPress Carbon	M 12		570100	313,00
	M 15		570110	313,00
	M 18[1)]		570120	313,00
	M 22		570130	313,00
	M 28[1)]		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 66,7 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579108 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Copper	M 12		570100	313,00
	M 15		570110	313,00
	M 18[1)]		570120	313,00
	M 22		570130	313,00
	M 28[1)]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 64,0 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579100 R	2.140,00
	XP 66,7 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579108 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579110 R	2.750,00
	XP 108,0 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579109 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Copper Gas	M 15		570110	313,00
	M 18[1)]		570120	313,00
	M 22		570130	313,00
	M 28[1)]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Stainless	M 15		570110	313,00
	M 18[1)]		570120	313,00
	M 22		570130	313,00
	M 28[1)]		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3)] / Z7 XL 45 kN[4)]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Aalberts integrated piping systems VSH XPress Stainless Gas	M 15		570110	313,00
	M 18[1)]		570120	313,00
	M 22		570130	313,00
	M 28[1)]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
AC-FIX PRESS (Global Piping Systems)	H 12*		570300	340,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	VX 16*		571635	435,00
	VX 20*		571640	435,00
AC-FIX PRESS DUO (Global Piping Systems)	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
ACOME MT	ACz 12*		572642	393,00
	ACz 16*		572644	393,00
	ACz 20*		572646	393,00
	ACz 25		572648	393,00
AHLSELL A-press elförzinkad M	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
AHLSELL A-press elförzinkad V	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
AHLSELL A-press koppar M	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
AHLSELL A-press koppar V	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
AHLSELL A-press rostfritt	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
AIRBEL PRESSCLIM	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
AIRBEL	M 15		570110	313,00
SERTINOX	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ALB	TH 16*		570460	377,00
Sistema Multicapa	TH 18*		570465	377,00
para calefacción y	TH 20*		570470	377,00
sanitario	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
ALB	TH 16*		570460	377,00
Sistema Multicapa	TH 20*		570470	377,00
para Gas	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
ALTECH Altech	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
APE MULTYGAS	TH 16*		570460	377,00
Serie AP Gas	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
APE Serie AP	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
APE Serie APL	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
AQUATECHNIK	H 16*		570320	340,00
Press-fitting metal	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
AQUATECHNIK	B 16*		570850	412,00
Universal	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
ARKA	H 16*		570320	340,00
DUROsystem	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
Aschl NIR	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

All prices excl. VAT

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
ASSOTHERM IPC-RAC Carbon Steel	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ASSOTHERM IPI-RAX Inox	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ASSOTHERM IPI-RAX Inox Gas	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ASSOTHERM IPM-Multistrato	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	THL 32		570487	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
ASSOTHERM IPR-RRA Copper	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ASSOTHERM IPR-RRA Copper Gas	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)	US ⅜"*		571450	429,00
	US ½"*		571455	429,00
	US ¾"*		571460	429,00
	US 1"*		571465	429,00
	US 1 ¼"		571470	429,00
	US 1 ½"		571475	429,00
	US 2"		571477	578,00
ATUSA ITALIA INSTALPRESS CARBON STEEL PRESS FITTINGS	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ATUSA ITALIA INSTALPRESS STAINLESS STEEL PRESS FITTINGS	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
AUSTEC PEX-B, PEX-AL-PEX (AUS)	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
AUSTEC PEX-AL-PEX GAS (AUS)	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
AYOR FIXOCONNECT Press	H 12*		570300	340,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
AYOR FIXOMULTIX	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
AYOR SOMATHERM FOR YOU -1	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	U 16*		570765	353,00
	U 20*		570775	353,00
AYOR SOMATHERM FOR YOU -2	H 12*		570300	340,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00

B

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Bampi BALPEX serie LP	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
Bampi BALPEX serie MP	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Bampi BALPEX Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
BARBI EASYPRESS (Industrial Blansol)	H 12*		570300	340,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
BARBI MULTIPEX (Industrial Blansol)	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
BEGETUBE/ IVAR	B 14*		570845	412,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
	Fz 75 (PR-3B)	Z4	572830 R	1.240,00
Béné inox Série 41	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Brass Form Master-Al-Pex	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
Brass & Fittings PRESSMAN MultiPress	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	ACz 20*		572646	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
Brass & Fittings PRESSMAN RetiPress	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	ACz 20*		572646	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
BRASSTECH	B 16*		570850	412,00
MULTItermoSAN	B 20*		570860	412,00
Brasspress	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00

C

Cello Products	VUS ½" (OD 15,9 mm)		571770	378,00
>B< Press	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
CGR	H 16*		570320	340,00
DYNAFLU	H 20*		570350	340,00
multicouche	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
CGR	H 12*		570300	340,00
DYNAFLU	H 16*		570320	340,00
PER	H 20*		570350	340,00
	H 25*		570360	340,00
	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
CHIALI	TH 16*		570460	377,00
CHIALIPEX	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
Climatrix	H 16*		570320	340,00
Climatrix Rhinopex	H 20*		570350	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Climatrix	TH 11,6*		570482	377,00
Variotherm	TH 16*		570460	377,00
System TH	TH 16 S (PR-2B)**	Z8	574782 R	252,00
ClouSet	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
Comap	RFz 12*		571320	393,00
PEX Press	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
Comap	TH 14*		570455	377,00
Multiskin	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	THL 32		570487	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Comap Multiskin Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	THL 32		570487	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
COMISA Press System	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	B 14*		570845	412,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
COMISA Press System Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
CONEL CONNECT INOX	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54 (PR-2B)	Z2	572851 R	706,00
CONEL CONNECT MULTI	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)**	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
(DN 26)	U 25*		570780	353,00
	U 32		570785	414,00
	VP 16*		570910	376,00
	VP 20*		570915	376,00
	VP 32		570925	416,00
CONEL CONNECT MV2	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)**	Z8	574734 R	277,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Z8	574798 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Conex Bänninger <A> Press Inox (304)	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Conex Bänninger <A> Press Inox (316L)	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Conex Bänninger >B< Flex	F 16*		570717	359,00
	F 18*		570720	359,00
	F 20*		570727	359,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
Conex Bänninger >B< Flex Gas	F 16*		570717	359,00
	F 18*		570720	359,00
	F 20*		570727	359,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
Conex Bänninger >B< MaxiPro	BMP ¼"		571700 R	374,00
	BMP ⅜"		571702 R	374,00
	BMP ½"		571704 R	374,00
	BMP ⅝"		571706 R	374,00
	BMP ¾"		571708 R	374,00
	BMP ⅞"		571710 R	374,00
	BMP 1"		571712 R	374,00
	BMP 1⅛"		571714 R	374,00

All prices excl. VAT

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Conex Bänninger >B< Press	V 12		570107	313,00
	V 14		570112	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 16 S (PR-2B)	Z8	574802 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
	M 15		570110	313,00
	M 22		570130	313,00
	M 28		570140	313,00
Conex Bänninger >B< Press XL copper	VFz 64,0 (PR-3B)	Z5	572815 R	1.240,00
	CBVFz 66,7 (PR-3B)	Z5	572847 R	1.240,00
	VFz 76,1 (PR-3B)[6]	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)[6]	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)[6]	Z5	572818 R	1.310,00
Conex Bänninger >B< Press carbon	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Conex Bänninger >B< Press XL carbon	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	CBM 88,9 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579144 R	2.750,00
	CBM 108,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579146 R	2.750,00
Conex Bänninger >B< Press Gas	V 12		570107	313,00
	V 14		570112	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 16 S (PR-2B)	Z8	574802 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Conex Bänninger >B< Press Inox	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Conex Bänninger >B< Press XL stainless	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	CBM 88,9 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579144 R	2.750,00
	CBM 108,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579146 R	2.750,00
Conex Bänninger >B< Press Solar	V 12		570107	313,00
	V 14		570112	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 16 S (PR-2B)	Z8	574802 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

D

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Debrunner Acifer d-a Presssystem C-Stahl	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
DUOPIPE SYSTEMS DUOFIL MKSYSTEM	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
DW Verbundrohr multitubo systems	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00

E

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
EBRILLE Isomonflex	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	H 26*		570370	340,00
	TH 26*		570475	377,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	U 32		570785	414,00
EBRILLE Monflex	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	H 26*		570370	340,00
	TH 26*		570475	377,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	U 32		570785	414,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
EFFEBI	M 15		570110	313,00
EFFEBI-PRESS	M 18		570120	313,00
Aisi316	M 22		570130	313,00
System M Profile[1]	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[8]	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
EFFEBI	V 12		570107	313,00
EFFEBI-PRESS	V 15		570115	313,00
Aisi316	V 18		570125	313,00
System V Profile	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
EFFEBI	M 12		570100	313,00
EFFEBI-PRESS	M 15		570110	313,00
Carbon-S	M 18		570120	313,00
System M Profile[1]	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
EFFEBI	V 12		570107	313,00
EFFEBI-PRESS	V 15		570115	313,00
Carbon-S	V 18		570125	313,00
System V Profile	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
EFFEBI	V 12		570107	313,00
EFFEBI-PRESS	V 14		570112	313,00
COPPER	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 16 S (PR-2B)	Z8	574802 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
EFFEBI	V 12		570107	313,00
EFFEBI-PRESS	V 15		570115	313,00
UNICO	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
EFFEBI	V 12		570107	313,00
EFFEBI-PRESS	V 15		570115	313,00
UNICO	V 18		570125	313,00
(GAS)	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
EFFEBI	M 15		570110	313,00
PRESSTIGE	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
EFFEBI	M 15		570110	313,00
PRESSTIGE 4E05	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
EFFEBI	M 15		570110	313,00
PRESSTIGE-GAS	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
EFFEBI	TH 16*		570460	377,00
TOF-GAS	TH 20*		570470	377,00
MULTIPINZA	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00

All prices excl. VAT

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
EFFEBI	TH 16*		570460	377,00
TOF	TH 18*		570465	377,00
MULTIPINZA	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	F 16*		570717	359,00
	F 18*		570720	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
EFIELD MULTILAYER PRESS DINGAS	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
EFIELD MULTILAYER PRESS WATER	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
Elkhart APOLLOXPRESS Fittings Copper and Low-Lead Brass	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
Elkhart APOLLOXPRESS LD-C Fittings Copper	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
EMMETI GERPEX-FIVPRESS	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	U 16*		570765	353,00
	U 20*		570775	353,00
EMPUR	TH 14*		570455	377,00
	TH 15*		570457	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 15 S (PR-2B)**	Z8	574780 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
Esta Rohr simplesta SH M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[8]	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Esta Rohr simplesta ST M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[8]	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
EUROTUBI EUROPA C-Steel Pressfitting System M-Profile[11]	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
EUROTUBI	M 15		570110	313,00
EUROPA	M 18		570120	313,00
Inox Pressfitting	M 22		570130	313,00
System M-Profile[1]	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Evans	VAU 15 (½") (OD 12,7 mm)		572687	324,00
Components	VAU 20 (¾") (OD 19,1 mm)		572689	324,00
Presslok	VAU 25 (1") (OD 25,4 mm)		572691	324,00
	ECI 1½"		571932	405,00
	ECI 2" (PZ-4G)		571934	1.010,00
	ECI 2½" XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579104 R	2.140,00
	ECI 3" XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579105 R	2.350,00
	ECI 4" XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579106 R	2.750,00

F

FAR Rubinetterie	TH 14*		570455	377,00
PRESSFAR	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
F.B.Q. BARONIO	V 12		570107	313,00
BQ PRESS SOLAR	V 14		570112	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
F.B.Q. BARONIO	V 12		570107	313,00
BQ PRESS WATER	V 14		570112	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
F.B.Q. BARONIO	V 12		570107	313,00
BQ PRESS GAS	V 14		570112	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 14 S (PR-2B)	Z8	574800 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
FERCOFLOOR	RFz 16*		571325	393,00
DUO Press	RFz 20*		571330	393,00
FERCO PEX	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
FERCOFLOOR	RFz 16*		571325	393,00
DUO Press	RFz 20*		571330	393,00
MULTIFER	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
FERRO systems	TH 16*		570460	377,00
BRASELI	TH 20*		570470	377,00
GPF GAS	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
FERRO systems	U 16*		570765	353,00
BRASELI	U 18*		570770	353,00
GPF MULT	U 20*		570775	353,00
Pressfitting	U 25*		570780	353,00
MULTICAPA	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
FERRO systems	U 16*		570765	353,00
BRASELI	U 18*		570770	353,00
GPF PPSU	U 20*		570775	353,00
Pressfitting	U 25*		570780	353,00
PEX y MULTICAPA	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
FERRO systems	RFz 16*		571325	393,00
BRASELI	RFz 20*		571330	393,00
GPF PRESS	RFz 25		571335	393,00
Pressfitting PEX	RFz 32		571340	393,00
FILINOX	FTB 15		571432	454,00
Filpress	FTB 18		571434	454,00
	FTB 22		571436	454,00
	FTB 28		571438	454,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN[4]	579111 R	2.750,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
FILINOX Instalpress Steel	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FILINOX Instalpress Inox	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FITTINGS ESTÁNDAR ECO-PRESS	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
FITTINGS ESTÁNDAR MULTICAPA	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
FITTINGS ESTÁNDAR PE-X	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
FORNARA ForPress	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
FORZA WATER CRIMP (AUS)	K16/P18*		572600	393,00
	K/20*		572605	393,00
	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
FORZA STAINLESS WATER CRIMP	K16/P18*		572600	393,00
	K/20*		572605	393,00
FORZA STESSO PEX WATER AND GAS CRIMP (AUS)	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
FORZA GAS CRIMP (AUS)	K16/P18*		572600	393,00
	K/20*		572605	393,00
	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
FORZA COPPER V PRESS (AUS)	VAU 15 (OD 12,7 mm)		572687	324,00
	VAU 20 (OD 19,1 mm)		572689	324,00
	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
	VAUFz 65 (PR-3B) (OD 63,5 mm)	Z5	572839 R	1.240,00
	VAUFz 80 (PR-3B) (OD 76,2 mm)	Z5	572840 R	1.240,00
	VAUFz 100 (PR-3B) (OD 101,6 mm)	Z5	572841 R	1.310,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Z8	574808 R	277,00
FORZA STAINLESS V PRESS (AUS)	V 15		570115	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
FRABO FRABOPRESS 316 GAS M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z!	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FRABO FRABOPRESS 316 GAS V	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
FRABO FRABOPRESS 316 M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FRABO FRABOPRESS 316 V	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
FRABO FRABOPRESS CHROME	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
FRABO FRABOPRESS C-STEEL M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FRABO FRABOPRESS C-STEEL V	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
FRABO FRABOPRESS GAS M	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FRABO FRABOPRESS GAS V	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
FRABO FRABOPRESS KOMBI	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
FRABO FRABOPRESS M	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
FRABO FRABOPRESS SOLAR	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
FRABO FRABOPRESS V	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Fränkische alpex-duo XS	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)**	Z8	574734 R	277,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Z8	574798 R	277,00
Fränkische alpex F50 PROFI	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)**	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
(DN 26)	U 25*		570780	353,00
	U 32		570785	414,00
	VP 16*		570910	376,00
	VP 20*		570915	376,00
	VP 32		570925	416,00

All prices excl. VAT

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Fränkische alpex L	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
	Fz 75 (PR-3B)	Z4	572830 R	1.240,00
	G			
gabotherm H+S	TH 10*		570467	377,00
	TH 12*		570452	377,00
	TH 14*		570455	377,00
	TH 15*		570457	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 10 S (PR-2B)**	Z8	574772 R	252,00
	TH 12 S (PR-2B)**	Z8	574776 R	252,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 15 S (PR-2B)**	Z8	574780 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Gallagher USA YogaPipe ACR	H 12* (¼")		570300	340,00
	U 14* (⅜")		570760	353,00
	U 16* (½")		570765	353,00
	U 18* (⅝")		570770	353,00
	U 20* (¾")		570775	353,00
	U 25* (⅞")		570780	353,00
	U 32 (1⅛")		570785	414,00
Geberit Mapress C-STAHL	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Geberit Mapress C-STAHL Sprinkler nass	M 22		570130	313,00
	M 28		570140	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
Geberit Mapress Edelstahl	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Geberit Mapress Edelstahl Gas	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Geberit Mapress Edelstahl Sprinkler	M 22		570130	313,00
	M 28		570140	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
Geberit Mapress Kupfer	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Geberit Mapress Kupfer Gas	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Geberit Mepla	G 16*		570400	378,00
	G 20*		570410	378,00
	G 26*		570420	401,00
	G 32		570430	429,00
	G 40		570440	555,00
	G 50		570450	580,00
	G 63 (PZ-S)		572470	1.640,00
Geberit Mepla Therm	G 16*		570400	378,00
	G 20*		570410	378,00
	G 26*		570420	401,00
Geberit Volex	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
General Fittings 5T00	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
General Fittings Ewoprex	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
General Fittings Serie 5S00	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
General Fittings Trident	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
General Fittings Trident Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
Giacomini Raccordi RM Giacomini	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
Giacomini RM MULTIGAS	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
Giacomini Valvole Giacomini serie R850V	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Golan Pipe Systems (Scandinavia) Alu-Pres	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
Grinnell G-PRESS Copper Fittings	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00

All prices excl. VAT

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
GS	TH 14*		570455	377,00
Wärmesysteme	TH 16*		570460	377,00
System TH	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
GS	V 15		570115	313,00
Wärmesysteme	V 18		570125	313,00
System V	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
H				
HASTINIK	M 15		570110	313,00
Hastinik/Hitpress	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
heima24	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
HELIROMA	U 16*		570765	353,00
Klimapress	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
HELIROMA	U 16*		570765	353,00
Klimapress PPSU	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
Henco	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	HE 32		571900	452,00
	HEz 40		571904	655,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Herotec	H 16*		570320	340,00
tempusPRESS	H 20*		570350	340,00
PLUS	H 25*		570360	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
Herotec	H 16*		570320	340,00
tempusPRESS	H 20*		570350	340,00
PLUS PPSU	H 25*		570360	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
HERZ PIPEFIX	TH 10*		570467	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 10 S (PR-2B)**	Z8	574772 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)**	Z8	574798 R	277,00
HIDRONIX	TH 16*		570460	377,00
MULTIGAS	TH 20*		570470	377,00
	TH 26*		570475	377,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
HIDRONIX MULTIPIPE	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
HIDRONIX UNICO	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
HITEC Sistema Multistrato	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
HITHERM-ISOTUBI NUMEPRESS	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
HITHERM HTpress	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
HITHERM HTfire	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
HITHERM HTair	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Hopewell press fit system	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
hp praski BAVARIA-press	TH 10*		570467	377,00
	TH 12*		570452	377,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 10 S (PR-2B)**	Z8	574772 R	252,00
	TH 12 S (PR-2B)**	Z8	574776 R	252,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
ICMA Sempiter	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
ICMA Sempigas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Idrosanitaria Bonomi Homegas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
Idrosanitaria Bonomi Idropress	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
IDROSISTEMI Ta-Press	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
IDROTRADE Storm Multipinza	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	THL 32		570487	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
IDROTRADE StormPRES [1]	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S) [8]	Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S) [8]	Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S) [8]	Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
IDROTRADE StormSTEEL [1]	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S) [8]	Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S) [8]	Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S) [8]	Z7 XL 45 kN [4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ILTA INOX/CHIBRO Pressfitting Cuni	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
ILTA INOX/CHIBRO Pressfitting inox	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Instantor Press System	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Instantor Copper Press Imperial	VI ½" S (PR-2B)	Z8	574850 R	252,00
	VI ¾" S (PR-2B)	Z8	574852 R	252,00
	VI 1" S (PR-2B)	Z8	574854 R	252,00
Instantor Copper Press Metric	M 15		570110	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
IPA IPANA Press	TH 10*		570467	377,00
	TH 11,6*		570482	377,00
	TH 12*		570452	377,00
	TH 14*		570455	377,00
	TH 15*		570457	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 22*		570472	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 28		570477	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 10 S (PR-2B)**	Z8	574772 R	252,00
	TH 11,6 S (PR-2B)**	Z8	574774 R	252,00
	TH 12 S (PR-2B)**	Z8	574776 R	252,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 15 S (PR-2B)**	Z8	574780 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 22 S (PR-2B)**	Z8	574790 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 28 S (PR-2B)**	Z8	574796 R	277,00
	TH 32 S (PR-2B)**	Z8	574798 R	277,00
IPA THu IPANA Press	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
IPALPEX (Industrie du Plastique et Accessoires)	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	THL 32		570487	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	K16/P18*		572600	393,00
	PF 22*		571980	424,00
IPLEX PIPELINES AUSTRALIA Iplex K1 (Gas)	K16/P18*		572600	393,00
	K/20*		572605	393,00
	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
IPLEX PIPELINES AUSTRALIA Iplex K2	K16/P18*		572600	393,00
	K/20*		572605	393,00
	K/25*		572610	393,00
ISOLTUBEX ISOLPEX IPERT	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFIz 25		571337	433,00
	RFIz 32		571342	433,00
ISOLTUBEX Multicapa	RFz 16*		571325	393,00
	RFz 18*		571327	393,00
	RFz 20*		571330	393,00
	RFIz 25		571337	433,00
	RFIz 32		571342	433,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
ISOLTUBEX Multicapa GAS	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFIz 25		571337	433,00
	RFIz 32		571342	433,00
ISOLTUBEX Multicapa-PPSU	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
ISOTUBI NUMEPRESS	M 15		570110	313,00
	M 18[1]		570120	313,00
	M 22		570130	313,00
	M 28[1]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
IVAR ALPEX-GAS	B 20		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
IVAR Ivar-Press	B 14*		570845	412,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
IVAR MULTI PRESS GAS ITALIA	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
IVAR Multi Press MP	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	F 16*		570717	359,00
	F 18*		570720	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
IVAR Multi Press Leak (MPL)	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00

All prices excl. VAT

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
IVAR Plastic Multi Press Leak (PMPL)	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
IVAR Plastic Multi Press PMP	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
IVT Edelstahl-Presssystem	M 15		570110	313,00
	M 18 [1]		570120	313,00
	M 22		570130	313,00
	M 28 [1]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
IVT PRIPRESS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

J

Jäger - Aquatec Aquapress H	H 14*		570310	340,00
	H 16*		570320	340,00
	H 17*		570330	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
Jäger - Aquatec C-Stahl - Press Typ M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Jäger - Aquatec Edelstahl - Press Typ M	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Jäger - Aquatec Kupfer - Press Typ V	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Jansen AG	TH 14*		570455	377,00
JANSEN COMISA	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Jaraflex-Presssystem	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
JUNGWOO	VUS ½" (OD 15,9 mm)		571770	378,00
JWPress	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00
K				
KAN	U 14*		570760	353,00
KAN-therm Press LBP	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
KAN	M 15		570110	313,00
KAN-therm Inox	M 18 [1]		570120	313,00
	M 22		570130	313,00
	M 28 [1]		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
KAN	M 12		570100	313,00
KAN-therm Steel	M 15		570110	313,00
	M 18 [1]		570120	313,00
	M 22		570130	313,00
	M 28 [1]		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 66,7 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579108 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
KAN	U 14*		570760	353,00
KAN-therm	U 16*		570765	353,00
UltraPRESS	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
KE KELIT	M 15		570110	313,00
COPPERFIX	M 18		570120	313,00
Kupfer	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
KE KELIT	U 16*		570765	353,00
KELIT KELOX	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
KE KELIT	U 16*		570765	353,00
KELOX-PPSU-W	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
KE KELIT	U 16*		570765	353,00
KELOX-ULTRAX	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
KE KELIT	U 16*		570765	353,00
KELOX-ULTRAX-W	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
KE KELIT	U 16*		570765	353,00
KELOX-WINDOX-U	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
KE KELIT	M 15		570110	313,00
steelFIX	M 18		570120	313,00
C-Stahl	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL [3] / Z7 XL 45 kN [4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
KE KELIT steelFIX Edelstahl	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
KEMBLA KemPress (AUS)	VAU 15 (OD 12,7 mm)		572687	324,00
	VAU 20 (OD 19,1 mm)		572689	324,00
	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
KEMBLA KemPress Gas (AUS)	VAU 15 (OD 12,7 mm)		572687	324,00
	VAU 20 (OD 19,1 mm)		572689	324,00
	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
KISAN Kisan KD	KI 16*		571360	399,00
	KI 20*		571370	399,00
	KI 25*		571375	399,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
KISAN Kisan WL	KI 16*		571360	399,00
	KI 20*		571370	399,00
	KI 25*		571375	399,00
	KI 32		571380	538,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
KISAN Kisan WM	KI 16*		571360	399,00
	KI 20*		571370	399,00
	KI 25*		571375	399,00
	KI 32		571380	538,00
KISAN Kisan WR	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)		572828 R	1.310,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
KISAN Kistal C	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
KISAN Kistal Inox	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	L			
LEGEND-PRESS press fitting system	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00
LK Systems LK >B<Press	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
LK Systems LK >B<Press Elförzinkat	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
LK Systems	V 15		570115	313,00
LK >B<Press	V 18		570125	313,00
Gas	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 54		570175	750,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
LK Systems	TH 16*		570460	377,00
LK Universal	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	M			
MAINCOR	U 16*		570765	353,00
MAINPRESS	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
MAINCOR	U 16*		570765	353,00
MAINFLOR	U 20*		570775	353,00
Mair Heiztechnik	H 11,5*		570315	340,00
M-Press	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Ma.s.ter System	TH 14*		570455	377,00
PRESSMASTER	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
Meier Tobler	H 16*		570320	340,00
Metalplast - Stramax	H 20*		570350	340,00
Serie MM	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
METALGRUP	U 16*		570765	353,00
Permatubo	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
METALGRUP	RFz 16*		571325	393,00
PexGrup	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
METALGRUP	U 16*		570765	353,00
MultiGrup	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
Mueller Streamline	VUS ½" (OD 15,9 mm)		571770	378,00
PRS Copper Press	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00
MULTITHERM	TH 16*		570460	377,00
PRESSSYSTEM	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Multicapas Industrial	RFz 16*		571325	393,00
AIS PEX	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
Multicapas Industrial	H 16*		570320	340,00
AIS XPRT	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
Multicapas Industrial	U 16*		570765	353,00
multitubo systems MC	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Multicapas Industrial multitubo systems MM	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
multipipe Deutschland multipipe mp	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

N

NEUTHERM MEKUPRESS-HT	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 40		570790	504,00
NIBCO Press System Copper	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
NICOLL FLUXO	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
NUPI Industrie Italiane Multinupi	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 18*		570720	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
Nussbaum Optifitt-Press	VMP ⅜" (OD 17,2 mm)		571740	435,00
	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Nussbaum Optiflex-Flowpress	VRX 16		571750	397,00
	VRX 20		571752	397,00
	VRX 25		571754	435,00
	VRX 32		571756	435,00
	VRX 40		571758	605,00
	VRX 50		571760	706,00
	VRX 63		571797	1.140,00
Nussbaum Optipress Aquaplus	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)	Z5	572815 R	1.240,00
	VFz 76,1 (PR-3B)	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)	Z5	572818 R	1.310,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Nussbaum Optipress-Gaz	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)	Z5	572815 R	1.240,00
	VFz 76,1 (PR-3B)	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)	Z5	572818 R	1.310,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Nussbaum Optipress-Therm	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)	Z5	572815 R	1.240,00
	VFz 76,1 (PR-3B)	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)	Z5	572818 R	1.310,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
O				
Oventrop Cofit P	H 16 A*		570620	435,00
	H 20 A*		570650	435,00
	H 26 A*		570670	435,00
	H 32 A		570680	435,00
	H 40 A		570690	756,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
Oventrop Cofit PD	H 16 A*		570620	435,00
	H 20 A*		570650	435,00
	H 26 A*		570670	435,00
Oventrop Cofit PDK	H 16 A*		570620	435,00
	H 20 A*		570650	435,00
Oventrop Cofit PD-HT	H 16 A*		570620	435,00
	H 20 A*		570650	435,00
	H 25 A*		570660	435,00
	H 32 A		570680	435,00
Oventrop Cofit PDK-HT	H 16 A*		570620	435,00
	H 20 A*		570650	435,00
P				
PBTub SERTIPRESS	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
PBTub SERTI-STEEL	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Pegler Yorkshire	> Aalberts integrated piping systems			
PERFEXIM PERFEKT SYSTEM	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
PERFEXIM PERFEKT SYSTEM PLUS	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
PERFILTUBO PERFILALUPEX	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
PERFILTUBO PERFILPRESS	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
PEXTUBE PexTube	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFIz 25		571337	433,00
	RFIz 32		571342	433,00
Pipelife C-PRESS	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Pipelife RADOPRESS	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Pipetec Connect	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
PLASTICA ALFA Multypex	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
PLASTICA ALFA Multypex Air	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
PLASTICA ALFA Multypexalfa Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
PLASTICA ALFA Multypexalfa Gas protek	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
PLASTICA ALFA Multypex Plus	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
PLASTICA ALFA	TH 16*		570460	377,00
Multypex Thermo	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
PLASTICA ALFA	TH 16*		570460	377,00
Multypex Thermo Plus	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
PLÁSTICOS FERRO	U 16*		570765	353,00
FERROPLAST	U 20*		570775	353,00
GPF MULT Pressfitting	U 25*		570780	353,00
MULTICAPA	U 32		570785	414,00
PLÁSTICOS FERRO	U 16*		570765	353,00
FERROPLAST	U 20*		570775	353,00
GPF PPSU	U 25*		570780	353,00
Pressfitting PEX	U 32		570785	414,00
y MULTICAPA				
PLÁSTICOS FERRO	RFz 16*		571325	393,00
FERROPLAST	RFz 20*		571330	393,00
GPF PRESS	RFz 25		571335	393,00
Pressfitting PEX	RFz 32		571340	393,00
PLUMBING PLUS	K16/P18*		572600	393,00
EZIPEX Crimp	K/20*		572605	393,00
(AUS)	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
PLUMBING PLUS	K16/P18*		572600	393,00
EZIPEX Gas	K/20*		572605	393,00
(AUS)	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		572687	324,00
EZIPRESS Gas	VAU 20 (OD 19,1 mm)		572689	324,00
(AUS)	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
	VAUFz 65 (PR-3B) (OD 63,5 mm)	Z5	572839 R	1.240,00
	VAUFz 80 (PR-3B) (OD 76,2 mm)	Z5	572840 R	1.240,00
	VAUFz 100 (PR-3B) (OD 101,6 mm)	Z5	572841 R	1.310,00
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		572687	324,00
EZIPRESS Solar	VAU 20 (OD 19,1 mm)		572689	324,00
(AUS)	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Z8	574808 R	277,00
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		572687	324,00
EZIPRESS Water	VAU 20 (OD 19,1 mm)		572689	324,00
(AUS)	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
	VAUFz 65 (PR-3B) (OD 63,5 mm)	Z5	572839 R	1.240,00
	VAUFz 80 (PR-3B) (OD 76,2 mm)	Z5	572840 R	1.240,00
	VAUFz 100 (PR-3B) (OD 101,6 mm)	Z5	572841 R	1.310,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Z8	574804 R	252,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Z8	574806 R	252,00
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Z8	574808 R	277,00
POLYPIPE	TH 10*		570467	377,00
POLYSURE	TH 15*		570457	377,00
	TH 22*		570472	377,00
	TH 28		570477	377,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
POLYSAN	M 15		570110	313,00
Handelsges.	M 18		570120	313,00
m.b.H. & Co KG	M 22		570130	313,00
(Krems/Öster-	M 28		570140	313,00
reich)	M 35		570150	313,00
POLYSAN-	M 42 (PR-3S)	Z2	572706 R	1.370,00
C-Stahl-Press-	M 54 (PR-3S)	Z2	572708 R	1.370,00
System M	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
POLYSAN	M 15		570110	313,00
Handelsges.	M 18		570120	313,00
m.b.H. & Co KG	M 22		570130	313,00
(Krems/Öster-	M 28		570140	313,00
reich)	M 35		570150	313,00
POLYSAN-	M 42 (PR-3S)	Z2	572706 R	1.370,00
Edelstahl	M 54 (PR-3S)	Z2	572708 R	1.370,00
Press-System 1.4520	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
POLYSAN	M 15		570110	313,00
Handelsges.	M 18		570120	313,00
m.b.H. & Co KG	M 22		570130	313,00
(Krems/Öster-	M 28		570140	313,00
reich)	M 35		570150	313,00
POLYSAN-	M 42 (PR-3S)	Z2	572706 R	1.370,00
Edelstahl	M 54 (PR-3S)	Z2	572708 R	1.370,00
Press-System Gas	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
POLYSAN	M 15		570110	313,00
Handelsges.	M 18		570120	313,00
m.b.H. & Co KG	M 22		570130	313,00
(Krems/Öster-	M 28		570140	313,00
reich)	M 35		570150	313,00
POLYSAN-	M 42 (PR-3S)	Z2	572706 R	1.370,00
Edelstahl	M 54 (PR-3S)	Z2	572708 R	1.370,00
Press-System Wasser	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
POLYSAN	TH 14*		570455	377,00
Handelsges.	TH 16*		570460	377,00
m.b.H. & Co KG	TH 17*		570462	377,00
(Krems/Öster-	TH 18*		570465	377,00
reich)	TH 20*		570470	377,00
POLYSAN-	TH 26*		570475	377,00
Press-System	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Österreich) POLYSAN-Henco-Press-System	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	HE 32		571900	452,00
	HEz 40		571904	655,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
POLYSAN (España) „Rainbow"	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
Prandelli Multyrama Pf	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
Prandelli Multyrama Pfm	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
PURMO Cleverfit Radial	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	VP 16*		570910	376,00
	VP 20*		570915	376,00
	VP 25		570920	376,00

R

Raccorderie Metalliche aesPRES[1)]	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Raccorderie Metalliche inoxPRES[1)]	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Raccorderie Metalliche MARINEPRES[1)]	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Raccorderie Metalliche steelPRES[1)]	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[8)]	Z7 XL 45 kN[4)]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
RBM Tita-fix	B 14*		570845	412,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	F 16*		570717	359,00
	F 18*		570720	359,00
	F 20*		570727	359,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
RBM Tita-gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Redi Nicoll Fluxo	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Redi Nicoll Fluxo Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
RIFENG U PRESS FITTING (F5)	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
RIFENG TH PRESS FITTING (F9)	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
RIQUIER A SERTIR	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
RIQUIER Système multicouche	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
Roth PressCheck	RN 14*		572672	353,00
	RN 16		572670	353,00
	RN 17*		572674	353,00
	RN 20*		572676	353,00
	RN 25/26		572678	353,00
	RN 32		572680	414,00
	RN 40 (PR-3S)	Z2	572714 R	1.370,00
	RN 50 (PR-3S)	Z2	572716 R	1.370,00
	RNz 63 (PR-3B)	Z4	572836 R	1.490,00
Rubinetterie Bresciane Bonomi TURBO CuNi	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO INOX	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Rubinetterie Bresciane Bonomi TURBO INOX GAS	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO STEEL	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Rubinetterie Bresciane Bonomi TURBO PRESS	B 14*		570845	412,00
	B 16*		570850	412,00
	B 18*		570855	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	H 14*		570310	340,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 14*		570760	353,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
Rubinetterie Bresciane Bonomi TURBO PRESS GAS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
	S			
SA.MI PLASTIC	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
SA.MI PLASTIC Multistrato Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
SANHA 3fit-Press Pb-free Serie 25000	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	Fz 40		570742	416,00
	Fz 50		570747	630,00
	F 63 (PZ-S)		572385	1.310,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
SANHA 3fit-Press PPSU Serie 35000	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
SANHA Heavy Steel Press	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
SANHA Heavy Steel Press Gas[9]	VMP ½" G (OD 21,3 mm)[11]		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-NiroSan Gas Presssystem Serie 17000	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)[7]	Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA-NiroSan Industry Presssystem Serie 18000	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA-NiroSan-Presssystem Serie 9000	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-NiroSan	SA 15		570935	376,00
SF Presssystem	SA 18		570940	376,00
Serie 19000	SA 22		570945	376,00
(silicone free)	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA	SA 15		570935	376,00
NiroTherm	SA 18		570940	376,00
Serie 91000	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA	SA 15		570935	376,00
NiroTherm	SA 18		570940	376,00
Industry	SA 22		570945	376,00
Serie 98000	SA 28		570950	376,00
	SA 35		570955	376,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA-Press	SA 12		570930	546,00
Chrom	SA 15		570935	376,00
Serie 16000	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-Press GAS Pressfittings Serie 10000/ Serie 11000	SA 12		570930	546,00
	SA 14		570932	546,00
	SA 15		570935	376,00
	SA 16		570937	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 12		570107	313,00
	V 14		570112	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA-Press Pressfittings Serie 6000	SA 12		570930	546,00
	SA 14		570932	546,00
	SA 15		570935	376,00
	SA 16		570937	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 12		570107	313,00
	V 14		570112	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-Press SOLAR Pressfittings Serie 12000/ Serie 13000	SA 12		570930	546,00
	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA PURAPRESS Serie 8000	SA 12		570930	546,00
	SA 14		570932	546,00
	SA 15		570935	376,00
	SA 16		570937	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 12		570100	313,00
	M 15[1]		570110	313,00
	M 18[1]		570120	313,00
	M 22[1]		570130	313,00
	M 28[1]		570140	313,00
	M 35[1]		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 64,0 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579100 R	2.140,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 12		570107	313,00
	V 14		570112	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	V 16		570117	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

All prices excl. VAT

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANHA-Therm Serie 24000	SA 12		570930	546,00
	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
SANHA-Therm Industry Serie 28000	SA 12		570930	546,00
	SA 15		570935	376,00
	SA 18		570940	376,00
	SA 22		570945	376,00
	SA 28		570950	376,00
	SA 35		570955	376,00
	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	XP 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579108 R	2.350,00
	M 66,7 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579107 R	2.350,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SANITOP PERMATUBO INOX	M 15		570110	313,00
	M 18[1]		570120	313,00
	M 22		570130	313,00
	M 28[1]		570140	313,00
	M 35		570150	313,00
	M 35 (PR-3S)	Z2	572727 R	1.370,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
SANPRO THPRESS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
SATEC SK VITerm	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
SAVEUR REFLEX PEX Water	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
SAVEUR REFLEX PEX-AL-PEX Gas	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
Schütz duo-flex tri-o-flex	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
Schwer Fittings AQUApress	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Seppelfricke	> Aalberts integrated piping systems			
SESTA SESTA GAS	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

[1] Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

[2] For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

[3] Driven by REMS Power-Press XL ACC, see page 188.

[4] Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

[5] For taking suitable pressing inserts.

[6] Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

[7] Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

[8] For making press joints for operating pressure ≤ PN 10.

[9] For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

[10] For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

[11] Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

[12] Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
SESTA	H 16*		570320	340,00
Sistema	H 20*		570350	340,00
multistrato	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	U 16*		570765	353,00
	U 20*		570775	353,00
SIGMA LI	TH 16*		570460	377,00
Premium	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
SLOVARM	U 16*		570765	353,00
PEX-THERM	U 20*		570775	353,00
	H 26*		570370	340,00
	U 32		570785	414,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
STANDARD	H 16*		570320	340,00
HIDRAULICA	H 20*		570350	340,00
MultiStandard	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
steeltrade	M 15		570110	313,00
Presssystem	M 18[1]		570120	313,00
Edelstahl	M 22		570130	313,00
Kontur M	M 28[1]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
STELBI	H 16*		570320	340,00
Polikraft	H 20*		570350	340,00
	H 26*		570370	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26*[12]		570750	414,00
STELBI	TH 16*		570460	377,00
Stelgas	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
STH Westco	M 15		570110	313,00
COPPER PRESS	M 22		570130	313,00
	M 28[1]		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00

T

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
TDM BRASS	H 16*		570320	340,00
Serie 1600	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	THL 32		570487	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
TDM BRASS	H 16*		570320	340,00
Serie 2600	H 18*		570340	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	THL 32		570487	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26*[12]		570750	414,00
	U 32		570785	414,00
TDM BRASS	TH 16*		570460	377,00
Serie 1700 gas	TH 20*		570470	377,00
	TH 26*		570475	377,00
	THL 32		570487	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
TermoConcept	Basic E01[5]		571855	618,00
TC-PRESS				
THERMOLUTZ	H 14*		570310	340,00
	H 16*		570320	340,00
	TH 20*		570470	377,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
TE-SA	TH 14*		570455	377,00
TE-SA press	TH 16*		570460	377,00
serie 800	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
THERMACOME	H 16*		570320	340,00
ACOPEX ALU	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00

All prices excl. VAT

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
TIEMME 1650 AL-COBRAPEX	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	THL 32		570487	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 14 S (PR-2B)**	Z8	574778 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
TIEMME 1700 COBRAPEX	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
TIEMME 1650 AL-COBRAPEX GAS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	THL 32		570487	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
TIGRE ALPEX GÁS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
TKM Systemtechnik	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
TRA Multi TRA+	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
TRA MULTITRAPRESS	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
TRA TRAPRESS	H 12*		570300	340,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	RFz 12*		571320	393,00
	RFz 16*		571325	393,00
	RFz 20*		571330	393,00
	RFz 25		571335	393,00
	RFz 32		571340	393,00
Tradelink TradePex Crimp Water	K16/P18*		572600	393,00
	K/20*		572605	393,00
	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
Tradelink TradePex Crimp Gas	K16/P18*		572600	393,00
	K/20*		572605	393,00
	K/25*		572610	393,00
	K32		572615	393,00
	K1/40		572620	393,00
	K1/50		572625	645,00
TUBIPLAST ITALY MULTILAYER PIPE	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 18*		570340	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 16*		570765	353,00
	U 18*		570770	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16*		570460	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
TWEETOP	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
	U			
UNICAL AG MAX-MULTIPEX	U 16*		570765	353,00
	U 20*		570775	353,00
	H 26*		570370	340,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
UNIDELTA DELTAPRESS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
UNIDELTA DELTAPRESS GAS	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 32		570785	414,00
Uponor	UP 14*		572630	353,00
	UP 16*		572632	353,00
	UP 20*		572636	353,00
	UP 25		572638	353,00
	UP 32		572640	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
	V			
Valsir Bravopress	B 16*		570850	412,00
	B 20*		570860	412,00
	B 26		570870	454,00
	B 32		570880	454,00
	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 32 V		570685	435,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
Valsir PEXAL	H 14*		570310	340,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	H 32 V		570685	435,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Van Marcke NV SYSTEMPEX	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	THz 75 (PR-3B)	Z4	572829 R	1.240,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
Van Marcke NV Tubipress	M 12		570100	313,00
	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 12 S (PR-2B)	Z8	574736 R	252,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
Variotherm System TH	TH 11,6*		570482	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 11,6 S (PR-2B)**	Z8	574774 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
VESBO CARBON	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
VESBO INOX	M 15		570110	313,00
	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
VESBO MULTIPRESS TH-U	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 26* [12]		570750	414,00
	U 32		570785	414,00
VESBO VPREMIUM	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	U 50		570795	605,00
	U 63 (PZ-S)		572365	1.310,00
Viega Fonterra	VX 12*		571630	435,00
	VP 14/15*		570905	376,00
	VP 16/17*		570910	376,00
	VP 20*		570915	376,00
	VP 25[2]		570920	376,00
Viega MegaPress (ASTM)[10]	VMP ⅜" (OD 17,2 mm)		571740	435,00
	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Viega MegaPress 304 FKM (ASTM)[10]	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega MegaPress 316 (ASTM)[10]	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega MegaPress 316 FKM (ASTM)[10]	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega MegaPress CuNi (ASTM)[10]	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega MegaPress FKM (ASTM)[10]	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega Megapress (EN)[9]	VMP ⅜" (OD 17,2 mm)		571740	435,00
	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega Megapress S (EN)[9]	VMP ⅜" (OD 17,2 mm)		571740	435,00
	VMP ½" G (OD 21,3 mm)		571766 R	435,00
	VMPz ¾" (OD 26,9 mm)		571764	435,00
	VMPz 1" (OD 33,7 mm)		571767	435,00
	VMPz 1¼" (PZ-S) (OD 42,4 mm)		572413	1.430,00
	VMPz 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	970,00
	VMPz 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	970,00
Viega Megapress S XL (EN[9])	VMPz 2½" XL (PR-3B) EN (OD 76,1 mm)	Z7 XL 45 kN[4]	579112 R	1.240,00
	VMPz 3" XL (PR-3B) (OD 88,9 mm)	Z7 XL 45 kN[4]	579113 R	1.240,00
	VMPz 4" XL (PR-3B) (OD 114,3 mm)	Z7 XL 45 kN[4]	579114 R	1.310,00
Viega Pexfit	VX 16*		571635	435,00
	VX 20*		571640	435,00
	VX 25*		571645	435,00
Viega Pexfit G	VX 16*		571635	435,00
	VX 20*		571640	435,00
	VX 25*		571645	435,00
Viega Prestabo	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)[6]	Z5	572815 R	1.240,00
	VFz 76,1 (PR-3B)[6]	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)[6]	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)[6]	Z5	572818 R	1.310,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Viega Profipress	V 12		570107	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)[6]	Z5	572815 R	1.240,00
	VFz 66,7 (PR-3B)	Z5	572846 R	1.240,00
	VFz 76,1 (PR-3B)[6]	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)[6]	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)[6]	Z5	572818 R	1.310,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viega Profipress G	V 12		570107	313,00
	VG 14		570132	313,00
	V 15		570115	313,00
	VG 16		570137	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)[6]	Z5	572815 R	1.240,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	VG 14 S (PR-2B)	Z8	574750 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	VG 16 S (PR-2B)	Z8	574754 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viega Profipress S	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viega Profipress Therm	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
Viega ProPress (ASTM)[10]	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
XL-C/XL-S	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
XL-C/XL-S	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
XL-C/XL-S	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
Viega ProPress 304 FKM (ASTM)[10]	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
XL-C/XL-S	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
XL-C/XL-S	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
XL-C/XL-S	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00
Viega ProPress 316 (ASTM)[10]	VUS ½" (OD 15,9 mm)		571770	378,00
	VUS ¾" (OD 22,2 mm)		571775	378,00
	VUS 1" (OD 28,6 mm)		571780	378,00
	VUS 1¼" (OD 34,9 mm)		571785	378,00
	VUS 1½" (OD 41,3 mm)		571790	729,00
	VUS 2" (OD 54,0 mm)		571795	750,00
XL-C/XL-S	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	1.240,00
XL-C/XL-S	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	1.240,00
XL-C/XL-S	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	1.310,00
Viega Propress WATER System AUS	VAU 15 (OD 12,7 mm)		572687	324,00
	VAU 20 (OD 19,1 mm)		572689	324,00
	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
Viega PropressG GAS System AUS	VAU 15 (OD 12,7 mm)		572687	324,00
	VAU 20 (OD 19,1 mm)		572689	324,00
	VAU 25 (OD 25,4 mm)		572691	324,00
	VAU 32 (OD 31,8 mm)		572693	340,00
	VAU 40 (OD 38,1 mm)		572695	504,00
	VAU 50 (OD 50,8 mm)		572697	892,00
Viega Raxinox	VRX 16		571750	397,00
	VRX 20		571752	397,00
Viega Raxofix	VRX 16		571750	397,00
	VRX 20		571752	397,00
	VRX 25		571754	435,00
	VRX 32		571756	435,00
	VRX 40		571758	605,00
	VRX 50		571760	706,00
	VRX 63		571797	1.140,00
Viega Sanfix[2]	VP 16/17[2]		570910	376,00
	VP 20[2]		570915	376,00
	VP 25[2]		570920	376,00
	VP 32		570925	416,00
	VP 40 (PZ-4G)		570970	997,00
	VPz 50 (PZ-S)		572350	1.310,00
	VPz 63 (PZ-S)		572355	1.310,00
Viega Sanfix Fosta[2]	VP 16/17[2]		570910	376,00
	VP 20[2]		570915	376,00
	VP 25[2]		570920	376,00
	VP 32		570925	416,00
	VP 40 (PZ-4G)		570970	997,00
	VPz 50 (PZ-S)		572350	1.310,00
	VPz 63 (PZ-S)		572355	1.310,00
Viega Sanpress	V 12		570107	313,00
	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VR 76,1 (PR-3B)[6]	Z5	572822 R	1.240,00
	VR 88,9 (PR-3B)[6]	Z5	572823 R	1.310,00
	VR 108,0 (PR-3B)[6]	Z5	572824 R	1.310,00
	V 12 S (PR-2B)	Z8	574748 R	252,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viega Sanpress Inox	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)[6]	Z5	572815 R	1.240,00
	VFz 76,1 (PR-3B)[6]	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)[6]	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)[6]	Z5	572818 R	1.310,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viega Sanpress Inox G	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 64,0 (PR-3B)[6]	Z5	572815 R	1.240,00
	VFz 76,1 (PR-3B)[6]	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)[6]	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)[6]	Z5	572818 R	1.310,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viega Smartpress	VX 16*		571635	435,00
	VX 20*		571640	435,00
	VX 25*		571645	435,00
Viega Temponox	V 15		570115	313,00
	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	VFz 76,1 (PR-3B)[6]	Z5	572816 R	1.240,00
	VFz 88,9 (PR-3B)[6]	Z5	572817 R	1.310,00
	VFz 108,0 (PR-3B)[6]	Z5	572818 R	1.310,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
Viessmann	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
Vogel & Noot EASYTEC	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
VSH	> Aalberts integrated piping systems			

W

Watts MTR Art press	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
WATTS RADIANT Watts WaterPEX	US ⅜"*		571450	429,00
	US ½"*		571455	429,00
	US ¾"*		571460	429,00
	US 1"*		571465	429,00
	US 1 ¼"		571470	429,00
	US 1 ½"		571475	429,00
WATTS RADIANT Watts RadiantPEX	US ⅜"*		571450	429,00
	US ½"*		571455	429,00
	US ¾"*		571460	429,00
	US 1"*		571465	429,00
	US 1 ¼"		571470	429,00
	US 1 ½"		571475	429,00
WATTS RADIANT Watts RadiantPEX-AL	U 16 (½")		570765	353,00
	U 20 (⅝")		570775	353,00
	U 25 (¾")		570780	353,00
	U 32 (1")		570785	414,00
Wavin Tigris K1/M1	U 50		570795	605,00
	U 63 (PR-3B)	Z4	572837 R	1.490,00
	U 63 (PZ-S)		572365	1.310,00
	U 75 (PR-3B)	Z4	572828 R	1.310,00
Wavin Tigris K5/M5	B 16*		570850	412,00
	B 20*		570860	412,00
	B 32		570880	454,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 25*		570360	340,00
	H 32		570380	340,00
	H 40 (PZ-4G)		570390	1.150,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 25*		570495	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 25 S (PR-2B)**	Z8	574792 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
	U 25*		570780	353,00
	U 32		570785	414,00
	U 40		570790	504,00
	UP 16*		572632	353,00
	UP 20*		572636	353,00
	UP 25		572638	353,00
	UP 32		572640	414,00

REMS pressing tongs
REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
WEECON	M 15		570110	313,00
PRESS-C-Stahl	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
WEECON	M 15		570110	313,00
PRESS-Edelstahl	M 18		570120	313,00
	M 22		570130	313,00
	M 28		570140	313,00
	M 35		570150	313,00
	M 42 (PZ-4G)		570160	1.010,00
	M 54 (PZ-4G)		570170	1.010,00
	M 42 (PR-3S)	Z2	572706 R	1.370,00
	M 54 (PR-3S)	Z2	572708 R	1.370,00
	M 76,1 XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579101 R	2.350,00
	M 88,9 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579110 R	2.750,00
	M 108,0 G XL (PR-3S)	Z6 XL[3] / Z7 XL 45 kN[4]	579111 R	2.750,00
	M 15 S (PR-2B)	Z8	574738 R	252,00
	M 18 S (PR-2B)	Z8	574740 R	252,00
	M 22 S (PR-2B)	Z8	574742 R	252,00
	M 28 S (PR-2B)	Z8	574744 R	252,00
	M 35 S (PR-2B)	Z8	574746 R	277,00
WEECON	V 15		570115	313,00
PRESSS-Kupfer	V 18		570125	313,00
	V 22		570135	313,00
	V 28		570145	313,00
	V 35		570155	313,00
	V 42		570165	729,00
	V 42 (PR-2B)	Z2	572850 R	653,00
	V 54		570175	750,00
	V 54 (PR-2B)	Z2	572851 R	706,00
	V 15 S (PR-2B)	Z8	574752 R	252,00
	V 18 S (PR-2B)	Z8	574756 R	252,00
	V 22 S (PR-2B)	Z8	574758 R	252,00
	V 28 S (PR-2B)	Z8	574760 R	252,00
	V 35 S (PR-2B)	Z8	574762 R	277,00
WEM	U 16*		570765	353,00
WIELAND-WERKE	TH 14[2]		570455	377,00
cuprotherm CTX[2]	TH 16[2]		570460	377,00
WKS-Press	TH 14*		570455	377,00
	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
WÜRTH	TH 16*		570460	377,00
Würth	TH 20*		570470	377,00
	TH 26*		570475	377,00
	HE 32		571900	452,00
	HEz 40		571904	655,00

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	KM
	X			
XtraConnect	F 16*		570717	359,00
	F 20*		570727	359,00
	F 26*		570730	389,00
	F 32		570735	389,00
	F 16 S (PR-2B)**	Z8	574728 R	252,00
	F 20 S (PR-2B)**	Z8	574730 R	252,00
	F 26 S (PR-2B)**	Z8	574732 R	252,00
	F 32 S (PR-2B)	Z8	574734 R	277,00
	H 16*		570320	340,00
	H 20*		570350	340,00
	H 26*		570370	340,00
	H 32		570380	340,00
	TH 16*		570460	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
	U 16*		570765	353,00
	U 20*		570775	353,00
(DN 26)	U 25*		570780	353,00
	U 32		570785	414,00
	VP 16*		570910	376,00
	VP 20*		570915	376,00
	VP 32		570925	416,00
	Z			
ZEWOTHERM	TH 12*		570452	377,00
Zewo Press Premium	TH 16*		570460	377,00
	TH 17*		570462	377,00
	TH 18*		570465	377,00
	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 40		570485	500,00
	TH 50 (PZ-S)		572400	1.310,00
	TH 63 (PZ-S)		572405	1.310,00
	TH 12 S (PR-2B)**	Z8	574776 R	252,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 17 S (PR-2B)**	Z8	574784 R	252,00
	TH 18 S (PR-2B)**	Z8	574786 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
ZEWOTHERM	TH 16*		570460	377,00
Zewo Press PPSU	TH 20*		570470	377,00
	TH 26*		570475	377,00
	TH 32		570480	377,00
	TH 16 S (PR-2B)**	Z8	574782 R	252,00
	TH 20 S (PR-2B)**	Z8	574788 R	252,00
	TH 26 S (PR-2B)**	Z8	574794 R	252,00
	TH 32 S (PR-2B)	Z8	574798 R	277,00
ZURN	US ⅜"*		571450	429,00
INDUSTRIES	US ½"*		571455	429,00
ZURN PEX	US ¾"*		571460	429,00
	US 1"*		571465	429,00
	US 1 ¼"		571470	429,00
	US 1 ½"		571475	429,00
	US 2"		571477	578,00

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

Accessories

For REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

Description	Art.-No.	KM
Adapter tongs Z8 for driving REMS pressing rings S (PR-2B)	574702R	**292,00**
Adapter tongs Z2 for driving REMS pressing rings M 35 – 54 (PR-3S), V 42 – 54 (PR-2B), RN 40 – 50 (PR-3S)	572795R	**292,00**
Adapter tongs Z4 for driving REMS pressing rings F 75 (PR-3B), TH 63 – 75 (PR-3B), U 63 – 75 (PR-3B), RN 63 (PR-3B)	572801RX	**628,00**
Adapter tongs Z5 for driving REMS pressing rings VFz/VR 64 – 108 (PR-3B), VMPz 1½ – 2" (PR-3B), VUSFz 2½ – 4" (PR-3B), VAUFz 65 – 100 (PR-3B)	572802RX	**628,00**
Adapter tongs Z6 XL for driving REMS pressing rings 64.0 – 108.0 XL (PR-3S), 2½ – 4" XL (PR-3S) with REMS Power-Press XL ACC	579120R	**756,00**
Adapter tongs Z7 XL 45 kN for driving REMS pressing rings 64.0 – 108.0 XL (PR-3S), 2½ – 4" XL (PR-3S), 2½ – 4" XL (PR-3B) with REMS Akku-Press XL 45 kN 22 V ACC	579123R	**798,00**
Steel case with insert for 6 pressing tongs (up to Ø 35 mm/1" and pressing tongs U 40, U 50, TH 40, F 40, F 50, G 40, VUS 1¼")/cropping tongs and compartment for pipe cutter up to 42 mm	570295R	**196,00**
Steel case with insert for 2 pressing tongs (M 42 (PZ-4G), M 54 (PZ-4G), V 42, V 54, H 40, H 40 A, VUS 1½", VUS 2")	570290R	**196,00**
Steel case with insert for adapter tongs Z2 and pressing rings M 42 (PR-3S) and M 54 (PR-3S) or pressing rings SA 42 (PR-3S) and SA 54 (PR-3S).	572810R	**196,00**
Steel case with insert for adapter tongs Z5 and 4 pressing rings VFz 64.0 – 108.0/VR 76.1 – 108.0/ VUSFz 2½ – 4" (PR-3B) or for adapter tongs Z5 and 1 pressing tong VMPz 1¼ (PZ-S) and 2 pressing rings VMPz 1½ – 2" (PR-3B)	572809R	**223,00**
Steel case with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	**196,00**
L-Boxx system case with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	**296,00**
L-Boxx system case with inserts for 8 pressing tongs (2B) and 6 pressing rings S (PR-2B)	571136R	**296,00**
L-Boxx system case with inserts for 3 different pressing rings VMPz 2½ – 4" XL (PR-3B)	571137R	**296,00**
XL-Boxx system case with inserts for 3 different pressing rings 64.0 – 108.0 XL (PR-3S) or 2½ – 4" XL (PR-3S)	579603R	**502,00**
Steel case with inserts for adapter tongs Z2 and pressing rings V 42 (PR-2B) and V 54 (PR-2B)	572813R	**112,00**

All prices excl. VAT

Confirmation of suitability

The suitability of crimping tools is determined basically by the manufacturer of crimping tools. Moreover the suitability of REMS crimping tools has been confirmed by the system manufacturer/supplier himself or approved through independent testing institutes.

Confirmation of suitability through the system manufacturer/supplier

More than 90 % of the manufacturers/suppliers of the pressfitting systems listed herein have tested REMS pressing tongs and confirmed the suitability for their pressfitting system.

Confirmation of suitability through independent testing institutes

The suitability of REMS pressing tongs for additional pressfitting systems have been confirmed through independent technical institutes:

TÜV-Certificates

Exist for Geberit Mepla, Geberit Mapress C-STAHL, Geberit Mapress EDELSTAHL, Geberit Mapress Kupfer, Nussbaum Cupress, Nussbaum Optipress, Uponor Unipipe, Viega-'profipress', Viega-'profipress G', Viega-'sanfix P', Viega-'sanpress', Viega-'Viegatherm P', Wavin Tigris. The TÜV-certificates confirm that REMS crimping tools are suitable for producing perfect and system-conformity pressing joints corresponding to these systems.

Suitability test according to DVGW W 534 (potable water)

Pressing joints produced with REMS pressing tools were tested by the state-operated material testing institute in Darmstadt/Germany or the material testing institute of the Land of North-Rhine-Westphalia, Germany according to DVGW work sheet W 534. These material testing institutes are certified by the DVGW for making these tests. A representative cross-section of press joints of pressfitting systems Geberit Mapress Edelstahl, Raccorderie Metalliche inoxPRES, Raccorderie Metalliche steelPRES, Uponor Unipipe, Viega Megapress, Viega Profipress and Viega Raxofix. was tested. The tests led to the result that all REMS pressing tools are suitable for producing perfect and system conformity pressing joints in accordance with these systems.

Suitability test according to DVGW G 5614/VP 625 or prEN 1254-7 (gas)

Pressing joints made with REMS pressing tools have been tested by the TÜV or by the Land Material Testing Institute Nordrhein-Westfalen or the DVGW Research Institute Karlsruhe according to DVGW Regulations G 5614/VP 625 or by the BSI (UK) according to prEN 1254-7. A representative cross-section of pressing joints of the pressfitting systems Geberit Mapress Edelstahl Gas, Geberit Mapress Kupfer Gas, Henco Gas, IBP >B<press Gas, Kembla KemPress Gas, Pegler Yorkshire X-Press Copper Gas, Raccorderie Metalliche inoxPRES Gas, Uponor MLC-G, Valsir PEXAL Gas, Viega Profipress G, Viega Pexfit G, Viega Sanpress INOX G, Viega PropressG GAS System (AUS) was tested. The tests led to the result that all REMS pressing tools are suitable for producing perfect and system conformity pressing joints in accordance with these systems.

potable water

gas

Hold-Harmless and Indemnification Agreement

REMS is the first system-independent machine and tool manufacturer to sign liability acceptance agreements for pressing tools.

A hold-harmless and indemnification agreement exists with the:

Zentralverband Sanitär Heizung Klima (Central Organization for the Sanitary-, Heating- and Climatization Industries),
Rathausallee 6, D-53757 St. Augustin,
referred to in the following as "ZVSHK",

Bundesindustrieverband Technische Gebäudeausrüstung e.V.,
Hinter Hoben 149, 53129 Bonn,
referred to in the following as "BTGA",

Verband Deutscher Kälte-Klima-Fachbetriebe e. V.
(German Association for Coolant & Air-Conditioning Profession Industries),
Kaiser-Friedrich-Straße 7, D-53113 Bonn,
referred to in the following as "VDKF",

Schweizerisch-Liechtensteinischem Gebäudetechnikverband
(Swiss-Liechtenstein Technical Building Association),
Auf der Mauer 11, CH-8023 Zürich,
referred to in the following as "suissetec",

The Zentralverband Sanitär Heizung Klima (ZVSHK), the Bundesindustrieverband Technische Gebäudeausrüstung e. V. (BTGA), the Verband Deutscher Kälte-Klima-Fachbetriebe e. V. (VDKF) and the Schweizerisch-Liechtensteinische Gebäudetechnikverband (suissetec) have made liability acceptance agreements in the interests of trade and industry with REMS GmbH & Co KG (REMS) for the radial pressing tools.

- Manual radial press REMS Eco-Press
- Cordless radial press REMS Mini-Press 14 V ACC
- Cordless radial press REMS Mini-Press 22 V ACC
- Cordless radial press REMS Mini-Press S 22 V ACC
- Electric radial press REMS Power-Press SE
- Electro-hydraulic radial press REMS Power-Press ACC
- Electro-hydraulic radial press REMS Power-Press XL ACC
- Cordless radial press REMS Akku-Press E 22 V ACC
- Cordless radial press REMS Akku-Press 22 V ACC
- Cordless radial press REMS Akku-Press 22 V Connected
- Cordless radial press REMS Akku-Press XL 45 kN 22V ACC
- REMS pressing tongs
- REMS pressing rings
- REMS pressing tongs Mini

This makes REMS the first system-independent machine- and tool manufacturer to have concluded a hold-harmless and indemnification agreement for pressing tools. The conclusion of the agreement was effected on the basis of a successful cooperation established on partnership between REMS, the crafts, trades and industry and their organizations.

Eligible for services and performances from this agreement are all independent professional craftsmen, and companies of such, who are enrolled in the register of artisans and craftsmen (referred to in the following as "SHK-Establishments"), in as far as they have been members of the crafts guild of the sanitary- heating- and climatization enterprises competent for their business location at the time the damage event has arisen, and this crafts guild is associated with a regional guild association, which is a member of the ZVSHK.

Entitled to the services from the agreement with the BTGA are all building technology companies (hereinafter referred to as "TGA companies") insofar as they were a member of the Land Industry Association **Technical Building Equipment** responsible at the seat of their company at the time of the damage case and therefore an indirect member of the BTGA or direct member of the BTGA.

Eligible for services and performances from this agreement with the VDKF are all coolant systems companies or professional organisations (referred to as Coolant and Air-Conditioning Profession Industries) who, at the time the damage is caused, are members of the VDKF.

Eligible for services and performances from this agreement are all building systems companies (following TGA companies) who, at the time the damaged is caused, are members of suissetec.

In as far as the radial pressing tools mentioned show a defect with regard to construction, manufacture or material, or if the operator's manuals are faulty, thereby causing damage for the customer of the SHK-establishment, the Coolant and Air-Conditioning Profession Industries, or the TGA-companies, for which the SHK-establishment or the TGA-company is liable, then REMS shall be additionally liable - aside of the statutory prescriptions – for the consequences resulting from leakage, in accordance with the stipulations and provisions of this hold-harmless agreement.

The assumption of liability agreements apply regardless of which pressfitting system is pressed with the suitable REMS pressing tools. The current status regarding suitability of the REMS pressing tools for pressfitting systems can be viewed on the Internet: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

For further information, please contact: **info@rems.de**

German Quality Product

Reliable and safe: REMS was the first system-independent machine and tool manufacturer to sign liability acceptance agreements for pressing tools as early as the year 2000.

ZVSHK

BTGA

suissetec

VDKF

REMS cropping tongs

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

High performance cropping tongs in forged and specially hardened steel for cutting threaded rods.

Steel, stainless steel up to hardness classification 4.8 (400 N/mm²) M 6 – M 12

REMS cropping tongs – for cutting threaded rods.

Made of forged and specially hardened steel.

Reversible cropping inserts for double service life.

M cropping inserts with high precision thread contour machined on CNC machining centres for exact guiding of the threaded rod in the cutting process Pliers parts, cropping inserts and specially machined and hardened cutting edges, made to fit exactly, for cutting without burr

Threaded rod can be screwed into a threaded connection of the pipe clip or the nut without rework after cutting

Cutting device in pliers design **(Patent EP 1 459 825, patent US 7,284,330).** Driven by REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force. All cropping tongs marked with * have an optional connection for manual drive through the radial press REMS Eco-Press.



German Quality Product

Patent EP 1 459 825
Patent US 7,284,330

Supply format

REMS cropping tongs. Cropping tongs with 1 pair of reversible cropping inserts for steel, stainless steel, M 6 – M 12. In a carton.

Description	for threaded rods	Art.-No.	KM
REMS cropping tongs M 6*	M 6	571890	**490,00**
REMS cropping tongs M 8*	M 8	571895	**490,00**
REMS cropping tongs M 10	M 10	571865	**490,00**
REMS cropping tongs M 12	M 12	571870	**490,00**

Accessories

Description	for threaded rods	Art.-No.	KM
Cropping inserts M 6 (pair)	M 6	571891	**225,00**
Cropping inserts M 8 (pair)	M 8	571896	**225,00**
Cropping inserts M 10 (pair)	M 10	571866	**225,00**
Cropping inserts M 12 (pair)	M 12	571871	**225,00**
Steel case with insert for 6 cropping tongs/pressing tongs and compartment for pipe cutter up to 42 mm		570295R	**196,00**

REMS cable shear

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

High-grade cable shear in forged and specially hardened steel for cutting electric cable.

Electric cable ≤ 300 mm² (Ø 30 mm)

REMS cable shear – Easy cutting of electric cable.

Made of forged and specially hardened steel.

Replaceable cutting blades manufactured on CNC production centres ensure a precision blade geometry and long service life. Large cutting range.

Driven by REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

German Quality Product

Supply format

REMS cable shear. Cable shears with 2 changeable cable cutters for electric cables ≤ 300 mm² (Ø 30 mm). In a carton.

	Art.-No.	KM
	571887	**802,00**

Accessories

Description	Art.-No.	KM
Cable cutters (pack of 2)	571889R02	**225,00**



Axial Press Jointing

	Cordless axial press 30 22V **Compression heads**	**244**
	Manual axial press	**245**
	Cordless axial press 25 22V **Cordless axial press 25 L 22V**	**246**
	Compression heads	**248**

REMS Ax-Press 30 22 V

Cordless axial press 30 kN

Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-Ion 22 V Technology. For battery and corded operation.

Axial compression	Ø 12 – 32 mm

REMS Ax-Press 30 22 V – up to Ø 32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*.

Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system-conformity, safe jointing.

Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads. Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

High pressing force for perfect pressing in seconds, e.g. Ø 26 mm in only 5 s. Thrust force 30 kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system.Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings, 4.4 Ah for approx. 380 pressings, 5.0 Ah for approx. 430 pressings, 9.0 Ah for approx. 780 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

e.g.
Brasstech,
General Fittings,
Georg Fischer pfci

German Quality Product

Info

Supply format

REMS Ax-Press 30 22 V Basic-Pack. Cordless axial press 30 kN for producing compression sleeve joints with crimping sleeve Ø 12 – 32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V, 50 – 60 Hz, 70 W. In sturdy steel case.

	Art.-No.	KM
	573018R220	**4.290,00**

Accessories

Description	Art.-No.	KM
REMS Ax-Press 30 22 V drive unit, without battery	573008R22	**3.200,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	**838,00**
Steel case with insert	573282R	**223,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

REMS compression heads

Compression sleeve system	Compression head	Art.-No.	KM
Brasstech Raptor/ Metalpex/ Raptor 2/ MULTItermoSAN	ME 14 (pack of 2)	573100	**219,00**
	ME 16 (pack of 2)	573102	**219,00**
	ME 20 (pack of 2)	573106	**219,00**
	ME 26 (pack of 2)	573108	**219,00**
	ME 32 (pack of 2)	573110	**240,00**
General Fittings Serie 5400	ME 14 (pack of 2)	573100	**219,00**
	ME 16 (pack of 2)	573102	**219,00**
	ME 20 (pack of 2)	573106	**219,00**
	ME 26 (pack of 2)	573108	**219,00**
	ME 32 (pack of 2)	573110	**240,00**

REMS compression heads

Compression sleeve system	Compression head	Art.-No.	KM
Georg Fischer pfci ALUPEX-EXPRESS/ Alupex Gas System	ME 16 (pack of 2)	573102	**219,00**
	ME 20 (pack of 2)	573106	**219,00**
	ME 26 (pack of 2)	573108	**219,00**
Logstor	ME 16 (pack of 2)	573102	**219,00**
	LR 20 (pack of 2)	573430	**219,00**
	LR 22 (pack of 2)	573432	**219,00**
	LR 25 (pack of 2)	573434	**219,00**
	LR 28 (pack of 2)	573436	**219,00**
	LR 32 (pack of 2)	573438	**240,00**

All prices excl. VAT

*Ambient temperature approx. 20°C.

Universal manual axial press for producing compression sleeve joints.

Axial compression	Ø 12 – 32 mm

REMS Ax-Press HK – universal up to Ø 22 mm
Ultra small, ultra light, ultra handy. Only 1.1 kg

REMS Ax-Press H – universal up to Ø 32 mm.
Handy and light. Only 1.4 kg.

Complete assortment of REMS compression heads, quickly interchangeable.

System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22 V ACC, REMS Ax-Press 25 L 22 V ACC. Thus easy, economic stocking.

Compression heads

Full range of REMS compression heads for all common compression sleeve systems (page 248 – 249). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 248). No need to change compression heads. Extremely simple, saves time.

Design

Compact, job site proven. Handy and light. REMS Ax-Press HK drive unit only 1.1 kg. REMS Ax-Press H drive unit only 1.4 kg. Works anywhere, free-hand, also in tight spots. 66 mm stroke. Quick-acting forward and release for easy, fast operation. Selectable compression head position **(Patent DE 10 2004 018 429, Patent ES 2 273 563, Patent FR 05 03513)** for pressing compression sleeve connectors with a clamping distance of ≤ 161 mm in one action and for double pressings. Quick-change compression heads and pressing inserts without tools. Secure fit of compression heads and pressing inserts by spring catch. REMS Ax-Press H with overload protection.

Expanding

Various pipe expanders and complete range of REMS expanding heads for all common compression sleeve systems (page 253 – 257).

Patent DE 10 2004 018 429
Patent ES 2 273 563
Patent FR 05 03513

e.g.
AC-FIX,
aquatherm,
BARBI,
FERRO systems
BRASELI,
Brass & Fittings,
COMAP,
EUROP'FLUIDES,
Fittings Estándar,
PB TUB,
PLÁSTICOS FERRO,
REVI,
RIQUIER,
TECE,
TIEMME,
VELTA

German Quality Product

Info

Supply format

REMS Ax-Press HK drive unit. Axial press for single-handed operation for producing compression sleeve joints Ø 12 – 22 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	KM
	574302R	**418,00**

Supply format

REMS Ax-Press H drive unit. Manual axial press for producing compression sleeve joints Ø 12 – 32 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	KM
	574300RX	**586,00**

Accessories

Description	Art.-No.	KM
REMS compression heads see page 248 – 249.		
Carrying bag for REMS Ax-Press HK/H drive unit and compression heads	574437R	**92,40**
Case with inlay for REMS Ax-Press HK drive unit and compression heads	574352R	**131,00**

REMS Ax-Press 25 22 V ACC
REMS Ax-Press 25 L 22 V ACC

Cordless axial press 20 kN with automatic return
Cordless axial press 13 kN with automatic return

Compact, handy power tool with automatic return for manufacturing compression sleeve joints. Li-Ion 22 V Technology. For battery and corded operation. For trade and industry. For the building site and the workshop.

Axial compression	Ø 12 – 40 mm

REMS Ax-Press 25 22 V ACC – universal up to Ø 40 mm. Super light, super handy. Fast. With automatic return. Optimum weight distribution for single-hand operation. Swivelling compression device. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings REHAU RAUTITAN PX Ø 16 mm with one battery charge*.

System advantage
Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22 V ACC, REMS Ax-Press 25 L 22 V ACC. Thus easy, economic stocking.

Compression heads for all common systems
Full range of REMS compression heads for all common compression sleeve systems (page 248 – 249). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

Twin compression heads
REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 248). No need to change compression heads. Extremely simple, saves time.

Design
Compact, handy, light. REMS Ax-Press 25 22 V ACC drive machine with battery weighs only 3.0 kg, only 28 cm long REMS Ax-Press 25 L 22 V ACC drive machine with battery weighs only 3.2 kg, only 31 cm long REMS Ax-Press 25 22 V ACC and REMS Ax-Press 25 L 22 V ACC with 40 mm stroke respectively REMS Ax-Press 25 22 V ACC with preset compression head position for pressing compression sleeve connectors with a clamping distance a ≤ 82 mm in one action REMS Ax-Press 25 L 22 V ACC with selectable compression head position for pressing compression sleeve connectors with a clamping distance a ≤ 116 mm in one action and for double pressings. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. LED work light for illuminating the work place. Swivelling compression device for working in confined area. Compression heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive
Enormous pressing force for fast and perfect jointing. Thrust force REMS Ax-Press 25 22 V 20 kN, thrust force REMS Ax-Press 25 L 22 V 13 kN. Powerful electro-hydraulic drive with automatic return (ACC), eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation
Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings, 4.4 Ah for approx. 880 pressings, 5.0 Ah for approx. 1000 pressings, 9.0 Ah for approx. 1800 pressings REHAU RAUTITAN PX Ø 16 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Expanding
Various pipe expanders and complete range of REMS expanding heads for all common pressure sleeve systems

REMS Ax-Press 25 22 V ACC

ACC
Automatic Circuit Control

with automatic circuit control and charging status check

e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth

REMS TECHNOLOGY LI-ION 22V

REMS Ax-Press 25 L 22 V ACC

ACC
Automatic Circuit Control

with automatic circuit control and charging status check

e.g.
AC-FIX,
BARBI,
FERRO systems
BRASELI,
Brass & Fittings,
EUROP´FLUIDES,
Fittings Estándar,
PLÁSTICOS FERRO,
Velta

REMS TECHNOLOGY LI-ION 22V

German Quality Product

Supply format

REMS Ax-Press 25 22 V ACC Basic-Pack. Cordless axial press 20 kN for producing compression sleeve joints Ø 12 – 40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance a ≤ 82 mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	KM
	573022 R220	**3.050,00**

Other voltages on request.

Info

Supply format

REMS Ax-Press 25 L 22 V ACC Basic-Pack. Cordless axial press 13 kN for producing compression sleeve joints Ø 12 – 40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance a ≤ 116 mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	KM
	573023 R220	**3.050,00**

Other voltages on request.

Info

Accessories

Description	Art.-No.	KM
REMS compression heads see page 248 – 249.		
REMS Ax-Press 25 22 V ACC drive unit, a ≤ 82 mm, without battery	573020 R22	**2.190,00**
REMS Ax-Press 25 L 22 V ACC drive unit, a ≤ 116 mm, without battery	573021 R22	**2.190,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567 R220	**838,00**
Steel case with insert	578290 R	**223,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

REMS compression heads

Accessories for REMS Ax-Press HK, REMS Ax-Press H,
REMS Ax-Press 25 22 V ACC, REMS Ax-Press 25 L 22 V ACC



REMS compression heads with spring lock for commercially available press inserts

Description	Use
Compression head Basic 20 (pack of 2)	for pipe fittings 20 mm and for standard press inserts outer Ø 20 mm
Compression head Basic 25 (pack of 2)	for pipe fittings 25 mm and for standard press inserts outer Ø 25 mm
Compression head Basic 32 (pack of 2)	for pipe fittings 32 mm and for standard press inserts outer Ø 32 mm

REMS twin compression heads

Description	Use
Twin compression head RH 16/20 (pack of 2)	for pipe fittings 16 and 20 mm

REMS compression head for T-pieces, elbows, splitters, transition pieces

Description	Use
Compression head UNI T/L (piece)	for T-pieces, elbows, splitters, in combination with an additional compression head; for transition pieces, in combination with a support bol

REMS support bolt for transition pieces

Description	for transition pieces inch	Art.-No.	KM
Support bolt ⅜"	⅜	573647R	**26,30**
Support bolt ½"	½	573648R	**30,30**
Support bolt ¾"	¾	573649R	**34,10**

Commercially available press inserts:

T's and elbows

Dm 16

Dm 20

Dm 22

Dm 25

Dm 32





All prices excl. VAT

REMS compression heads

Accessories for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22 V ACC, REMS Ax-Press 25 L 22 V ACC

Select compression heads yourself!

Search for the required compression sleeve system in the table below and select the correct compression heads.

High-grade compression heads in forged and specially hardened steel. Quickly interchangeable, without tools. The REMS compression heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, safe jointing. Drive through REMS axial presses.

Compr. heads Uni

Compr. head UNI T/L



Compr. heads Basic for press inserts

Pressure sleeves system	Compression head mm	Number of pressing heads	fits REMS Ax-Press HK[1]	H	25	25 L	Art.-No.	KM
AC-FIX (Global Piping System)	UNI 12	2	•	•		•	573630	**219,00**
	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 20*	2	•	•		•	573624	**242,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2	•	•		•	573628	**242,00**
aquatherm	AT 16	2	•	•	•		573120	**219,00**
	AT 20	2	•	•	•		573122	**219,00**
	AT 25	2	•	•	•		573124	**219,00**
	AT 32	2	•	•	•		573126	**240,00**
	AT 40	2	•	•	•		573128	**261,00**
BARBI GLADIATOR (Industrial Blansol)	UNI 18	2		•		•	573634	**219,00**
	UNI 22	2		•		•	573638	**219,00**
	UNI 26	2		•		•	573642	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI 40	2				•	573652	**261,00**
	UNI T/L**	1		•		•	573646 R	**218,00**
	Basic 20*	2		•		•	573624	**242,00**
	Basic 25*	2		•		•	573616	**242,00**
	Basic 32*	2		•		•	573628	**242,00**
BARBI RETICULADO (Industrial Blansol)	UNI 12	2	•	•		•	573630	**219,00**
	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI 40	2				•	573652	**261,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 20*	2	•	•		•	573624	**242,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2		•		•	573628	**242,00**
FERRO systems BRASELI GPF AXIAL	UNI 12	2	•	•		•	573630	**219,00**
	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 20*	2	•	•		•	573624	**242,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2	•	•		•	573628	**242,00**
Brass & Fittings PRESSMAN PowerFit	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 20*	2	•	•		•	573624	**242,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2	•	•		•	573628	**242,00**
COMAP PEXY	UNI 12	2	•	•			573630	**219,00**
	UNI 16	2	•	•			573632	**219,00**
	UNI 20	2	•	•			573636	**219,00**
	UNI 25	2		•			573640	**219,00**
	UNI 32	2		•			573644	**219,00**
	UNI T/L**	1	•	•			573646 R	**218,00**
	Basic 25*	2	•	•			573616	**242,00**
	Basic 32*	2	•	•			573628	**242,00**
EUROP´FLUIDES HYDROFLUIDES	UNI 12	2	•	•		•	573630	**219,00**
	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2	•	•		•	573628	**242,00**
Fittings Estándar	UNI 12	2	•	•		•	573630	**219,00**
	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 20*	2	•	•		•	573624	**242,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2	•	•		•	573628	**242,00**
General Fittings Serie 3400 PEX Gold-Fix	RE 16	2			•		573160	**219,00**
	RE 20	2			•		573162	**219,00**
	RE 25	2			•		573172	**219,00**
	RE 32	2			•		573178	**219,00**
	RO 16	2			•		573184	**219,00**
	RO 20	2			•		573186	**219,00**
General Fittings Serie 3400 PEX/AL/PEX Gold-Fix	RE 16	2			•		573160	**219,00**
	RE 20	2			•		573162	**219,00**
	RE 25	2			•		573172	**219,00**
	RE 32	2			•		573178	**219,00**
	RO 16	2			•		573184	**219,00**
	RO 20	2			•		573186	**219,00**
General Fittings Serie 3400 PEX Gold-Therm	RH 17	2			•		573168	**219,00**
	RH 20	2			•		573170	**219,00**
HERZ QUICK FIX	HC 16	2		•	•	•	573112	**219,00**
	HC 20	2		•	•	•	573114	**219,00**
	HC 26	2		•	•	•	573116	**219,00**
	HC 32	2		•	•	•	573118	**240,00**
IVT PRINETO	IV 16/17	3			•		573320	**328,00**
	IV 20/21	3			•		573325	**328,00**
	IV 25/26	3			•		573330	**328,00**
	IV 32/33	3			•		573335	**328,00**

Pressure sleeves system	Compression head mm	Number of pressing heads	fits REMS Ax-Press HK[1]	H	25	25 L	Art.-No.	KM
PB TUB Sertigliss	UNI 12	2	•	•			573630	**219,00**
	UNI 16	2	•	•			573632	**219,00**
	UNI 20	2	•	•			573636	**219,00**
	UNI 25	2		•			573640	**219,00**
	UNI 32	2		•			573644	**219,00**
	UNI T/L**	1	•	•			573646 R	**218,00**
	Basic 25*	2	•	•			573616	**242,00**
	Basic 32*	2	•	•			573628	**242,00**
PLÁSTICOS FERRO FERROPLAST GPF AXIAL	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI 32	2		•		•	573644	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 20*	2	•	•		•	573624	**242,00**
	Basic 25*	2	•	•		•	573616	**242,00**
	Basic 32*	2	•	•		•	573628	**242,00**
PLUMBING PLUS EZIPEX Sleeve Water (AUS)	RH 16 L	2			•		573150	**219,00**
	RH 20 L	2			•		573152	**219,00**
	RH 16/20 L	2			•		573158	**437,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
PLUMBING PLUS EZIPEX Sleeve Gas (AUS)	RH 16 L	2			•		573150	**219,00**
	RH 20 L	2			•		573152	**219,00**
	RH 16/20 L	2			•		573158	**437,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
REHAU RAUTHERM SDR 11 LX	RH 12	2			•		573164	**219,00**
	RH 16	2			•		573166	**219,00**
	RH 20	2			•		573170	**219,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
REHAU RAUTHERM S (REHAU HAS)	RH 17	2			•		573168	**219,00**
	RH 20	2			•		573170	**219,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
REHAU RAUTITAN PX/MX/SX/RX/ gas/sprinkler	RE 16	2			•		573160	**219,00**
	RE 20	2			•		573162	**219,00**
	RE 25	2			•		573172	**219,00**
	RE 32	2			•		573178	**219,00**
	RE 40	2			•		573176	**261,00**
REHAU (GBR) EVERLOC	RH 16	2			•		573166	**219,00**
	RH 20	2			•		573170	**219,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
REVEL-PEX	RV 16	2	•	•	•		573400	**219,00**
	RV 20	2	•	•	•		573402	**219,00**
	RV 25	2	•	•	•		573404	**219,00**
	RV 32	2			•		573406	**240,00**
REVI REVIUNI	TC 12/14/16	2		•			573360	**219,00**
	TC 18/20	2		•			573364	**219,00**
	TC 25	2		•			573367	**219,00**
	TC 32	2		•			573370	**240,00**
REVI REVITERM	TC 12/14/16	2		•			573360	**219,00**
Riquier à glissement	UNI 12	2	•	•			573630	**219,00**
	UNI 16	2	•	•			573632	**219,00**
	UNI 20	2	•	•			573636	**219,00**
	UNI 25	2		•			573640	**219,00**
	UNI 32	2		•			573644	**219,00**
	UNI T/L**	1	•	•			573646 R	**218,00**
	Basic 25*	2	•	•			573616	**242,00**
Seppelfricke SD Sistemi Italia Sylver	RE 16	2			•		573160	**219,00**
	RE 20	2			•		573162	**219,00**
	RE 25	2			•		573172	**219,00**
	RE 32	2			•		573178	**219,00**
	RO 16	2			•		573184	**219,00**
	RO 20	2			•		573186	**219,00**
Seppelfricke SD Sistemi Italia Neroflex	RE 16	2			•		573160	**219,00**
	RE 20	2			•		573162	**219,00**
	RE 25	2			•		573172	**219,00**
	RE 32	2			•		573178	**219,00**
	RO 16	2			•		573184	**219,00**
	RO 20	2			•		573186	**219,00**
TECE TECEflex	TC 12/14/16	2	•	•	•		573360	**219,00**
	TC 18/20	2	•	•	•		573364	**219,00**
	TC 25	2		•	•		573367	**219,00**
	TC 32	2		•	•		573370	**240,00**
TIEMME Assialpex	RE 16	2		•	•		573160	**219,00**
	RE 20	2		•	•		573162	**219,00**
	RE 25	2		•	•		573172	**219,00**
	RE 32	2		•	•		573178	**219,00**
Tradelink TradePex Sleeve Water	RH 16 L	2			•		573150	**219,00**
	RH 20 L	2			•		573152	**219,00**
	RH 16/20 L	2			•		573158	**437,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
Tradelink TradePex Sleeve Gas	RH 16 L	2			•		573150	**219,00**
	RH 20 L	2			•		573152	**219,00**
	RH 16/20 L	2			•		573158	**437,00**
	RH 25	2			•		573154	**219,00**
	RH 32	2			•		573156	**240,00**
Velta Eurojauge	UNI 12	2	•	•		•	573630	**219,00**
	UNI 16	2	•	•		•	573632	**219,00**
	UNI 20	2	•	•		•	573636	**219,00**
	UNI 25	2		•		•	573640	**219,00**
	UNI T/L**	1	•	•		•	573646 R	**218,00**
	Basic 25*	2	•	•		•	573616	**242,00**
Würth PRINETO	IV 16/17	3			•		573320	**328,00**
	IV 20/21	3			•		573325	**328,00**
	IV 25/26	3			•		573330	**328,00**
	IV 32/33	3			•		573335	**328,00**

Pressure sleeve systems for gas installations may only be pressed with the yellow-highlighted pressing heads in the table. Observe the national regulations.

Compression heads for additional compression sleeve systems on request.

[1] For producing compression sleeve connection of Ø 12 – 22 mm.

* **Compression heads with spring lock**

Compression head Basic 20 — for pipe fittings 20 mm and for standard press inserts outer Ø 20 mm

Compression head Basic 25 — for pipe fittings 25 mm and for standard press inserts outer Ø 25 mm

Compression head Basic 32 — for pipe fittings 32 mm and for standard press inserts outer Ø 32 mm

** **Compression head for T-pieces, elbows, splitters, transition pieces**

Compression head UNI T/L — for T-pieces, elbows, splitters, in combination with an additional compression head;

for transition pieces, in combination with a support bolt, see page 248.

Expanding
Extracting

	Hand tube expander Cu	252
	Expander head Cu	252
	One-hand pipe expander	253
	Hand tube expander P	253
	Cordless pipe expander Cu	254
	Cordless pipe expander P	254
	Cordless pipe expander P-CEF	254
	Electro-hydraulic pipe expander P-CEF	256
	Expander head P Expander head P-CEF	257
	Hand tube extractor	258
	Electric tube extractor Electric tube expander	259

REMS Ex-Press Cu

Hand tube expander

Proven quality tool for expanding and calibrating pipes for pipe installation without fittings.	
Soft copper tubes s ≤ 1.5 mm	Ø 8 – 42 mm Ø ⅜ – 1⅛"
Soft aluminium tubes, soft precision steel tubes s ≤ 1.2 mm	Ø 8 – 42 mm Ø ⅜ – 1⅛"
Soft stainless steel tubes s ≤ 1 mm	Ø 8 – 42 mm Ø ⅜ – 1⅛"

German Quality Product

Info

REMS Ex-Press Cu – for making sockets yourself. 6-face mandrel for even and concentric expanding. Extra long sockets according to DVGW. Expander heads with calibration neck, fit other makes as well.

Cost advantage

Pipe installation without fittings. No costs for fittings, storage, procurement. Savings in soldering joints, soldering material and working hours. Using up pipe pieces to provide sockets.

Design

Robust quality tool. Torsion-free, power-transmitting expander levers with ergonomically designed handles, for effortless expanding. 6-face mandrel for even and concentric expanding. Extra long sockets, spring-loaded return of mandrel release. Also for other suitable makes of expander heads.

Expander heads

Quick-change. Extra long expander heads result in extra long sockets for perfect pipe connections according to DVGW. Special neck at expander head specially for calibration of deformed pipe ends.

Supply format

REMS Ex-Press Cu Set. Hand tube expander Ø 8 – 42 mm, Ø ⅜ – 1⅛". Soft copper tubes Ø 8 – 42 mm, Ø ⅜ – 1⅛", s ≤ 1.5 mm, soft aluminium tubes and soft steel precision tubes Ø 8 – 42 mm, Ø ⅜ – 1⅛", s ≤ 1.2 mm, soft stainless steel tubes Ø 8 – 42 mm, Ø ⅜ – 1⅛", s ≤ 1 mm. Expander drive. Choice of expander heads for pipes in mm or inch. In sturdy steel case.

Description	Art.-No.	KM
Set 12 + 15 + 18 + 22	150000R	**945,00**
Set 12 + 15 + 22 + 28	150005R	**977,00**
Set 15 + 18 + 22 + 28	150006R	**977,00**
Set 12 + 15 + 18 + 22 + 28	150007R	**1.110,00**
Set 12 + 14 + 16 + 18 + 22 + 28 + 32	150008R	**1.380,00**
Set 12 + 14 + 16 + 18 + 22	150010R	**1.100,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞ + 1⅛"	150017R	**1.310,00**
Set ½ + ⅝ + ⅞ + 1⅛"	150018R	**1.030,00**
Set ⅜ + ½ + ⅝ + ⅞"	150019R	**987,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞ + 1"	150020R	**1.310,00**

Accessories

Description	Pipes Ø mm/inch	Art.-No.	KM
Expander head Cu (fit expander drives of REMS Ex-Press Cu 22V ACC and other makes also)	8	150100R	**131,00**
	10	150105R	**131,00**
	12	150110R	**131,00**
	14	150120R	**131,00**
	15	150125R	**131,00**
	16	150130R	**131,00**
	18	150140R	**131,00**
	20	150145R	**184,00**
	22	150150R	**131,00**
	24	150155R	**210,00**
	25	150160R	**184,00**
	26	150165R	**157,00**
	28	150170R	**157,00**
	30	150175R	**210,00**
	32	150180R	**157,00**
	34	150185R	**210,00**
	35	150190R	**210,00**
	36	150195R	**210,00**
	40	150205R	**210,00**
	42	150210R	**184,00**
	⅜"	150220R	**131,00**
	½"	150225R	**131,00**
	⅝"	150230R	**131,00**
	¾"	150235R	**157,00**
	⅞"	150240R	**157,00**
	1"	150245R	**184,00**
	1⅛"	150250R	**184,00**
Expander drive Cu (taper angle 18°)		150500R	**366,00**
Steel case with insert		150600R	**112,00**

All prices excl. VAT

REMS Ex-Press H

One-hand pipe expander

Robust, compact quality tool for expanding tubes.
For one-hand operation.

PEX tubes Serie S 5 according to ISO 4065 Ø 12 – 40 mm

German Quality Product

REMS Ex-Press H – universal up to Ø 40 mm.

Robust, compact quality tool. Super light, only 0.7 kg.

Stepped mandrels for expanding several tube dimensions, no tool change required.

Torsion-free, leveraged expander tool for effortless expanding.
For one-hand operation.

Supply format

REMS Ex-Press H. One-hand pipe expander for PEX tubes Serie S 5 according to ISO 4065 Ø 12 – 40 mm. In a carton.

	Art.-No.	KM
	150550R	**397,00**

REMS Ex-Press P

Hand tube expander

Proven quality tool for expanding tubes.

Plastic tubes, multi-layer composite tubes Ø 12 – 32 mm

German Quality Product

REMS Ex-Press P – for expanding tubes. Conical mandrel for even and concentric expanding.

Design

Robust quality tool. Torsion-free, power-transmitting expander levers with ergonomically designed handles, for effortless expanding. Conical mandrel (taper angle 18°) for even and concentric expanding. Long mandrel guidance, spring-loaded mandrel release. Also for other suitable makes of expander heads.

Expander heads for all common systems

Complete assortment of REMS expander heads P for all common compression sleeve systems (page 257). Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding.

Info

e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth

Supply format

REMS Ex-Press P Set. Hand tube expander for plastic tubes and multi-layer composite tubes Ø 12 – 32 mm. REMS Ex-Press P. Expander heads P for tubes in mm. In sturdy steel case.

Description	Compr. sleeve system	Art.-No.	KM
Set AT P 16 + 20 + 25	aquatherm SHT PB/PE-Rohre	150021R	**1.200,00**
Set AT V 16 + 20 + 25	aquatherm SHT Mehrschicht-Metall-verbundrohre	150033R	**1.200,00**
Set IV 16/17 + 20/21 + 25/26	IVT PRINETO, Würth PRINETO	150026R	**1.200,00**
Set RH HAS 17 + 20 + 25	REHAU RAUTHERM S (REHAU HAS), General Fittings Serie 3400 PEX Gold-Therm	150027R	**1.200,00**
Set RH HIS 16 + 20 + 25	REHAU RAUTITAN flex/ gas flex/pink/his, General Fittings Serie 3400 PEX, REVEL, Seppelfricke SD Sistemi Italia Neroflex, TIEMME Assialpex	150028R	**1.200,00**
Set RH MKV 16 + 20 + 25	REHAU RAUTITAN stabil/ gas stabil, General Fittings Serie 3400 PEX/AL/PEX, Seppelfricke SD Sistemi Italia Sylver	150022R	**1.200,00**
Set RH 16 + 20 + 25	REHAU RAUTHERM (série S 5), REHAU (GBR) EVERLOC	150029R	**1.200,00**
Set TC 16 + 18/20 + 25	TECE TECEflex	150025R	**1.200,00**

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads, see table page 257.

Accessories

Description	Art.-No.	KM
Expander heads P see page 257.		
Expander drive REMS Ex-Press P (taper angle 18°)	150510R	**414,00**
Steel case with insert	150600R	**112,00**

All prices excl. VAT

REMS Ex-Press 22 V ACC

Cordless pipe expander 20 kN with automatic return

Compact, handy power tool with automatic return for fast, easy expansion of pipes/rings. Li-Ion 22 V Technology. For cordless and mains operation. For trade and industry. For the building site and the workshop.

Expander Cu
for holding the REMS Cu expander heads and suitable expander heads of other makes for:

Soft copper pipes, s ≤ 1.5 mm	Ø 8 – 42 mm Ø ⅜ – 1¾"
Soft aluminium pipes, soft precision steel pipes, s ≤ 1.2 mm	Ø 8 – 42 mm Ø ⅜ – 1¾"
Soft stainless steel pipes, s ≤ 1 mm	Ø 8 – 42 mm Ø ⅜ – 1¾"

Expander P
for holding the REMS P expander heads and suitable expander heads of other makes for:

Plastic tubes, composite tubes	Ø 12 – 40 mm

Expander P-CEF
for holding the REMS P-CEF expander heads and suitable expander heads of other makes for:
Cold Expansion Fittings made of plastic (P-CEF)

Ø 16 – 40 mm
Ø ½ – 1½"
s ≤ 4.95 mm

REMS Ex-Press 22 V ACC – fast, easy electric expanding up to Ø 42 mm. With automatic return. Conical expanding mandrel for even centric expanding. E.g. REMS Ex-Press Cu 22 V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 600 expansions of soft copper pipe 15 × 1 mm with one battery charge*.

System advantage

Only **one** drive unit, optionally with **expander Cu** for holding the REMS Cu expander heads and suitable expander heads of other makes, **expander P** for holding the REMS P expander heads and suitable expander heads of other makes, **expander P-CEF** for holding the REMS P-CEF expander heads and suitable expander heads of other makes.

Expander heads for all common systems

Quick-change, without tools. Also for other suitable makes of expander tongs.
REMS expander heads Cu (page 252) with extra long segments provide an extra long muff for a perfect pipe joint in accordance with DVGW. Collar on the expander head for calibrating unround pipe ends.
REMS expander heads P (page 257) are system-specific and correspond to the requirements of the respective compression sleeve systems. Therefore, perfectly system-conformant, exact expanding.
REMS expander heads P-CEF (page 257) are system-specific and correspond to the requirements of the respective systems. Automatic, gradual expansion until reaching the given end position which is determined by the expander head.

Design

Ultra light, ultra small, ultra handy. Drive unit with battery pack weighs only 2.7 kg. Drive unit with expander only 26 cm long. Can therefore be used anywhere, free hand, over head, also in very confined spaces. Optimum weight distribution for one-hand operation. Ergonomically designed housing. LED work light for illuminating the work place. Expanding mandrel of the Cu and P expanders with conical angle 18°, expanding mandrel of the P-CEF expander with conical angle 20°, or even centric expanding. Long mandrel guide, spring-loaded mandrel recoil. Also for other suitable makes of expander heads.

Drive

High expanding force for perfect, split-second expanding. Thrust force 20 kN. Powerful electro-hydraulic drive with automatic return (ACC), with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety switch.

with automatic circuit control and charging status check

REMS Ex-Press Cu

REMS Ex-Press P

REMS Ex-Press P-CEF

German Quality Product

LED

Info

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful.
REMS Ex-Press Cu 22 V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 600 expansions, 4.4 Ah for approx. 1050 expansions, 5.0 Ah for approx. 1200 expansions, 9.0 Ah for approx. 2160 expansions of soft copper pipe 15 × 1 mm with one battery charge*.
REMS Ex-Press P 22 V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 750 expansions, 4.4 Ah for approx. 1320 expansions, 5.0 Ah for approx. 1500 expansions, 9.0 Ah for approx. 2700 expansions of REHAU RAUTITAN flex Ø 16 × 2.2 mm with one battery charge*.
REMS Ex-Press P-CEF 22 V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 200 expansions, 4.4 Ah for approx. 360 expansions, 5.0 Ah for approx. 410 expansions, 9.0 Ah for approx. 740 expansions of Uponor Quick & Easy Ø 16 × 1.8 with one battery charge*.
Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion xbattery 21.6 V, as accessory.

REMS Ex-Press 22 V ACC

Cordless pipe expander 20 kN with automatic return

Supply format

REMS Ex-Press Cu 22 V ACC Basic-Pack. Cordless pipe expander 20 kN for fast expanding of copper pipes Ø 8 – 42 mm. Electro-hydraulic drive with automatic return, with powerful 21.6 V, 380 W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6 V, 2.5 Ah battery, 220 – 240 V, 50 – 60 Hz, 70 W rapid charger. Cu expander for holding the REMS Cu expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.	KM
	575020 R220	**3.050,00**

Other voltages on request.

Supply format

REMS Ex-Press P 22 V ACC Basic-Pack. Cordless pipe expander 20 kN for fast expanding of plastic and composite tubes Ø 12 – 40 mm. Electro-hydraulic drive with automatic return, with powerful 21.6 V, 380 W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6 V, 2.5 Ah battery, 220 – 240 V, 50 – 60 Hz, 70 W rapid charger. P expander for holding the REMS P expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.	KM
	575021 R220	**3.050,00**

Other voltages on request.

e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth

Supply format

REMS Ex-Press P-CEF 22 V ACC Basic-Pack. Cordless pipe expander 20 kN for fast expanding of plastic tubes Ø 16 – 40 mm. Electro-hydraulic drive with automatic return, with powerful 21.6 V, 380 W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6 V, 2.5 Ah battery, 220 – 240 V, 50 – 60 Hz, 70 W rapid charger. P-CEF expander for holding the REMS P-CEF expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.	KM
	575022 R220	**3.050,00**

Other voltages on request.

e.g.
Brass & Fittings,
Uponor

Accessories

Description	Art.-No.	KM
REMS Ex-Press 22 V ACC drive unit, without expander, without battery	575010 R22	**2.190,00**
Expander Cu for holding the REMS Cu expander heads and suitable expander heads of other makes for: Conical angle 18°.	575252 R	**157,00**
Expander heads Cu see page 252		
Expander P for holding the REMS P expander heads and suitable expander heads of other makes for: Conical angle 18°.	575253 R	**157,00**
Expander heads P see page 257.		
Expander P-CEF for holding the REMS P-CEF expander heads and suitable expander heads of other makes for: Conical angle 20°.	575256 R	**157,00**
Expander heads P-CEF see page 257.		
Expander tongs P-CEF (conical angle 20°), for accommodating the expander heads P-CEF 16 – 40 mm, ½ – 1½"	150515 R	**414,00**
Battery Li-Ion 21.6 V, 2.5 Ah	571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah	571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah	571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah	571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567 R220	**838,00**
Steel case with insert	578290 R	**223,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111		

All prices excl. VAT

*Ambient temperature approx. 20°C.

REMS Power-Ex-Press P-CEF ACC

Electro-hydraulic pipe expander 34 kN
with automatic return

Compact, handy power tool for fast, easy expanding of pipes/rings. For trade and industry. For the building site and the workshop.

Cold Expansion Fittings made of plastic (P-CEF)
Ø 16 – 63 mm
Ø ½ – 2"
s ≤ 6.3 mm

with automatic circuit control

REMS Power-Ex-Press P-CEF ACC – Fast, easy electric expanding up to Ø 63 mm. With automatic return. For Uponor Quick & Easy and Giacomini GX System.

Expander heads

Large expanding capacity up to Ø 63 mm. Automatic, gradual expansion until reaching the given end position which is determined by the expander head. Use of the REMS P-CEF expander heads and suitable expander heads of other makes for: Expander 50 – 63 mm, 2", for holding the REMS P-CEF expander heads 50 – 63 mm, 2" and suitable expander heads of other makes. Expander 16 – 40 mm, ½ – 1½", for holding the REMS P-CEF expander heads 16 – 40 mm, ½ – 1½" and suitable expander heads of other makes, as an accessory.

Execution

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.6 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip.

Drive

High pressing force for fast, perfect expanding. Thrust force 34 kN. Powerful electro-mechanical drive with automatic return (ACC), with proven universal motor, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle. Safety tip switch.

German Quality Product

Info

Supply format

REMS Power-Ex-Press P-CEF ACC Basic-Pack. Electro-hydraulic pipe expander 34 kN for expanding tubes/coils of the Uponor Quick & Easy system Ø 16 – 63 mm, Ø ½ – 2", s ≤ 6.3 mm. Electro-hydraulic drive with automatic retraction, ith proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Expanding device 50 – 63 mm, 2". Without expander heads. In sturdy steel case.

	Art.-No.	KM
	575017R220	**2.960,00**

Note assembly instructions of system supplier. Battery tube expander for other systems on request. Other voltages on request.

Accessories

Description	Art.-No.	KM
Expander 16 – 40 mm, ½ – 1½", for holding the P-CEF expander heads 16 – 40 mm, ½ – 1½"	575100R	**248,00**
Expander heads P-CEF see page 257.		
Steel case with insert	575278R	**223,00**

All prices excl. VAT

REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 253), REMS Ex-Press P 22 V ACC cordless pipe expander (page 254 – 255) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P Ø × s	Art.-No.	KM
aquatherm grey pipe PB/PE-RT-Rohre	AT P 14 × 2,0	150828	**244,00**
	AT P 16 × 2,0	150842	**244,00**
	AT P 18 × 2,0	150873	**244,00**
	AT P 20 × 2,0	150882	**244,00**
	AT P 25 × 2,3	150912	**244,00**
aquatherm grey pipe Mehrschicht-Metallverbundrohre (MVR)	AT V 16 × 2,4	150843	**244,00**
	AT V 20 × 2,4	150883	**244,00**
	AT V 25 × 2,7	150913	**244,00**
	AT V 32 × 3,2	150957	**263,00**
	AT V 40 × 3,5	150958	**288,00**
General Fittings Serie 3400 PEX Gold-Fix	RH HIS 16 × 2,2	150849	**244,00**
	RH HIS 20 × 2,8	150888	**244,00**
	RH HIS 25 × 3,5	150916	**244,00**
	RH HIS 32 × 4,4	150945	**244,00**
General Fittings Serie 3400 PEX/AL/PEX Gold-Fix	RH MKV 16,2 × 2,6	150858	**244,00**
	RH MKV 20 × 2,9	150897	**244,00**
	RH MKV 25 × 3,7	150926	**244,00**
	RH MKV 32 × 4,7	150952	**244,00**
General Fittings Serie 3400 PEX Gold-Therm	RH HAS 17 × 2,0	150868	**244,00**
	RH HAS 20 × 2,0	150887	**244,00**
HERZ QUICK FIX	HC P 16 × 2,0	150806	**244,00**
	HC P 20 × 2,0	150807	**244,00**
	HC P 26 × 3,0	150808	**244,00**
	HC P 32 × 3,0	150809	**244,00**
IVT PRINETO	IV 16 × 2,2/17 × 2,8	150845	**244,00**
	IV 20 × 2,8/21 × 3,4	150885	**244,00**
	IV 25 × 3,5/26 × 4,0	150914	**244,00**
	IV 32 × 4,4/33 × 4,9	150943	**263,00**
REHAU RAUTHERM (série S 5)	RH 12 × 1,1	150812	**244,00**
	RH 16 × 1,5	150846	**244,00**
	RH 20 × 1,9	150886	**244,00**
	RH 25 × 2,3 (RH HAS 25 × 2,3)	150915	**244,00**
	RH 32 × 2,9 (RH HAS 32 × 2,9)	150944	**244,00**
REHAU RAUTHERM S (REHAU HAS)	RH HAS 17 × 2,0	150868	**244,00**
	RH HAS 20 × 2,0	150887	**244,00**
	RH HAS 25 × 2,3	150915	**244,00**
	RH HAS 32 × 2,9	150944	**244,00**
REHAU RAUTITAN flex/ RAUTITAN gas flex/ RAUTITAN pink/ RAUTITAN his	RH HIS 16 × 2,2	150849	**244,00**
	RH HIS 20 × 2,8	150888	**244,00**
	RH HIS 25 × 3,5	150916	**244,00**
	RH HIS 32 × 4,4	150945	**244,00**
	RH HIS 40 × 5,5	150946	**263,00**
REHAU RAUTITAN stabil/ RAUTITAN gas stabil	RH MKV 16,2 × 2,6	150858	**244,00**
	RH MKV 20 × 2,9	150897	**244,00**
	RH MKV 25 × 3,7	150926	**244,00**
	RH MKV 32 × 4,7	150952	**244,00**
	RH MKV 40 × 6,0	150947	**263,00**
REHAU (GBR) EVERLOC	RH 16 × 1,5	150846	**244,00**
	RH 20 × 1,9	150886	**244,00**
	RH 25 × 2,3 (RH HAS 25 × 2,3)	150915	**244,00**
	RH 32 × 2,9 (RH HAS 32 × 2,9)	150944	**244,00**
REVEL	RH HIS 16 × 2,2	150849	**244,00**
	RH HIS 20 × 2,8	150888	**244,00**
	RH HIS 25 × 3,5	150916	**244,00**
	RH HIS 32 × 4,4	150945	**244,00**
Seppelfricke SD Sistemi Italia Neroflex	RH HIS 16 × 2,2	150849	**244,00**
	RH HIS 20 × 2,8	150888	**244,00**
	RH HIS 25 × 3,5	150916	**244,00**
	RH HIS 32 × 4,4	150945	**244,00**
Seppelfricke SD Sistemi Italia Sylver	RH MKV 16,2 × 2,6	150858	**244,00**
	RH MKV 20 × 2,9	150897	**244,00**
	RH MKV 25 × 3,7	150926	**244,00**
	RH MKV 32 × 4,7	150952	**244,00**
TECE TECEflex	TC 12/14	150826	**244,00**
	TC 16	150855	**244,00**
	TC 18/20	150894	**244,00**
	TC 25	150923	**244,00**
	TC 32	150950	**244,00**
TIEMME Assialpex	RH HIS 16 × 2,2	150849	**244,00**
	RH HIS 20 × 2,8	150888	**244,00**
	RH HIS 25 × 3,5	150916	**244,00**
	RH HIS 32 × 4,4	150945	**244,00**

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.

Choose expander heads yourself!

Search for the required compression sleeve system in the table below and select the correct expander heads.



German Quality Product

REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 253), REMS Ex-Press P 22 V ACC cordless pipe expander (page 254 – 255) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P Ø × s	Art.-No.	KM
Würth PRINETO	IV 16 × 2,2/17 × 2,8	150845	**244,00**
	IV 20 × 2,8/21 × 3,4	150885	**244,00**
	IV 25 × 3,5/26 × 4,0	150914	**244,00**
	IV 32 × 4,4/33 × 4,9	150943	**263,00**

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.

REMS expander heads P-CEF

Full range of REMS P-CEF expander heads for easy expanding of pipes/rings. Quick-change, without tools. The REMS P-CEF expander heads are system-specific and correspond to the requirements of the respective systems. Therefore, perfectly system-conformant, exact expanding. Conical angle 20°. Driven by REMS Ex-Press P-CEF 22 V ACC cordless pipe expander (page 254 – 255), REMS Power-Ex-Press P-CEF ACC electro-hydraulic pipe expander (page 256) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P-CEF Ø × s	Art.-No.	KM
Uponor Quick & Easy	P-CEF 16 × 1.8	150960R	**263,00**
	P-CEF 20 × 1.9	150961R	**263,00**
	P-CEF 25 × 2.3	150962R	**263,00**
	P-CEF 32 × 2.9	150963R	**263,00**
	P-CEF 40 × 3.7	150968R	**288,00**
Expander drive P-CEF (taper angle 20°), for holding the P-CEF expander heads 16 – 40 mm, ½ – 1½"		150515R	**414,00**

System-related and/or national differences of the wall thickness s of the pipes must be considered in the selection of the expander heads.

REMS Hurrican H

Hand tube extractor

Economic manual tool for efficiently making T-branches for pipe installations without fittings.

Hard and soft copper tubes	Ø 10 – 22 mm Ø ⅜ – ⅞" s ≤ 1.5 mm

German Quality Product

REMS Hurrican H – for making T-branches yourself. Inexpensive. Also on tubes already installed.

System advantage
Only **one** type of extractor tools for REMS Hurrican H, REMS Hurrican and REMS Twist/Hurrican. Simple, inexpensive storage. No confusion possible.

Cost advantage
No costs for T-pieces, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety by fewer tube joints.

Design
Compact, handy, light. Can be used anywhere, free-hand, on pipes already installed. Drill head for exact drilling start without centre punching, drilling depth stop according to size of the T-outlet. Limitation of insertion depth to avoid obstruction by using the dimpling pliers. Handy gripping tongs for fixing the tool holder on the pipe, as an accessory.

Drill head drive
Drive with conventional electric drill.

Extractor tools
Special design of extractor tools facilitate even and smooth material deformation without burrs and notches. Therefore no secondary treatment required.

Tool holder drive
With standard ratchet and hexagon socket 11 mm or with spanner. Upgrade to electric pipe neck expander by buying the REMS Twist/Hurrican drive machine.

Info

Supply format

REMS Hurrican H Set. Hand tube extractor for hard and soft copper tubes Ø 10 – 22 mm, Ø ⅜ – ⅞", s ≤ 1.5 mm. Tool holder, drill head, dimpling pliers, lubricant. Extractor tools for tubes in mm or inch. In sturdy case.

Description	Art.-No.	KM
Set 12 + 15 + 18 + 22	151003R	**1.120,00**
Set 12 + 14 + 16 + 18 + 22	151004R	**1.240,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞"	151005R	**1.290,00**

Accessories

Description	Tubes Ø mm/inch	Art.-No.	KM
Extractor tool	10	151105R	**138,00**
	12	151110R	**138,00**
	14	151120R	**138,00**
	15	151125R	**138,00**
	16	151130R	**138,00**
	18	151140R	**138,00**
	20	151145R	**138,00**
	22	151150R	**138,00**
	⅜"	151155R	**146,00**
	½"	151160R	**142,00**
	⅝"	151165R	**142,00**
	¾"	151170R	**142,00**
	⅞"	151175R	**142,00**
REMS Twist/Hurrican drive unit with stabiliser		151402R220	**752,00**
Grip wrench for clamping the tool holder		076117	**223,00**
Tool holder		151200R	**173,00**
Drill head		151210RMM	**259,00**
Dimpling pliers		151230R	**81,90**
Ratchet ½"		074021	**156,00**
Hexagon socket 11 mm		074041	**15,80**
Lubricant (tin)		151240	**18,90**
Case with inlay		151618R	**110,00**

All prices excl. VAT

REMS Hurrican

Electric tube extractor

Powerful, compact electric tool for efficient machining of T-branches of hard and soft tubes for tube installations without fittings.

Hard and soft copper tubes	Ø 10 – 22 mm Ø ⅜ – ⅞" s ≤ 1.5 mm

German Quality Product

Info

REMS Hurrican – for making T-branches yourself. Inexpensive. Also on tubes already installed.

System advantage

Only **one** type of extractor tools for REMS Hurrican H, REMS Hurrican and REMS Twist/Hurrican. Simple, inexpensive storage. No confusion possible.

Cost advantage

No costs for T-branches, storage, procurement. Savings in soldering joints, soldering material and working hours. Higher safety by fewer tube joints.

Design

Compact, handy, light. Can be used anywhere, free-hand, on pipes already installed. Drill head provides precise drilling without punching with any standard power drill. Drill depth-stop according to the size of T-branch. Tool holder for holding the extractor tools. Limitation of insertion depth to avoid obstruction by using the dimpling pliers. Handy grip wrench for clamping the tool holder onto the pipe.

Drive

Proven drive unit with hexagon mount. Enormously powerful. Handly, light, only 1.5 kg. Can be used anywhere, free-hand, also on pipes already installed. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. Stepless, electronic speed control. The speed can be continuously controlled electronically by variable pressure on the safety switch from 0 to 1,000 rpm (accelerator switch).

Extractor tools

Special design of extractor tools facilitate even and smooth material deformation without burrs and notches. Therefore no secondary treatment required.

REMS Twist/Hurrican

Space and weight-saving combination set for efficient production of T-branches and for efficient cold-expanding of hard and soft tubes for installations without fittings. Only one drive unit for expanding and extracting tools. Price advantage!
See page 261.

Supply format

REMS Hurrican Set. Electric tube extractor for hard and soft copper tube Ø 10 – 22 mm, Ø ⅜ – ⅞", s ≤ .5 mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50 – 60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Safety tip switch. Continuous, electronic speed control from 0 to 1,000 rpm (accelerator switch). Drive holder. Tool holder, drill head, dimpling pliers, lubricant. Extractor tools for pipes in mm or inch. In sturdy steel case.

Description	Art.-No.	KM
Set 12 + 15 + 18 + 22	151000R220	**2.000,00**
Set 12 + 14 + 16 + 18 + 22	151010R220	**2.120,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞"	151002R220	**2.150,00**

Other voltages on request.

Accessories

Description	Tubes Ø mm/inch	Art.-No.	KM
Extractor tool	10	151105R	**138,00**
	12	151110R	**138,00**
	14	151120R	**138,00**
	15	151125R	**138,00**
	16	151130R	**138,00**
	18	151140R	**138,00**
	20	151145R	**138,00**
	22	151150R	**138,00**
	⅜"	151155R	**146,00**
	½"	151160R	**142,00**
	⅝"	151165R	**142,00**
	¾"	151170R	**142,00**
	⅞"	151175R	**142,00**
REMS Twist/Hurrican drive unit with stabiliser		151402R220	**752,00**
Tool holder		151200R	**173,00**
Drill head		151210RMM	**259,00**
Dimpling pliers		151230R	**81,90**
Lubricant (tin)		151240	**18,90**
Case with inlay		151618R	**110,00**

REMS Twist

Electric tube expander

Powerful, compact power tool for rational cold expanding of hard and soft copper pipes for pipe installation without fittings.

Hard and soft copper tubes	Ø 12 – 22 mm Ø ⅜ – ⅞" s ≤ 1 mm

German Quality Product

Info

REMS Twist – for making sockets yourself. Cold-expanding of hard copper pipes.

Cost advantage
No costs for annealing hard copper tubes, for deburring and cleaning, for fittings, storage, procurement. Savings in soldering joints, soldering material and working hours. Higher safety by fewer tube joints. Using up tube pieces to make sockets.

Design
Compact, robust, job site-proven. Simple and fast working free-hand, at vice or workbench. No adjustments. Integrated clamping device provides safe support against torque in both directions.

Drive
Proven drive unit with hexagon mount. Enormously powerful. Handly, light, only 1.5 kg. Can be used anywhere, free-hand, also on pipes already installed. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. The speed can be continuously controlled electronically by variable pressure on the safety switch from 0 to 1,000 rpm (accelerator switch).

Expander tools
One quick-changing expander tool of each tube size with rotating mandrel for easy expanding and smooth operation. Without annealing, standard socket in just a few seconds, extra long.

REMS Twist/Hurrican
Space and weight-saving combination set for efficient production of T-branches and for efficient cold-expanding of hard and soft tubes for installations without fittings. Only one drive unit for expanding and extracting tools. Price advantage!
See page 261.

Supply format

REMS Twist Set. Electric tube expander for hard and soft copper tubes Ø 12 – 22 mm, Ø ⅜ – ⅞", s ≤ 1 mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50 – 60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Safety tip switch. Continuous, electronic speed control from 0 to 1,000 rpm (accelerator switch).. Drive holder. Lubricant. Expander tools for mm or inch. In sturdy steel case.

Description	Art.-No.	KM
Set 12 + 15 + 18 + 22	156000R220	**2.190,00**
Set 12 + 14 + 16 + 18 + 22	156002R220	**2.520,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞"	156004R220	**2.520,00**

Other voltages on request.

Accessories

Description	Tubes Ø mm/inch	Art.-No.	KM
Expander tool	12	156150	**351,00**
	14	156200	**351,00**
	15	156225	**351,00**
	16	156250	**351,00**
	18	156300	**351,00**
	22	156350	**351,00**
	⅜"	156375	**351,00**
	½"	156400	**351,00**
	⅝"	156425	**351,00**
	¾"	156450	**351,00**
	⅞"	156475	**351,00**
REMS Twist/Hurrican drive unit with stabiliser		151402R220	**752,00**
Lubricant (tin)		151240	**18,90**
Steel case with insert		151600R	**223,00**

All prices excl. VAT

REMS Twist/Hurrican

Electric tube extractor
Electric tube expander

Powerful, compact power tool for rational manufacture of T-joints and rational cold expanding of hard and soft copper pipes for pipe installation without fittings. Combination of REMS Twist and REMS Hurrican.

Extracting:	
Hard and soft copper tubes	Ø 10 – 22 mm Ø ⅜ – ⅞" s ≤ 1.5 mm
Expanding:	
Hard and soft copper tubes	Ø 12 – 22 mm Ø ⅜ – ⅞" s ≤ 1 mm

REMS Hurrican for making T-branches yourself. Inexpensive. Also on tubes already installed.

REMS Twist for making sockets yourself. Cold-expanding of hard copper tubes.

Space and weight saving combi set. Only **one** drive unit for expander and extractor tools. Price advantage!

Description see REMS Hurrican and REMS Twist (page 259 – 260).

German Quality Product

Info

Supply format

REMS Twist/Hurrican Combi Set. Electric tube expander and electric tube extractor for hard and soft copper tubes. Expanding Ø 12 – 22 mm, Ø ⅜ – ⅞", s ≤ 1 mm, extracting Ø 10 – 22 mm, Ø ⅜ – ⅞", s ≤ 1.5 mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50 – 60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Stepless, electronic safety switch. Drive holder. Tool holder, drill head, dimpling pliers, lubricant. Choice of expander and extractor tools for pipes in mm or inch. In sturdy steel case.

Description	Art.-No.	KM
Set 12 + 15 + 18 + 22	156010R220	**3.120,00**
Set 12 + 14 + 16 + 18 + 22	156012R220	**3.610,00**
Set ⅜ + ½ + ⅝ + ¾ + ⅞"	156014R220	**3.720,00**

Other voltages on request.

Accessories

Description	Tubes Ø mm/inch	Art.-No.	KM
Expander tool	12	156150	**351,00**
	14	156200	**351,00**
	15	156225	**351,00**
	16	156250	**351,00**
	18	156300	**351,00**
	22	156350	**351,00**
	⅜"	156375	**351,00**
	½"	156400	**351,00**
	⅝"	156425	**351,00**
	¾"	156450	**351,00**
	⅞"	156475	**351,00**
Extractor tool	10	151105R	**138,00**
	12	151110R	**138,00**
	14	151120R	**138,00**
	15	151125R	**138,00**
	16	151130R	**138,00**
	18	151140R	**138,00**
	20	151145R	**138,00**
	22	151150R	**138,00**
	⅜"	151155R	**146,00**
	½"	151160R	**142,00**
	⅝"	151165R	**142,00**
	¾"	151170R	**142,00**
	⅞"	151175R	**142,00**
REMS Twist/Hurrican drive unit with stabiliser		151402R220	**752,00**
Tool holder		151200R	**173,00**
Drill head 10 – 22 mm		151210RMM	**259,00**
Drill head ⅜ – ⅞"		151210RMM	**259,00**
Dimpling pliers		151230R	**81,90**
Lubricant (tin)		151240	**18,90**
Steel case with insert		151600R	**223,00**



Soldering

	Cleaning pads	264
	Electric soldering pliers	264
	Electric soldering unit	265
	Turbo soldering torches	266
	Solder wire and solder paste	267

REMS Cu-Vlies

Cleaning pads

Metal-free, highly flexible cleaning pads for cleaning surfaces to be soldered on copper tubes and soldering fittings. Also for other materials.

REMS Cu-Vlies – clean surfaces according to DVGW.

Universal use, for many materials, highly flexible. Cleans metallic clear, dirt and oxide-free, according to DVGW work sheet GW 2. Clean finish. Multiple use, reusable by washing out, thus long service life. Can be used wet or dry.

German Quality Product

Supply format

REMS Cu-Vlies. Metal-free, highly flexible cleaning pad for cleaning areas to be soldered on copper pipes and soldering fittings. Pack of 10.

	Art.-No.	KM
	160300R	**20,80**

REMS Hot Dog 2

Electric soldering pliers

Efficient, light-weight electric tool for soft soldering. Directly connected to a socket, no transformer required. For trade and industry. For the building site and the workshop.

Copper tubes	Ø 10 – 28 mm Ø ⅜ – 1⅛"
Heating capacity	800°C

REMS Hot Dog 2 – the smallest and most powerful soldering pliers. Super fast without flame.

Super fast soldering, e.g. Ø 18 mm in only 15 s. Enormous heating capacity up to 800°C through 2 heating cartridges. For permanent use.

Super light and handy, complete only 0.7 kg. Can be used anywhere, in confined areas also.

German Quality Product

Info

Supply format

REMS Hot Dog 2 Set. Electric soldering pliers for soft soldering copper tubes Ø 10 – 28 mm, Ø ⅜ – 1⅛". 230 V, 50 – 60 Hz, 440 W. 250 g REMS Lot Cu 3 and REMS Paste Cu 3. Cleaning brush. In steel case with fire retarding insert.

	Art.-No.	KM
	163020R220	**922,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS soldering material see page 267.		
Steel case with fire-proof inlay	163350R	**156,00**

All prices excl. VAT

REMS Contact 2000

Electric soldering unit

Compact, powerful electric tool for soft soldering.
With safety transformer. For trade and industry.
For the building site and the workshop.

Copper tubes	Ø 6 – 54 mm Ø ¼ – 2⅛"
Heating capacity	900°C (1650°F)

REMS Contact 2000 – the smallest, strongest and fastest unit of its kind. 2000 W soldering power. 4 m long soldering tongs cable.

Handy, compact. Favourable weight, small in size for work and transport. L × W × H: 210 × 150 × 140 mm.

Enormous heating capacity (900°C) ensures super-fast soldering. Rated power = Soldering capacity = 2000 W! Soldering time, e.g. for Ø 18 mm in only 18 s.

Can be used anywhere, with rod electrodes in tight spots also. Ready to solder any time, to be connected to a socket only. No adjustment of soldering current necessary. Wide work radius thanks to 4 m cable length. Flexible cable protector hose.

Indifferent to temperature influences electric control of soldering current.

Prisma-electrodes for universal use, maximum use through favorable seat. Rod-electrodes for working in tight spots. Electrode holders and bolts in stainless steel. Electrodes can be easily replaced.

German Quality Product

Info

Prisma-electrodes for universal use, maximum use through favorable seat.

Supply format

REMS Contact 2000. Electric soldering unit for soft soldering of copper tubes Ø 6 – 54 mm, Ø ¼ – 2⅛". 230 V, 50 – 60 Hz, 2000 W, control voltage 24 V. Soldering pliers with 4 m cable length. Safety transformer, 2 prism electrodes. In a carton.

	Art.-No.	KM
	164011 R220	**1.620,00**

Other voltages on request.

Supply format

REMS Contact 2000 Super-Pack. Electric soldering unit for soft soldering of copper tubes Ø 6 – 54 mm, Ø ¼ – 2⅛". 230 V or 110 V, 50 – 60 Hz, 2000 W, control voltage 24 V. Soldering pliers with 4 m cable length, safety transformer, 4 prism electrodes, 2 rod electrodes, 250 g quality soft solder REMS Lot Cu 3, 250 g quality soft solder paste REMS Paste Cu 3, 1 pipe cutter REMS RAS Cu-INOX 3-35, pack of 10 cleaning pads REMS Cu-Vlies. In sturdy steel case.

	Art.-No.	KM
	164050 R220	**2.020,00**

Accessories

Description	Art.-No.	KM
Prism electrodes (pack of 2)	164111 R	**51,50**
Prism electrodes with holders (pack of 2)	164110 R	**86,50**
Rod electrodes (pack of 2)	164115 R	**53,60**
Steel case with insert	164250 R	**261,00**
REMS soldering material see page 267.		

REMS Blitz

Turbo soldering torch propane

Handy self-lighting torch with turbo-flame for fast soft soldering and economic gas consumption.	
Copper tubes	≤ Ø 35 mm
Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.	
Flame temperature	1950°C (3500°F)

German Quality Product

Info

REMS Blitz – extremely fast soft soldering.

Piezo-electric self-lighting
Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 200 g/h!

Design
Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube. Small gas bottles can be used.

Turbo-flame
Spot-flame with turbo-twisting-booster for high heating capacity and super fast soft soldering.

Supply format

REMS Blitz. Turbo soldering torch propane for soft soldering of copper tubes ≤ Ø 35 mm. Piezo-electric self-lighting. Hose connector BSPP ⅜" LH. Hollow cap nut and socket BSPP ⅜" LH. In blister pack.

	Art.-No.	KM
	160010R	**494,00**

Accessories

Description	Art.-No.	KM
REMS soldering material see page 267.		
High pressure hose 3 m, BSPP ⅜ LH	152106	**183,00**
Pressure reducer for 5 or 11 kg gas bottles (2 bar)	152109	**236,00**

REMS Macho

Turbo soldering torch acetylene

Handy self-lighting torch with turbo-flame for extremely fast brazing and soft soldering. Economic gas consumption.	
Copper tubes and others	≤ Ø 64 mm
Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.	
Flame temperature	2500°C

German Quality Product

Info

REMS Macho – super fast brazing.

Piezo-electric self-lighting
Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 360 g/h!

Acetylene only
Injection torch burns atmospheric oxygen. Hence only acetylene necessary.

Design
Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube.

Turbo-flame
Spot-flame with turbo-twisting-booster for extremely high heating capacity and super fast brazing.

Supply format

REMS Macho. Turbo soldering torch acetylene for brazing and soft soldering of copper tubes and others ≤ Ø 64 mm. Piezo-electric self-lighting. Hose connector BSPP ⅜" LH. Hollow cap nut and socket ⅜" LH. In blister pack.

	Art.-No.	KM
	161010R	**544,00**

Accessories

REMS soldering material see page 267.

All prices excl. VAT

REMS Lot Cu 3

Soft solder Sn97Cu3, ISO 9453:2014

Soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation ≤ 110°C (230°F).

In accordance with DVGW work sheet GW 2.

Alloy (weight %)	97 % Sn, 3 % Cu
Melting temperature	230 – 250°C (450 – 480°F)

German Quality Product

REMS Lot Cu 3 – quality soft solder.

Lead-free, harmless to health and environment.
Silver-free, complies with standards. Very low price.

Supply format

REMS Lot Cu 3. 250-g spool soft solder wire Sn97Cu3, ISO 9453:2014, Ø 3 mm, for soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation ≤ 110°C (230°F).

	Art.-No.	KM
	160200 R	**105,00**

REMS Paste Cu 3

Soft solder paste of solder powder Sn97Cu3 according to ISO 9453:2014 and flux 3.1.1.C, EN 29454-1:1994

Soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation ≤ 110°C (230°F).

In accordance with DVGW work sheet GW 7 (DVGW-Reg.-Nr. DV-0101AT2244)

German Quality Product

REMS Paste Cu 3 – quality soft solder paste.

Lead-free, harmless to health and environment.
Silver-free, complies with standards. Very low price.

No additional flux consumption, paste contains flux already.
Thus less danger of corrosion.

No overheating of tube and fitting because the melting of solder and the required temperature for soldering is clearly visible through the change of colour of paste.

High filling level of soldering joint, thereby good stability. Easy cleaning of remnants which are soluable in cold water.

Plastic bottle with brush integrated in cap which cannot get lost.

Supply format

REMS Paste Cu 3. 250-g soft solder paste of solder powder Sn97Cu3 according ISO 9453:2014 and flux 3.1.1.C, EN 29454-1:1994, for soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation ≤ 110°C (230°F). DVGW approval mark.
In plastic bottle with integrated brush.

	Art.-No.	KM
	160210 R	**79,80**

REMS Lot P6

Brazing solder ISO 17672-CuP 179

Brazing of copper tubes with copper, red copper cast and brass fittings in cold and hot water installation, gas installation, refrigerating and air conditioning applications.

In accordance with DVGW work sheet GW 2.

Alloy (weight %)	94 % Cu, 6 % P
Melting temperature	710 – 890°C (1310 – 1640°F)

REMS Lot P6 – quality brazing solder.

Universally applicable for almost all types of joints in copper pipe installations.

Specially useful for capillary brazing joints of copper pipe installations without fittings. Wide melting range due to low phosphor content result in higher toughness of soldering joint.

Silver-free, complies with standards. Very low price.

Supply format

REMS Lot P6. 1 kg brazing solder (rods) ISO 17672-CuP 179, ⌀ 2 mm, for brazing of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, gas installation, refrigerating and air conditioning applications. In a carton.

	Art.-No.	KM
	160220 R	**125,00**

Freezing

	Pipe freezer CO_2	**270**
	Electric pipe freezing unit	**271**

REMS Eskimo

Pipe freezer

Simple, fast freezing of unemptied pipes with a carbon dioxide coolant. For repair, extensions of piping systems.

Steel, copper, plastic, composite pipes
Ø ⅛ – 2"
Ø 10 – 60 mm

Refrigerant: carbon dioxide.

Refrigerating capacity to –79°C (–110°F).

Non toxic, non flammable.

REMS Eskimo – freezing instead of draining.
Super fast. Automatic refrigerant feed. High cooling capacity, e.g. ¾" steel pipe in only 5 min.
Very small, indestructible freeze collars.

Refrigerant
Carbon dioxide coolant with high cooling performance up to –79°C. Non toxic. Non flammable. Easy to obtain.

Design
Tight contact between freeze collars and pipe and direct flow of the refrigerant onto the pipe ensure extremely short freezing times and economic refrigerant consumption. Freezing is possible on one or two sides, with additional T-distributors further freeze collars can also be connected.

Freeze collars
Easy. Rapid assembly, without special tools. Very small, highly flexible, indestructible freeze collars in cold-resistant thermoplastic elastomer, for operating even in the tightest spots. Clamping screws cannot get lost.

Handle piece with injector
Ergonomically designed handle pieces in plastic for comfortable operation. Unbreakable brass injector (injection nozzle). Fast and secure connection to freeze collars. No setting, the correct amount of refrigerant is automatically supplied.

High pressure hoses
Flexible, buckling-resistant and fractureproof high pressure hoses. Extra long for wide work radius. Extendable any time. Turnable hollow cap nut at bottle connector prevents high pressure hoses from tangling.

German Quality Product

Info

Supply format

REMS Eskimo Set. Pipe freezing device for carbon dioxide coolant. For steel, cast iron, lead, copper, plastic pipes Ø ⅛ – 2", Ø 10 – 60 mm. Two freezing jackets each in 10 different sizes for the whole working range, flange connection with T-junction, locking nut, 2 handles with injector, 2 high-pressure hoses. In sturdy carrying case.

	Art.-No.	KM
	130002R	**1.210,00**

Accessories

Description	Size		Art.-No.	KM
Freezing jacket	⅛"	10/12 mm	130450	**81,70**
	¼"	15 mm	130455	**81,70**
	⅜"	18 mm	130460	**81,70**
	½"	22 mm	130465	**81,70**
	¾"	28 mm	130470	**81,70**
	1"	35 mm	130475	**81,70**
	1¼"	42 mm	130480	**109,00**
	1½"		130485	**109,00**
		54 mm	130490	**109,00**
	2"	60 mm	130495	**109,00**
High-pressure hose 2 m			130415	**233,00**
T-distributor for further collar			130207	**51,50**
Bottle connection with T-distributor			130383	**95,40**
Locking nut			130209	**12,60**
Double nipple			130208	**19,60**
Handle piece with injector			130410	**113,00**
Case with inlay			130430R	**206,00**

All prices excl. VAT

REMS Frigo 2 F-Zero

Electric pipe freezing unit

Easy, fast freezing of pipes which are not drained.
Closed refrigerant circuit. Environmentally safe.
For repair and extension of piping systems.

Steel, copper, plastic,
composite pipes
Ø ⅛ – 2"
Ø 10 – 60 mm

REMS Frigo 2 F-Zero – electrically freezing instead of draining. Super fast up to 2". High cooling capacity, e.g. ¾" steel pipe in only 9 min*. Particularly compact, patented deep-freezer heads, for very fast assembly. Temperature display with LCD digital thermometer.

System advantage
Only one pipe freezing unit for the complete working range up to 2". One-size freezer heads for the core working range Ø ¼ – 1" / Ø 15 – 35 mm, no reducing inserts required. Aid the cooling process simply by spraying with water. Always clean freezer heads, no pastes/greases required.

Closed refrigerant circuit
Electric pipe freezing unit with closed refrigerant circuit. Environmentally safe. Can be used anywhere, also in closed rooms. Refrigerant R-290. High cooling capacity. Ideal also for longer repairs.

Design
Robust, compact. Very small deep-freezer heads fitted parallel to the pipe leaving refrigerant hoses for working in confined areas and niches also. Single or double freezing possible.

Cooling aggregate
Very quiet. Cooling aggregate, 430 W, in sturdy sheet metal housing with ventilating side openings for optimum air circulation. Large top compartment, easily accessible, for refrigerant hoses and accessories. Weighs only 23 kg. Easy to carry.

Deep-freezer heads
Very compact deep-freezer heads with special geometrically shaped cavities for seating different pipe diameters. Very small, only 50 mm wide. All pipe sizes from Ø ¼ – 1" resp. Ø 15 – 35 mm can be frozen with only one deep-freezer head. Deep-freezer inserts for the rest of the capacity up to 2", 60 mm. Tightening straps for simple and quick assembly of deep-freezer heads onto the pipe, without tools.

Refrigerant hoses
Flexible, extra-long refrigerant hoses, 2.5 m long, in wear resistant, synthetic rubber for large work radius.

LCD-Digital-Thermometer
LCD digital thermometer with clip, for exact temperature display directly at the freezing points.

German Quality Product

Info



Super fast up to 2"

R-290

Supply format

REMS Frigo 2 F-Zero Set. Electric pipe freezing unit with closed refrigerant circuit. For steel, copper, plastic, composite pipes, Ø ⅛ – 2", Ø 10 – 60 mm. Cooling aggregate 230 V or 110 V, 50 Hz, 430 W, 2 refrigerant hoses, 2.5 m long, 2 LCD digital thermometers, 2 tightening straps, squirt bottle. Equipped for Ø ¼ – 1¼", 15 – 42 mm. In sturdy sheet metal housing. In a carton.

	Art.-No.	KM
	131012R220	**3.760,00**

Accessories

Description	Size	Art.-No.	KM
Extension kit up to 2", 60 mm	1½ – 2" / 54 – 60 mm	131160R	**523,00**
Deep-freeze inserts (pack of 2)	⅛" 10, 12 mm	131110R	**190,00**
	1½"	131156R	**175,00**
	54 mm	131157R	**175,00**
	2" 60 mm	131158R	**175,00**
Clamping band		131104R	**30,90**
LCD digital thermometer		131116R	**77,50**

All prices excl. VAT

*ambient/water temperature approx. 18°C.

2023.10.25 15:14:00 PM
X 1.0
10 m
REMS CamSys 2

Pipe and Drain inspection
Pipe and Drain cleaning

	Endoscope cameras	274
	Electronic camera inspection systems	276
	Drain cleaner for manual and electric operation	282
	Electric drain cleaning machine	283
	Cordless drain cleaning machine	284
	Electric pipe and drain cleaning machines	286

REMS MiniScope

Endoscope camera

Mobile, handy endoscope camera for low-cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes, etc. For cordless operation.

Camera head	Ø 8 mm

REMS MiniScope – Brilliant pictures of cavities, shafts and pipes.

Design

Ultra light and handy. Controller unit with camera cable set only 0.4 kg. Can be used everywhere, free hand, over head, also in very confined spaces Sturdy, impact-proof plastic housing with ergonomically shaped handle. The buttons are located directly underneath the display so that it is possible to hold the device by the handle and operate the buttons with one hand. On/Off button, button for rotating, mirroring of the image by 180° respectively, button for regulating the brightness of the LEDs in the camera head in 8 stages, button for regulating the brightness of the colour display in 8 stages. Power LED for indicating the operating state. Battery compartment for 4 commercially available 1.5 V, AA, LR6 batteries. Plug-screw connections for changing the camera cable set without tools. Sturdy case for controller unit, camera cable set 8-1 and accessories.

Controller unit with TFT-LCD colour display

Controller unit with 2.3" colour display with state of the art TFT-LCD technology for brilliant pictures, 320 × 240 pixels.

Battery operation

Controller unit with four 1.5 V, AA, LR6 batteries for approx. 6 hours of continuous operation.

Exchangeable camera cable set Color

Camera cable set Color 8-1, consisting of colour camera Ø 8 mm (640 × 480 pixels), with CMOS sensor, with dimmable white light LEDs for optimum setting of the brightness and fixed focus function, for automatic picture focus, protected against occasional immersion in water (IP 67), 1 m flexible push cable and add-on mirror, add-on hook, add-on magnet.

×2

Info

Supply format

REMS MiniScope Set. Mobile, handy endoscope camera for low cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes etc. Controller unit with 2.3" TFT-LCD colour display. 4 batteries 1.5 V, AA, LR6. Camera cable set Color 8-1 with 1 m flexible push cable and add-on mirror, add-on hook, add-on magnet. In sturdy case.

	Art.-No.	KM
	175401 R6	**271,00**

All prices excl. VAT

REMS CamScope HD

Endoscope camera

Mobile, handy endoscope camera for low-cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes, etc. Documentation of photos and videos on MicroSD card. For battery and mains operation.

Camera head	Ø 8 mm

REMS CamScope HD – Brilliant pictures and videos of cavities, shafts and pipes in HD quality (1920 × 1080 pixels). MicroSD card slot.

Design

Ultra light and handy. Controller unit with pistol grip and camera cable set only 0.5 kg. Can be used everywhere, free hand, over head, also in very confined spaces Sturdy, impact-proof plastic housing with ergonomically shaped handle. The buttons are located directly underneath the display so that it is possible to hold the device by the pistol grip and operate the buttons with one hand. Bottoms, among other things, for regulating the brightness of the LEDs in the camera head and the display in 4 stages each, for rotating, mirroring and zooming the image shown in the display, calling and navigating in the menu. Power LED for indicating the operating state integrated into the On-Off button. Li-Ion 3.7 V battery with 4.0 Ah for long service life. Different HD camera cable sets can be used. Plug-screw connections for changing the camera cable sets without tools. Sturdy case of controller unit with pistol grip, camera cable set Color 8-1 HD 180°/90°, USB cable and accessories.

Controller unit with TFT-LCD colour display

Controller unit with pistol grip with 5" colour display with state-of-the-art TFT-LCD technology and 480 × 854 pixels, for brilliant pictures and videos. Selectable menu language. MicroSD card slot. Pictures and videos in HD quality can be saved on a MicroSD card for simple documentation of the inspection result. 4x digital zoom. The date and time of the recording can be saved in the photo and video as an option. Immediate playback of saved recordings or transmission to other devices via MicroSD card. USB port for direct connection to a PC or laptop and for charging the battery.

Cordless and mains operation

Li-Ion technology. Controller unit with pistol grip with integrated 3.7 V, 4.0 Ah Li-Ion battery. Light and powerful. High energy density for approx. 5 hours continuous operation. The unit can be used in mains mode whilst charging the battery with the USB cable. No memory effect for maximum battery performance.

Exchangeable camera cable set Color

Consisting of colour camera Ø 8 mm, with CMOS sensor, with dimmable white light LEDs for optimum setting of the brightness and fixed focus function, for automatic picture focus, protected against occasional immersion in water (IP 67).

Camera cable set Color 8-1 HD 180°/90° with 180° straight and 90° angled colour camera, with 1 m flexible push cable and add-on hook, add-on magnet. Images and videos can be viewed and recorded from the selected colour camera or from both colour cameras simultaneously.

Camera cable set Color 8-5 HD with 5 m flexible push cable as an accessory.

Info

Supply format

REMS CamScope HD Set. Mobile, handy endoscope camera for low cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes etc. Documentation of pictures and videos in HD quality on MicroSD card. Endoscope camera with 5" TFT-LCD colour display, 4x digital zoom, MicroSD card slot, USB port, integrated 3.7 V, 4.0 Ah Li-ion battery. Camera cable set Color 8-1 HD 180°/90°, 180° straight colour camera and 90° angled colour camera, with 1 m flexible push cable and add-on hook, add-on magnet. 32 GB MicroSD card. USB cable. In sturdy case.

	Art.-No.	KM
	175400R4	**481,00**

Accessories

Description	Art.-No.	KM
Camera cable set Color 8-5 HD, colour camera Ø 8 mm, 1280 × 720 pixels, with 5 m formable push cable	175440R	**187,00**

REMS CamSys

Electronic camera inspection system

Mobile, handy camera inspection system for inexpensive inspection and damage analysis of pipes, drains, chimneys and other hollow cavities. With electronic metering. Also for inspection after pipe cleaning work and for acceptance of new installations or repairs. Documentation of pictures and videos on SD card. For battery and corded operation.

Camera head	Ø 25 mm
Pipe Drains, chimneys, other cavities	Ø (40) 50 – 150 mm

REMS CamSys – Brilliant pictures and videos of pipes and drains. SD card slot. Electronic metering. Cordless and mains operation.

System advantage

Only **one** controller unit with TFT-LCD colour display for connecting different camera cable sets for different requirements. Therefore inexpensive conversion possible.

Design

Mobile, handy, light. Can be used everywhere, even in very narrow places. Controller unit connected to the camera cable set by a 2 m connecting cable, removable for easy cleaning of the camera cable set. Various camera cable sets can be used. Plug-screw connections for changing the camera cable sets and the controller unit without tools. Sturdy case for controller unit, voltage supply/charger and accessories.

Controller unit with TFT-LCD colour display

Controller unit with 3.5" colour display with state of the art TFT-LCD technology for brilliant pictures and videos, 89 mm screen diagonal, 320 × 240 pixels. Very light and handy, only 0.4 kg. Sturdy, impact-proof plastic housing, spray protected. Small dimensions: 172 × 121 × 58 mm. Keys for setting the brightness of the LEDs of the colour camera head. Full screen, 2x zoom, 4x rotation options for the picture. SD card slot. Pictures and videos can be saved on an SD card for simple documentation of the inspection result. Insertion depth of the camera is stored in the picture and the video, optionally also date and time of the recording. Pictures can be taken during video recording without impairing the video recording. Immediate playback of saved recordings or transmission to other devices with SD card. Pictures can also be taken later from the video during playback of recorded videos on the controller's colour display. USB connector for direct connection to PC or laptop. Video output socket Composite-Video PAL/NTSC for connecting an external monitor. Connection for voltage supply/charger Li-Polymer 100 – 240 V.

Cordless and mains operation

Li-Polymer Technology. Controller unit with integrated Li-Polymer battery 3.7 V, 4.0 Ah. Light and powerful. Power supply/charger 100 – 240 V, 15 W, with USB port and USB cable for connecting power supply/charger, laptop or other voltage supply. No memory effect for maximum battery performance.

High resolution special colour camera

High resolution special colour camera Ø 25 mm with CMOS image sensor and 8 ultra bright, white LEDs with adjustable light intensity up to 1700 mcd and concentrated radiation angle for brilliant colour pictures with even illumination. Low light requirement due to very high light sensitivity (0.1 lux). Fixed focus and special lens with 90° wide angle, also for detecting the smallest details.

Exchangeable cable camera sets

Camera cable sets S-Color, consisting of special high-resolution colour camera with optional **30 m push cable Ø 5.4 mm**, flexible, for Ø 50 – 150 mm, in hasp with electronic metre counter, **20 m push cable Ø 4.5 mm**, very flexible, for small pipe diameters and narrower bends Ø (40) 50 – 150 mm, in the hasp with electronic metre counter or **10 m push cable Ø 4.5 mm** with length mark, very flexible, for small pipe diameters and narrower pipe bends Ø (40) 50 – 150 mm, in the cable reel, with connection for controller unit. Very small, rounded camera head Ø 25 mm, water-tight up to 20 m (0.2 MPa/2 bar/29 psi) and highly flexible sliding spring tapered towards the push cable for effortless feeding even through several pipe bends. Camera head with strong, quick-change protective cap with inserted mineral glass pane. Bend-manoeuvring push cable in hybrid technology, with glass fibre core, data cables and plastic sheath, very stable, for long life. Robust, owder-coated, easy to clean cable cage. Hasp with rotary cage for simple unwinding and winding of the push cable and integrated sensor for electronic metering. Carrying case for camera cable set as an accessory.

Guide bodies

Various guide bodies for larger pipe diameters, firmly lockable on the camera head, as an accessory.



Info

Supply format

REMS CamSys Set S-Color. Electronic camera inspection system for low-cost inspection and damage analysis. Documentation of pictures and videos on SD card with specification of date and time. Controller unit in microprocessor technology with 3.5" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery, 3.7 V, 4.0 Ah, in sturdy, impact-proof plastic housing, spray protected. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100 – 240 V, 50 – 60 Hz, 15 W, SD card 4 GB, USB cable, in sturdy case. Camera cable set S-Color with high resolution special colour camera Ø 25 mm with CMOS image sensor and push cable.

Description	Version	Art.-No.	KM
Set S-Color 10 K	10 m push cable Ø 4.5 mm with length mark, very flexible, in cable reel. For small pipe diameters and narrower pipe bends Ø (40) 50 – 150 mm, drains, shafts, stacks and other cavities.	175008R220	**5.040,00**
Set S-Color 20 H	20 m push cable Ø 4.5 mm, very flexible, in the hasp with electronic metre counter. For small pipe diameters and narrower pipe bends Ø (40) 50 – 150 mm, drains, shafts, stacks and other cavities.	175007R220	**6.990,00**
Set S-Color 30 H	30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metre counter. For pipes Ø 50 – 150 mm, drains, shafts, stacks and other cavities.	175010R220	**7.200,00**

Accessories

Description	Art.-No.	KM
REMS CamSys Basic-Pack. Controller unit in microprocessor technology with 3.5" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery, 3.7 V, 4.0 Ah, in sturdy, impact-proof plastic housing, spray protected. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100 – 240 V, 50 – 60 Hz, 15 W, SD card 4 GB, USB cable, in sturdy case.	175000R220	**2.840,00**
Camera cable set S-Color 10 K with high resolution special colour camera Ø 25 mm with CMOS image sensor, 10 m push cable Ø 4.5 mm with length marking, very flexible, with connection for controller unit, in cable reel. For small diameters and narrower pipe bends Ø (40) 50 – 150 mm.	175305R	**2.210,00**
Camera cable set S-Color 20 H with high resolution special colour camera Ø 25 mm with CMOS image sensor and 20 m push cable Ø 4.5 mm, flexible, in the hasp with electronic metering and connection for controller unit. For small diameters and narrower pipe bends Ø (40) 50 – 150 mm.	175306R	**4.160,00**
Camera cable set S-Color 30 H with high resolution special colour camera Ø 25 mm with CMOS image sensor and 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering and connection for controller unit. For Ø 50 – 150 mm.	175011R	**4.370,00**
Guide body Ø 62 mm S-Color/S-Color S, for camera cable set S-Color/S-Color S	175057R	**218,00**
Guide body Ø 100 mm S-Color/S-Color S, for camera cable set S-Color/S-Color S	175058R	**252,00**
Protective cap S-Color/S-Color S with mineral glass pane, sealing ring, for camera cable set S-Color/S-Color S	175026R	**73,50**
Carrying case for camera cable set	175123R	**261,00**
Case with inlay	175018R	**200,00**

REMS CamSys 2

Electronic camera inspection system

Mobile, handy camera inspection system for inexpensive inspection and damage analysis of pipes, drains, chimneys and other hollow cavities. Self-levelling camera. Transmitter for localising camera heads. Electronic metering. Also for inspection after pipe cleaning work and for acceptance of new installations or repairs. Documentation of pictures and videos with voice recording on SD card. For battery and corded operation.

Camera head S-Color/S-Color S	Ø 25 mm
Camera head S-Color S-N	Ø 33 mm
Pipes, drains, chimneys, other cavities	
Camera head S-Color	Ø (40) 50 – 150 mm
Camera head S-Color S	Ø 50 – 150 mm
Camera head S-Color S-N	Ø 70 – 150 mm

REMS CamSys 2 – Brilliant pictures and videos of pipes and drains. Voice recording Self-levelling camera. Transmitter for localising camera heads. SD card slot. Electronic metering. Cordless and mains operation.

System advantage

Only **one** controller unit with TFT-LCD colour display for connecting different camera cable sets for different requirements. Therefore inexpensive conversion possible.

Design

Mobile, handy, light. Can be used everywhere, even in very narrow places. Controller unit connected to the camera cable set by a 2 m connecting cable, removable for easy cleaning of the camera cable set. Various camera cable sets can be used. Plug-screw connections for changing the camera cable sets and the controller unit without tools. Sturdy case for controller unit, voltage supply/charger and accessories.

Controller unit with TFT-LCD colour display

Controller unit with 7" colour display with state of the art TFT-LCD technology for brilliant pictures and videos, 178 mm screen diagonal, 720 × 480 pixels. Very light and handy, only 1.3 kg. Sturdy, impact-proof plastic housing, spray protected, glare protection. Integrated stand for different angles of inclination of the screen. Ergonomic grips with soft-grip and adjustable clamping bands, keys for picture and video, for one-hand operation by right and left handers. Small dimensions: 270 × 164 × 70 mm. Keys for setting the brightness of the LEDs of the colour camera head. Full screen, 2x zoom, 4x rotation options for the picture. Adjustable automatic switch-off. SD card slot. Pictures and videos with voice recording can be saved on an SD card for simple documentation of the inspection result. Insertion depth of the camera is stored in the picture and the video, optionally also date and time of the recording. Pictures can be taken during video recording without impairing the video recording. Immediate playback of saved recordings or transmission to other devices with SD card. Pictures can also be taken later from the video during playback of recorded videos on the controller's colour display. USB connector for direct connection to PC or laptop. Video output socket Composite-Video PAL/NTSC for connecting an external monitor. Connection for voltage supply/charger 100 – 240 V.

Cordless and mains operation

Li-Polymer Technology. Controller unit with integrated Li-Polymer battery 3.7 V, 7.6 Ah. Light and powerful. Power supply/charger 100 – 240 V, 15 W, with USB port and USB cable for connecting power supply/charger, laptop or other voltage supply. No memory effect for maximum battery performance.

High resolution special colour camera

High resolution special colour camera with CMOS image sensor and ultra bright, white light emitting diodes (LEDs) with adjustable light intensity up to 1700 mcd and concentrated radiation angle for brilliant colour pictures with evenly bright illumination. Low light requirement due to very high light sensitivity (0.1 lux). Fixed focus and special lens with 90° wide angle, also for detecting the smallest details.



Info

REMS CamSys 2

Electronic camera inspection system

Exchangeable cable camera sets

Camera cable set S-Color, consisting of a special high resolution colour camera Ø 25 mm with 20 m push cable Ø 4.5 mm, very flexible, for small pipe diameters and narrower bends Ø (40) 50 – 150 mm, in the hasp with electronic metering or 10 m push cable Ø 4.5 mm with length mark, very flexible, for small pipe diameters and narrower pipe bends Ø (40) 50 – 150 mm, in the cable reel. **Camera cable set S-Color S**, consisting of a special high resolution colour camera Ø 25 mm with 30 m push cable Ø 5.4 mm, flexible, for Ø 50 – 150 mm, in the hasp with electronic metering and 33 kHz transmitter for localising the camera head. **Camera cable set S-Color S-N**, consisting of a special high resolution colour camera Ø 33 mm with 30 m push cable Ø 5.4 mm, flexible, for Ø 70 – 150 mm, in the hasp with electronic metering, 33 kHz transmitter for localising the camera head and self-levelling camera for upright pictures and videos. Connection for controller unit. Very small, rounded camera head, water-proof up to 20 m (0.2 MPa/2 bar/29 psi) and highly flexible sliding spring tapered towards the push cable for effortless feeding even through several pipe bends. Camera head with strong, quick-change protective cap with inserted mineral glass pane. Bend-manoeuvring push cable in hybrid technology, with glass fibre core, data cables and plastic sheath, very stable, for long life. Robust, powder-coated, easy to clean cable cage. Hasp with rotary cage for simple unwinding and winding of the push cable and integrated sensor for electronic metering. Carrying case for camera cable set as an accessory.

Guide bodies

Guide body S-Color/S-Color S and S-Color S-N Ø 62 mm and Ø 100 mm, for greater pipe diameters, can be locked to camera head S-Color/S-Color S or S-Color S-N, as an accessory.

Tracker

REMS Explorer for localising a camera head with a 33 kHz transmitter, for determining the position of damages or the course of a pipe, as an accessory.

Supply format

REMS CamSys 2 Set S-Color. Electronic camera inspection system for low-cost inspection and damage analysis. Documentation of pictures and videos with voice recording on SD card with specification of date and time. Controller unit in microprocessor technology with 7" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery 3.7 V, 7.6 Ah, in sturdy, impact-proof plastic housing, spray protected, glare protection, stand. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100 – 240 V, 50 – 60 Hz, 15 W, SD card 4 GB, USB cable, video cable, in sturdy case. Camera cable set S-Color with high resolution special colour camera with CMOS image sensor and push cable.

Description	Version	Art.-No.	KM
Set S-Color 10 K	High resolution special colour camera Ø 25 mm, 10 m push cable Ø 4.5 mm with length mark, very flexible, in the cable reel. For small pipe diameters and narrower pipe bends Ø (40) 50 – 150 mm, drains, shafts, stacks and other cavities.	175301 R220	**6.180,00**
Set S-Color 20 H	High resolution special colour camera Ø 25 mm, 20 m push cable Ø 4.5 mm, very flexible, in the hasp with electronic metering. For small pipe diameters and narrower pipe bends Ø (40) 50 – 150 mm, drains, shafts, stacks and other cavities.	175302 R220	**8.130,00**
Set S-Color S 30 H	High resolution special colour camera Ø 25 mm, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For pipes Ø 50 – 150 mm, drains, shafts, stacks and other cavities.	175303 R220	**8.550,00**
Set S-Color S-N 30 H	High resolution special colour camera Ø 33 mm, self-levelling, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For pipes Ø 70 – 150 mm, drains, shafts, stacks and other cavities.	175304 R220	**9.280,00**

All prices excl. VAT

Description	Art.-No.	KM
REMS CamSys 2 Basic-Pack Controller unit in microprocessor technology with 7" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery, 3.7 V, 7.6 Ah, in sturdy, impact-proof plastic housing, glare protection, stand, spray protected. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100 – 240 V, 50 – 60 Hz, 15 W, SD card 4 GB, USB cable, video cable, in sturdy case.	175300R220	**3.970,00**
Camera cable set S-Color 10 K High resolution special colour camera Ø 25 mm, 10 m push cable Ø 4.5 mm with length mark, very flexible, in the cable reel. For small diameters and narrower pipe bends Ø (40) 50 – 150 mm.	175305R	**2.210,00**
Camera cable set S-Color 20 H High resolution special colour camera Ø 25 mm, 20 m push cable Ø 4.5 mm, very flexible, in the hasp with electronic metering. For small diameters and narrower pipe bends Ø (40) 50 – 150 mm.	175306R	**4.160,00**
Camera cable set S-Color S 30 H High resolution special colour camera Ø 25 mm, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For Ø 50 – 150 mm.	175307R	**4.580,00**
Camera cable set S-Color S-N 30 H High resolution special colour camera Ø 33 mm, self-levelling, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For Ø 70 – 150 mm.	175308R	**5.320,00**
Guide body Ø 62 mm S-Color/S-Color S, for camera head S-Color/S-Color S	175057R	**218,00**
Guide body Ø 100 mm S-Color/S-Color S, for camera head S-Color/S-Color S	175058R	**252,00**
Guide body Ø 62 mm S-Color S-N, for camera head S-Color S-N	175343R	**121,00**
Guide body Ø 100 mm S-Color S-N, for camera head S-Color S-N	175339R	**169,00**
Protective cap S-Color/S-Color S with mineral glass pane, sealing ring, for camera head S-Color/S-Color S	175026R	**73,50**
Protective cap S-Color S-N with mineral glass pane, sealing ring, for camera head S-Color S-N	175330R	**175,00**
REMS Explorer, tracker for localising a camera head with a 33 kHz transmitter	175312R	**4.020,00**
Carrying case for camera cable set	175123R	**261,00**
Case with inlay	175323R	**200,00**

REMS Explorer
2023.10.25 15:14:00 PM
X 1.0
REMS CamSys 2

REMS Pull-Push

Suction and pressure cleaning device

Proven, reliable suction and pressure cleaning device for fast clearance of blockages.

REMS Pull-Push – fast clearance of blockages.

High pressing force by front, adjustable handle.

Optimum adaptation to the cleaning task by 2 sleeves:
Short sleeve for wash basins and baths, long sleeve for toilets.

Info

Supply format

REMS Pull-Push. Suction and pressure cleaning device for fast clearance of blockages. With short and long sleeve. In a box.

	Art.-No.	KM
	170300R	**271,00**

REMS Mini-Cobra

Drain cleaner for manual and electric operation

Proven, handy device for the fast unblocking of pipes, e.g. for kitchens, bathrooms and toilets.

For pipes	Ø 20 – 50 (75) mm
For drain cleaning cables	Ø 6, 8, 10 mm

REMS Mini-Cobra – by hand or electric. Indispensable to remove small blockages.

Design

Simple, robust, practical design. Handy, light. Only 2.9 kg. Easy operation also in traps and tight bends. Easy insertion of cable directly through strainers in sinks and drains. Locking of cable by quick-action chuck.

Drain cleaning cables

Cables in high quality spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight bends. Cable end with bulbous head (sink strainer head), thus easy to bend.

Cable drum

In hot-galvanized spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Cable end with bulbous head. Corrosion-resistant cable drum in shock-proof, glass-fibre reinforced plastic prevents pollution of the environment. Ventilation of the cable drum interior enables self-drying of cable. View to cable at all times.

Drive

By hand with easy action, easy grip crank handle or with suitable electric drill/ with suitable electric screwdriver, speed ≤ 300 rpm. Hexagon adapter for electric drive located in the drum cover.

German Quality Product

Info

Supply format

REMS Mini-Cobra. Pipe cleaning device for pipes Ø 20 – 50 (75) mm, with crank handle and hexagonal driver for electric drill/screwdriver. For drain cleaning cables Ø 6, 8 and 10 mm. Cable drum in shock-proof, glass-fibre reinforced plastic. Quick-action chuck. Cable Ø 8 mm × 7.5 m long. In a carton.

	Art.-No.	KM
	170010R	**376,00**

Accessories

Description	Ø × Length	Art.-No.	KM
Drain cleaning cable	8 mm × 7.5 m	170200	**140,00**
	10 mm × 10 m	170205	**284,00**
Drain cleaning cable with core	8 mm × 7.5 m	170201	**199,00**
L-Boxx H system case with inserts		170118R	**296,00**

All prices excl. VAT

REMS Mini-Cobra S

Electric drain cleaning machine

Electric pipe cleaning device with fast switchover.
For effortless and quick application to remove pipe blockages in kitchen, bath, toilet.

For pipes	Ø 20 – 50 (75) mm
For drain cleaning cables	Ø 8, 10 mm



German Quality Product

Info

REMS Mini-Cobra S – Fast clearance of pipe blockages. Ultra fast reversal of direction of spiral feed/return by fast switchover.

Design
Compact unit of drive machine and cable drum. Handy, light. Only 5.7 kg. Combined thrust and grip handle for controlling the automatic feed-forward and reverse and for safe holding of the unit. Easy operation also in traps and tight bends.

Fast switchover
For easy operation and fast clearance of pipe blockages. Ultra fast reversal of direction of spiral feed/return by fast switchover **(Patent EP 3 059 022)** also under full load without changing the motor's direction of rotation, avoids looping of the drain cleaning cables when suddenly encountering resistance from pipe blockages, for long life of the drain cleaning cables.

Drain cleaning cables
Drain cleaning cables in high quality spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Cable end with bulbous head (sink strainer head), thus easy to bend. Drain cleaning cables with core in high quality spring steel prevents ingress of dirt and generation of long fibres in the cable windings.

Cable drum
Corrosion resistant cable drum in shock-proof, glass-fibre reinforced plastic prevents pollution of the environment. Ventilation of the cable drum interior enables self-drying of cable. View of the cable at any time.

Drive
Proven drive unit with hexagon mount. Enormously powerful. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. Stepless, electronic speed control. The speed between 0 and 950 rpm is controlled by pressing the tip switch steplessly (acceleration switch).

Patent EP 3 059 022

Supply format

REMS Mini-Cobra S. Electric pipe cleaning device with fast switchover, for pipes Ø 20 – 50 (75) mm. For drain cleaning cables Ø 8 and 10 mm. Drive unit with maintenance-free gear, universal motor 230 V or 110 V, 50 – 60 Hz, 630 W, high-torque forward and reverse at low speed. Safety tip switch. Stepless, electronic speed control (acceleration switch) between 0 and 950 rpm. Cable drum in shock-proof, glass-fibre reinforced plastic. Cable Ø 8 mm, with core, 7.5 m long.

Description	Art.-No.	KM
REMS Mini-Cobra S, in a carton	170022R220	**1.140,00**
REMS Mini-Cobra S Set, in sturdy steel case.	170023R220	**1.350,00**

Accessories

Description	Ø × Length	Art.-No.	KM
Drain cleaning cable with core	8 mm × 7.5 m	170201	**199,00**
Drain cleaning cable	10 mm × 10 m	170205	**284,00**
Steel case		185058R	**223,00**

REMS Mini-Cobra S 22 V VE

Cordless drain cleaning machine

Mobile, handy, cordless pipe cleaning device with fast switchover. For effortless and quick application to remove pipe blockages in kitchen, bath, toilet. Li-Ion 22 V Technology. For battery and corded operation.

For pipes	Ø 20 – 50 (75) mm
For drain cleaning cables	Ø 8, 10 mm

REMS Mini-Cobra S 22 V VE – fast clearance of pipe blockages anywhere. Ultra fast reversal of direction of spiral feed/return by fast switchover. With powerful, brushless battery motor.

Design

Compact unit of cordless drive unit and spiral drum. Mobile, handy, light. Complete with battery pack only 5.2 kg. Combined thrust and grip handle for controlling the automatic feed-forward and reverse and for safe holding of the unit. Easy operation also in traps and tight bends. Integrated LED work light for illuminating the work place.

Fast switchover

For easy operation and fast clearance of pipe blockages. Ultra fast reversal of direction of spiral feed/return by fast switchover **(Patent EP 3 059 022)** also under full load without changing the motor's direction of rotation, avoids looping of the drain cleaning cables when suddenly encountering resistance from pipe blockages, for long life of the drain cleaning cables.

Drain cleaning cables

Drain cleaning cables in high quality spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Cable end with bulbous head (sink strainer head), thus easy to bend. Drain cleaning cables with core in high quality spring steel prevents ingress of dirt and generation of long fibres in the cable windings.

Cable drum

Corrosion resistant cable drum in shock-proof, glass-fibre reinforced plastic prevents pollution of the environment. Ventilation of the cable drum interior enables self-drying of cable. View of the cable at any time.

Drive

High-performance electro-mechanical drive with powerful, brushless motor 21.6 V, 500 W output, extra torque powerful left and right hand rotation at specially adapted speed, robust, precision ball bearing-mounted gear, maintenance-free. Safety switch, electronically controlled for jolt-free switching on and off. Continuous, electronic speed control. The speed can be continuously controlled by variable pressure on the safety switch from 0 to 560 rpm (accelerator switch /VE)).

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 1.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. 220 – 240 V/21.6 V, 15 A output, voltage supply for mains operation instead of Li-Ion battery 21.6 V, as accessory.

German Quality Product

Info

Patent EP 3 059 022

REMS Mini-Cobra S 22 V VE

Cordless drain cleaning machine

Supply format

REMS Mini-Cobra S 22 V VE. Cordless pipe cleaning device with fast switchover, for pipes Ø 20 – 50 (75) mm. For drain cleaning cables Ø 8 and 10 mm. Drive unit with powerful, brushless battery motor 21.6 V, 500 W, maintenance-free, robust gear, extra torque powerful left and right hand rotation at low speeds, safety switch. Continuous, electronic speed control (accelerator switch (VE)) from 0 to 560 rpm. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V, 50 – 60 Hz, 70 W. Cable drum in shock-proof, glass-fibre reinforced plastic. Cable Ø 8 mm, with core, 7.5 m long.

Description	Art.-No.	KM
REMS Mini-Cobra S 22 V VE, in a carton	170025 R220	**1.560,00**
REMS Mini-Cobra S 22 V VE Set, in L-Boxx H system case	170027 R220	**1.870,00**

Other voltages on request.

Accessories

Description	Ø × Length	Art.-No.	KM
Drain cleaning cable with core	8 mm × 7.5 m	170201	**199,00**
Drain cleaning cable	10 mm × 10 m	170205	**284,00**
Battery Li-Ion 21.6 V, 2.5 Ah		571571 R22	**523,00**
Battery Li-Ion 21.6 V, 4.4 Ah		571574 R22	**754,00**
Battery Li-Ion 21.6 V, 5.0 Ah		571581 R22	**628,00**
Battery Li-Ion 21.6 V, 9.0 Ah		571583 R22	**838,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W		571585 R220	**355,00**
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W		571587 R220	**838,00**
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.		571567 R220	**838,00**
L-Boxx H system case with inserts		170118 R	**296,00**
REMS Lumen 2800 22 V, cordless LED flood light, see page 111			

REMS Cobra 22/32

Handy, robust, compact machines for versatile use in pipe and drain cleaning. High-speed rotator with connectable cable sections. Proven technology.

For pipes	Ø 20 – 250 mm
For pipe and drain cleaning cables	Ø 8, 16, 22, 32 mm

All pipe and drain cleaning cables and tools can also be used for other makes.

REMS Cobra – clear pipe – easy and fast. High-speed rotator with cable sections for work length up to 100 m. Effective chain knocking and milling up to 740 rpm. Closed drive spindle protects motor and drive against dirt and water.

High speed rotator with connectable cable sections

High-speed rotator, 740 rpm (REMS Cobra 22) resp. 520 rpm (REMS Cobra 32), with cable sections for effective fast operation, e.g. during chain knocking or milling. Under difficult conditions also, e.g. roots and hard incrustations. Cable sections to be connected as needed up to 70 m (REMS Cobra 22) resp. 100 m (REMS Cobra 32) work length. No unnecessary rotating of long pipe and drain cleaning cables.

Design

Robust, practical, splash-proof. Maintenance-free. Small in size. Favourable weight, drive unit REMS Cobra 22 only 19 kg, drive unit REMS Cobra 32 only 24 kg. Machine frame made of distortion-free cast aluminium with protective covers in shock-proof plastic material. REMS Cobra 22 with holders for part spirals 16 and 22 for fixing the part spirals to the machine frame when changing spirals. Chucking system which is located outside the machine housing with straight through undivided drive spindle for the pipe and drain cleaning cable. This enables a complete seal of the machine interior against dirt and water. Connecting cable with integrated personal protection switch (PRCD). Guide hose prevents excess rotation of pipe and drain cleaning cables and pollution of the environment. Legs with rubber caps guarantee a safe, floor-protecting stand.

High-performance pipe and drain cleaning cables

Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Rapid action coupling for fast extension and shortening. T-groove coupling with safety lock through spring-loaded thrust pin. Manual feed-forward for sensitive operation. Standard pipe and drain cleaning cable for universal pipe and drain cleaning jobs, highly flexible, specially suited for tight or several consecutive pipe bends. Pipe and drain cleaning cable S with thicker special spring steel for very difficult to remove obstructions, e.g. root cutting. Drain cleaning cables with weather-proof and temperature resistant plastic core prevents drain cleaning cable from dirt and generation of long fibres in the cable windings. Drive through REMS Cobra 22, REMS Cobra 32 or drive machines of other makes.

Clamping jaws for cable drive

Clamping jaws in high-grade hardened steel, resistant to wear and precise fit. Instant and exact clamping and opening of pipe and drain cleaning cables allow optimum control, power transmission and operating safety. REMS Cobra 22: Choice of pipe and drain cleaning cables Ø 16 mm and 22 mm, without changing the clamping jaws. Pipe and drain cleaning cable Ø 8 mm with adapter drum 22/8 and integrated clamping jaws, as accessory. REMS Cobra 32: Choice of drain cleaning cables Ø 22 and 32 mm, without changing the clamping jaws. Drain cleaning cables Ø 16 mm with clamping jaws 16, as accessory. Pipe and drain cleaning cable Ø 8 mm with adapter drum 32/8 and integrated clamping jaws, as accessory.

Drive

Powerful, quiet running capacitor motor with high torque, 750 W (REMS Cobra 22), 1050 W (REMS Cobra 32), right and left-hand rotation. Full transmission of motor power by a slipping-proof maintenance-free toothed belt drive. Straight through closed drive spindle. Permanently lubricated, maintenance-free roller bearings. Fast and secure run and stop of pipe and drain cleaning cable through strong, centrally located pressing lever provides central power input. Lever doubles as a carrying device without awkward locking.

Pipe and drain cleaning tools

Large variety of pipe and drain cleaning tools (page 288 – 289), also fit into pipe and drain cleaning machines of other makes.

German Quality Product

German Quality Product

Straight through closed drive spindle protects motor and drive against dirt and water.

Supply format

REMS Cobra 22 Set. Electric pipe and drain cleaning machine for pipes Ø 20 – 150 mm. Drive unit with maintenance-free belt drive, capacitor motor 230 V, 50 Hz, 750 W, right and left-hand rotation, guide hose. Personal protection switch (PRCD). Choice of cable and tool set 16 or/and 22. In a carton.

Description	Version	Art.-No.	KM
Set 16	5 cable sections 16 × 2.3 m in cable carrier, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator, 1 pair of guide gloves, steel case for tool set	172010R220	**3.660,00**
Set 22	5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator 22/32, 1 pair of guide gloves, steel case for tool set	172011R220	**4.040,00**
Set 16 + 22	5 cable sections 16 × 2.3 m in cable carrier, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator, 5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator 22/32, 2 pairs of guide gloves, steel case for each tool set	172012R220	**4.730,00**

Info

Supply format

REMS Cobra 32 Set. Electric pipe and drain cleaning machine for pipes Ø 20 – 250 mm (½ – 10"). Drive unit with maintenance-free belt drive, capacitor motor 230 V, 50 Hz, 1050 W, right and left-hand rotation, guide hose. Personal protection switch (PRCD). Choice of cable and tool set 32 or cable and tool sets 22 and 32 or 16 and 22. In a carton.

Description	Version	Art.-No.	KM
Set 32	4 cable sections 32 × 4.5 m in cable carrier, straight auger 32, retrieving auger 32, funnel auger 32, toothed cross-blade borer 32/45, cable joint separator 22/32, 1 pair of guide gloves, case for tool set	174010R220	**7.940,00**
Set 22 + 32	5 cable sections 22 x 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed-cross-blade borer 22/35, cable joint-separator 22/32, 4 cable sections 32 x 4.5 m in cable carrier, straight-auger 32, retrieving auger 32, funnel-auger 32, toothed cross-blade borer 32/45, cable joint separator 22/32.2 pairs of guide gloves, steel case/ case for each tool set	174011R220	**9.350,00**
Set 16 + 22	5 cable sections 16 x 2.3 m in cable carrier, 2 clamping jaws 16, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator 16, 5 cable sections 22 x 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator 22/32, 2 pairs of guide gloves,steel case for each tool set	174012R220	**8.550,00**

Info

Accessories

Description	Art.-No.	KM
REMS Cobra 22 drive unit with guide hose	172000R220	**3.340,00**
REMS Cobra 32 drive unit with guide hose	174000R220	**6.180,00**

Pipe and drain cleaning tools see page 288 – 289.

REMS Cobra 22/32

Accessories for REMS Cobra 22, REMS Cobra 32 and other makes

Description	Size	Art.-No.	KM
Cable and tool set 16 consisting of 5 cable sections 16 × 2.3 m in cable carrier, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator, 1 pair of guide gloves, steel case for tool set		172050R	**1.220,00**
Cable and tool set 22 consisting of 5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator, 1 pair of guide gloves, steel case for tool set		172051R	**1.710,00**
Cable and tool set 32 consisting of 4 cable sections 32 × 4.5 m in cable carrier, straight auger 32, retrieving auger 32, funnel auger 32, toothed cross-blade borer 32/45, cable joint separator 22/32, 1 pair of guide gloves, case for tool set		174050R	**2.190,00**
Adapter drum REMS Cobra 22/8 with cable Ø 8 mm × 7.5 m long, with bulbous head		170011	**1.360,00**
Adapter drum REMS Cobra 32/8 with cable Ø 8 mm × 7.5 m long, with bulbous head		170012	**1.360,00**
Clamping jaws 16 (pack of 2) for REMS Cobra 32 for clamping drain cleaning cables Ø 16 mm		174101	**245,00**
Pipe and drain cleaning cable			
for pipe-Ø 10 – 50 (75) mm	8 × 7.5 m	170200	**140,00**
for pipe-Ø 25 – 125 mm	16 × 2.3 m	171200	**139,00**
for pipe-Ø 50 – 150 mm	22 × 4.5 m	172200	**221,00**
for pipe-Ø 50 – 250 mm	32 × 4.5 m	174200	**309,00**
Pipe and drain cleaning cable (5 pieces) in cable carrier			
for pipe-Ø 25 – 125 mm	16 × 2.3 m	171201	**911,00**
Pipe and drain cleaning cable (5 pieces) in cable carrier			
for pipe-Ø 50 – 150 mm	22 × 4.5 m	172201	**1.170,00**
Pipe and drain cleaning cable (4 pieces) in cable carrier			
for pipe-Ø 50 – 250 mm	32 × 4.5 m	174201	**1.480,00**
Pipe and drain cleaning cable S With thick special spring steel for high stability, e.g. during root cutting, milling, chain knocking			
for pipe-Ø 25 – 125 mm	16 × 2 m	171205	**178,00**
for pipe-Ø 50 – 150 mm	22 × 4 m	172205	**296,00**
for pipe-Ø 50 – 250 mm	32 × 4 m	174205	**527,00**
Pipe and drain cleaning cable with core prevents clogging of pipe and drain cleaning cable with dirt			
for pipe-Ø 25 – 125 mm	16 × 2.3 m	171210	**193,00**
for pipe-Ø 50 – 150 mm	22 × 4.5 m	172210	**353,00**
for pipe-Ø 50 – 250 mm	32 × 4.5 m	174210	**414,00**
Pipe and drain cleaning cable with core (5 pieces) in cable carrier			
for pipe-Ø 50 – 150 mm	22 × 4.5 m	172203	**1.780,00**
Pipe and drain cleaning cable with core (4 pieces) in cable carrier			
for pipe-Ø 50 – 250 mm	32 × 4.5 m	174203	**1.900,00**
Cable reduction 22/16 for connecting individual cables of different sizes	22/16	172154	**252,00**
Cable reduction 32/22 for connecting individual cables of different sizes	32/22	174154	**292,00**
Cable carrier (empty)	16	171150	**216,00**
	22	172150	**217,00**
	32	174150	**240,00**
Cable joint separator for releasing the safety lock	16	171151	**8,40**
	22/32	172151	**9,50**

All prices excl. VAT

Description	Size	Art.-No.	KM
Straight auger for exploring the obstruction to withdraw a sample. Clearing of solid blockages caused by e.g. textiles, paper, kitchen waste	 16 22 32	 171250 172250 174250	 **70,40** **92,40** **117,00**
Bulbous auger for minor obstructions caused by textiles and papers. Flexible, facilitates advancement in tight bends.	 16 22 32	 171265 172265 174265	 **70,40** **92,60** **121,00**
Funnel auger for textile and paper obstructions in particular. Especially useful for cleaning larger diameter pipes. Also be used as a recovery tool for cables left in the pipe.	 16 22 32	 171270 172270 174270	 **77,70** **101,00** **138,00**
Retrieving auger with extended, specially angled grappling arms. Used to recover cables left in the pipe. Not suitable for boring operations.	 16 22 32	 171275 172275 174275	 **70,40** **99,10** **119,00**
Serrated blade borer for boring out greasy or heavily silted pipes, e.g. drains of washing machines, dishwashers. Riveted to the connector (not soldered or welded), so as to prevent any deformation of the hardened spring steel blades.	 16/25 22/35 22/45 32/55	 171280 172280 172281 174282	 **64,50** **94,70** **120,00** **156,00**
Serrated cross-blade borer Universal use for obstructions of all kinds, including incrustations, e.g. limescale deposites on the inside of the pipe. Riveted to the connector (not soldered or welded), so as to prevent any defor- mation of the hardened spring steel blades. Operation with pipe and drain cleaning cable S recommended.	 16/25 16/35 22/35 22/45 22/65 32/45 32/65 32/90 32/115	 171290 171291 172290 172291 172293 174291 174293 174295 174296	 **125,00** **140,00** **167,00** **188,00** **180,00** **189,00** **227,00** **280,00** **301,00**
Forked cutter to remove moderate to severe silting or persistent grease contamination. Made of hardened spring steel.	 16	 171305	 **82,50**
Cross-forked cutter to remove moderate to severe silting or persistent grease contamination. Made of hardened spring steel. Operation with pipe and drain cleaning cable S recommended.	 16	 171306	 **123,00**
Serrated forked cutter Versatile use, e.g. for removal of slurries and for mincing (crushing) of root infested pipe. Made of hardened spring steel.	 22/65 32/65 32/90	 172305 174305 174306	 **199,00** **219,00** **257,00**
Root cutter specially designed for root infested pipe. Hardened, replacable ring-type saw, cutting to front and rear. Operation with pipe and drain cleaning cable S recommended.	 22/65 32/65 32/90	 172310 174310 174311	 **294,00** **326,00** **372,00**
Chain knocker, smooth rings for final pipe and drain cleaning for removal of grease deposites and incrustations, e.g. limescale deposites on the inside of the pipe. For sensitive pipes, e.g. plastic.	 16 22 32	 171340 172340 174340	 **234,00** **307,00** **372,00**
Chain knocker, spiked links for final pipe and drain cleaning for removal of grease deposites and incrustations, e.g. limescale deposites on the inside of the pipe. For cast and concrete pipes.	 16 22 32	 171341 172341 174341	 **280,00** **380,00** **439,00**
Guide gloves, pair for secure gripping and guiding of pipe and drain cleaning cables		 172610	 **49,60**
Riveted guide glove, left **Riveted guide glove, right** for secure gripping and guiding of pipe and drain cleaning cables. Fully leather, inner surface riveted.		 172611 172612	 **104,00** **104,00**



Plastic Pipe Welding

Electric sleeve welding unit 292

Sleeve welding units 293

Butt welding machines 294

Butt welding units 298

REMS EMSG 160-2

Electric sleeve welding unit

Powerful, handy unit for welding plastic drain pipes with electric sleeves in PE.

Plastic pipes and electric sleeves in PE Ø 32 – 160 mm

For Geberit, Akatherm-Euro, Coes, Valsir, Waviduo

REMS EMSG 160-2 – automatic welding. Electronic control. Acoustic and visual monitoring of welding process.

Smallest sizes. Super-handy, light, only 1.1 kg. Can be used anywhere.

Electronic control with micro controller for automatic adjustment of welding current (welding temperature) and welding time according to sleeve size.

Automatic compensation of welding time in accordance with the ambient temperature.

Acoustic and visual monitoring of welding process.

Angled electrofusion plug for use in very confined spaces.

Wide work radius through extra-long cables.

Sturdy, impact-proof plastic housing with snap hook, for hanging next to the welding point. Dust and splash water-protected.

Manual pipe scraper for treating the surface of the pipe ends to be welded.

Info

Angled electrofusion plug for use in very confined spaces.

Supply format

REMS EMSG 160-2. Electric sleeve welding unit 230 V, 50 – 60 Hz, 1000 W, for welding plastic drain pipes with electric sleeves in PE made by Akatherm-Euro, Coes, Geberit, Valsir, Waviduo, Ø 32 – 160 mm. Electronic control, with acoustic and visual monitoring of welding process. In a sturdy, impact-proof plastic housing with snap hook. Welding lead 3.9 m. Manual pipe scraper. In sturdy case.

	Art.-No.	KM
	261002R220	**1.560,00**

All prices excl. VAT

Powerful electric tools for efficient sleeve welding.
Can be used anywhere, free-hand or on the work bench.

Plastic pipes and fittings
in PB, PE, PP, PVDF Ø 16 – 125 mm

REMS MSG – heating element according to DVS. High quality PTFE coating of heating spigots/sockets.

Design

Handy, light, safe. Free-hand or work bench assembly. Supplied in standard with supporting stand and bench support for mounting the unit in a horizontal or vertical position (bench support not supplied for MSG 25).

Heating element according to DVS

Plate-shaped, plane parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. Heating spigots and heating sockets according to DVS. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area. Fastening screws in stainless steel.

Temperature and temperature control

Choice of
- adjustable temperature 180 – 290°C, preadjusted to 260°C for PP pipes, with electronic temperature control with tight tolerance (EE) or
- Fixed temperature for PP pipes at 263°C, with electronic temperature control with a tolerance of +/- 1% (FE).

The electronic and manual temperature control automatically controls the preadjusted temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Supply format

REMS MSG. Sleeve welding unit for plastic pipes and fittings in PB, PE, PP, PVDF. Heating element 230 V, 50 – 60 Hz, without PTFE-coated heating spigots and heating sockets. Optionally adjustable temperature 180 – 290°C, pre-set for PP pipes at 260°C, with electronic temperature control (EE) or fixed temperature for PP pipes at 263°C, with electronic temperature control (FE). Support stand. Bench support for mounting the welding unit in a horizontal or vertical position (not for MSG 25). Hexagon key for assembly and dismantling of heating spigots and heating sockets. In a carton.

Description	Pipes Ø mm	Power W	Art.-No.	KM
25 EE	16 – 25	500	256020R220	**1.050,00**
63 FE	16 – 63	800	256213R220	**771,00**
63 EE	16 – 63	800	256220R220	**991,00**
125 EE	16 – 125	1400	256320R220	**1.470,00**

Other voltages available.

Info



Supply format

REMS MSG 63 FE Set. As REMS MSG 63 FE, but with PTFE-coated heating spigots, heating sockets for Ø 20, 25, 32 mm. Fastening screws in stainless steel. In steel case.

Description	Pipes Ø mm	Power W	Art.-No.	KM
	16 – 63	800	256233R220	**1.140,00**

Other voltages available.

Supply format

REMS MSG 63 EE Set. As REMS MSG 63 EE, but with PTFE-coated heating spigots, heating sockets for Ø 20, 25, 32 mm. Fastening screws in stainless steel. In steel case.

Description	Pipes Ø mm	Power W	Art.-No.	KM
	16 – 63	800	256240R220	**1.620,00**

Other voltages available.

Accessories

Description	Pipes Ø mm	Art.-No.	KM
Heating spigot, heating socket, fastening screw in stainless steel	16	256400	**111,00**
	17	256410	**111,00**
	18	256420	**111,00**
	19	256430	**111,00**
	20	256440	**111,00**
	25	256450	**124,00**
	32	256460	**138,00**
	40	256470	**183,00**
	50	256480	**210,00**
	63	256490	**282,00**
	75	256500	**496,00**
	90	256510	**538,00**
	110	256520	**626,00**
	125	256530	**731,00**
Steel case			
REMS MSG 25 , REMS MSG 63		256242	**282,00**
REMS MSG 125		256342	**374,00**

REMS SSM 160RS

Butt welding machine

Handy, easy-to-carry compact machine. Complete only 45 kg. Ideal for sanitary installations and installation of drain pipes, chimney reconstruction with PVDF pipes. For job site and workshop.

Plastic pipes and fittings in PB, PE, PP, PVDF — Ø 40 – 160 mm

PE Ø 40 – 90 mm	SDR ≥ 6
PE Ø 40 – 110 mm	SDR ≥ 9
PE Ø 40 – 125 mm	SDR ≥ 11
PE Ø 40 – 140 mm	SDR ≥ 17
PE Ø 40 – 160 mm	SDR ≥ 21

REMS SSM 160RS – ideal for the pipe fitter. Light and compact. Heating element according to DVS. Electronic temperature control. High-quality PTFE coating. Powerful facing cutter. Closed facing cutter housing.

Design

Light and compact. Low weight, complete only 60 kg.
Can be easily carried by one person.
- Base frame in cast aluminium
- Free suspension of butt welding unit REMS SSG 180 for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches.
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Can be used on the workbench or on the tubular stand provided as standard (= sub-frame = transport device).

Heating element according to DVS

Plate-shaped, plane parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area. Protective cover for heating element.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device, also for angular branches

Sturdy quick clamping device made of nickel-plated steel, consisting of 2 vices with 2 clamping inserts each for pipes of Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. Also suitable for angular branches.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes Ø 160 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm.

Info

Supply format

REMS SSM 160RS. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF, PE Ø 40 – 90 mm SDR ≥ 6, PE Ø 40 – 110 mm SDR ≥ 9, PE Ø 40 – 125 mm SDR ≥ 11, PE Ø 40 – 140 mm SDR ≥ 17, PE Ø 40 – 160 mm SDR ≥ 21. Butt welding unit with PTFE-coated heating element 230 V, 50 – 60 Hz, 1200 W. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Protective cover for heating element. Electric planing device 230 V, 50-60 Hz, 500 W. Pressing device. Quick clamping device, also for angular branches, consisting of 2 vices with 2 clamping inserts each Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. 2 pipe rests Ø 160 mm with pipe rest inserts Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm. Work key. Steel case for pipe support inserts and clamp inserts. Tubular stand = base frame = carrying device.

	Art.-No.	KM
	252026R220	**9.230,00**

Accessories

Description	Art.-No.	KM
Planing blade (piece)	252103R	**252,00**

All prices excl. VAT

REMS SSM 160KS

Butt welding machine

Powerful, proven, easy-to-transport compact machine.
Ideal for sanitary installation, drain pipe installation, chimney reconstruction with PVDF pipes.
For job site and workshop.

Plastic pipes and fittings
in PB, PE, PP, PVDF — Ø 40 – 160 mm

PE Ø 40 – 90 mm	SDR ≥ 6
PE Ø 40 – 110 mm	SDR ≥ 9
PE Ø 40 – 125 mm	SDR ≥ 11
PE Ø 40 – 140 mm	SDR ≥ 17
PE Ø 40 – 160 mm	SDR ≥ 21

REMS SSM 160KS – ideal for the pipe fitter. Heating element according to DVS. Electronic temperature control. High-quality PTFE coating. Powerful facing cutter. Closed facing cutter housing.

Design

Compact, robust, job site-proven. Machine on sheet metal base weighs 101 kg. Easy to carry.

- Base frame in aluminium cast
- Free suspension of butt welding unit REMS SSG 180 for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches.
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Machine on sheet steel base with built-in drawer for clamping and pipe rest inserts
- Suitable for use on a work bench or on the standard supplied sheet metal cabinet (= carrying case).

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area. Protective cover for heating element.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device, also for angular branches

Sturdy quick clamping device made of nickel-plated steel, consisting of 2 vices with 2 clamping inserts each for pipes of Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. Also suitable for angular branches.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes of Ø 160 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm.

Info

Supply format

REMS SSM 160KS. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF, PE Ø 40 – 90 mm SDR ≥ 6, PE Ø 40 – 110 mm SDR ≥ 9, PE Ø 40 – 125 mm SDR ≥ 11, PE Ø 40 – 140 mm SDR ≥ 17, PE Ø 40 – 160 mm SDR ≥ 21. Butt welding unit with PTFE-coated heating element 230 V 50 – 60 Hz, 1200 W. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Protective cover for heating element. Electric planing device 230 V, 50-60 Hz, 500 W. Pressing device. Quick clamping device, also for angular branches, consisting of 2 vices with 2 clamping inserts each Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. 2 pipe rests Ø 160 mm with pipe rest inserts Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm. Sheet steel base with built-in drawer. Work key. Closed sheet metal cabinet = carrying case.

	Art.-No.	KM
	252046R220	**12.320,00**

Accessories

Description	Art.-No.	KM
Planing blade (piece)	252103R	**252,00**

REMS SSM 250KS

Butt welding machine

Powerful, proven, easy-to-transport compact machine.
Ideal for sanitary installation, drain pipe installation, chimney reconstruction with PVDF pipes.
For job site and workshop.

Plastic pipes and fittings
in PB, PE, PP, PVDF — Ø 75 – 250 mm

PE Ø 75 – 140 mm	SDR ≥ 6
PE Ø 75 – 160 mm	SDR ≥ 9
PE Ø 75 – 180 mm	SDR ≥ 11
PE Ø 75 – 200 mm	SDR ≥ 13.6
PE Ø 75 – 225 mm	SDR ≥ 17.6
PE Ø 75 – 250 mm	SDR ≥ 22

REMS SSM 250KS – compact and robust.

Design

Compact, robust, job site-proven. Easy to carry.
Machine on sheet metal base weighs 109 kg.

- Base frame in aluminium cast
- Free suspension of butt welding unit for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches.
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Machine on sheet steel base with built-in drawer for clamping and pipe rest inserts.
- Suitable for use on a work bench or on the standard supplied sheet metal cabinet (= carrying case).

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device for angular branches

Sturdy quick clamping device made of nickel-plated steel which grips the pipe all round, consisting of 2 clamps Ø 250 mm with jaws Ø 250 mm, with 2 clamping jaws and 2 clamping inserts each for pipes of Ø 75, 90, 110, 125, 160, 200 mm. Also suitable for angular branches. Clamping jaws and clamping inserts available for pipes of Ø 140, 180, 225 mm.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes Ø 75, 90, 110, 125, 140, 160, 180, 200, 225, 250 mm. Pipe rest inserts available for pipes of Ø 140, 180, 225 mm.

Info

Supply format

REMS SSM 250K. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF. PE Ø 75 – 140 mm SDR ≥ 6, PE Ø 75 – 160 mm SDR ≥ 9, PE Ø 75 – 180 mm SDR ≥ 11, PE Ø 75 – 200 mm SDR ≥ 13.6, PE Ø 75 – 225 mm SDR ≥ 17.6, PE Ø 75 – 250 mm SDR ≥ 22. Butt welding unit with PTFE-coated heating element 230 V, 50 – 60 Hz, 1300 W. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Electric facing cutter unit 230 V, 50 – 60 Hz, 500 W. Quick clamping device, also for angular branches, consisting of 2 clamps Ø 250 mm with jaws Ø 250 mm, with 2 clamping jaws and 2 clamping inserts each for pipes of Ø 75, 90, 110, 125, 160, 200 mm. 2 pipe rests with pipe rest inserts Ø 75, 90, 110, 125, 160, 200, 250 mm. Sheet steel base with built-in drawer. Work key. Closed sheet metal cabinet = carrying case.

	Art.-No.	KM
	254025R220	**19.990,00**

Accessories

Description	Art.-No.	KM
Planing blade (piece)	254103	**372,00**

All prices excl. VAT

REMS SSM 315RF

Butt welding machine

Compact, easy-to-transport high-performance machine for sanitary installation, drain pipe installation, chimney reconstruction with PVDF pipes. For job site and workshop.

Plastic pipes and fittings
in PB, PE, PP, PVDF — Ø 90 – 315 mm

PE Ø 90 – 180 mm	SDR ≥ 6
PE Ø 90 – 200 mm	SDR ≥ 7.4
PE Ø 90 – 225 mm	SDR ≥ 9
PE Ø 90 – 250 mm	SDR ≥ 13.6
PE Ø 90 – 280 mm	SDR ≥ 17
PE Ø 90 – 315 mm	SDR ≥ 21

REMS SSM 315RF – convenient for job site and workshop.

Design

Compact, robust, job site-proven. Weight including tubular stand on wheels 154 kg.

- Base frame in aluminium cast
- Free suspension of butt welding unit for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Standard supply with tubular wheel stand for secure standing and easy transport.

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device

Sturdy quick clamping devices made of nickel-plated steel which grip the pipe all round, for pipes of Ø 315 mm. 4 clamping inserts each for pipes of Ø 90, 110, 125, 160, 200, 250 mm. Clamping inserts available for pipes of Ø 140, 180, 225, 280 mm.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes Ø 315 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe rest inserts each for pipes of Ø 90, 110, 125, 160, 200, 250 mm. Pipe rest inserts available for pipes of Ø 140, 180, 225, 280 mm.

Info

Supply format

REMS SSM 315RF. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF. PE Ø 90 – 180 mm SDR ≥ 6, PE Ø 90 – 200 mm SDR ≥ 7.4, PE Ø 90 – 225 mm SDR ≥ 9, PE Ø 90 – 250 mm SDR ≥ 13.6, PE Ø 90 – 280 mm SDR ≥ 17, PE Ø 90 – 315 mm SDR ≥ 21. Butt welding unit with PTFE-coated heating element 230 V, 50 – 60 Hz, 3000 W. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Electric facing cutter unit 230 V, 50 – 60 Hz, 500 W. Pressing device. 2 quick clamping devices Ø 315 mm with 2 clamping inserts each for pipes of Ø 90, 110, 125, 160, 200, 250 mm. 2 pipe supports Ø 315 mm with pipe support inserts Ø 90, 110, 125, 160, 200, 250 mm. Ring spanner. Boxes for clamping and pipe rest inserts. Tubular stand on wheels.

	Art.-No.	KM
	255020R220	**27.290,00**

Accessories

Description	Art.-No.	KM
Planing blade (piece)	255103	**397,00**

Powerful electric tools for efficient butt welding.
Can be used anywhere, free-hand or on the work bench.

Plastic pipes and fittings
in PB, PE, PP, PVDF ≤ Ø 280 mm

REMS SSG – heating element according to DVS.
Electronic temperature control.
High-quality PTFE coating.

Design

Handy, light, safe. Free-hand or work bench assembly. Supplied as standard with supporting stand. Bench support available as accessory for mounting the unit in a horizontal or vertical position.

Heating element according to DVS

Plate-shaped, plane parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.



Info

Supply format

REMS MSG. Butt welding unit for plastic pipes and fittings in PB, PE, PP, PVDF. PTFE-coated heating element 230 V, 50 – 60 Hz. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Support stand. In a carton.

Description	Heating element Ø mm	Pipes ≤ Ø mm	Power W	Art.-No.	KM
110/45° EE	125	110	500	250020R220	**1.050,00**
125 EE	145	125	700	250120R220	**1.140,00**
180 EE	200	180	1200	250220R220	**1.310,00**
280 EE	300	280	1300	250320R220	**1.580,00**

Accessories

Description	Art.-No.	KM
Bench support for mounting the unit		
in a horizontal or vertical position		
REMS SSG 110/45°, 125, 180	250041	**140,00**
REMS SSG 280	250341	**144,00**
Steel case		
REMS SSG 110/45°	250042	**219,00**
REMS SSG 125	250142	**219,00**
REMS SSG 180	250242	**219,00**
REMS SSG 280	250342	**311,00**
Protection cover for heating element		
REMS SSG 110, 110/45°, 125	250143	**86,70**
REMS SSG 180	250243	**89,30**
REMS SSG 280	250343	**103,00**

Diamond core drilling
Diamond chasing and cutting machine
Wet and dry suction

	Electric diamond core drilling machines	302
	Drill stands	310
	Universal diamond core drilling crowns	312
	Universal diamond core drilling crowns LS	314
	Electric diamond core drilling machine with micro-pulse technology	316
	Dry diamond core drilling crowns LS	319
	Tile drilling	320
	Diamond chasing and cutting machine	322
	Diamond cutting discs	323
	Dry and wet extractor	324

REMS Picus S1

Electric diamond core drilling machine

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete, steel-reinforced concrete	≤ Ø 102 (132) mm
Masonry and other materials	≤ Ø 162 mm

REMS Universal diamond core drilling crowns, also suitable for drive machines of other makes, see page 312 – 314.

Info

REMS Picus S1 – Core drilling instead of chiselling. Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min.

1 system – 4 applications. Ideal for plumbers.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. For many materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only **one** type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1¼ male, BSPP ½ female. Robust, suitable for the building site. Extra light, only 5.2 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min. Practical spade handle and stabiliser for hand held drilling. Throat Ø 60 mm for holding the drive machine in the drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick-coupling with water stop and hose connection ½". Suction rotor for sucking off dust for dry drilling with connection for conventional vacuum cleaner, as accessory.

Drive

Robust, powerful 1850 W universal motor. Load speed drilling spindle 580 rpm. Stable, maintenance-free gear. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1¼ female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m^3). Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2 and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

Drilling start aid

Drilling start aid G ½ UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill Ø 8 mm.

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).

REMS Simplex 2

REMS Titan

REMS Picus S1

Electric diamond core drilling machine

REMS Picus S1 Basic-Pack

Supply format

REMS Picus S1 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete ≤ Ø 102 (132) mm, masonry and other materials ≤ Ø 162 mm. For dry and wet drilling, hand held or with drill stand. Drive machine with drilling crown connecting thread UNC 1¼ male, BSPP ½ female, maintenance-free gear with safety slip clutch, universal motor 230 V, 50 – 60 Hz, 1850 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Load speed drilling spindle 580 rpm. Water supply device with adjustable shut-off valve and quick coupling with water stop and ½" hose connection. Stabiliser. Drilling start aid G ½ UDKB with drill Ø 8 mm, Allen key size 3. Single open-ended wrench size 32. In sturdy steel case.

	Art.-No.	KM
	180010R220	**3.300,00**

Other voltages on request.

REMS Picus S1 Set Simplex 2

Supply format

REMS Picus S1 Set Simplex 2. REMS Picus S1 Basic-Pack with REMS Simplex 2 drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	KM
	180032R220	**5.360,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Picus S1 drive unit	180000R220	**3.200,00**
Steel case with inlay	180600R	**261,00**
REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 312.		
REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 314.		
REMS Pull 2 L / M, dry and wet extractors, see page 324		
Additional accessories see page 310 – 311.		

REMS Picus S3

Electric diamond core drilling machine

Powerful, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete, steel-reinforced concrete	≤ Ø 152 (200) mm
Masonry and other materials	≤ Ø 250 mm

REMS Universal diamond core drilling crowns, also suitable for drive machines of other makes, see page 312 – 314.

REMS Picus S3 – Core drilling instead of chiselling. Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min.

1 system – 4 applications. Ideal for plumbers.

Universal use
Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile and efficient, e.g. drilling in steel-reinforced concrete, masonry and other materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage
Only **one** type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design
Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1¼ male, BSPP ½ female. Robust, suitable for the building site. Only 7.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min. Practical spade handle and stabiliser for hand held drilling. Throat Ø 60 mm for holding the drive machine in the drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick-coupling with water stop and hose connection ½". Suction rotor for sucking off dust for dry drilling with connection for conventional vacuum cleaner, as accessory.

Drive
Robust, powerful 2200 W universal motor. Stable, maintenance-free 3-speed gear for optimum selection of load speed according to the drilling diameter. Load speed drilling spindle 530 rpm, 1280 rpm, 1780 rpm. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics
Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns
Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1¼ female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Dust extraction in accordance with EN 60335-2-69
When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m^3). Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2 and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

Drilling start aid
Drilling start aid G ½ UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill Ø 8 mm, as accessory.

Water extractor unit
Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

Drill stand
REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).

Info

REMS Simplex 2

REMS Titan

REMS Picus S3

Electric diamond core drilling machine

REMS Picus S3 Basic-Pack

REMS Picus S3 Set Titan

REMS Picus S3 Set 62-82-132 Titan

Supply format

REMS Picus S3 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete ≤ Ø 152 (200) mm, masonry and other materials ≤ Ø 250 mm. For dry and wet drilling, hand held or with drill stand. Drive machine with drilling crown connecting thread UNC 1¼ male, BSPP ½ female, maintenance-free 3-speed gear with safety slip clutch, universal motor 230 V, 50 – 60 Hz, 2200 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock, personal protection switch (PRCD). Load speed drilling spindle 530 rpm, 1280 rpm, 1780 rpm. Water supply with adjustable shut-off valve and quick-coupling with water stop and hose connection ½". Stabiliser. Starting aid BSPP ½, Allen key size 3. Single open-ended wrench size 32. In sturdy steel case.

	Art.-No.	KM
	180011R220	**4.100,00**

Other voltages on request.

Supply format

REMS Picus S3 Set Titan. REMS Picus S3 Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	KM
	180029R220	**7.230,00**

Other voltages on request.

Supply format

REMS Picus S3 Set 62+82+132 Titan. REMS Picus S3 Basic-Pack with REMS Universal diamond core drilling crowns UDKB Ø 62+82+132 mm and REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	KM
	180028R220	**8.500,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Picus S3 drive unit	180001R220	**3.990,00**
Steel case with inlay	180600R	**261,00**
REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 312.		
REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 314.		
REMS Pull 2 L / M, dry and wet extractors, see page 324		
Additional accessories see page 310 – 311.		

REMS Picus SR

Electric diamond core drilling machine
with speed regulation

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. With speed regulation. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete, steel-reinforced concrete	≤ Ø 162 (200) mm
Masonry and other materials	≤ Ø 250 mm

REMS Universal diamond core drilling crowns, also suitable for drive machines of other makes, see page 312 – 314.

REMS Picus SR – Core drilling instead of chiselling. Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min. With speed regulation.

1 system – 4 applications.
Ideal for plumbers.

Universal use
Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile and efficient, e.g. drilling in steel-reinforced concrete, masonry and other materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage
Only **one** type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design
Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1¼ male, BSPP ½ female. Robust, suitable for the building site. Extra light, only 6.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min. Practical spade handle and stabiliser for hand held drilling. Throat Ø 60 mm for holding the drive machine in the drill stand. Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick-coupling with water stop and hose connection ½".

Drive
Robust, powerful 2200 W universal motor. Overheating protection by temperature monitoring of the motor's field winding with a PTC resistor (Positive Temperature Coefficient). Stable, maintenance-free, 2-step gear. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Speed-Regulation
Stepless electronic speed regulation of the drive machine for selecting the speed according to the material. The speed is steplessly adjustable on the dial: 250 rpm to 500 rpm (1st gear) or 600 rpm to 1200 rpm (2nd gear). The electronic speed control that is being used keeps the selected speed constant, also under load. The speed of the drilling crown is kept at the nominal value until it meets with resistance and drops below a critical value. The drive motor stops. When the load on the drive unit is relieved again, the drill runs back up to nominal speed so that work can continue immediately at nominal speed **(Patent EP 2 085 191)**. Advantage: The optimum drilling speed (load speed) selected for the respective material and the drilling crown diameter remains constant for the entire duration of the drilling. For the best drilling performance and maximum life of the drilling crowns.

Multifunction electronics
Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns
Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1¼ female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Dust extraction in accordance with EN 60335-2-69
When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³). Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2 and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

German Quality Product

With speed regulation for the best drilling performance and maximum life of the drilling crowns.

Info

REMS Simplex 2

REMS Titan

REMS Picus SR

Electric diamond core drilling machine
with speed regulation

Drilling start aid

Drilling start aid G ½ UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill Ø 8 mm, as accessory.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

REMS Picus SR Basic-Pack

REMS Picus SR Set Titan

REMS Picus SR Set 62-82-132 Titan

Supply format

REMS Picus SR Basic-Pack. For core drilling in concrete, steel-reinforced concrete ≤ Ø 162 (200) mm, masonry and other materials ≤ Ø 250 mm. For dry or wet drilling, hand held or with drill stand. Drive machine with drilling crown connection thread UNC 1¼ male, G ½ female, maintenance-free 2-step gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 2200 W. Stepless electronic speed regulation 250 rpm to 500 rpm (1st gear) or 600 rpm to 1200 rpm (2nd gear), overheating protection. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Water supply device with adjustable shut-off valve and quick coupling with water stop and ½" hose connection. Stabiliser. Spacer set. Single open ended wrench size 32. In sturdy steel case.

	Art.-No.	KM
	183010R220	**3.470,00**

Other voltages on request.

Supply format

REMS Picus SR Set Titan. REMS Picus SR Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	KM
	183022R220	**6.260,00**

Other voltages on request.

Supply format

REMS Picus SR Set 62+82+132 Titan. REMS Picus SR Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete and REMS Universal diamond core drilling crowns UDKB Ø 62+82+132 mm.

	Art.-No.	KM
	183023R220	**7.250,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Picus SR drive unit	183000R220	**2.690,00**
Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand, consisting of spacer and 2 cylinder head screws M 8×65	183632R	**98,30**
Steel case with inlay	180600R	**261,00**
REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 312.		
REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 314.		
REMS Pull 2 L / M, dry and wet extractors, see page 324		
Additional accessories see page 310–311.		

REMS Picus S2/3,5

Electric diamond core drilling machine

Powerful. robust core drilling machine for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Dry or wet drilling with drill stand. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, masonry and other materials Ø 40 – 300 mm

REMS Universal diamond core drilling crowns, also suitable for drive machines of other makes, see page 312 – 314.

REMS Picus S2/3,5 – Core drilling instead of chiselling. Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 2 min.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile and efficient, e.g. drilling in steel-reinforced concrete, masonry and other materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only **one** type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1¼ male. Light loosening ring, for light loosening of the diamond core crowns. Compact, robust, suitable for the building site. Weight just 14.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 2 min. Clamping plate for fast clamping to the drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick coupling with water stop and hose connection ½".

Drive

Robust, powerful 3420 W universal motor. Stable, maintenance-free 2-speed gear for optimum selection of load speed according to the drilling diameter. Load speed drilling spindle 320 rpm, 760 rpm. Blocking protection by safety slip clutch. Rocker switch. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1¼ female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

Drill stand REMS Titan

Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Drill column made of rigid, unbendable square precision steel tube ⍈ 50 mm, with extra narrow tolerance, for low-vibration guiding of the slide. Continuously tiltable with degree scale up to 45°, with double support by adjustable, single-part steel girders, for maximum thrust pressure. Highly stable, 3-sided guidance of the drill column in the base plate and triple cross fastening for high rigidity in vertical drilling. 4 Eyebolts for levelling unevenness of the floor, for exact standing position. Drill depth scale. Slide guided on all sides by adjustable, pretensioned plastic slide bearings. Precision in-feed drive ensures easy, low-vibration drilling and precise, low-vibration drill thrust. For high thrust pressure and long life of the drilling crowns. Spirit level integrated in the slide for exact alignment of the drill stand. Locking of the slide for simple assembly of the drilling crown and safe transport. Rigid connection plate made of wear-resistant spheroidal iron. Quick-clamping device for accommodating drive units with a suitable connection plate. Highly stable clamping bracket, unbendable and rigid, for accommodating drive units with Ø 60 mm clamping throat. Rack and pinion force transmission with ergonomically designed pressing lever which can be inserted in both sides of the slide. Wide steel rack. Base plate with groove for sealing ring of the vacuum fastening. Vacuum fastening as accessory. Drill column with adjustable clamping head for clamping the drill stand between the ceiling and floor or between two walls. Mobile drill stand for easy transport. Weight 19.5 kg.

With tools, consisting of Allen key size 6, single open ended wrench size SW 19 and SW 30 and fastening kit for masonry and concrete, consisting of 2 M12 splaying anchors, 10 M12 hammer anchors for concrete, setting iron for M12 hammer anchors, cord threaded bar M12 × 52, quick clamping nut, washer, carbide masonry drill Ø 15 mm SDS-plus, in box.

Info

REMS Titan

REMS Picus S2/3,5

Electric diamond core drilling machine

REMS Picus S2/3,5 Basic-Pack

Supply format

REMS Picus S2/3,5 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed, Ø 40 – 300 mm. For dry and wet drilling with drill stand. Drive machine with drilling crown connecting thread UNC 11/4 male, maintenance-free 2-speed gear with safety slip clutch, universal motor 230 V, 50 – 60 Hz, 3420 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Load speed drilling spindle 320 rpm, 760 rpm. Water supply device with adjustable shut-off valve and quick coupling with water stop and hose connection ½". Light loosening ring. Single open-ended wrench size 32. In a carton.

	Art.-No.	KM
	180012R220	**6.430,00**

Other voltages on request.

REMS Picus S2/3,5 Set Titan

Supply format

REMS Picus S2/3,5 Set Titan. REMS Picus SR/3.5 Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	KM
	180030R220	**9.560,00**

Other voltages on request.

Accessories

Description
REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 312.
REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 314.
REMS Pull 2 L / M, dry and wet extractors, see page 324
Additional accessories see page 310 – 311.

Supply format

REMS Simplex 2. Robust, handy drilling stand for core drilling up to Ø 202 mm. Drill column made of rigid, unbendable square precision steel tube ⍁ 50 mm, with extra narrow tolerance, for low-vibration guiding of the slide. Drilling column guided in sturdy stand and double bolted for high rigidity during drilling. Steel section stand. 4 Set screws for levelling unevenness of the floor, for exact standing position. Clamping bracket for holding drive machines with clamping throat Ø 60 mm. Slide guided on all sides by adjustable, pretensioned plastic slide bearings. Precision in-feed drive ensures easy, low-vibration drilling and precise, low-vibration drill thrust. For high thrust pressure and long life of the drilling crowns. Spirit level integrated in the slide for exact alignment of the drill stand. Locking of the slide for simple assembly of the drilling crown and safe transport. Stable clamping bracket, unbendable and rigid, for accommodating drive units with Ø 60 mm clamping throat. Rack and pinion force transmission with ergonomically designed pressing lever which can be inserted in both sides of the slide. Wide steel rack Weight 12 kg.

With tools comprising Allen key size 6, single open ended wrench size SW 19 and SW 30 and fastening kit for masonry and concrete, consisting of 2 M12 splaying anchors, 10 M12 hammer anchors for concrete, setting iron for M12 hammer anchors, cord threaded bar M12 × 52, quick clamping nut, washer, carbide masonry drill Ø 15 mm SDS-plus in box.

For REMS Picus S1, REMS Picus S3, REMS Picus SR, REMS Picus DP and other makes.

Info

	Art.-No.	KM
	183700R	**2.060,00**

Supply format

REMS Titan. Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Drill column made of rigid, unbendable square precision steel tube ⍁ 50 mm, with extra narrow tolerance, for low-vibration guiding of the slide. Continuously tiltable with degree scale up to 45°, with double support by adjustable, single-part steel girders, for maximum thrust pressure. Highly stable, 3-sided guidance of the drill column in the base plate and triple cross fastening for high rigidity in vertical drilling. 4 Eyebolts for levelling unevenness of the floor, for exact standing position. Drill depth scale. Slide guided on all sides by adjustable, pretensioned plastic slide bearings. Precision in-feed drive ensures easy, low-vibration drilling and precise, low-vibration drill thrust. For high thrust pressure and long life of the drilling crowns. Spirit level integrated in the slide for exact alignment of the drill stand. Locking of the slide for simple assembly of the drilling crown and safe transport. Rigid connection plate made of wear-resistant spheroidal iron. Quick-clamping device for accommodating drive units with a suitable connection plate. Highly stable clamping bracket, unbendable and rigid, for accommodating drive units with Ø 60 mm clamping throat. Rack and pinion force transmission with ergonomically designed pressing lever which can be inserted in both sides of the slide. Wide steel rack. Base plate with groove for sealing ring of the vacuum fastening. Vacuum fastening as accessory. Drill column with adjustable clamping head for clamping the drill stand between the ceiling and floor or between two walls. Mobile drill stand for easy transport Weight 19.5 kg.

With tools comprising Allen key size 6, single open ended wrench size SW 19 and SW 30 and fastening kit for masonry and concrete, consisting of 2 M12 splaying anchors, 10 M12 hammer anchors for concrete, setting iron for M12 hammer anchors, cord threaded bar M12 × 52, quick clamping nut, washer, carbide masonry drill Ø 15 mm SDS-plus in box.

System advantage: For REMS Picus S1, REMS Picus S3, REMS Picus SR, REMS Picus S2/3,5, REMS Picus DP and other makes. Use spacer set (see below) when using with REMS Picus SR.

Info

	Art.-No.	KM
	183600R	**3.130,00**

Description	Art.-No.	KM
Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand, consisting of spacer and 2 cylinder head screws M 8 × 65	183632R	**98,30**

Accessories

For REMS Picus S1, REMS Picus S3, REMS Picus SR, REMS Picus S2/3,5 and other makes

Description	Art.-No.	KM
Water pressure tank for 10 ltr of water, for wet drilling without water connection	182006R	**416,00**
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	**117,00**
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	**56,90**
Hammer anchor M12 (pack of 50), for concrete	079005R50	**223,00**
Setting iron for hammer anchor M12	182050R	**32,60**
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	**129,00**
Splaying anchor M12 (pack of 10), for masonry, reusable	079006R10	**208,00**
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	**148,00**
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	**110,00**
Titan vacuum fastening, consisting of cover plate with nipple for ⅜" screw connection and sealing ring for base plate.	183603R	**202,00**
Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	**3.870,00**
Laser drilling centre pointer	183604R	**263,00**
Drilling start aid G ½ UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 180160 R), with carbide masonry drill Ø 8 mm	180140R	**186,00**
Carbide masonry drill Ø 8 mm for drilling aid	079013	**38,20**
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	**77,60**
Light loosening ring, for light loosening of the diamond core crown	180015	**41,80**
Drilling crown extension 200 mm	180155R	**124,00**
Sharpening stone for diamond core drilling crowns	079012	**131,00**
Circular spirit level, magnetic, for aligning the drill stand	182010R	**153,00**
Suction rotor for dust extraction with G ½ male connecting thread, UNC 1¼ male connecting thread and with connection for REMS Pull 2 and other suitable extractors.	180160R	**351,00**
Water suction device, for wet drilling up to Ø 170 mm, consisting of water collection ring with pressure ring, rubber washer Ø 200 mm and universal pressure pad for all REMS drilling stands.	183606R	**796,00**
Rubber washer Ø 200 mm (pack of 10), for water suction device	183675R10	**151,00**
REMS Pull 2 L / M, dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		



REMS Universal diamond core drilling crowns

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

High quality universal diamond core drilling crowns. Inductively soldered. Universally usable for dry and wet drilling, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed and other	Ø 32 – 300 mm

REMS Universal diamond core drilling crowns – Inductively soldered. Diamond segments with conical cut for fast, easy and quiet drilling. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, for dry and wet drilling, hand held or with drill stand.

Single connecting thread UNC 1¼ female. Drilling depth 420 mm.

Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with conical cut ("roof shape") for fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Drive through all REMS Picus drive machines and suitable drive machines of other makes having connecting thread UNC 1¼ male. Adapter for using REMS Universal diamond core drilling crowns in drive machines having other connecting threads/other tool holders, as accessory.

Suck off dusts that occur during dry drilling with REMS Pull 2 M safety vacuum cleaner, certified for extracting health hazardous dusts of dust class M (page 324).



Info

REMS Universal diamond core drilling crowns

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

Supply format

REMS Universal diamond core drilling crown. Inductively soldered, resolderable. Universally usable for dry and wet drilling, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1¼ female. Drilling depth 420 mm. In a carton.

Ø × drilling depth × connection	Number of segments	Art.-No.	KM
UDKB 32 × 420 × UNC 1¼	4	181010R	**290,00**
UDKB 42 × 420 × UNC 1¼	4	181015R	**271,00**
UDKB 52 × 420 × UNC 1¼	5	181020R	**288,00**
UDKB 62 × 420 × UNC 1¼	6	181025R	**313,00**
UDKB 72 × 420 × UNC 1¼	7	181030R	**355,00**
UDKB 82 × 420 × UNC 1¼	7	181035R	**385,00**
UDKB 92 × 420 × UNC 1¼	8	181040R	**435,00**
UDKB 102 × 420 × UNC 1¼	8	181045R	**445,00**
UDKB 112 × 420 × UNC 1¼	9	181050R	**471,00**
UDKB 122 × 420 × UNC 1¼	10	181055R	**531,00**
UDKB 127 × 420 × UNC 1¼	10	181059R	**552,00**
UDKB 132 × 420 × UNC 1¼	11	181060R	**576,00**
UDKB 152 × 420 × UNC 1¼	12	181065R	**685,00**
UDKB 162 × 420 × UNC 1¼	12	181070R	**725,00**
UDKB 182 × 420 × UNC 1¼	12	181075R	**802,00**
UDKB 200 × 420 × UNC 1¼	12	181080R	**848,00**
UDKB 225 × 420 × UNC 1¼	13	181085R	**1.040,00**
UDKB 250 × 420 × UNC 1¼	14	181090R	**1.060,00**
UDKB 300 × 420 × UNC 1¼	22	181095R	**1.390,00**

Accessories

Description	Art.-No.	KM
Light loosening ring, for light loosening of the diamond core crown	180015	**41,80**
Drilling crown extension 200 mm	180155R	**124,00**
Adapter UNC 1¼ male to G ½ male	180052	**63,60**
Adapter UNC 1¼ male to G ½ female	180056	**57,80**
Adapter UNC 1¼ male for Hilti BI, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BI tool holder.	180053	**97,70**
Adapter UNC 1¼ male for Hilti BU, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BU tool holder.	180054	**225,00**
Adapter UNC 1¼ male for Hilti BL, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BL tool holder.	180057R	**225,00**
Sharpening stone for diamond core drilling crowns	079012	**131,00**
Single open ended wrench size 41 for UDKB	079003	**77,60**

Additional adapters for using REMS Universal diamond core drilling crowns in drive machines of other makes, on request.

REMS Universal diamond core drilling crowns LS

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

High quality universal diamond core drilling crowns. Laser welded. Universally usable for dry and wet drilling, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed and other — Ø 32 – 200 mm

Info

REMS universal diamond core drilling crowns LS – laser welded. Diamond segments with conical cut for fast, easy and quiet drilling. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, for dry and wet drilling, hand held or with drill stand.

Single connecting thread UNC 1¼ female. Drilling depth 420 mm.

Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with conical cut ("roof shape") for fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Drive through all REMS Picus drive machines and suitable drive machines of other makes having connecting thread UNC 1¼ male. Adapter for using REMS Universal diamond core drilling crowns in drive machines having other connecting threads/other tool holders, as accessory.

Suck off dusts that occur during dry drilling with REMS Pull 2 M safety vacuum cleaner, certified for extracting health hazardous dusts of dust class M (page 324).

REMS Universal diamond core drilling crowns LS

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

Supply format

REMS Universal diamond core drilling crown. Laser welded! High temperature-resistant! Universally usable for dry and wet drilling, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1¼ female. Drilling depth 420 mm. In a carton.

Ø × drilling depth × connection	Number of segments	Art.-No.	KM
UDKB LS 32 × 420 × UNC 1¼	1	181410R	**319,00**
UDKB LS 42 × 420 × UNC 1¼	4	181415R	**298,00**
UDKB LS 52 × 420 × UNC 1¼	5	181420R	**317,00**
UDKB LS 62 × 420 × UNC 1¼	6	181425R	**345,00**
UDKB LS 72 × 420 × UNC 1¼	6	181430R	**391,00**
UDKB LS 82 × 420 × UNC 1¼	7	181435R	**424,00**
UDKB LS 92 × 420 × UNC 1¼	8	181440R	**479,00**
UDKB LS 102 × 420 × UNC 1¼	9	181445R	**492,00**
UDKB LS 112 × 420 × UNC 1¼	9	181450R	**519,00**
UDKB LS 122 × 420 × UNC 1¼	10	181455R	**586,00**
UDKB LS 127 × 420 × UNC 1¼	10	181459R	**609,00**
UDKB LS 132 × 420 × UNC 1¼	10	181460R	**634,00**
UDKB LS 152 × 420 × UNC 1¼	11	181465R	**754,00**
UDKB LS 162 × 420 × UNC 1¼	12	181470R	**798,00**
UDKB LS 182 × 420 × UNC 1¼	13	181475R	**964,00**
UDKB LS 200 × 420 × UNC 1¼	14	181480R	**1.020,00**

Accessories

Description	Art.-No.	KM
Light loosening ring, for light loosening of the diamond core crown	180015	**41,80**
Drilling crown extension 200 mm	180155R	**124,00**
Adapter UNC 1¼ male to G ½ male	180052	**63,60**
Adapter UNC 1¼ male to G ½ female	180056	**57,80**
Adapter UNC 1¼ male for Hilti BI, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BI tool holder.	180053	**97,70**
Adapter UNC 1¼ male for Hilti BU, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BU tool holder.	180054	**225,00**
Adapter UNC 1¼ male for Hilti BL, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BL tool holder.	180057R	**225,00**
Sharpening stone for diamond core drilling crowns	079012	**131,00**
Single open ended wrench size 41 for UDKB	079003	**77,60**

Additional adapters for using REMS Universal diamond core drilling crowns in drive machines of other makes, on request.

All prices excl. VAT

REMS Picus DP

Electric diamond core drilling machine
with micro-pulse technology

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. With micro-pulse technology. Especially for dry drilling, hand held or with drill stand. For trade and industry.

Concrete, steel-reinforced concrete	≤ Ø 162 (202) mm
Masonry and other materials	≤ Ø 202 mm

REMS dry diamond core drilling crowns, also suitable for drive machines of other makes, see page 319.

REMS Picus DP – with micro-pulse technology
For core drilling without water. Clean, easy, fast, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 5 min.

Especially for dry drilling

Drive machine with micro-pulse technology, specially developed for dry drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Suitable for many, especially hard materials. For pipeline and cable ducting, ventilation channels, test core drilling. In combination with the REMS Pull 2 M vacuum cleaner, ideal for making core bores in finished rooms, e.g. in residential, office and industrial buildings.

Design

Compact, handy drive machine for low-vibration core drilling, with drilling crown connecting thread UNC 1¼ male, BSPP ½ female. Compact drive unit for low-vibration core drilling, with drilling crown connecting thread UNC 1¼ outside, G ½ inside. Micro-pulse technology can be switched on and off: Pulse disc with 24 teeth generates 28,800 pulses min^{-1} in idle mode at 1,200 min^{-1}, under load at 880 min^{-1} 21,120 pulses min^{-1}. Robust, suitable for the building site. Extra light, only 7 kg. Simple, fast work without water, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 5 min. Practical spade handle and stabiliser for hand held drilling. Integrated suction rotor for dust extraction with connection for REMS Pull 2 M and other suitable vacuum cleaners. Throat Ø 60 mm for holding the drive machine in the drill stand.

Drive

Robust, powerful 2200 W universal motor. Load speed drilling spindle 8080 rpm. Stable, maintenance-free gear. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Dry diamond core drilling crowns LS

Especially for dry drilling with core drilling machines with micro-pulse technology, laser welded, high temperature-resistant (page 319), for drilling without water, hand held or with drill stand. Connecting thread UNC 1¼ female. Drilling depth 320 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for dry drilling in steel-reinforced concrete and masonry. Light loosening ring, for light loosening of the dry diamond core drilling crown, as accessory.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m^3). Observe the national regulations.

Use REMS Pull 2 M for high-performance extraction of drilling dusts from the drilling gap during dry drilling (page 324). The REMS Pull 2 M safety vacuum cleaner is certified for extracting health hazardous dusts of dust class M.

Drilling start aid

Drilling start aid G ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 318).

German Quality Product

Info

REMS Simplex 2

REMS Titan

REMS Picus DP

Electric diamond core drilling machine
with micro-pulse technology

REMS Picus DP Basic-Pack

REMS Picus DP Set Simplex 2

Supply format

REMS Picus DP Basic-Pack. Electric diamond core drilling machine with micro-pulse technology for core drilling without water in concrete, steel-reinforced concrete ≤ Ø 162 (202) mm, masonry and other materials ≤ Ø 202 mm, hand held or with drill stand. Drive unit with drilling crown male connection thread UNC 1¼, female connection thread G ½, maintenance-free gear with safety slip clutch, 110 V / 230 V, 50–60 Hz, 2200 W universal motor, integrated dust extraction. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Load speed drilling spindle 880 rpm. Stabiliser. Drill start aid G ½ TDKB with Ø 8 mm drill, size 3 Allen key. Size 32 opened ended wrench. In sturdy steel case.

	Art.-No.	KM
	180016 R220	**5.230,00**

Other voltages on request.

REMS Picus DP Set Titan

Supply format

REMS Picus DP Set Simplex 2. REMS Picus DP Basic-Pack with REMS Simplex 2 drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	KM
	180033 R220	**7.290,00**

Other voltages on request.

Supply format

REMS Picus DP Set Titan. REMS Picus DP Basic-Pack with REMS Titan drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	KM
	180035 R220	**8.360,00**

Other voltages on request.

REMS Picus DP/Pull 2 M Set-Pack

Supply format

REMS Picus DP/Pull 2 M Set-Pack. REMS Picus DP Basic-Pack, Art.-No. 180016 R110G, and REMS Pull 2 M Set, Art.-No. 185601 R220G.

	Art.-No.	KM
	180036 R220	**7.390,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
REMS Picus DP drive unit	180003 R220	**5.130,00**
Steel case with inlay	180600 R	**261,00**
REMS dry diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 319.		
REMS Pull 2 M, dry and wet extractor, see page 324		
Additional accessories see page 318.		

Description	Art.-No.	KM
REMS Simplex 2. Robust, handy drilling stand for core drilling up to Ø 202 mm. Description see page 310.	183700R	**2.060,00**
REMS Titan. Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Description see page 310.	183600R	**3.130,00**
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	**117,00**
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	**56,90**
Hammer anchor M12 (pack of 50), for concrete	079005R50	**223,00**
Setting iron for hammer anchor M12	182050R	**32,60**
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	**129,00**
Splaying anchor M12 (pack of 10), for masonry, reusable	079006R10	**208,00**
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	**148,00**
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	**110,00**
Titan vacuum fastening, consisting of cover plate with nipple for ⅜" screw connection and sealing ring for base plate.	183603R	**202,00**
Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	**3.870,00**
Laser drilling centre pointer	183604R	**263,00**
Drilling start aid G ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	180145R	**186,00**
Carbide masonry drill Ø 8 mm for drilling aid	079013	**38,20**
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	**77,60**
Light loosening ring, for light loosening of the diamond core crown	180015	**41,80**
Drilling crown extension 200 mm	180155R	**124,00**
Sharpening stone for diamond core drilling crowns	079012	**131,00**
Circular spirit level, magnetic, for aligning the drill stand	182010R	**153,00**
REMS Pull 2 M, dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		

REMS dry diamond core drilling crowns LS

For REMS Picus DP and other suitable makes

High quality dry diamond core drilling crowns. Laser welded. Especially for dry drilling with core drilling machines with micro-pulse technology, e.g. REMS Picus DP, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material.

Concrete, steel-reinforced concrete, aggregate concrete, brick, clinker, all kinds of masonry, natural stone, asphalt, all kinds of screed and other Ø 32 – 202 mm



REMS dry diamond core drilling crowns LS – Laser welded, high temperature-resistant. Especially for dry drilling with core drilling machines with micro-pulse technology. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, hand held or with drill stand.

Single connecting thread UNC 1¼ female. Drilling depth 320 mm.

Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with diamonds positioned in the bonding agent. For fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Driven by a REMS Picus DP drive unit and suitable drive units of other makes with UNC 1¼ outer connecting thread.

Use REMS Pull 2 M for high-performance extraction of drilling dusts from the drilling gap during dry drilling (page 324). The REMS Pull 2 M safety vacuum cleaner is certified for extracting health hazardous dusts of dust class M.

Info

Supply format

REMS dry diamond core drilling crowns LS. Laser welded, high temperature-resistant. Especially for dry drilling with core drilling machines with micro-pulse technology, e.g. REMS Picus DP, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1¼ female. Drilling depth 320 mm. In a carton.

Ø × drilling depth × connection	Number of segments	Art.-No.	KM
TDKB LS 32 × 320 × UNC 1¼	3	181500R	**349,00**
TDKB LS 42 × 320 × UNC 1¼	4	181502R	**326,00**
TDKB LS 52 × 320 × UNC 1¼	5	181504R	**347,00**
TDKB LS 62 × 320 × UNC 1¼	5	181506R	**378,00**
TDKB LS 72 × 320 × UNC 1¼	6	181508R	**429,00**
TDKB LS 82 × 320 × UNC 1¼	6	181510R	**464,00**
TDKB LS 92 × 320 × UNC 1¼	6	181512R	**523,00**
TDKB LS 102 × 320 × UNC 1¼	7	181514R	**536,00**
TDKB LS 112 × 320 × UNC 1¼	7	181516R	**565,00**
TDKB LS 122 × 320 × UNC 1¼	8	181532R	**649,00**
TDKB LS 127 × 320 × UNC 1¼	8	181518R	**672,00**
TDKB LS 132 × 320 × UNC 1¼	8	181520R	**691,00**
TDKB LS 142 × 320 × UNC 1¼	8	181522R	**739,00**
TDKB LS 152 × 320 × UNC 1¼	8	181524R	**823,00**
TDKB LS 162 × 320 × UNC 1¼	9	181526R	**874,00**
TDKB LS 182 × 320 × UNC 1¼	9	181528R	**964,00**
TDKB LS 202× 320 × UNC 1¼	10	181530R	**1.030,00**

Accessories

Description	Art.-No.	KM
Light loosening ring, for light loosening of the diamond core crown	180015	**41,80**
Drilling crown extension 200 mm	180155R	**124,00**
Sharpening stone for diamond core drilling crowns	079012	**131,00**
Single open ended wrench size 41 for UDKB	079003	**77,60**

Additional adapters for using REMS dry diamond core drilling crowns LS in drive machines of other makes, on request.

REMS tile drilling

Diamond tipped dry drilling crowns for fast, clean drilling in all kinds of tiles. Ideal for assembly and renovation.

Ceramic, fine clay, granite, marble etc.

REMS tile drilling – for dry drilling.

Can be used universally for dry drilling without hammering in ceramic, fine clay, granite, marble and other materials. No cracking of the tiles.

No water necessary.

Special wax filling inside the dry drilling crown as a cooling lubricant, becomes liquid when heated and cools the dry drilling crown.

Simple, free-hand starting by drill aid with vacuum fastening. Hexagon connection for ¼" bit holders.

Drive by cordless REMS Helix 22 V VE power drill (page 108) and other electric drills/screwdrivers (speed ≥ 1,000 rpm).

Supply format

REMS tile drilling Set 6 + 8 + 10. Diamond-studded dry drilling crowns with special wax filling. For ceramic, fine clay, granite, marble and other materials. Tile drilling Ø 6, 8, 10 mm, drill aid with vacuum fastening. In blister pack.

	Art.-No.	KM
	181700R	**418,00**

Accessories

Description	Art.-No.	KM
REMS tile drilling Ø 5 mm	181710R	**103,00**
REMS tile drilling Ø 6 mm	181711R	**103,00**
REMS tile drilling Ø 8 mm	181712R	**105,00**
REMS tile drilling Ø 10 mm	181713R	**107,00**
REMS tile drilling Ø 12 mm	181714R	**116,00**
REMS tile drilling Ø 14 mm	181715R	**168,00**
REMS Helix 22 V VE, cordless drill/screwdriver, see page 108		

All prices excl. VAT

REMS
Push DP
REMS
TDK8 LS Ø 152mm
Art.-Nr. 181524R

REMS Krokodil 180 SR

Compact, handy power tool for dry chasing and cutting, e.g. of concrete, steel-reinforced concrete, all kinds of masonry, natural stone, all kinds of screed. For trade and industry.

Chase depth	≤ 61 mm
Chase width	≤ 62 mm
Number of diamond cutting discs	1 – 3

REMS Universal diamond cutting discs, also for suitable drive machines of other makes, see page 323.

REMS Krokodil 180 SR – chasing instead of chiselling. Full contact support plate. Multi-function electronics.

Universal use
Universal drive machine for dry chasing and cutting. Ideal for producing chases/grooves for laying pipes and electric cables in heating, sanitary and electrical installation, air-conditioning and cooling technology.

Design
Compact, handy drive machine, only 8.0 kg. Robust, suitable for building site conditions. Fast, easy working, e.g. chases in masonry 500 mm long, 61 mm deep, only 34 s. Full contact support plate during the entire chasing/cutting process for guided plunge-in of the diamond cutting discs, dust-free, safe working and easy, even feed. Practical switch handle with triple force-transmitting leverage for easy plunge-in and effective feeding. Swivel handle, for optimum working position and ergonomic work. Locking of the drive shaft for easy changing of the universal diamond cutting discs. Spacer discs of different thicknesses according to desired chase width screws to the cutting discs in a stable block, ensure an even chase width. Continuously adjustable depth stop. Suction nozzle for connecting a dust extractor integrated into the housing.

Drive
Robust, powerful universal motor, 2,000 W. Load speed of the drive shaft of the cutting discs 3,300 rpm. Overheating protection by temperature monitoring of the motor's field winding with a PTC resistor (Positive Temperature Coefficient). Strong, maintenance-free gear. Connecting cable 5.7 m. Safety switch with lock. Restart protection in case of mains failure.

Speed Regulation
The electronic tachometer speed control used for regulation keeps the speed constant, also under load. The speed of the cutting disc is kept at the nominal value until it meets with resistance and drops below a critical value. The drive motor stops. When the load on the drive unit is relieved again, the drill runs back up to nominal speed so that work can continue immediately at nominal speed **(Patent EP 2 085 191)**. Advantage: The chasing and cutting speed (load speed) is maintained during the entire chasing and cutting process for a high chasing and cutting performance.

Multi-function electronics
Multifunction electronics with start-up current limiting for soft starting for delicate engagement of the diamond cutting discs, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond cutting discs
Universally usable for straight chasing and cutting. Specially developed, high quality diamond segments with high diamond content and special bonding for excellent chasing/drilling performance and very long life. Optionally REMS Universal diamond cutting discs LS Turbo, laser-welded, high temperature-resistant, for fast cuts and cuts in hard materials or REMS Universal diamond cutting discs LS H-P, high-performance, laser-welded, high temperature-resistant, for fast cuts and cuts in very hard materials, with long life (page 323), metal body in accordance with EN 13236. Mounting bore Ø 22.23 mm.

Dust extraction in accordance with EN 60335-2-69
When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m^3). Observe the national regulations. REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

Full contact support plate during the entire chasing/cutting process for guided plunge-in of the diamondcutting discs, dust-free, safe working and easy, even feed.

Supply format

REMS Krokodil 180 SR Basic-Pack. Electric diamond chasing and cutting grinder with speed regulation. For chasing and cutting concrete, steel-reinforced concrete, all kinds of masonry, natural stone, all kinds of screed. Chase depth 61 mm, continuously adjustable. Chase width ≤ 62 mm, stepped with spacer discs 3, 6, 10, 20 mm. Drive machine with drive shaft Ø 22.2 mm, for 1, 2 or 3 diamond cutting discs in accordance with EN 13236, ≤ Ø 180 mm, with maintenance-free gear, 230 V, 50 – 60 Hz, 2,000 W universal motor. Multifunction electronics with soft start, idling speed limiting, overload protection, overheating protection. Restart protection in case of mains failure. Connecting cable 5.7 m. Safety switch with lock. Load speed 3,300 rpm. Suction nozzle for connecting an extractor/dust extractor. Pin wrench size 13. In sturdy steel case.

	Art.-No.	KM
	185011 R220	**2.500,00**

Other voltages on request.

Info

Accessories

Description	Art.-No.	KM
REMS Krokodil 180 SR drive unit	185001 R220	**2.400,00**
REMS Universal diamond cutting disc LS-Turbo Ø 180 mm, laser-welded, high temperature-resistant, for fast cuts and cuts in very hard materials, with metal body in accordance with EN 13236	185026 R	**119,00**
REMS Universal diamond cutting disc LS H-P Ø 180 mm, high-performance, laser-welded, high temperature-resistant, for fast cuts and cuts in very hard materials, long life, with metal body in accordance with EN 13236.	185027 R	**190,00**
Chasing chisel for removing the ridge after chasing	185024 R	**51,00**
Steel case	185058 R	**223,00**
REMS Pull 2 L / M, dry and wet extractors, see page 324		

REMS Pull 2 L / M

Dry and wet extractor

Powerful, electric dry and wet extractor with automatic filter cleaning. For commercial use in trade and industry.

For extraction of dusts, dirt and liquids.

Ideal for dust extracting when chasing, cutting, drilling, core drilling and grinding.

Certified as extractor and dust extractor for extracting health hazardous dusts.

Ideal for extracting drilling sludge during core drilling.

REMS Pull 2 L	
Dust class in accordance with EN 60335-2-69	L
Exposure limit/work place limit	> 1 mg/m³
Penetration level	≤ 0.1 %
REMS Pull 2 M	
Dust class in accordance with EN 60335-2-69	M
Exposure limit/work place limit	> 0.1 mg/m³
Penetration level	≤ 0.1 %

REMS Pull 2 – for dry and wet suction.
Constantly high suction performance by permanent automatic filter cleaning.
Certified for extracting health hazardous dusts.

Universal use

Powerful, handy extractor for dry and wet suction. For extraction of dusts, dirt and liquids. Excellently suited for dust extracting when chasing, cutting, drilling, core drilling and grinding. Certified as an extractor and dust extractor for extracting health hazardous dusts of dust class L or M in accordance with EN 60335-2-69. For commercial use in trade and industry.

Design

Compact, handy design. REMS Pull 2 L only 13.5 kg, REMS Pull 2 M only 14.2 kg. Light and manoeuvrable by rubber wheels and steerable castors, lockable by castor with brake Large tank capacity 31 l, filling volume for liquids 17 l. On/Off switch with selection without filter cleaning or with filter cleaning with a 15 s or 60 s cycle. Adapter for connecting a power tool to the vacuum cleaner. Flexible 4 m, electrically conductive suction hose (Pull M), ergonomically angled handle, 2 pluggable, chrome-plated metal suction pipes 0.5 m for adapting the suction pipe length. Wide wet/dry surface attachment 300 mm with rubber-coated castors, optionally brush strips for extracting dusts and dirt or rubber lips for extracting liquids. Joint attachment for confined spaces. Large working radius by long 7.5 m connecting lead. Holders for connecting lead, suction hose, metal suction tubes and accessories integrated into the extractor. Practical handle for easy transport. Integrated fittings for fixing a REMS L-Boxx system case.

REMS Pull 2 M is suitable and certified for the extraction of health hazardous dusts of dust class M in accordance with EN 60335-2-69, with electronic volume flow monitoring, selector switch for adapting the suction power to different suction hose diameters (21, 27, 32, 35, 40 mm) and stopper for the suction hose connection nozzle.

Permanent automatic filter cleaning

REMS Pull 2 L and REMS Pull 2 M with innovative, patented, automatic filter cleaning, prevents clogging of the filter with dust, especially effective in fine dust applications. The flat pleated filter is cleaned automatically by targeted, powerful shots of air every 15 s or 60 s depending on the setting. The suction force remains constantly high during cleaning. Patented flat folded filter system.

Drive

Robust, powerful bypass motor, 1,200 W, with high-power turbine. High suction power, continuously adjustable up to an air rate ≤ 143 m³/h, for optimum adaptation to the suction surface and the extracted product.

Automatic switch-off

Filling level limiting with automatic switch off on reaching the maximum liquid filling level when extracting electrically conductive liquids.

Automatic power tool on/off

Appliance socket for power tools up to 2,200 W, with electronic automatic on/off integrated into the extractor. The extractor switches on/off automatically when the power tool is switched on/off. For convenient working.

Anti-static system (REMS Pull 2 M)

Static charge is dissipated to the earthed upper section of the extractor by electrically conductive metal suction pipes, electrically conductive handle E, electrically conductive suction hose E and electrically conductive suction hose connection nozzle.

Certified extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69.

Extraction of health hazardous dusts when chasing and cutting:

REMS Pull 2 M Set

Extraction of health hazardous dusts when dry drilling:

REMS Pull 2 M Set D

REMS Pull 2 L / M

Dry and wet extractor

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³. Observe the national regulations.

Water extraction

PES flat folded filter required for extraction of water. Use wet filter bag or polythene bag if necessary. Wet filter bags separate the water from the sucked up solids when extracting dirty water. Polythene bags simplify disposal of the dirt and prevent dirt from collecting in the tank.

Extraction of drilling sludge when wet drilling with REMS drill stands:

REMS Pull 2 L Set W

Supply format

REMS Pull 2 Set. Electric dry and wet extractor for commercial use. For extraction of dusts, dirt and liquids. Ideal for dust extracting when chasing, cutting, drilling, core drilling and grinding. Certified extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69[1]. Bypass motor 230 V, 50 – 60 Hz, 1,200 W. On/Off switch with selection for automatic filter cleaning. Suction power switch for continuous adjustment of the air flow ≤ 143 m³/h. Filling level limiting with automatic switch-off for wet suction. Automatic filter cleaning. Appliance socket for power tools up to 2,200 W, with electronic automatic on/off. Large tank capacity 31 l, filling volume for liquids 17 l. Mobile, 2 wheels, castor/castor with brake. Connecting cable 7.5 m. 1 felt filter bag, 1 flat pleated filter PES. Flat suction attachment wet/dry 300 mm with rollers, brush strips, rubber lips. Joint attachment. Pull 2 suction hose/power tool adapter. Integrated holders for connecting cable, suction hose and accessories. In a box.

Description	Version	Art.-No.	KM
Pull 2 L Set	Dust class L. Exposure limit/work place limit > 1 mg/m³, penetration level ≤ 0.1 %, 2 metal suction pipes 0.5 m each, handle, 4 m suction hose, suction hose connection nozzle.	185600R220	**1.620,00**
Pull 2 L Set W	REMS Pull 2 L set with water suction device. Ideal for extraction of drilling sludge when wet drilling with REMS drill stands.	185603R220	**2.410,00**
Pull 2 M Set	Dust class M. Exposure limit/work place limit > 0.1 mg/m³, penetration level ≤ 0.1 %. Electronic volume flow monitor with acoustic signal. Selector switch for suction hose diameter. Stopper for the suction hose connection nozzle. Antistatic system with 2 electrically conductive metal suction pipes 0.5 m each, E handle, 4 m E suction hose, suction hose connection nozzle. 1 polythene bag.	185601R220	**2.160,00**
Pull 2 M Set D	REMS Pull 2 M Set including suction rotor for dust extraction. Ideal for extracting health hazardous dusts when dry drilling with REMS Picus S1, Picus SR, Picus S3 etc.	185604R220	**2.520,00**

Extraction of health hazardous dusts when chasing and cutting:

REMS Pull 2 L Set

REMS Pull 2 L Set

Safety extractor of dust class L

REMS Pull 2 M Set

Safety extractor of dust class M

Accessories

Description	Art.-No.	KM
Felt filter bag (pack of 5), polyester felt, 3-ply, tear-proof, for wet and dry extraction, M-certified, for normal dirt, fine dusts, abrasive dusts, wet dirt	185511R05	**114,00**
Wet filter bag (pack of 5), paper-polyester woven felt, tear-proof, for wet and dry extraction, for abrasive dusts, wet dirt, liquids	185512R05	**190,00**
Polythene bag (pack of 10), for wet and dry extraction of non-health hazardous dusts, for normal dirt, fine dusts, abrasive dusts, wet dirt, liquids. Prevents soiling of the tank.	185513R10	**107,00**
Flat folded filter PES, polyester, nano-coated, 1 piece, water-resistant, non-rotting, washable with water. For wet and dry extraction, M-certified	185515R01	**172,00**
Suction rotor for dust extraction see page 311	180160R	**351,00**
Water suction device see page 311	183606R	**796,00**
Adapter suction hose/power tool, for connecting a power tool to the extractor	185654R	**130,00**



All prices excl. VAT

[1] Observe the national regulations for the collection and disposal of health hazardous dusts.

PRESS

Drying
Dehumidifying
Aeration and deaeration

Air dehumidifier/ building dryer 328

Construction ventilators 330

REMS Secco 50/80

Powerful, highly efficient air dehumidifiers/building driers for drying rooms, e.g. after mains water damage, flooding, dehumidification of damp cellar rooms etc. and for fast drying of concrete, masonry, plaster and screed for example. For commercial use in trade and industry.

REMS Secco 50	
Dehumidification rate	≤ 50 l/24 h
Air volume	≤ 265 m^3/h
REMS Secco 80	
Dehumidification rate	≤ 80 l/24 h
Air volume	≤ 850 m^3/h

REMS Secco – for drying and dehumidification.

Universal use
Powerful, highly efficient air dehumidifiers/building driers for drying rooms, e.g. after mains water damage, flooding, dehumidification of damp cellar rooms etc. and for fast drying of concrete, masonry, plaster and screed for example. For commercial use in trade and industry.

Design Secco 50
Compact, handy construction in robust, plastic housing. Weight 21 kg. Large air extraction areas with washable air filter. Electronic hygrostat for regulating the desired humidity: Switches off automatically on reaching the nominal humidity, switches back on automatically when humidity rises. Upward air outlet for optimum air circulation. Condensation draining into an internal 7.7 l condensation tank, hose extendible from the rear, for draining condensation into a tank to be provided or directly into the drain system. Automatic switch-off with switch-off signal when using the internal 7.7 litre condensation tank on reaching the maximum condensation filling level. Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer, as an accessory. Sturdy plastic housing with castors for easy transport.

Design Secco 80
Compact, handy construction in robust, powder-coated sheet steel housing. Weight 51 kg. Large air extraction areas with washable air filter. Electronic hygrostat for regulating the desired humidity: Switches off automatically on reaching the nominal humidity, switches back on automatically when humidity rises. Side air outlet for optimum air circulation. Hose for draining condensation into an internal 11.5 l condensation tank (accessory), extendible at the side, for draining condensation into a tank to be provided or directly into the drain system. On/Off switch for operation with and without internal 11.5 litre condensation tank. Automatic switch-off with switch-off signal when using the internal 11.5 litre condensation tank on reaching the maximum condensation filling level. Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer. Device socket for detachable connecting cable. Practical compartment for the connecting cable during transport. Sturdy, mobile tubular steel frame with large castors for easy transport, also over steps. Easy glide down and pull-up of the machine over the back of the tubular steel frame, e.g. from and onto the loading platform of a vehicle.

Chiller unit Secco 50
High dehumidification rate by high quality chiller unit with highly efficient rotation compressor and high-performance capacitor motor 230 V, 760 W with electronic thawing system, for continuous operation. Very quiet running, also suitable for living rooms. Dehumidification rate ≤ 50 l/24 h, air volume ≤ 265 m^3/h. High quality coolant R-290.

Chiller unit Secco 80
High dehumidification rate by high quality chiller unit with highly efficient rotation compressor and high-performance condensation motor 230 V, 680 W with automatic hot-gas thawing system, for continuous operation. Very quiet running, also suitable for living rooms. Dehumidification rate ≤ 80 l/24 h, air volume ≤ 850 m^3/h. High quality coolant R-290.

Electronic control unit Secco 50
Large, illuminated control panel with clear display of actual and nominal humidity, operating state of the chiller unit, thawing function. Keys for setting the desired humidity in 5 % steps between 30 % and 90 % as well as for setting the continuous operation. Keys for 2 fan speeds. Key for timer. Memory function saves the settings for automatic continuation of operation after a power failure.

Electronic control unit Secco 80
Illuminated 3" display with LCD technology, 70 mm screen diagonal, with clear display of actual and nominal humidity, operating hours, operating state of the chiller unit, the thawing function, the compressor protection function and the operating position for internal 11.5 litre condensation tank. Keys for setting the desired humidity in 1 % steps between 30 % and 90 % as well as for setting the continuous operation. Memory function saves the settings for automatic continuation of operation after a power failure.

Condensation tank with pump Secco 50 and Secco 80
Condensation tank with condensation pump for pumping the condensation out of the condensation tank into a higher tank or a wash basin, as an accessory.

Exhaust air set Secco 80

Generously dimensioned exhaust air hose Ø 200 mm, 10 m long, with metal fastening eyes for hanging up on site, with connecting flange, for distribution of the exhaust air in the room, for dehumidifying cavities, e.g. above intermediate ceilings and for additional blowing of wet surfaces (accessory).

REMS Orkan

For supporting electric dehumidifiers/construction driers. For faster drying and dehumidification after floods and water mains damage, it is an advantage to improve the air exchange with electric construction ventilators REMS Orkan (page 330).

R-290

Info

Supply format

REMS Secco 50 Set. Electric air dehumidifier/building dryer for commercial use. For drying rooms, dehumidifying cellars etc. and drying concrete, masonry, plaster and screed. Chiller unit with rotation compressor and capacitor motor 230 V, 50 Hz, 760 W, with automatic thawing system, for continuous operation. Very quiet running. Dehumidification rate ≤ 50 l/24 h, air volume ≤ 265 m^3/h. Electronic control unit with large, illuminated display and memory function. Electronic humidity switch. Air filter. Internal 7.7 l condensation tank. In sturdy plastic housing with casters. In a carton.

	Art.-No.	KM
	132011R220	**1.580,00**

Other voltages on request.

R-290

Info

Supply format

REMS Secco 80 Set. Electric air dehumidifier/building dryer for commercial use. For drying rooms, dehumidifying cellars etc. and drying concrete, masonry, plaster and screed. Chiller unit with rotation compressor and capacitor motor 230 V, 50 Hz, 680 W, with automatic hot-gas thawing system, for continuous operation. Very quiet running. Dehumidification rate ≤ 80 l/24 h, air volume ≤ 850 m^3/h. Electronic control unit with illuminated 3" display and memory function. Electronic hygrostat, operating hours counter, electricity meter. Air filter. In a sturdy sheet steel housing on a mobile tubular steel frame with large castors. In a carton.

	Art.-No.	KM
	132010R220	**4.390,00**

Other voltages on request.

Accessories

Description	Art.-No.	KM
11.5 litre condensation tank Secco 80 for discharge of condensation in the sheet steel housing. For REMS Secco 80.	132100R	**108,00**
Exhaust air set Secco 80, consisting of exhaust air hose Ø 200 mm, 10 m long, with metal fastening eyes for hanging up on site, with connecting flange, for distribution of the exhaust air in the room, for dehumidifying cavities, e.g. above intermediate ceilings and for additional blowing of wet surfaces.	132104R	**645,00**
Condensation tank with Secco 50 pump for pumping the condensation out of the condensation tank into a higher tank or a wash basin. Pumping height ≤ 2 m. For REMS Secco 50.	132129R220	**788,00**
Condensation tank with Secco 80 pump for pumping the condensation out of the condensation tank into a higher tank or a wash basin. Pumping height ≤ 2 m. For REMS Secco 80.	132121R220	**788,00**
Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer. For REMS Secco 50 and others.	132132R220	**111,00**
REMS Detect W, dielectric moisture measuring device for non-destructive moisture measurement in building materials, e.g. concrete, masonry, plaster, wood. In a case.	132115R	**473,00**
REMS Orkan, electric construction ventilator, see page 330.		

REMS Orkan 1360/2050

Electric construction ventilator

Powerful, highly efficient electric construction ventilator for supporting dehumidifiers/construction driers after floods and water mains damage. Ideal for aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms and for speeding up the drying of concrete, masonry, plaster and screed, for example. For commercial use in trade and industry.

REMS Orkan 1360	
Air volume	1360 m^3/h
Power	145 W
REMS Orkan 2050	
Air volume stage I	1740 m^3/h
Power stage I	355 W
Air volume stage II	2050 m^3/h
Power stage II	450 W

REMS Orkan – for aeration.

Universal use

Powerful, highly efficient construction ventilator for supporting dehumidifiers/ construction driers after floods and water mains damage. Ideal for aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms and for speeding up the drying of concrete, masonry, plaster and screed, for example. For commercial use in trade and industry.

Design Orkan 1360

Axial fan in sturdy plastic housing of rotation-moulded polyethylene for a long life. Compact, handy design, weighing only 6.8 kg, with low-noise, single-phase capacitor motor 230 V, 145 W, with practical handle for carrying. Generated air volume 1,360 m^3/h.

Large-diameter exhaust air and suction hose, Ø 200 mm, 10 m long, e.g. for extracting air from rooms, spaces, shafts and cavities, for discharging sucked-in air or dusts to the outside and for inflating bouncy castles, hot-air balloons, for example, as an accessory. An exhaust and suction hose can be fitted to the aeration or deaeration side of the construction ventilator as the situation requires. Dust sack, Ø 200 mm, 2,980 mm long, washable, for collecting coarse and fine dusts up to dust class M, as an accessory.

Design Orkan 2050

Turbo radial fan with 2 air volume stages, in sturdy plastic housing of rotation-moulded polyethylene for a long life. Compact, handy design, weighing only 10 kg, with low-noise, single-phase capacitor motor 230 V, 355/450 W, with practical handle for carrying. Horizontal air outlet, adjustable to below 45° or vertical by appropriate resting surfaces on the plastic housing. Generated air volume in 2 selectable stages 1,740/2,050 m^3/h. Especially suitable for speeding up drying of concrete, masonry, plaster and screed, for example.

Supply format

REMS Orkan 1360. Electric construction ventilator for commercial use. For aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms, for supporting the drying of, e.g., concrete, masonry, plaster and screed and for inflating bouncy castles, hot air balloons, for example. Capacitor motor 230 V, 50 Hz, 145 W, for continuous operation. Very quiet running. Air volume 1,360 m^3/h. In a sturdy plastic housing. In a carton.

	Art.-No.	KM
	132300 R220	**830,00**

Other voltages on request.

Info

Supply format

REMS Orkan 2050. Electric construction ventilator for commercial use. For aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms. Especially also for drying of, e.g., concrete, masonry, plaster and screed. Capacitor motor 230 V, 50 Hz, 355/450 W, for continuous operation. Very quiet running. Air volume 1,740/2,050 m^3/h. In a sturdy plastic housing. In a carton.

	Art.-No.	KM
	132301 R220	**876,00**

Other voltages on request.

Info

Accessories

Description	Art.-No.	KM
Exhaust air and suction hose, Ø 200 mm, 10 m long, for extracting air from rooms, spaces, shafts and cavities, for discharging sucked-in air or dusts to the outside and for inflating bouncy castles, hot-air balloons, for example. For REMS Orkan 1360.	132307 R	**321,00**
Dust sack, Ø 200 mm, 2,980 mm long, washable, for collecting coarse and fine dusts up to dust class M. For REMS Orkan 1360.	132308 R	**297,00**
Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer. For REMS Orkan and others.	132132 R220	**111,00**
REMS Detect W, dielectric moisture measuring device for non-destructive moisture measurement in building materials, e.g. concrete, masonry, plaster, wood. In a case.	132115 R	**473,00**
REMS Secco, electric air dehumidifiers/building driers, see page 328.		

Index

A

Aeration and deaeration ... 327
Akku-Press 22 V ACC ... 192–193
Akku-Press 22 V Connected ... 194–195
Akku-Press E 22 V ACC ... 190–191
Akku-Press XL 45 kN 22 V ACC ... 196–197
Amigo ... 25
Amigo 2 ... 26
Amigo 2 Compact ... 27
Amigo 22 V ... 28–29
Amigo E ... 24
Aquila 3B ... 105
Aquila WB ... 105
Assembling ... 103
Attachment heads for button dies / intermediate rings / guide bushings ... 31
Axial Press Jointing ... 243
Ax-Press 25 22 V ACC ... 246–247
Ax-Press 25 L 22 V ACC ... 246–247
Ax-Press 30 22 V ... 244
Ax-Press HK / H ... 245

B

Bending ... 127
Bending formers and back formers ... 143
Blitz ... 266
Brazing solder ISO 17672-CuP 179 ... 267
Butt welding machine ... 294–297
Butt welding units ... 298

C

Cable shear ... 241
Calc-Push ... 116
Calibrating ... 73
Calibrating tool and outer-inner pipe deburrer ... 100
Calibrating tools and inner pipe deburrers ... 101
Calibrating tools and outer-inner pipe deburrers ... 101
CamScope HD ... 275
CamSys ... 276–277
CamSys 2 ... 278–280
Cat 22 V VE ... 60–61
Catch S ... 104
Catch W ... 104
Cat VE ... 59
Cento ... 84–85
Cento 22 V ... 86–87
Chain pipe vice ... 105
Chain pipe vice for workbench ... 105
Chamfering ... 73
Chasers ... 44
Chasers and Holders ... 44
Circular pipe sawing machine ... 70
CleanH ... 119, 123
Cleaning ... 113
Cleaning and preservation unit for heating systems ... 119, 123
Cleaning pads ... 264
CleanM ... 123
Cobra 22/32 ... 286–289
Collum ... 49
Collum 22 V ... 50–51
Compression heads ... 248–249
Confirmation of suitability ... 239
Contact 2000 ... 265
Cordless axial press 13 kN with automatic return ... 246–247
Cordless axial press 20 kN with automatic return ... 246–247
Cordless axial press 30 kN ... 244
Cordless die stock with quick-change die heads ... 28–29
Cordless drain cleaning machine ... 284–285
Cordless LED flood light ... 111
Cordless pipe cutter ... 83
Cordless pipe cutting machine ... 86
Cordless pipe expander 20 kN with automatic return ... 254–255
Cordless pipe reciprocating saw ... 66–67
Cordless power drill/screwdriver ... 108–109
Cordless radial press 22 kN with automatic circuit control ... 147–151
Cordless radial press 32 kN with automatic circuit control ... 190–191
Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display ... 192–193
Cordless radial press 32 kN with Connected functionality via Wi-Fi radio standard and OLED display ... 194–195
Cordless radial press XL 45 kN with automatic circuit control ... 196–197
Cordless roll grooving machine ... 50–51
Cordless tube bender ... 132–133, 140–141
Cordless universal reciprocating saw ... 60–61
Cropping tongs ... 241
Cropping tongs Mini ... 184
Curvo ... 136–137
Curvo 22 V ... 140–141
Curvo 50 ... 138–139
Cut 110 Cu-INOX ... 95
Cut 110 P ... 94
Cutter wheels ... 81
Cutting ... 73
Cu-Vlies ... 264

D

Deburring ... 73
Dehumidifying ... 327
Diamond chasing and cutting machine ... 301
Diamond chasing and cutting machines ... 322–323
Diamond core drilling ... 301
Dies ... 30, 40
Disinfecting ... 113
Disinfection unit for drinking water installations ... 119, 123
Drain cleaner for manual and electric operation ... 282
Drill stands ... 310
Dry and wet extractor ... 324–325
Dry diamond core drilling crowns LS ... 319
Drying ... 327
DueCento ... 88–89

E

Eco-Press ... 185
Electric air dehumidifiers/building driers ... 328–329, 331
Electric construction ventilator ... 330–331
Electric decalcifying pump ... 116
Electric diamond core drilling machine ... 302–305, 308–309
Electric diamond core drilling machine with micro-pulse technology ... 316–317
Electric diamond core drilling machine with speed regulation ... 306–307
Electric die stock with quick-change die heads ... 24–27
Electric drain cleaning machine ... 283
Electric filling and flushing unit ... 124–125
Electric LED flood light ... 110
Electric pipe and drain cleaning machines ... 286–287
Electric pipe and tube bender ... 136–139
Electric pipe cutter ... 82
Electric pipe freezing unit ... 271
Electric pressure testing pump ... 115
Electric radial press 32 kN ... 186
Electric reciprocating pipe saws ... 62–63
Electric sleeve welding unit ... 292
Electric soldering pliers ... 264
Electric soldering unit ... 265
Electric tube expander ... 260–261
Electric tube extractor ... 259, 261
Electro-hydraulic pipe expander 34 kN with automatic return ... 256
Electro-hydraulic radial press 32 kN with automatic retraction ... 187
Electro-hydraulic radial press XL 32 kN with automatic retraction ... 188
Electronic camera inspection system ... 276–279
Electronic flushing and pressure testing unit with compressor ... 120–123
Electronic flushing unit with compressor ... 117–119
EMSG 160-2 ... 292
Endoscope camera ... 274–275
E-Push 2 ... 115
Eskimo ... 270
Eva ... 22
Expander heads P ... 257
Expander heads P-CEF ... 257
Expanding ... 251
Ex-Press 22 V ACC ... 254–255
Ex-Press Cu ... 252
Ex-Press H ... 253
Ex-Press P ... 253
Extracting ... 251

F

Filling ... 113
Flushing ... 113
Folding work bench ... 70–71
Folding work benches ... 106
Freezing ... 269
Frigo 2 F-Zero ... 271

H

Hand die stock with quick-change die heads ... 22
Hand pressure testing pump ... 114
Hand tube bender ... 142
Hand tube expander ... 252–253
Hand tube extractor ... 258
Helix 22 V VE ... 108–109
Herkules ... 107
Hold-Harmless and Indemnification Agreement ... 240
Hot Dog 2 ... 264
Hurrican ... 259
Hurrican H ... 258
Hydro-Swing ... 130–131
Hydro-Swing 22 V ... 132–133

I

Inner pipe deburrer ... 97

J

Jumbo ... 106

Index

K

KaliGrat E ... 100
KaliGrat H ... 101
KaliGrat R ... 101
Krokodil 180 SR ... 322–323

L

Lot Cu 3 ... 267
Lot P6 ... 267
Lumen 2800 22 V ... 111
Lumen 5000/7000/10000 ... 110

M

Machine cleaner ... 123
Macho ... 266
Magnum RG ... 52–53
Magnum (up to 2") ... 34–35
Magnum (up to 3") ... 36–37
Magnum (up to 4") ... 38–39
Manual axial press ... 245
Manual radial press ... 185
Material supports ... 107
Mini-Cobra ... 282
Mini-Cobra S ... 283
Mini-Cobra S 22 V VE ... 284–285
Mini-Press 14 V ACC ... 147
Mini-Press 22 V ACC ... 148–149
Mini-Press S 22 V ACC ... 150–151
MiniScope ... 274
MSG ... 293
Multi-Push S ... 117–119
Multi-Push SL/SLW ... 120–123

N

Nano ... 82
Nano 11 V ... 83
Nippelfix ... 46
Nippelspanner ... 46
NoCor ... 119, 123

O

Oil-hydraulic hand pipe bender ... 130–131
Oil-hydraulic pipe bender ... 134–135
One-hand axial press ... 245
One-hand pipe expander ... 253
One-hand pipe shears ... 90–92
One-hand pipe shears with ratchet feed ... 93
Orkan 1360/2050 ... 330–331
Outer-inner pipe deburrer ... 98–99
Outer-inner tube deburrer ... 97

P

Paste Cu 3 ... 267
Peroxi Color ... 119, 123
Picus DP ... 316–317
Picus S1 ... 302–303
Picus S2/3,5 ... 308–309
Picus S3 ... 304–305
Picus SR ... 306–307
Pipe and Drain cleaning ... 273
Pipe and Drain inspection ... 273
Pipe chamfering tools ... 96
Pipe cutter ... 80
Pipe cutters ... 74–79
Pipe cutting and pipe chamfering tool ... 94
Pipe cutting machine ... 84–85, 88
Pipe cutting tool ... 95
Pipe freezer ... 270
Pipe shears with ratchet feed ... 93
Pipe slitter ... 80
Plastic Pipe Welding ... 291
Pneumatic reciprocating pipe saw ... 64
Portable pipe workstation with chain pipe vice ... 105
Power-Ex-Press P-CEF ACC ... 256
Power-Press ACC ... 187–188
Power-Press SE ... 186
Preserving ... 113
Pressing rings ... 152–183, 198–237
Pressing tongs ... 198–237
Pressing tongs Mini ... 152–183
Pressure testing ... 113
Pull 2 L / M ... 324–325
Pull-Push ... 282
Puma VE ... 58
Push ... 114
Python ... 134–135

Q

Quick-change die heads ... 30
Quick-change die heads S ... 23

R

Radial Press Jointing ... 145
RAG ... 96
RAS Cu ... 77–78
RAS Cu-INOX ... 75–76
RAS P ... 78–79
RAS P/SW 45/L ... 80
RAS St ... 74
RAS W INOX ... 80
Reciprocating saws ... 56–57
REG 3 – 35 ... 97
REG 8 – 35 ... 98
REG 10 – 42 ... 98
REG 10 – 54 ... 99
REG 10 – 54 E ... 99
REG St ¼ – 2" ... 97
REG Universal ... 97
Roll Grooving ... 21
Roll grooving attachment ... 48
Roll grooving machine ... 49, 52–53
ROS P ... 92–93
ROS P 26/SW 35 S ... 91
ROS PEX ... 92
ROS P flex ... 90

S

Sanitol ... 47
Saw blades ... 69
Sawing ... 55
Secco 50/80 ... 328–329
Single-hand tube bender ... 128–129
Sinus ... 142
Sleeve welding units ... 293
Soft solder paste of solder powder Sn97Cu3 according to ISO 9453:2014 and flux 3.1.1.C, EN 29454-1:1994 ... 267
Soft solder Sn97Cu3, ISO 9453:2014 ... 267
Solar-Push ... 124–125
Soldering ... 263
Special saw blades ... 68
Spezial ... 47
SSG ... 298
SSM 160KS ... 295
SSM 160RS ... 294
SSM 250KS ... 296
SSM 315RF ... 297
Suction and pressure cleaning device ... 282
Swedish pattern wrench 'S' ... 104
Swing ... 128–129

T

Thread-cutting oil ... 47
Threading ... 21
Threading machine ... 32–39, 42–43
Thread tables ... 45
Tiger 22 V VE ... 66–67
Tiger pneumatic ... 64
Tiger/VE/SR ... 62–63
Tile drilling ... 320
Tornado ... 32–33
Turbo Cu-INOX ... 70
Turbo K ... 71
Turbo soldering torch acetylene ... 266
Turbo soldering torch propane ... 266
Twist ... 260
Twist/Hurrican ... 261

U

Unimat 75 ... 42–43
Universal circular metal sawing machine with automatic cooling lubricant unit ... 71
Universal deburrer ... 97
Universal diamond core drilling crowns ... 312–313
Universal diamond core drilling crowns LS ... 314–315
Universal electric reciprocating saw ... 58–59
Universal saw blades ... 68

V

V-Jet H ... 119, 123
V-Jet TW ... 119, 123

W

Water pump pliers ... 104
Wet and dry suction ... 301

List of articles

Art.-No.	RG	VE	Page
043054	Z		119, 122, 125
045159	Z		119, 122
047069	Z		122
074021	Z		258
074041	Z		258
076117	Z		258
079003	Z		311, 313, 315, 318–319
079005	Z		311, 318
079006	Z		311, 318
079010	Z		311, 318
079012	Z		311, 313, 315, 318–319
079013	Z		311, 318
079018	Z		311, 318
079019	Z		311, 318
090015	Z		119, 123
091072	Z		119, 123
091073	Z		119, 123
110000	Z		46
110100	Z		46
110200	Z		46
110300	Z		46
110400	Z		46
110500	Z		46
110600	Z		46
110620	Z		46
110621	Z		46
111000	Z		46
111100	Z		46
111200	Z		46
111300	Z		46
111400	Z		46
111500	Z		46
111620	Z		46
111621	Z		46
111700	Z		46
111800	Z		46
111900	Z		46
113000	H		74
113100	H		74
113200	H	10	75
113210	V	10	76, 81, 94–95
113213	V	10	76, 81
113220	V	10	81
113225	V	10	78, 81
113230	H	10	75
113240	H	10	75
113241	H	10	75
113250	H	10	77
113255	H	10	77
113260	H	10	77
113300	H	10	76
113320	H	8	77
113330	H	8	75
113340	H	10	77
113350	H	10	75
113351	H	10	75
113360	Z	10	76, 78, 97
113370	H		78
113380	H		76
113385	H		76
113400	H		76
113401	H		76
113410	H		78
113450	H		80
113461	V	10	80–81
113480	H	10	80
113481	Z		80
113500	H		76
113810	H		98
113815	Z		98
113825	H	10	98
113830	H	10	99
113835	H	10	99
113840	Z		85, 87
113900	H	10	97
113910	H	10	97
114000	H		100
114001	H		100
114030	Z		100
114032	Z		100
114033	Z		100
114034	Z		100
114035	Z		100
114036	Z		100
114037	Z		100
114038	Z		100
114039	Z		100
114040	Z		100
114041	Z		100
114042	Z		100
114043	Z		100
114044	Z		100
114045	Z		101
114046	Z		101
114047	Z		101
114048	Z		101
114060	Z		101
114061	Z		101
115000	H		114
115001	H		114
115045	Z		114–115, 122
115110	Z		114–115
115140	Z		122
115217	Z		125
115220	Z		125
115221	Z		125
115311	M		125
115312	M		125
115314	Z		125
115315	Z		125
115319	Z		125
115323	Z		125
115324	Z		125
115325	Z		125
115326	Z		125
115375	Z		125
115500	M		115
115602	Z		119, 123
115604	Z		119, 123
115605	Z	6	119, 123
115607	Z	6	119, 123
115608	Z	6	119, 123
115609	Z		119, 122
115610	M		122
115611	M		122
115612	Z		119, 123
115621	Z		119, 122
115633	Z		119, 122
115661	Z		122
115667	Z		122
115677	Z		119, 123
115703	Z		119, 123
115747	Z		122
115810	M		118
115900	M		116
116000	H		104
116005	H		104
116010	H		104
116015	H		104
116020	H		104
116050	H		104
116055	H		104
116060	H		104
120120	Z		107
120125	Z		107
120130	Z		107
120200	Z		106
120240	Z		106
120250	Z		105
120270	Z		105
130002	H		270
130207	Z		270
130208	Z		270
130209	Z		270
130383	Z		270
130410	Z		270
130415	Z		270
130430	Z		270
130450	Z		270
130455	Z		270
130460	Z		270
130465	Z		270
130470	Z		270
130475	Z		270
130480	Z		270
130485	Z		270
130490	Z		270
130495	Z		270
131012	M		271
131104	Z		271
131110	Z		271
131116	Z		271
131156	Z		271
131157	Z		271
131158	Z		271
131160	Z		271
132010	M		329
132011	M		329
132100	Z		329
132104	Z		329
132115	Z		329, 331
132121	Z		329
132129	Z		329
132132	Z		329, 331
132300	M		331
132301	M		331
132307	Z		331
132308	Z		331
140100	V	4	47
140101	V		47
140103	V		47
140105	V	12	47
140106	V	15	47
140110	V	4	47
140113	V		47
140115	V	12	47
140116	V	15	47
140119	V	15	123
140120	V	15	137, 139, 141–142
150000	H		252
150005	H		252
150006	H		252
150007	H		252
150008	H		252
150010	H		252
150017	H		252
150018	H		252
150019	H		252
150020	H		252
150021	H		253
150022	H		253
150025	H		253
150026	H		253
150027	H		253
150028	H		253
150029	H		253
150033	H		253
150100	Z		252
150105	Z		252
150110	Z		252
150120	Z		252
150125	Z		252
150130	Z		252
150140	Z		252
150145	Z		252
150150	Z		252
150155	Z		252
150160	Z		252
150165	Z		252
150170	Z		252
150175	Z		252
150180	Z		252
150185	Z		252
150190	Z		252
150195	Z		252
150205	Z		252
150210	Z		252
150220	Z		252
150225	Z		252
150230	Z		252
150235	Z		252
150240	Z		252
150245	Z		252
150250	Z		252
150500	Z		252
150510	Z		253
150515	Z		255, 257
150550	H		253
150600	Z		252–253
150806	Z		257
150807	Z		257
150808	Z		257
150809	Z		257
150812	Z		257
150826	Z		257
150828	Z		257
150842	Z		257
150843	Z		257
150845	Z		257
150846	Z		257
150849	Z		257
150855	Z		257
150858	Z		257
150868	Z		257
150873	Z		257
150882	Z		257
150883	Z		257
150885	Z		257
150886	Z		257
150887	Z		257
150888	Z		257
150894	Z		257
150897	Z		257
150912	Z		257
150913	Z		257
150914	Z		257
150915	Z		257
150916	Z		257
150923	Z		257
150926	Z		257
150943	Z		257
150944	Z		257
150945	Z		257
150946	Z		257
150947	Z		257
150950	Z		257
150952	Z		257
150957	Z		257
150958	Z		257
150960	Z		257
150961	Z		257
150962	Z		257
150963	Z		257
150968	Z		257
151000	E		259
151002	E		259
151003	H		258
151004	H		258
151005	H		258
151010	E		259
151105	Z		258–259, 261
151110	Z		258–259, 261
151120	Z		258–259, 261
151125	Z		258–259, 261
151130	Z		258–259, 261
151140	Z		258–259, 261
151145	Z		258–259, 261
151150	Z		258–259, 261
151155	Z		258–259, 261
151160	Z		258–259, 261
151165	Z		258–259, 261
151170	Z		258–259, 261
151175	Z		258–259, 261
151200	Z		258–259, 261
151210	Z		258–259, 261
151230	Z		258–259, 261
151240	Z		258–261
151402	Z		258–261
151600	Z		259–261
151618	Z		258
152106	Z		266
152109	Z		266
153020	H		129
153021	H		129
153022	H		129
153023	H		129
153025	H		129
153026	H		129
153027	H		129
153028	H		129
153029	H		129
153030	H		128
153100	Z		129
153115	Z		129, 131, 133
153125	Z		129
153140	Z		129
153155	Z		129, 131, 133
153160	Z		129, 131, 133
153170	Z		129, 131, 133
153175	Z		129, 131, 133
153180	Z		129, 131, 133
153185	Z		129, 131, 133
153190	Z		129, 131, 133
153195	Z		129, 131, 133
153200	Z		129, 131, 133
153205	Z		129, 131, 133
153210	Z		129, 131, 133
153265	Z		128–129
153270	Z		129
153300	Z		128
153303	Z		128
153304	Z		128
153305	Z		128
153306	Z		128
153307	Z		128
153400	Z		133
153401	E		133
153410	E		133
153411	E		133
153412	E		133
153413	E		133
153414	E		133
153415	E		133
153416	E		133
153417	E		133
153418	E		133
153419	E		132
153450	Z		131, 133
153455	Z		133
153500	Z		131
153501	Z		131, 133
153510	H		131
153520	H		131
153521	H		131
153522	H		131
153523	H		131
153525	H		131
153526	H		131
153527	H		131
153528	H		131
153529	H		131
153531	Z		131, 133
153532	Z		131, 133
153540	Z		131, 133

RG: discount group VE: packing unit (pieces)

List of articles

Art.-No.	RG	VE	Page
153570	Z		131
154000	Z		142
154001	H		142
154002	H		142
154003	H		142
154004	H		142
154010	H		142
154160	Z		142
156000	E		260
156002	E		260
156004	E		260
156010	E		261
156012	E		261
156014	E		261
156150	Z		260–261
156200	Z		260–261
156225	Z		260–261
156250	Z		260–261
156300	Z		260–261
156350	Z		260–261
156375	Z		260–261
156400	Z		260–261
156425	Z		260–261
156450	Z		260–261
156475	Z		260–261
160010	H		266
160200	V	10	267
160210	V	10	267
160220	V	10	267
160300	V	25	264
161010	H		266
163020	E		264
163350	Z		264
164011	E		265
164050	E		265
164110	Z		265
164111	Z		265
164115	Z		265
164250	Z		265
170010	H		282
170011	Z		288
170012	Z		288
170022	E		283
170023	E		283
170025	E		285
170027	E		285
170118	Z		282, 285
170200	Z		282, 288
170201	Z		282–283, 285
170205	Z		282–283, 285
170300	H		282
171150	Z		288
171151	Z		288
171200	Z		288
171201	Z		288
171205	Z		288
171210	Z		288
171250	Z		289
171265	Z		289
171270	Z		289
171275	Z		289
171280	Z		289
171290	Z		289
171291	Z		289
171305	Z		289
171306	Z		289
171340	Z		289
171341	Z		289
172000	Z		287
172010	M		287
172011	M		287
172012	M		287
172050	Z		288
172051	Z		288
172150	Z		288
172151	Z		288
172154	Z		288
172200	Z		288
172201	Z		288
172203	Z		288
172205	Z		288
172210	Z		288
172250	Z		289
172265	Z		289
172270	Z		289
172275	Z		289
172280	Z		289
172281	Z		289
172290	Z		289
172291	Z		289
172293	Z		289
172305	Z		289
172310	Z		289
172340	Z		289
172341	Z		289
172610	Z		289
172611	Z		289
172612	Z		289
174000	Z		287
174010	M		287
174011	M		287
174012	M		287
174050	Z		288
174101	Z		288
174150	Z		288
174154	Z		288
174200	Z		288
174201	Z		288
174203	Z		288
174205	Z		288
174210	Z		288
174250	Z		289
174265	Z		289
174270	Z		289
174275	Z		289
174282	Z		289
174291	Z		289
174293	Z		289
174295	Z		289
174296	Z		289
174305	Z		289
174306	Z		289
174310	Z		289
174311	Z		289
174340	Z		289
174341	Z		289
175000	Z		277
175007	M		277
175008	M		277
175010	M		277
175011	Z		277
175018	Z		277
175026	Z		277, 280
175057	Z		277, 280
175058	Z		277, 280
175123	Z		277, 280
175210	Z		111
175211	Z		111
175220	Z		110
175221	Z		110
175222	Z		110
175230	Z		110–111
175300	Z		280
175301	M		279
175302	M		279
175303	M		279
175304	M		279
175305	Z		277, 280
175306	Z		277, 280
175307	Z		280
175308	Z		280
175312	Z		280
175323	Z		280
175330	Z		280
175339	Z		280
175343	Z		280
175400	E		275
175401	E	6	274
175440	Z		275
180000	Z		303
180001	Z		305
180003	Z		317
180010	E		303
180011	E		305
180012	E		309
180015	Z		311, 313, 315, 318–319
180016	E		317
180028	E		305
180029	E		305
180030	E		309
180032	E		303
180033	E		317
180035	E		317
180036	E		317
180052	Z		313, 315
180053	Z		313, 315
180054	Z		313, 315
180056	Z		313, 315
180057	Z		313, 315
180140	Z		311
180145	Z		318
180155	Z		311, 313, 315, 318–319
180160	Z		311, 325
180600	Z		303, 305, 307, 317
181010	V		313
181015	V		313
181020	V		313
181025	V		313
181030	V		313
181035	V		313
181040	V		313
181045	V		313
181050	V		313
181055	V		313
181059	V		313
181060	V		313
181065	V		313
181070	V		313
181075	V		313
181080	V		313
181085	V		313
181090	V		313
181095	V		313
181410	V		315
181415	V		315
181420	V		315
181425	V		315
181430	V		315
181435	V		315
181440	V		315
181445	V		315
181450	V		315
181455	V		315
181459	V		315
181460	V		315
181465	V		315
181470	V		315
181475	V		315
181480	V		315
181500	V		319
181502	V		319
181504	V		319
181506	V		319
181508	V		319
181510	V		319
181512	V		319
181514	V		319
181516	V		319
181518	V		319
181520	V		319
181522	V		319
181524	V		319
181526	V		319
181528	V		319
181530	V		319
181532	V		319
181700	V		320
181710	V		320
181711	V		320
181712	V		320
181713	V		320
181714	V		320
181715	V		320
182006	Z		311
182010	Z		311, 318
182050	Z		311, 318
183000	Z		307
183010	E		307
183022	E		307
183023	E		307
183600	Z		310, 318
183603	Z		311, 318
183604	Z		311, 318
183605	Z		311, 318
183606	Z		311, 325
183607	Z		311, 318
183632	Z		307, 310
183670	Z		311, 318
183675	Z		311
183700	Z		310, 318
185001	Z		323
185011	E		323
185024	Z		323
185026	V		323
185027	V		323
185058	Z		283, 323
185511	Z		325
185512	Z		325
185513	Z		325
185515	Z		325
185600	M		325
185601	M		325
185603	M		325
185604	M		325
185654	Z		325
190051	Z		109
190053	Z		109
190100	Z		109
190110	E		109
250020	E		298
250041	Z		298
250042	Z		298
250120	E		298
250142	Z		298
250143	Z		298
250220	E		298
250242	Z		298
250243	Z		298
250320	E		298
250341	Z		298
250342	Z		298
250343	Z		298
252026	M		294
252046	M		295
252103	Z		294–295
254025	M		296
254103	Z		296
255020	M		297
255103	Z		297
256020	E		293
256213	E		293
256220	E		293
256233	E		293
256240	E		293
256242	Z		293
256320	E		293
256342	Z		293
256400	Z		293
256410	Z		293
256420	Z		293
256430	Z		293
256440	Z		293
256450	Z		293
256460	Z		293
256470	Z		293
256480	Z		293
256490	Z		293
256500	Z		293
256510	Z		293
256520	Z		293
256530	Z		293
261002	E		292
290000	H		79
290001	H	10	78
290002	H	10	78
290016	V	10	79, 81
290023	V	10	79, 81
290050	H		79
290100	H		79
290116	V	10	79, 81
290200	H		79
290216	V	10	79, 81
290300	H		79
290316	V	5	79, 81
290400	H		94
290410	H		95
290411	H		95
290412	H		95
290420	Z		94
290421	Z		94
290422	Z		94
290423	Z		94
290424	Z		94
290425	Z		94
290426	Z		94
290427	Z		94
290430	Z		94
290431	Z		94
290432	Z		94
290433	Z		94–95
290437	Z		94
290440	Z		94–95
290444	Z		94
290445	Z		94
290446	Z		94
290447	Z		94
290448	Z		94
290449	Z		94
290500	H		79
291000	H		93
291010	H		93
291023	Z		93
291036	Z		93
291037	Z		93
291101	H		93
291112	Z		93
291200	H		93
291201	Z		93
291220	H		93
291221	Z		93
291240	H	8	92
291241	Z		92
291242	H	8	91
291243	Z		91
291244	Z		91
291250	H		93
291251	Z		93
291270	H		93
291271	Z		93
291290	H		93
291400	H	10	90
291401	Z		90
291410	H	10	90
291411	Z		90

List of articles

Art.-No.	RG	VE	Page
291420	H	8	92
291421	Z		92
291430	H	8	90
291431	Z		90
292011	Z		96
292110	H		96
292210	H		96
340100	Z		37, 39
340110	Z		53
340200	M		33
340201	M		33
340202	M		33
340206	M		33
340207	M		33
340208	M		33
340220	M		35
340221	M		35
340222	M		35
340226	M		35
340227	M		35
340228	M		35
340230	M		53
340231	M		53
340232	M		53
341000	Z		33, 35, 37, 39
341401	S		40
341402	S		40
341403	S		40
341404	S		40
341406	S		40
341407	S		40
341408	S		40
341409	S		40
341411	S		40
341412	S		40
341413	S		40
341414	S		40
341416	S		40
341417	S		40
341418	S		40
341419	S		40
341426	S		40
341427	S		40
341428	S		40
341429	S		40
341430	S		40
341431	S		40
341432	S		40
341433	S		40
341434	S		40
341435	S		40
341436	S		40
341437	S		40
341438	S		40
341439	S		40
341440	S		40
341441	S		40
341442	S		40
341443	S		40
341444	S		40
341445	S		40
341446	S		40
341466	S		40
341467	S		40
341468	S		40
341469	S		40
341470	S		40
341471	S		40
341472	S		40
341473	S		40
341474	S		40
341475	S		40
341476	S		40
341477	S		40
341478	S		40
341479	S		40
341480	S		40
341481	S		40
341482	S		40
341483	S		40
341484	S		40
341485	S		40
341486	S		40
341487	S		40
341488	S		40
341489	S		40
341490	S		40
341491	S		40
341493	S		40
341494	S		40
341495	S		40
341496	S		40
341497	S		40
341498	S		40
341499	S		40
341614	V	10	33, 35, 37, 39, 74, 81

Art.-No.	RG	VE	Page
342080	S		35, 37, 39
344100	Z		33, 35, 37, 39, 53
344105	Z		33, 35, 37, 39, 53
344150	Z		33, 35, 37, 39, 53
347000	M		33, 35, 37, 39, 48
347001	M		48
347005	M		51
347006	M		49
347007	Z		48
347008	M		49
347009	M		49
347010	Z		49
347030	Z		48
347034	Z		48
347035	Z		48
347040	Z		48
347046	Z		48
347047	Z		48
347053	Z		48
380303	M		37
380304	M		37
380305	M		37
380306	M		37
380307	M		37
380308	M		37
380309	M		37
380310	M		37
380311	M		37
380312	M		37
380313	M		37
380314	M		37
380426	M		39
380427	M		39
380428	M		39
380429	M		39
380430	M		39
380431	M		39
380441	M		39
380442	M		39
380443	M		39
380444	M		39
380445	M		39
380446	M		39
380447	M		39
380448	M		39
381000	Z		37, 39
381050	Z		37
381401	S		40
381405	S		40
381410	S		40
381415	S		40
381430	S		40
381431	S		40
381432	S		40
381433	S		40
381622	V	5	37, 39, 74, 81
520003	H		22
520004	H		22
520008	H		22
520009	H		22
520010	H		22
520013	H		22
520014	H		22
520015	H		22
520016	H		22
520017	H		22
520025	Z		23
520026	Z		23
520056	Z		23
521000	Z		30
521002	S		30
521010	Z		30
521012	S		30
521020	Z		30
521022	S		30
521026	Z		23
521030	Z		30
521032	S		30
521036	Z		23
521040	Z		30
521042	S		30
521046	Z		23
521050	Z		30
521052	S		30
521056	Z		23
521060	Z		30
521062	S		30
521066	Z		23
521070	Z		30
521072	S		30
521080	Z		30
521082	S		30
521100	Z		30
521102	S		30
521110	Z		30
521112	S		30

Art.-No.	RG	VE	Page
521120	Z		30
521122	S		30
521130	Z		30
521132	S		30
521140	Z		30
521142	S		30
521150	Z		30
521152	S		30
521160	Z		30
521162	S		30
521170	Z		30
521172	S		30
521180	Z		30
521182	S		30
521200	Z		30
521202	S		30
521210	Z		30
521212	S		30
521220	Z		30
521222	S		30
521230	Z		30
521232	S		30
521240	Z		30
521242	S		30
521250	Z		30
521252	S		30
521260	Z		30
521262	S		30
521270	Z		30
521272	S		30
521280	Z		30
521282	S		30
521300	Z		30
521302	S		30
521310	Z		30
521312	S		30
521320	Z		30
521322	S		30
521330	Z		30
521332	S		30
521340	Z		30
521342	S		30
521350	Z		30
521352	S		30
522000	Z		22–27, 29
522051	Z		23
526050	Z		22
526052	Z		23
530000	Z		25
530003	Z		24
530004	Z		29, 51
530013	E		24
530014	E		24
530015	E		29
530016	E		29
530020	E		25
530022	E		25
530023	E		25
533000	Z		24–25
536000	Z		24–25
540000	Z		26
540001	Z		27
540020	E		26
540022	E		26
540023	E		27
540024	E		27
540025	E		27
541401	Z		31
541404	Z		31
541406	Z		31
541410	Z		31
541413	Z		31
541414	Z		31
541415	Z		31
541416	Z		31
543000	Z		26
543010	Z		27, 29
543100	Z		24–26, 63–64
546000	Z		26–27
560000	Z		63
560001	Z		63
560002	Z		64
560003	Z		58
560004	Z		59
560008	Z		63
560010	E		61
560011	Z		67
560020	E		63
560022	E		64
560023	E		58
560026	E		63
560027	E		63
560040	E		59
560052	E		61
560053	E		67
561001	V		68

Art.-No.	RG	VE	Page
561002	V		68
561003	V		68
561004	V		68
561005	V		68
561006	V		68
561007	V		68
561008	V		68
561101	V		69
561102	V		69
561103	V		69
561104	V		69
561105	V		69
561106	V		69
561107	V		69
561108	V		69
561109	V		69
561110	V		69
561111	V		69
561112	V		69
561113	V		69
561114	V		69
561115	V		69
561116	V		69
561117	V		69
561118	V		69
561119	V		69
561120	V		69
561121	V		69
561122	V		69
561123	V		69
561124	V		69
561125	V		69
561126	V		69
563000	Z		63–64, 67
563008	Z		63–64
563100	Z		63–64
563200	Z		63–64
563203	Z		63–64
565051	Z		71
566030	Z		29, 61, 67, 141
566051	Z		58–59, 63–64
570100	Z		200–201, 207–209, 212–213, 217, 220, 229–231, 234
570107	Z		200–201, 207–208, 210, 212, 221, 229–231, 235–236
570110	Z		200–204, 206–221, 224–232, 234, 237
570112	Z		200, 207–208, 210, 230
570115	Z		200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
570117	Z		200, 207–208, 210, 230
570120	Z		200–204, 206–221, 224–232, 234, 237
570125	Z		200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
570130	Z		200–204, 206–221, 224–232, 234, 237
570132	Z		200, 230, 235
570135	Z		200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
570137	Z		200, 230, 235
570140	Z		200–204, 206–221, 224–232, 234, 237
570145	Z		200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
570150	Z		200–204, 206–221, 224–232, 234, 237
570155	Z		200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
570160	Z		200, 203, 206, 209, 213, 215–216, 220, 231, 234, 237
570165	Z		200–201, 207–208, 210–212, 214, 219, 221–224, 228–231, 235–237
570170	Z		200, 203, 206, 209, 213, 215–216, 220, 231, 234, 237
570175	Z		200–201, 207–208, 210–212, 214, 219, 221–224, 228–231, 235–237
570280	Z		186–187
570290	Z		238
570295	Z		238, 241
570300	Z		201, 204–205, 213, 233
570310	Z		204–206, 210, 216, 219, 222, 226–227, 232, 234

RG: discount group VE: packing unit (pieces)

List of articles

Art.-No.	RG	VE	Page
570315	Z		222
570320	Z		201–206, 208–212, 214–219, 222–223, 226–228, 232–234, 236–237
570330	Z		219
570340	Z		201–202, 204–206, 209–210, 214, 216, 218–219, 222–223, 226–227, 232–233
570350	Z		201–206, 208–212, 214–219, 222–223, 226–228, 232–234, 236–237
570360	Z		201–202, 204–206, 209, 214–216, 218–219, 222–223, 232–233, 236
570370	Z		202–212, 214, 216–219, 222–223, 226–228, 232–234, 237
570380	Z		201–206, 208–212, 214–219, 222–223, 226–228, 232–234, 236–237
570390	Z		202, 205, 208–210, 214–218, 222–223, 228, 233–234, 236
570400	Z		214
570410	Z		214
570420	Z		214
570430	Z		214
570440	Z		214
570450	Z		214
570452	Z		213, 216, 218, 237
570455	Z		200, 205–206, 209–210, 213, 215–216, 218, 220, 222, 225–228, 231–233, 236–237
570457	Z		209, 213, 218, 225
570460	Z		200–206, 208–228, 231–234, 236–237
570462	Z		209–210, 213, 216, 218, 220, 225–226, 231, 237
570465	Z		202, 204–206, 209–210, 213–216, 218, 220, 222–228, 231–233, 237
570467	Z		213, 215–216, 218, 225
570470	Z		200–206, 208–228, 231–234, 236–237
570472	Z		218, 225
570475	Z		201–220, 222–228, 231–234, 236–237
570477	Z		218, 225
570480	Z		200–206, 208–228, 231–234, 236–237
570482	Z		205, 218, 234
570485	Z		200, 202–206, 209–210, 213–228, 232–234, 236–237
570487	Z		203, 205–206, 217–218, 232–233
570495	Z		200–204, 206, 209–210, 213–216, 218–224, 227, 231–233, 236
570620	Z		224
570650	Z		224
570660	Z		224
570670	Z		224
570680	Z		224
570685	Z		234
570690	Z		224
570717	Z		202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237
570720	Z		206, 209, 218, 223, 226
570727	Z		202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237
570730	Z		202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237
570735	Z		202, 206, 209, 211–212, 214, 217–219, 223, 226, 228, 237
570742	Z		204, 209, 213, 217–218, 228
570747	Z		204, 209, 213, 217–218, 228
570750	Z		202–205, 209, 211, 216–220, 223, 227–228, 232–234
570760	Z		200, 205, 210, 213, 216, 220, 222–223, 226–227
570765	Z		200–220, 222–228, 232–234, 236–237
570770	Z		201–202, 204–207, 209–210, 213–214, 216, 218, 220, 222–224, 226–227, 232–233
570775	Z		200–228, 232–234, 236–237
570780	Z		200–201, 203–204, 206–207, 209–216, 218–227, 232–234, 236–237
570785	Z		200–228, 232–234, 236–237
570790	Z		200, 202, 204–205, 207, 209–211, 214–224, 226–228, 231–234, 236
570795	Z		204–205, 207, 209–211, 214–224, 226–228, 231–234, 236
570845	Z		204, 206, 218, 226–227
570850	Z		202, 204–206, 209, 211, 214, 217–219, 223, 226–228, 234, 236
570855	Z		204, 206, 209, 214, 218, 223, 226–227
570860	Z		202, 204–206, 209, 211, 214, 217–219, 223, 226–228, 234, 236
570870	Z		202, 204–206, 209, 211, 214, 217–219, 223, 226–228, 234
570880	Z		202, 204–206, 209, 211, 214, 217–219, 223, 227–228, 234, 236
570905	Z		234
570910	Z		206, 212, 226, 234, 236–237
570915	Z		206, 212, 226, 234, 236–237
570920	Z		226, 234, 236
570925	Z		206, 212, 236–237
570930	Z		229–231
570932	Z		230
570935	Z		214, 228–231
570937	Z		230
570940	Z		214, 228–231
570945	Z		214, 228–231
570950	Z		214, 228–231
570955	Z		214, 228–231
570970	Z		236
571136	Z		238
571137	Z		238
571283	Z		187
571290	Z		191, 193, 195
571320	Z		201–202, 204–205, 224, 227, 233
571325	Z		201–202, 204–206, 210–211, 215, 218, 222–225, 227, 232–233
571327	Z		204, 206, 211, 218
571330	Z		201–202, 204–206, 210–211, 215, 218, 222–225, 227, 232–233
571335	Z		201–202, 204–206, 210–211, 215, 222–225, 227, 232–233
571337	Z		218, 224
571340	Z		201, 204, 206, 210–211, 215, 222–223, 225, 232–233
571342	Z		218, 224
571360	Z		221
571370	Z		221
571375	Z		221
571380	Z		221
571432	Z		210
571434	Z		210
571436	Z		210
571438	Z		210
571450	Z		203, 236–237
571455	Z		203, 236–237
571460	Z		203, 236–237
571465	Z		203, 236–237
571470	Z		203, 236–237
571475	Z		203, 236–237
571477	Z		203, 237
571480	Z		213
571485	Z		213
571545	Z		147
571555	Z		147
571560	Z		83, 147
571565	Z		147
571567	Z		109, 133, 149, 151, 191, 193, 195, 244, 247, 255, 285
571571	Z		109, 111, 133, 149, 151, 191, 193, 195, 244, 247, 255, 285
571574	Z		61, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285
571578	Z		29, 51, 61, 67, 87, 141, 197
571581	Z		61, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285
571583	Z		29, 51, 61, 67, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285
571585	Z		29, 51, 61, 67, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285
571587	Z		29, 51, 61, 67, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285
571630	Z		234
571635	Z		201, 235–236
571640	Z		201, 235–236
571645	Z		235–236
571700	Z		206
571702	Z		206
571704	Z		206
571706	Z		206
571708	Z		206
571710	Z		206
571712	Z		206
571714	Z		206
571740	Z		223, 234–235
571750	Z		223, 236
571752	Z		223, 236
571754	Z		223, 236
571756	Z		223, 236
571758	Z		223, 236
571760	Z		223, 236
571764	Z		223, 228, 234–235
571766	Z		223, 228, 234–235
571767	Z		223, 228, 234–235
571770	Z		205, 209, 214, 220–223, 235–236
571775	Z		205, 209, 214, 220–223, 235–236
571780	Z		205, 209, 214, 220–223, 235–236
571785	Z		205, 209, 214, 220–223, 235–236
571790	Z		205, 209, 214, 220–223, 235–236
571795	Z		205, 209, 214, 220–223, 235–236
571797	Z		223, 236
571855	Z		232
571865	Z		241
571866	Z		184, 241
571870	Z		241
571871	Z		241
571887	Z		241
571889	Z		241
571890	Z		241
571891	Z		184, 241
571895	Z		241
571896	Z		184, 241
571900	Z		215, 226, 237
571904	Z		215, 226, 237
571932	Z		210
571934	Z		210
571980	Z		218
572101	Z		186
572111	E		186
572350	Z		236
572355	Z		236
572365	Z		204–205, 207, 209–211, 214–224, 226–228, 231–234, 236
572385	Z		204, 209, 213, 217–218, 228
572400	Z		200, 202–206, 209–210, 213–218, 220–228, 232–234, 236–237
572405	Z		200, 202–206, 209–210, 213–218, 220–228, 232–234, 236–237
572413	Z		223, 228, 234–235
572470	Z		214
572600	Z		211, 218, 225, 233
572605	Z		211, 218, 225, 233
572610	Z		211, 218, 225, 233
572615	Z		211, 218, 225, 233
572620	Z		211, 218, 225, 233
572625	Z		211, 218, 225, 233
572630	Z		234
572632	Z		234, 236
572636	Z		234, 236
572638	Z		234, 236
572640	Z		234, 236
572642	Z		201
572644	Z		201
572646	Z		201, 204
572648	Z		201
572670	Z		227
572672	Z		227
572674	Z		227
572676	Z		227
572678	Z		227
572680	Z		227
572687	Z		210–211, 221, 225, 236
572689	Z		210–211, 221, 225, 236
572691	Z		210–211, 221, 225, 236
572693	Z		211, 221, 225, 236
572695	Z		211, 221, 225, 236
572697	Z		211, 221, 225, 236
572706	Z		200–204, 206–213, 215–221, 224–232, 234, 237
572708	Z		200–204, 206–213, 215–221, 224–232, 234, 237
572714	Z		227
572716	Z		227
572727	Z		206, 213, 231
572795	Z		238
572801	Z		238
572802	Z		238
572809	Z		238
572810	Z		238
572813	Z		238
572815	Z		207, 223–224, 235–236
572816	Z		207, 223–224, 235–236
572817	Z		207, 223–224, 235–236
572818	Z		207, 223–224, 235–236
572819	Z		209, 214, 220–222, 235–236
572820	Z		209, 214, 220–222, 235–236
572821	Z		209, 214, 220–222, 235–236
572822	Z		236
572823	Z		236
572824	Z		236
572828	Z		204–205, 207, 214–215, 220–224, 227, 233–234, 236
572829	Z		205, 215, 218, 222–223, 225–226, 233–234
572830	Z		204, 213
572836	Z		227
572837	Z		204–205, 207, 209–210, 214–216, 218, 220, 222–224, 226–228, 232–234, 236
572839	Z		211, 225
572840	Z		211, 225
572841	Z		211, 225
572844	Z		223, 228, 234–235
572845	Z		223, 228, 234–235
572846	Z		235
572847	Z		207
572850	Z		200, 206–208, 210–212, 219, 223–224, 228–231, 235–237
572851	Z		200, 206–208, 210–212, 219, 223–224, 228–231, 235–237
573008	Z		244
573018	E		244
573020	Z		247
573021	Z		247
573022	E		247
573023	E		247
573100	Z		244
573102	Z		244
573106	Z		244
573108	Z		244
573110	Z		244
573112	Z		249
573114	Z		249
573116	Z		249
573118	Z		249
573120	Z		249
573122	Z		249
573124	Z		249
573126	Z		249
573128	Z		249
573150	Z		249
573152	Z		249
573154	Z		249
573156	Z		249
573158	S		249
573160	Z		249
573162	Z		249
573164	Z		249
573166	Z		249
573168	Z		249
573170	Z		249
573172	Z		249
573176	Z		249
573178	Z		249
573184	Z		249
573186	Z		249
573282	Z		244
573320	Z		249

List of articles

Art.-No.	RG	VE	Page
573325	Z		249
573330	Z		249
573335	Z		249
573360	Z		249
573364	Z		249
573367	Z		249
573370	Z		249
573400	Z		249
573402	Z		249
573404	Z		249
573406	Z		249
573430	Z		244
573432	Z		244
573434	Z		244
573436	Z		244
573438	Z		244
573616	Z		249
573624	Z		249
573628	Z		249
573630	Z		249
573632	Z		249
573634	Z		249
573636	Z		249
573638	Z		249
573640	Z		249
573642	Z		249
573644	Z		249
573646	Z		249
573647	Z		248
573648	Z		248
573649	Z		248
573652	Z		249
574000	H		185
574300	H		245
574302	H		245
574352	Z		245
574430	Z		185
574436	Z		82–83, 185
574437	Z		245
574516	Z		183, 238
574700	Z		147, 149, 151, 183
574702	Z		185, 238
574704	Z		183, 238
574728	Z		156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237
574730	Z		156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237
574732	Z		156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237
574734	Z		156, 159, 161, 163–165, 167–169, 172, 174, 176, 183, 202, 206, 209, 211–212, 214, 217–219, 223, 226, 228, 237
574736	Z		154–155, 160, 162, 164–165, 168, 170, 177–178, 181, 200–201, 207–209, 212–213, 217, 220, 229–231, 234
574738	Z		154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237
574740	Z		154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237
574742	Z		154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237
574744	Z		154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237
574746	Z		154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237
574748	Z		154–155, 160–164, 170–171, 177–178, 181–182, 200–201, 207–208, 210, 212, 221, 229–231, 235–236
574750	Z		154, 177–178, 181, 200, 230, 235
574752	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
574754	Z		154, 177–178, 181, 200, 210, 230, 235
574756	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
574758	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
574760	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
574762	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237
574764	Z		182
574766	Z		182
574768	Z		182
574770	Z		182
574772	Z		164, 166–168, 213, 215–216, 218
574774	Z		168, 218, 234
574776	Z		164, 167–168, 183, 213, 216, 218, 237
574778	Z		154, 158, 161–162, 164, 166–171, 174–175, 179, 183, 200, 209–210, 213, 215–216, 218, 220, 222, 225–226, 228, 232–233
574780	Z		161, 164, 168, 209, 213, 218
574782	Z		154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237
574784	Z		161–162, 164, 167–169, 174, 183, 209–210, 213, 216, 218, 220, 225–226, 237
574786	Z		155–159, 161–162, 164–166, 168–169, 171–175, 179–180, 183, 202, 204–206, 209–210, 213–214, 216, 218, 220, 222–226, 228, 232–233, 237
574788	Z		154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237
574790	Z		168, 218
574792	Z		154, 156, 158, 161–162, 164–172, 178–180, 182, 200–202, 206, 209–210, 213–216, 218–224, 232–233, 236
574794	Z		154–176, 178–183, 201–220, 222–228, 231–234, 236–237
574796	Z		168, 218
574798	Z		154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237
574800	Z		154, 160, 162, 200, 207–208, 210
574802	Z		154, 160, 162, 200, 207–208
574804	Z		163, 173, 182, 211, 225
574806	Z		163, 173, 182, 211, 225
574808	Z		163, 173, 182, 211, 225
574850	Z		168, 217
574852	Z		168, 217
574854	Z		168, 217
574856	Z		182
575010	Z		255
575017	E		256
575020	E		255
575021	E		255
575022	E		255
575100	Z		256
575252	Z		255
575253	Z		255
575256	Z		255
575278	Z		256
576000	Z		193
576003	Z		195
576006	Z		191
576010	E		193
576011	E		193
576014	E		195
576015	E		195
576016	E		191
576017	E		191
576345	Z		191, 193, 195
577000	Z		187
577010	E		187
577013	E		187
578001	Z		147
578002	Z		149
578003	Z		151
578010	E		149
578012	E		147
578013	E		147
578014	E		149
578015	E		151
578016	E		151
578290	Z		147, 149, 151, 247, 255
578295	Z		183–184
578299	Z		147, 149, 151
578310	Z		154–155, 160, 162, 164–165, 168, 170, 177–178, 181
578312	Z		154–157, 159–170, 172–179, 181–182
578314	Z		154–157, 159–170, 172–179, 181–182
578316	Z		154–157, 159–170, 172–179, 181–182
578318	Z		154–157, 159–170, 172–179, 181–182
578324	Z		154–155, 160–164, 170–171, 177–178, 181–182
578326	Z		154, 160, 162, 177–178
578328	Z		154–155, 159–164, 166, 169–172, 176–178, 181–182
578330	Z		154, 160, 162, 177–178
578332	Z		154–155, 159–164, 166, 169–172, 176–178, 181–182
578334	Z		154–155, 159–164, 166, 169–172, 176–178, 181–182
578336	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182
578338	Z		154, 177–178, 181
578340	Z		154, 177–178, 181
578342	Z		164, 166–168, 173
578344	Z		158, 168, 181
578346	Z		164, 167–168, 183
578348	Z		154, 158, 161–162, 164, 166–171, 174–175, 178–180, 182–183
578350	Z		161, 164, 168, 173
578352	Z		154–159, 161–176, 178–183
578354	Z		161–162, 164, 167–169, 174, 178, 183
578356	Z		155–159, 161–162, 164–169, 171–175, 178–180, 183
578358	Z		154–159, 161–176, 178–183
578360	Z		154, 156, 158–159, 161–162, 164–172, 175, 178–180, 182
578362	Z		154–176, 178–183
578364	Z		154–159, 161–176, 178–183
578368	Z		156, 158, 167–168, 179–180
578370	Z		166, 174, 183
578372	Z		154, 158, 162, 164, 166, 170–172, 174–175
578374	Z		154–176, 178–183
578376	Z		154–162, 164–166, 168, 170–172, 174–175, 179–180
578378	Z		154–176, 178–183
578380	Z		154, 156–157, 159–175, 178–183
578382	Z		154–176, 178–183
578386	Z		154–155, 157–158, 161–163, 165–172, 174–176, 178–182
578390	Z		154–157, 159–170, 172–179, 181–182
578392	Z		155–158, 161, 163, 166–170, 172, 175–176, 179–181
578394	Z		171
578396	Z		154, 157–158, 164, 180
578398	Z		157–158, 162, 166, 169, 171, 174–175, 179–180
578400	Z		154–159, 161–169, 171–172, 174–176, 178–180, 182–183
578402	Z		169
578404	Z		154–159, 161–162, 165–166, 168–169, 171–172, 174–175, 179–180
578406	Z		154–159, 161–169, 171–172, 174–176, 178–180, 182–183
578408	Z		154, 156–159, 161, 165–169, 171–172, 179–180, 182
578410	Z		155–169, 171–172, 174–176, 178–180, 183
578412	Z		154–159, 161–169, 171–172, 174–176, 178–180, 182–183
578420	Z		172
578426	Z		172
578430	Z		172
578432	Z		172
578434	Z		175
578436	Z		175
578438	Z		175
578440	Z		175
578442	Z		175
578444	Z		165
578446	Z		165
578448	Z		165
578450	Z		165
578452	Z		165
578454	Z		175
578456	Z		156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183
578458	Z		159, 161, 168, 172, 174
578460	Z		156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183
578462	Z		156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183
578464	Z		156, 159, 161, 163–165, 167–169, 172, 174, 176, 183
578466	Z		157–158, 168, 174–175
578468	Z		155–158, 161, 163, 165, 167–169, 172, 174–176, 180, 182
578470	Z		157–158, 161, 165, 168, 172, 174–175
578472	Z		155–158, 161, 163, 165, 167–169, 172, 174–176, 180, 182
578474	Z		155–158, 161, 163, 165, 167–169, 172, 174–176, 180
578476	Z		155–158, 161, 163, 165, 167–169, 172, 175–176, 180, 182
578478	Z		161, 164, 167–168, 176
578480	Z		181
578482	Z		159, 164, 174, 181–183
578484	Z		159, 164, 174, 181–183
578486	Z		181–182
578488	Z		159, 164, 174, 182–183
578490	Z		154–155, 157–158, 172, 175, 179–180
578492	Z		154–155, 157–159, 162–163, 166, 171–173, 175, 179–180
578494	Z		154–155, 157–159, 162–163, 166, 171–173, 175, 179–180
578496	Z		154–155, 157–159, 162–163, 166, 171–173, 175, 179–180
578498	Z		154, 157–159, 162–163, 166, 171–173, 179–180
578510	Z		177–178
578512	Z		177–178
578514	Z		166, 176–178
578516	Z		177–178
578518	Z		166, 176–178
578520	Z		166, 176–178
578522	Z		166, 176–178
578524	Z		170
578526	Z		170
578528	Z		170
578530	Z		170
578534	Z		156, 182–183
578536	Z		156, 182–183
578538	Z		156, 182–183
578540	Z		156, 182–183
578550	Z		181
578552	Z		154, 181–182
578554	Z		154, 181–182
578556	Z		181–182
578566	Z		158, 161, 166, 169–172, 182
578568	Z		158, 161, 166, 169–172, 182

RG: discount group VE: packing unit (pieces)

List of articles

Art.-No.	RG	VE	Page
578570	Z		158, 161, 166, 169–172, 182
578572	Z		174
578576	Z		180
578578	Z		180, 182
578582	Z		180, 182
578584	Z		180, 182
578586	Z		180, 182
578588	Z		168, 173
578590	Z		168, 173
578592	Z		163, 168, 173, 180
578594	Z		163, 168, 173, 180
578596	Z		163, 168, 173, 180
578598	Z		163, 168, 173, 180
578600	Z		163, 168, 173, 180
578602	Z		180
578604	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182
578606	Z		158, 161, 166, 169–172, 182
578608	Z		154
578610	Z		154
578612	Z		154, 158
578614	Z		154
578618	Z		179
578620	Z		184
578621	Z		184
578622	Z		184
578624	Z		154–158, 161–162, 164–176, 178–183
578630	Z		162–163, 170, 173, 182
578632	Z		162–163, 170, 173, 182
578634	Z		162–163, 170, 173, 182
578636	Z		163, 170, 173, 182
578638	Z		157–159, 163
578640	Z		172, 182
578642	Z		172, 182
578644	Z		172, 182
578646	Z		172, 182
578652	Z		175
578654	Z		175
578656	Z		175
578659	Z		183
578660	Z		172, 181
578664	Z		172, 176, 181
578666	Z		172, 176, 181
578670	Z		164
578700	Z		159
578702	Z		159
578704	Z		159
578706	Z		159
578708	Z		159
578710	Z		159
578712	Z		159
578714	Z		159
578716	Z		168
578718	Z		168
578720	Z		168
578740	Z		173, 183
578742	Z		173, 183
578744	Z		173, 183
578746	Z		173, 183
579000	Z		188
579001	Z		197
579010	E		188
579012	E		188
579014	E		197
579100	Z		200, 207, 228, 230
579101	Z		200–204, 207–213, 215–221, 224–232, 234, 237
579104	Z		210
579105	Z		210
579106	Z		210
579107	Z		212–213, 230–231
579108	Z		200, 207, 220, 230–231
579109	Z		200
579110	Z		200–204, 207–213, 215–221, 224–232, 234, 237
579111	Z		200–204, 207–213, 215–221, 224–232, 234, 237
579112	Z		235
579113	Z		235
579114	Z		235
579120	Z		188, 238
579123	Z		197, 238
579144	Z		207
579146	Z		207
579240	Z		188
579600	Z		119, 123
579601	Z		188, 197
579603	Z		238
580000	Z		137, 142
580004	Z		141
580010	E		137
580014	E		141
580020	E		137
580021	E		137
580022	E		137
580023	E		137
580024	E		137
580025	E		137
580026	E		137
580027	E		137
580028	E		137
580029	E		137
580030	E		137
580031	E		137
580033	E		137
580034	E		137
580035	E		137
580036	E		137
580037	E		137
580038	E		137
580039	E		137
580040	E		137
580051	E		141
580052	E		141
580053	E		141
580054	E		141
580055	E		141
580056	E		141
580057	E		141
580058	E		141
580059	E		141
580060	E		141
580061	E		141
580062	E		141
580063	E		141
580064	E		141
580065	E		141
580066	E		141
580067	E		141
580068	E		141
580069	E		141
580100	Z		139
580110	E		139
581070	Z		143
581080	Z		143
581110	Z		143
581130	Z		143
581150	Z		143
581180	Z		143
581200	Z		143
581210	Z		143
581220	Z		143
581230	Z		143
581240	Z		143
581260	Z		143
581270	Z		143
581280	Z		143
581310	Z		143
581320	Z		143
581330	Z		143
581350	Z		143
581360	Z		143
581370	Z		143
581380	Z		143
581390	Z		143
581400	Z		143
581410	Z		143
581420	Z		143
581430	Z		143
581440	Z		143
581450	Z		143
581460	Z		143
581470	Z		143
581480	Z		143
581490	Z		143
581500	Z		143
581510	Z		143
581520	Z		143
581530	Z		143
581540	Z		143
582036	Z		137, 139, 141–142
582110	Z		139
582120	Z		139
586000	Z		137
586012	Z		139
586100	Z		137, 141
586150	Z		137, 141
590000	Z		135
590020	E		135
590021	E		135
590022	E		135
590051	Z		135
590052	Z		135
590053	Z		135
590054	Z		135
590055	Z		135
590056	Z		135
590057	Z		135
590058	Z		135
590059	Z		135
590060	Z		135
590061	Z		135
590062	Z		135
590111	Z		135
590150	Z		135
590153	Z		135
590160	Z		135, 139
731200	Z		31
731205	Z		31
731210	Z		31
731220	Z		31
731230	Z		31
731240	Z		31
731250	Z		31
731301	Z		31
731302	Z		31
731303	Z		31
731304	Z		31
731305	Z		31
731306	Z		31
731307	Z		31
731308	Z		31
731309	Z		31
731310	Z		31
731311	Z		31
731312	Z		31
731320	Z		31
731321	Z		31
731322	Z		31
731323	Z		31
731324	Z		31
731325	Z		31
731326	Z		31
731700	Z		24–27, 29, 97
750003	U		43
750004	U		43
751000	Z		43
751040	Z		43
751050	Z		43
751060	Z		43
751070	Z		43
751080	Z		43
751090	Z		43
751096	Z		43
751097	Z		43
751098	Z		43
751100	Z		43
751102	Z		43
751501	S		44
751502	S		44
751503	S		44
751504	S		44
751505	S		44
751506	S		44
751507	S		44
751508	S		44
751509	S		44
751510	S		44
751511	S		44
751516	S		44
751517	S		44
751518	S		44
751519	S		44
751520	S		44
751521	S		44
751522	S		44
751523	S		44
751524	S		44
751525	S		44
751526	S		44
751527	S		44
751528	S		44
751544	S		44
751545	S		44
751546	S		44
751547	S		44
751548	S		44
751549	S		44
751550	S		44
751551	S		44
751552	S		44
751557	S		44
751558	S		44
751559	S		44
751560	S		44
751561	S		44
751562	S		44
751563	S		44
751564	S		44
751565	S		44
751566	S		44
751567	S		44
751568	S		44
751569	S		44
751570	S		44
751571	S		44
753240	Z		43
759250	S		44
759251	S		44
759252	S		44
759253	S		44
759254	S		44
759255	S		44
759256	S		44
759257	S		44
759258	S		44
759259	S		44
759260	S		44
759261	S		44
759262	S		44
759263	S		44
759264	S		44
759265	S		44
759270	S		44
759271	S		44
759272	S		44
759273	S		44
759274	S		44
759275	S		44
759276	S		44
759277	S		44
759278	S		44
759279	S		44
759280	S		44
759281	S		44
759282	S		44
759330	S		44
759360	S		44
759361	S		44
759362	S		44
759363	S		44
759364	S		44
759365	S		44
759366	S		44
759367	S		44
759368	S		44
759370	S		44
759371	S		44
759372	S		44
759373	S		44
759374	S		44
759375	S		44
759376	S		44
759377	S		44
759378	S		44
759379	S		44
759380	S		44
759381	S		44
759382	S		44
759383	S		44
759384	S		44
844010	E		82
844011	E		83
844045	Z		82–83
844050	Z		82–83
844051	Z		82–83
844510	Z		83
845001	M		85
845002	M		87
845003	M		85
845004	M		89
845050	Z		85, 87, 89
845051	Z		85, 87, 89
845052	Z		85, 87, 89
845053	Z		85, 87, 89
845054	Z		85
845055	Z		85, 87, 89
845057	Z		89
845060	Z		89
845085	Z		85
845110	Z		85, 87
845118	Z		85, 87
845131	Z		85
845218	Z		85, 87
845220	Z		85, 87, 89
845230	Z		89
845530	Z		85, 87
849006	M		70
849007	M		71
849310	Z		49, 51, 70–71, 85, 87
849315	Z		49, 51, 70–71, 85, 87
849700	Z		71
849703	Z		70–71
849706	Z		70–71

Notes

Notes

REMS

www.rems.de

Head Office

Germany: REMS GmbH & Co KG
Postfach 1631 · 71306 Waiblingen · Germany
Stuttgarter Straße 83 · 71332 Waiblingen · Germany
Tel +49 7151 17 07-0
info@rems.de

Branch Offices

Denmark: REMS Scandinavia A/S
Snedkervej 1 · 4600 Køge · Denmark
Tel +45 56 63 14 00
DNK@rems.de

France: REMS SARL
2, Rue du Stade · 67250 Hoffen · France
Tel +33 388 80 44 53
FRA@rems.de

Great Britain: REMS (U.K.) LIMITED
Unit 5 · Ash Industrial Estate
Flex Meadow · Harlow · Essex CM19 5TJ · U.K.
Tel +44 1279 413698
GBR@rems.de

Italy: REMS S.R.L.
Via Sirtori, 13/D · 20017 Passirana di Rho (Milano) · Italy
Tel +39 02 9 30 21 11
ITA@rems.de

Poland: REMS POLSKA Sp. z o.o.
Dąbrowa · Ulica Piaskowa 19 · 62-070 Dopiewo · Poland
Tel +48 61 654 09 00
POL@rems.de

Spain: REMS ESPAÑA, S.A.U.
Pol. Ind. San José de Valderas
Calle Herramientas, 28 · 28918 Leganés (Madrid) · Spain
Tel +34 916 444 833
ESP@rems.de

Czech Republic: REMS Česká republika s.r.o.
Nádražní 271 · 253 01 Hostivice · Czech Republic
Tel +420 2 20 98 28 80
CZE@rems.de

Prodaja samo preko ovlaštenih trgovaca.

Obavijest trgovcima i prezentacija preko zastupnika tvrtke REMS:

SAFETY SAVJETOVANJE
Mob: +385 (0)98 / 210-454
E-mail: Andrej.Vukelic@rems.de

CR.TA.GO.
Mob: +385 (0)98 / 377-119
E-mail: Goran.Crnic@rems.de

BIH@rems.de · www.rems.de

RE112023094001BIH00 · Subject to alterations and errors. © Copyright 2024 by REMS GmbH & Co KG, Waiblingen.